

HEAP AND COPY CONSTRUCTOR

Lecturer: 陈笑沙

TABLE OF CONTENTS

- 6.1 About the Heap
- 6.2 The Need for new and delete
- 6.3 Allocating Heap Objects
- 6.4 Copy Constructor
- 6.5 Shallow Copy vs. Deep Copy
- 6.6 Temporary Objects
- 6.7 Constructors for Type Conversion
- 6.8 Further Reading

6.1 ABOUT THE HEAP

The program resides in memory to run, with its memory layout consisting of four regions:

6.1 ABOUT THE HEAP

The program resides in memory to run, with its memory layout consisting of four regions:

- Code region

6.1 ABOUT THE HEAP

The program resides in memory to run, with its memory layout consisting of four regions:

- Code region
- Data region (global data area)

6.1 ABOUT THE HEAP

The program resides in memory to run, with its memory layout consisting of four regions:

- Code region
- Data region (global data area)
- Heap region

6.1 ABOUT THE HEAP

The program resides in memory to run, with its memory layout consisting of four regions:

- Code region
- Data region (global data area)
- Heap region
- Stack region

6.1 ABOUT THE HEAP

6.1 ABOUT THE HEAP

- **Code area** stores executable instructions

6.1 ABOUT THE HEAP

- **Code area** stores executable instructions
 - Read-only, possibly shared by multiple processes (such as dynamic libraries), fixed size, loaded at runtime

6.1 ABOUT THE HEAP

- **Code area** stores executable instructions
 - Read-only, possibly shared by multiple processes (such as dynamic libraries), fixed size, loaded at runtime
- **Global data area** saves global variables and static variables, constant strings

6.1 ABOUT THE HEAP

- **Code area** stores executable instructions
 - Read-only, possibly shared by multiple processes (such as dynamic libraries), fixed size, loaded at runtime
- **Global data area** saves global variables and static variables, constant strings
 - Read and write, lifecycle consistent with the program

6.1 ABOUT THE HEAP

- **Code area** stores executable instructions
 - Read-only, possibly shared by multiple processes (such as dynamic libraries), fixed size, loaded at runtime
- **Global data area** saves global variables and static variables, constant strings
 - Read and write, lifecycle consistent with the program
- **Heap area** dynamic memory allocation and storage area

6.1 ABOUT THE HEAP

- **Code area** stores executable instructions
 - Read-only, possibly shared by multiple processes (such as dynamic libraries), fixed size, loaded at runtime
- **Global data area** saves global variables and static variables, constant strings
 - Read and write, lifecycle consistent with the program
- **Heap area** dynamic memory allocation and storage area
 - Manual management, address from low to high, variable size, dynamically allocated at runtime, fragmentation problems may be relatively severe

6.1 ABOUT THE HEAP

- **Code area** stores executable instructions
 - Read-only, possibly shared by multiple processes (such as dynamic libraries), fixed size, loaded at runtime
- **Global data area** saves global variables and static variables, constant strings
 - Read and write, lifecycle consistent with the program
- **Heap area** dynamic memory allocation and storage area
 - Manual management, address from low to high, variable size, dynamically allocated at runtime, fragmentation problems may be relatively severe
- **Stack area** stores local variables, function parameters, return addresses, and saves function call context (such as register status)

6.1 ABOUT THE HEAP

- **Code area** stores executable instructions
 - Read-only, possibly shared by multiple processes (such as dynamic libraries), fixed size, loaded at runtime
- **Global data area** saves global variables and static variables, constant strings
 - Read and write, lifecycle consistent with the program
- **Heap area** dynamic memory allocation and storage area
 - Manual management, address from low to high, variable size, dynamically allocated at runtime, fragmentation problems may be relatively severe
- **Stack area** stores local variables, function parameters, return addresses, and saves function call context (such as register status)
 - Automatic management, address from high to low, limited size, fast access

6.1 ABOUT THE HEAP

C language heap allocation and release

```
1  #include <stdlib.h>
2  #include <stdio.h>
3
4  int num = 10; // Data area
5
6  int main()
7  {
8      int* arr = (int*)malloc(sizeof(int) * num); // Heap area application
9      for (int i = 0; i < num; i++) {
10         arr[i] = i; // arr and i are stack variables
11         printf("%d\n", arr[i]);
12     }
13
14     free(arr); // Release
15     return 0;
```

You can view the assembly code on <https://godbolt.org> to intuitively feel the underlying principles (it is best to clear the Compiler options option)

6.1 ABOUT THE HEAP

C language heap allocation and release

```
1  #include <stdlib.h>
2  #include <stdio.h>
3
4  int num = 10; // Data area
5
6  int main()
7  {
8      int* arr = (int*)malloc(sizeof(int) * num); // Heap area application
9      for (int i = 0; i < num; i++) {
10         arr[i] = i; // arr and i are stack variables
11         printf("%d\n", arr[i]);
12     }
13
14     free(arr); // Release
15     return 0;
```

You can view the assembly code on <https://godbolt.org> to intuitively feel the underlying principles (it is best to clear the Compiler options option)

6.1 ABOUT THE HEAP

C language heap allocation and release

```
1  #include <stdlib.h>
2  #include <stdio.h>
3
4  int num = 10; // Data area
5
6  int main()
7  {
8      int* arr = (int*)malloc(sizeof(int) * num); // Heap area application
9      for (int i = 0; i < num; i++) {
10         arr[i] = i; // arr and i are stack variables
11         printf("%d\n", arr[i]);
12     }
13
14     free(arr); // Release
15     return 0;
```

You can view the assembly code on <https://godbolt.org> to intuitively feel the underlying principles (it is best to clear the Compiler options option)

6.1 ABOUT THE HEAP

C language heap allocation and release

```
2 #include <stdio.h>
3
4 int num = 10; // Data area
5
6 int main()
7 {
8     int* arr = (int*)malloc(sizeof(int) * num); // Heap area application
9     for (int i = 0; i < num; i++) {
10         arr[i] = i; // arr and i are stack variables
11         printf("%d\n", arr[i]);
12     }
13
14     free(arr); // Release
15     return 0;
16 }
```

You can view the assembly code on <https://godbolt.org> to intuitively feel the underlying principles (it is best to clear the Compiler options option)

6.1 ABOUT THE HEAP

C language heap allocation and release

```
2 #include <stdio.h>
3
4 int num = 10; // Data area
5
6 int main()
7 {
8     int* arr = (int*)malloc(sizeof(int) * num); // Heap area application
9     for (int i = 0; i < num; i++) {
10         arr[i] = i; // arr and i are stack variables
11         printf("%d\n", arr[i]);
12     }
13
14     free(arr); // Release
15     return 0;
16 }
```

You can view the assembly code on <https://godbolt.org> to intuitively feel the underlying principles (it is best to clear the Compiler options option)

6.2 THE NEED FOR `new` AND `delete`

C++ contains many object data, and when applying for the heap, you also need to initialize the memory (constructor); when releasing memory, you need to call the destructor.

```
1  class Point {  
2  public:  
3      Point() { x = 1; y = 1; } // No parameter constructor  
4      void print() { cout << x << ", " << y; }  
5      void set(int x, int y) {  
6          this->x = x;  
7          this->y = y;  
8      }  
9      ~Point() { // do something ... }  
10 private:  
11     int x, y;  
12 };
```

6.2 THE NEED FOR `new` AND `delete`

C++ contains many object data, and when applying for the heap, you also need to initialize the memory (constructor); when releasing memory, you need to call the destructor.

```
1  class Point {  
2  public:  
3      Point() { x = 1; y = 1; } // No parameter constructor  
4      void print() { cout << x << ", " << y; }  
5      void set(int x, int y) {  
6          this->x = x;  
7          this->y = y;  
8      }  
9      ~Point() { // do something ... }  
10 private:  
11     int x, y;  
12 };
```

6.2 THE NEED FOR `new` AND `delete`

The shortcomings of `malloc` and `free`.

```
1 int main() {  
2     // No constructor called  
3     Point* pd = (Point*)malloc(10 * sizeof(Point));  
4     for (int i = 0; i < 10; i++)  
5         pd[i].set(1, 1); // Need to initialize like this  
6     free(pd); // No destructor called  
7     return 0;  
8 }
```


6.2 THE NEED FOR `new` AND `delete`

The shortcomings of `malloc` and `free`.

```
1 int main() {  
2     // No constructor called  
3     Point* pd = (Point*)malloc(10 * sizeof(Point));  
4     for (int i = 0; i < 10; i++)  
5         pd[i].set(1, 1); // Need to initialize like this  
6     free(pd); // No destructor called  
7     return 0;  
8 }
```

6.2 THE NEED FOR `new` AND `delete`

The shortcomings of `malloc` and `free`.

```
1 int main() {  
2     // No constructor called  
3     Point* pd = (Point*)malloc(10 * sizeof(Point));  
4     for (int i = 0; i < 10; i++)  
5         pd[i].set(1, 1); // Need to initialize like this  
6     free(pd); // No destructor called  
7     return 0;  
8 }
```

6.2 THE NEED FOR `new` AND `delete`

The shortcomings of `malloc` and `free`.

```
1 int main() {  
2     // No constructor called  
3     Point* pd = (Point*)malloc(10 * sizeof(Point));  
4     for (int i = 0; i < 10; i++)  
5         pd[i].set(1, 1); // Need to initialize like this  
6     free(pd); // No destructor called  
7     return 0;  
8 }
```

6.3 ALLOCATING HEAP OBJECTS

```
1  int main() {  
2      Point* pd = new Point; // Allocate a single object  
3      Point* pds = new Point[10]; // Allocate an array  
4      pd->print(); // Already initialized, no need to set again  
5      pds[2].print();  
6  
7      delete pd; // Release a single object  
8      delete[] pds; // Release multiple objects  
9  
10     return 0;  
11 }
```

6.3 ALLOCATING HEAP OBJECTS

```
1  int main() {  
2      Point* pd = new Point; // Allocate a single object  
3      Point* pds = new Point[10]; // Allocate an array  
4      pd->print(); // Already initialized, no need to set again  
5      pds[2].print();  
6  
7      delete pd; // Release a single object  
8      delete[] pds; // Release multiple objects  
9  
10     return 0;  
11 }
```

6.3 ALLOCATING HEAP OBJECTS

```
1  int main() {  
2      Point* pd = new Point; // Allocate a single object  
3      Point* pds = new Point[10]; // Allocate an array  
4      pd->print(); // Already initialized, no need to set again  
5      pds[2].print();  
6  
7      delete pd; // Release a single object  
8      delete[] pds; // Release multiple objects  
9  
10     return 0;  
11 }
```

6.3 ALLOCATING HEAP OBJECTS

```
1  int main() {  
2      Point* pd = new Point; // Allocate a single object  
3      Point* pds = new Point[10]; // Allocate an array  
4      pd->print(); // Already initialized, no need to set again  
5      pds[2].print();  
6  
7      delete pd; // Release a single object  
8      delete[] pds; // Release multiple objects  
9  
10     return 0;  
11 }
```

6.3 ALLOCATING HEAP OBJECTS

```
1  int main() {  
2      Point* pd = new Point; // Allocate a single object  
3      Point* pds = new Point[10]; // Allocate an array  
4      pd->print(); // Already initialized, no need to set again  
5      pds[2].print();  
6  
7      delete pd; // Release a single object  
8      delete[] pds; // Release multiple objects  
9  
10     return 0;  
11 }
```


6.3 ALLOCATING HEAP OBJECTS

```
1  int main() {  
2      Point* pd = new Point; // Allocate a single object  
3      Point* pds = new Point[10]; // Allocate an array  
4      pd->print(); // Already initialized, no need to set again  
5      pds[2].print();  
6  
7      delete pd; // Release a single object  
8      delete[] pds; // Release multiple objects  
9  
10     return 0;  
11 }
```

6.3 ALLOCATING HEAP OBJECTS

```
1  int main() {  
2      Point* pd = new Point; // Allocate a single object  
3      Point* pds = new Point[10]; // Allocate an array  
4      pd->print(); // Already initialized, no need to set again  
5      pds[2].print();  
6  
7      delete pd; // Release a single object  
8      delete[] pds; // Release multiple objects  
9  
10     return 0;  
11 }
```

6.3 ALLOCATING HEAP OBJECTS

```
1  int main() {
2      Point* pd = new Point; // Allocate a single object
3      Point* pds = new Point[10]; // Allocate an array
4      pd->print(); // Already initialized, no need to set again
5      pds[2].print();
6
7      delete pd; // Release a single object
8      delete[] pds; // Release multiple objects
9
10     return 0;
11 }
```

6.3 ALLOCATING HEAP OBJECTS

6.3 ALLOCATING HEAP OBJECTS

- `new` and `delete` are C++ operators, no need to introduce new header files

6.3 ALLOCATING HEAP OBJECTS

- `new` and `delete` are C++ operators, no need to introduce new header files
- Its functionality covers C language, can apply for basic data types

6.3 ALLOCATING HEAP OBJECTS

- `new` and `delete` are C++ operators, no need to introduce new header files
- Its functionality covers C language, can apply for basic data types
- Performance is the same as C language, automatic type matching, no need to convert

6.3 ALLOCATING HEAP OBJECTS

You can pass constructor parameters when using new:

```
1  class Point {
2  public:
3      Point(int x, int y): x(x), y(y) {}
4      void print() { cout << x << ", " << y; }
5      void set(int x, int y) {
6          this->x = x;
7          this->y = y;
8      }
9  };
10
11 int main() {
12     Point* p = new Point(3, 4);
13     p->print();
14     delete p; // cannot have parameters
15     return 0;
```


6.3 ALLOCATING HEAP OBJECTS

You can pass constructor parameters when using new:

```
1  class Point {
2  public:
3      Point(int x, int y): x(x), y(y) {}
4      void print() { cout << x << ", " << y; }
5      void set(int x, int y) {
6          this->x = x;
7          this->y = y;
8      }
9  };
10
11 int main() {
12     Point* p = new Point(3, 4);
13     p->print();
14     delete p; // cannot have parameters
15     return 0;
```

6.3 ALLOCATING HEAP OBJECTS

You can pass constructor parameters when using new:

```
2  public:
3      Point(int x, int y): x(x), y(y) {}
4      void print() { cout << x << ", " << y; }
5      void set(int x, int y) {
6          this->x = x;
7          this->y = y;
8      }
9  };
10
11  int main() {
12      Point* p = new Point(3, 4);
13      p->print();
14      delete p; // cannot have parameters
15      return 0;
16  }
17  return 0;
```

6.3 ALLOCATING HEAP OBJECTS

You can pass constructor parameters when using new:

```
2  public:
3      Point(int x, int y): x(x), y(y) {}
4      void print() { cout << x << ", " << y; }
5      void set(int x, int y) {
6          this->x = x;
7          this->y = y;
8      }
9  };
10
11 int main() {
12     Point* p = new Point(3, 4);
13     p->print();
14     delete p; // cannot have parameters
15     return 0;
16 }
17 return 0,
```

6.3 ALLOCATING HEAP OBJECTS

You can pass constructor parameters when using new:

```
2  public:
3      Point(int x, int y): x(x), y(y) {}
4      void print() { cout << x << ", " << y; }
5      void set(int x, int y) {
6          this->x = x;
7          this->y = y;
8      }
9  };
10
11 int main() {
12     Point* p = new Point(3, 4);
13     p->print();
14     delete p; // cannot have parameters
15     return 0;
16 }
17 return 0;
```

6.3 ALLOCATING HEAP OBJECTS

You can pass constructor parameters when using new:

```
1  class Point {  
2  public:  
3      Point(int x, int y): x(x), y(y) {}  
4      void print() { cout << x << ", " << y; }  
5      void set(int x, int y) {  
6          this->x = x;  
7          this->y = y;  
8      }  
9  };  
10  
11 int main() {  
12     Point* p = new Point(3, 4);  
13     p->print();  
14     delete p; // cannot have parameters  
15     return 0;
```

6.4 COPY CONSTRUCTOR

Common operations on objects:

6.4 COPY CONSTRUCTOR

Common operations on objects:

- Creation (constructor)

6.4 COPY CONSTRUCTOR

Common operations on objects:

- Creation (constructor)
- Comparison

6.4 COPY CONSTRUCTOR

Common operations on objects:

- Creation (constructor)
- Comparison
- Assignment

6.4 COPY CONSTRUCTOR

Common operations on objects:

- Creation (constructor)
- Comparison
- Assignment
- Copy constructor

6.4 COPY CONSTRUCTOR

Common operations on objects:

- Creation (constructor)
- Comparison
- Assignment
- Copy constructor
- Destruction (destructor)

6.4 COPY CONSTRUCTOR

BEYOND THE TOPIC

In essence, not all objects support these operations, and there is no strict limitation in C++ on which objects need to support which operations. After C++ 20, the concept of concept has been introduced to address this issue.

6.4 COPY CONSTRUCTOR

When a class does not customize these operations, the compiler will automatically add a default operation.

```
class Student {  
public:  
    Student(); // Default constructor  
    Student(const Student& other); // Default copy constructor  
    ~Student(); // Default destructor  
    Student& operator=(const Student& other); // Default assignment function  
    bool operator==(const Student& other) const; // Default comparison function  
};
```

6.4 COPY CONSTRUCTOR

We can customize copy constructors:

```
1  #include <iostream>
2
3  using namespace std;
4
5  class Student {
6  public:
7      Student(const string &name, int age)
8          : name(name), age(age) {
9          cout << "Constructing Student " << name << endl;
10     }
11     Student(const Student &other) {
12         cout << "Constructing copy of Student "
13             << other.name << endl;
14         name = other.name;
15         age = other.age;
```

6.4 COPY CONSTRUCTOR

We can customize copy constructors:

```
1 //include <iostream>
2
3 using namespace std;
4
5 class Student {
6 public:
7     Student(const string &name, int age)
8         : name(name), age(age) {
9         cout << "Constructing Student " << name << endl;
10    }
11    Student(const Student &other) {
12        cout << "Constructing copy of Student "
13            << other.name << endl;
14        name = other.name;
15        age = other.age;
16    }
```

6.4 COPY CONSTRUCTOR

We can customize copy constructors:

```
6 public:
7     Student(const string &name, int age)
8         : name(name), age(age) {
9         cout << "Constructing Student " << name << endl;
10    }
11    Student(const Student &other) {
12        cout << "Constructing copy of Student "
13            << other.name << endl;
14        name = other.name;
15        age = other.age;
16    }
17    ~Student() {
18        cout << "Destructing Student " << name << endl;
19    }
20    void setName(const string &name) { this->name = name; }
21    age = other.age;
```


6.4 COPY CONSTRUCTOR

We can customize copy constructors:

```
11 Student(const Student &other) {
12     cout << "Constructing copy of Student "
13         << other.name << endl;
14     name = other.name;
15     age = other.age;
16 }
17 ~Student() {
18     cout << "Destructing Student " << name << endl;
19 }
20 void setName(const string &name) { this->name = name; }
21
22 private:
23     int age;
24     string name;
25 };
```

6.4 COPY CONSTRUCTOR

We can customize copy constructors:

```
20 void setName(const string &name) { this->name = name; }
21
22 private:
23     int age;
24     string name;
25 };
26
27 int main() {
28     Student s{"Eric", 12};
29     Student s2 = s;
30     Student s3{"Alice", 20};
31     s3 = s; // this will not call copy constructor
32     s2.setName("Bob");
33     return 0;
34 }
35
```

6.4 COPY CONSTRUCTOR

We can customize copy constructors:

```
20 void setName(const string &name) { this->name = name; }
21
22 private:
23     int age;
24     string name;
25 };
26
27 int main() {
28     Student s{"Eric", 12};
29     Student s2 = s;
30     Student s3{"Alice", 20};
31     s3 = s; // this will not call copy constructor
32     s2.setName("Bob");
33     return 0;
34 }
35
```

6.4 COPY CONSTRUCTOR

6.4 COPY CONSTRUCTOR

- If the same class object's reference is used as a parameter, then this constructor is called a copy constructor.

6.4 COPY CONSTRUCTOR

- If the same class object's reference is used as a parameter, then this constructor is called a copy constructor.
- Features of the copy constructor

6.4 COPY CONSTRUCTOR

- If the same class object's reference is used as a parameter, then this constructor is called a copy constructor.
- Features of the copy constructor
 - It is a constructor, which will be automatically called by the system when creating an object.

6.4 COPY CONSTRUCTOR

- If the same class object's reference is used as a parameter, then this constructor is called a copy constructor.
- Features of the copy constructor
 - It is a constructor, which will be automatically called by the system when creating an object.
 - It takes an already created object as a parameter and assigns the data members of the object to the new object as needed.

6.4 COPY CONSTRUCTOR

6.4 COPY CONSTRUCTOR

- If no copy constructor is defined, the compiler will generate a default copy constructor for the class.

6.4 COPY CONSTRUCTOR

- If no copy constructor is defined, the compiler will generate a default copy constructor for the class.
- The default copy constructor uses bitwise copying to complete the copying of objects to objects.

6.5 SHALLOW COPY VS. DEEP COPY

Consider the following situation, what is the problem?

```
1  #include <iostream>
2
3  using namespace std;
4
5  class Array {
6  public:
7      explicit Array(int size) {
8          this->size = size;
9          arr = new int[size];
10     }
11     Array(const Array &other) {
12         this->size = other.size;
13         this->arr = other.arr;
14     }
15     void set(int i, int value) { arr[i] = value; }
```

6.5 SHALLOW COPY VS. DEEP COPY

Consider the following situation, what is the problem?

```
19  for (int i = 0; i < size - 1; i++)
20      cout << arr[i] << ", ";
21  (size>0 ? cout<<arr[size - 1] : cout) << "]" << endl;
22  }
23  ~Array() { delete[] arr; }
24
25  private:
26  int *arr;
27  int size;
28  };
29
30  int main() {
31      Array a{10};
32      Array b = a;
33      a.set(2, 100);
34      void set(int i, int value) { arr[i] = value; }
```

6.5 SHALLOW COPY VS. DEEP COPY

Consider the following situation, what is the problem?

```
1 #include <iostream>
2
3 using namespace std;
4
5 class Array {
6 public:
7     explicit Array(int size) {
8         this->size = size;
9         arr = new int[size];
10    }
11    Array(const Array &other) {
12        this->size = other.size;
13        this->arr = other.arr;
14    }
15    void set(int i, int value) { arr[i] = value; }
16    void set(int i, int value) { arr[i] = value; }
```

6.5 SHALLOW COPY VS. DEEP COPY

Consider the following situation, what is the problem?

```
5 class Array {  
6 public:  
7     explicit Array(int size) {  
8         this->size = size;  
9         arr = new int[size];  
10    }  
11    Array(const Array &other) {  
12        this->size = other.size;  
13        this->arr = other.arr;  
14    }  
15    void set(int i, int value) { arr[i] = value; }  
16    int get(int i) const { return arr[i]; }  
17    void print() {  
18        cout << "[";  
19        for (int i = 0; i < size - 1; i++)  
20            cout << " " << arr[i] << ", ";  
21    }
```

6.5 SHALLOW COPY VS. DEEP COPY

Consider the following situation, what is the problem?

```
8   this->size = size;
9   arr = new int[size];
10  }
11  Array(const Array &other) {
12      this->size = other.size;
13      this->arr = other.arr;
14  }
15  void set(int i, int value) { arr[i] = value; }
16  int get(int i) const { return arr[i]; }
17  void print() {
18      cout << "[";
19      for (int i = 0; i < size - 1; i++)
20          cout << arr[i] << ", ";
21      (size > 0 ? cout << arr[size - 1] : cout) << "]" << endl;
22  }
23  void set(int i, int value) { arr[i] = value; }
```


6.5 SHALLOW COPY VS. DEEP COPY

Consider the following situation, what is the problem?

```
12  this->size = other.size;
13  this->arr = other.arr;
14  }
15  void set(int i, int value) { arr[i] = value; }
16  int get(int i) const { return arr[i]; }
17  void print() {
18      cout << "[";
19      for (int i = 0; i < size - 1; i++)
20          cout << arr[i] << ", ";
21      (size > 0 ? cout << arr[size - 1] : cout) << "]" << endl;
22  }
23  ~Array() { delete[] arr; }
24
25 private:
26  int *arr;
27  void set(int i, int value) { arr[i] = value; }
```

6.5 SHALLOW COPY VS. DEEP COPY

Consider the following situation, what is the problem?

```
23 ~Array() { delete[] arr; }
24
25 private:
26 int *arr;
27 int size;
28 };
29
30 int main() {
31     Array a{10};
32     Array b = a;
33     a.set(2, 100);
34     a.print();
35     b.print();
36     return 0;
37 }
38 void set(int i, int value) { arr[i] = value; }
```

6.5 SHALLOW COPY VS. DEEP COPY

A change in one object also affects another object because they share the same memory space.

```
1  #include <iostream>
2
3  using namespace std;
4
5  class Array {
6  public:
7      explicit Array(int size) {
8          this->size = size;
9          arr = new int[size];
10     }
11     Array(const Array &other) {
12         this->size = other.size;
13         this->arr = other.arr;
14     }
```

```
15 void set(int i, int value) { arr[i] = value; }
```

6.5 SHALLOW COPY VS. DEEP COPY

A change in one object also affects another object because they share the same memory space.

```
5 class Array {  
6 public:  
7     explicit Array(int size) {  
8         this->size = size;  
9         arr = new int[size];  
10    }  
11    Array(const Array &other) {  
12        this->size = other.size;  
13        this->arr = other.arr;  
14    }
```

```
15 void set(int i, int value) { arr[i] = value; }
```

6.5 SHALLOW COPY VS. DEEP COPY

How to modify?

```
1  #include <iostream>
2
3  using namespace std;
4
5  class Array {
6  public:
7      explicit Array(int size) {
8          this->size = size;
9          arr = new int[size];
10     }
11     Array(const Array &other) {
12         this->size = other.size;
13         this->arr = other.arr;
14     }
15     void set(int i, int value) { arr[i] = value; }
```

6.5 SHALLOW COPY VS. DEEP COPY

How to modify?

```
1  #include <iostream>
2
3  using namespace std;
4
5  class Array {
6  public:
7      explicit Array(int size) {
8          this->size = size;
9          arr = new int[size];
10     }
11     Array(const Array &other) {
12         this->size = other.size;
13         this->arr = new int[this->size];
14         for (int i = 0; i < this->size; i++)
15             this->arr[i] = other.arr[i];
```


6.6 TEMPORARY OBJECTS

Consider following situation
(example/lec06/tempObject):

```
1  #include <iostream>
2
3  using namespace std;
4
5  class A {
6  public:
7      A(string id) : id(id) {
8          cout << "Constructing A with id " << id << endl;
9      }
10     A(const A &other) : id(other.id) {
11         cout << "Copy " << other.id << endl;
12     }
13
14 private:
15     string id;
```

6.6 TEMPORARY OBJECTS

Consider following situation
(example/lec06/tempObject):

```
3 using namespace std;
4
5 class A {
6 public:
7     A(string id) : id(id) {
8         cout << "Constructing A with id " << id << endl;
9     }
10    A(const A &other) : id(other.id) {
11        cout << "Copy " << other.id << endl;
12    }
13
14 private:
15     string id;
16 };
17
18 using namespace std;
```

6.6 TEMPORARY OBJECTS

Consider following situation
(example/lec06/tempObject):

```
13
14 private:
15     string id;
16 };
17
18 A returnValueFunc(A a) {
19     A b = a;
20     // If there is no return value optimization,
21     // a copy will occur here
22     return b;
23 }
24
25 int main() {
26     A a("a1");
27     A b = a;
28     string id;
29     A b = a;
```

6.6 TEMPORARY OBJECTS

Consider following situation
(example/lec06/tempObject):

```
16  };
17
18  A returnValueFunc(A a) {
19      A b = a;
20      // If there is no return value optimization,
21      // a copy will occur here
22      return b;
23  }
24
25  int main() {
26      A a("a1");
27      A b = a;
28      A c = returnValueFunc(b);
29      return 0;
30  }
31  using namespace std;
```

6.6 TEMPORARY OBJECTS

Consider following situation
(example/lec06/tempObject):

```
16  };
17
18  A returnValueFunc(A a) {
19      A b = a;
20      // If there is no return value optimization,
21      // a copy will occur here
22      return b;
23  }
24
25  int main() {
26      A a("a1");
27      A b = a;
28      A c = returnValueFunc(b);
29      return 0;
30  }
31  using namespace std;
```

6.6 TEMPORARY OBJECTS

Consider following situation
(example/lec06/tempObject):

```
16  };
17
18  A returnValueFunc(A a) {
19      A b = a;
20      // If there is no return value optimization,
21      // a copy will occur here
22      return b;
23  }
24
25  int main() {
26      A a("a1");
27      A b = a;
28      A c = returnValueFunc(b);
29      return 0;
30  }
31  using namespace std;
```

6.6 TEMPORARY OBJECTS

```
1  #include <iostream>
2
3  using namespace std;
4
5  class A {
6  public:
7      A(string id) : id(id) {
8          cout << "Constructing A with id " << id << endl;
9      }
10     A(const A &other) : id(other.id) {
11         cout << "Copy " << other.id << endl;
12     }
13
14 private:
15     string id;
```

6.6 TEMPORARY OBJECTS

How many copies occurred?

```
1  #include <iostream>
2
3  using namespace std;
4
5  class A {
6  public:
7      A(string id) : id(id) {
8          cout << "Constructing A with id " << id << endl;
9      }
10     A(const A &other) : id(other.id) {
11         cout << "Copy " << other.id << endl;
12     }
13
14 private:
15     string id;
```


6.6 TEMPORARY OBJECTS

How many copies occurred?

```
13
14 private:
15     string id;
16 };
17
18 A returnValueFunc(A a) {
19     A b = a;
20     // If there is no return value optimization,
21     // a copy will occur here
22     return b;
23 }
24
25 int main() {
26     A a("a1");
27     A b = a;
28     string ret = returnValueFunc(a);
29 }
```

6.6 TEMPORARY OBJECTS

6.6 TEMPORARY OBJECTS

- In C++, if function parameters are passed by value, a copy will occur

6.6 TEMPORARY OBJECTS

- In C++, if function parameters are passed by value, a copy will occur
- If function parameters are returned by value, it will be considered a temporary object and optimized

6.6 TEMPORARY OBJECTS

- In C++, if function parameters are passed by value, a copy will occur
- If function parameters are returned by value, it will be considered a temporary object and optimized
- You can add the `-fno-elide-constructors` parameter to disable return value optimization

6.6 TEMPORARY OBJECTS

Consider the following situation:

```
A a = A("a");
```

6.6 TEMPORARY OBJECTS

Consider the following situation:

```
A a = A("a");
```

At this point, it seems like an **unnamed object** is created using `A("a")`, and then the copy constructor is called to initialize `a`. However, in reality, the constructor will still be called.

6.7 CONSTRUCTORS FOR TYPE CONVERSION

A constructor with only one parameter can perform type conversion

```
1  class Student {  
2      Student(const string& name) : name(name) {}  
3  private:  
4      string name;  
5  };  
6  
7  void f(Student stu) {...}  
8  
9  // can be called like this  
10 f("Trump");
```


6.7 CONSTRUCTORS FOR TYPE CONVERSION

A constructor with only one parameter can perform type conversion

```
1  class Student {  
2      Student(const string& name) : name(name) {}  
3  private:  
4      string name;  
5  };  
6  
7  void f(Student stu) {...}  
8  
9  // can be called like this  
10 f("Trump");
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

A constructor with only one parameter can perform type conversion

```
1  class Student {  
2      Student(const string& name) : name(name) {}  
3  private:  
4      string name;  
5  };  
6  
7  void f(Student stu) {...}  
8  
9  // can be called like this  
10 f("Trump");
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

A constructor with only one parameter can perform type conversion

```
1  class Student {  
2      Student(const string& name) : name(name) {}  
3  private:  
4      string name;  
5  };  
6  
7  void f(Student stu) {...}  
8  
9  // can be called like this  
10 f("Trump");
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

A constructor with only one parameter can perform type conversion

```
1  class Student {  
2      Student(const string& name) : name(name) {}  
3  private:  
4      string name;  
5  };  
6  
7  void f(Student stu) {...}  
8  
9  // can be called like this  
10 f("Trump");
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

A constructor with only one parameter can perform type conversion

```
1  class Student {  
2      Student(const string& name) : name(name) {}  
3  private:  
4      string name;  
5  };  
6  
7  void f(Student& stu) {...} // cannot do this  
8  
9  // can be called like this  
10 f("Trump");
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

A constructor with only one parameter can perform type conversion

```
1  class Student {  
2      Student(const string& name) : name(name) {}  
3  private:  
4      string name;  
5  };  
6  
7  void f(const Student& stu) {...} // this is ok  
8  
9  // can be called like this  
10 f("Trump");
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

A constructor with only one parameter can perform type conversion

```
1  class Student {  
2      Student(const string& name) : name(name) {}  
3  private:  
4      string name;  
5  };  
6  
7  void f(Student&& stu) {...} // this is also ok  
8  
9  // can be called like this  
10 f("Trump");
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

6.7 CONSTRUCTORS FOR TYPE CONVERSION

Consider the following situation:

6.7 CONSTRUCTORS FOR TYPE CONVERSION

Consider the following situation:

```
1  class A {  
2  public:  
3      int i;  
4      A(int n) : i(n) {}  
5  };  
6  
7  class B {  
8  public:  
9      int i;  
10     B(int n) : i(n) {}  
11 };  
12  
13 void f(A a) {}  
14 void f(B b) {} // overload  
15
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

Consider the following situation:

```
1  class A {  
2  public:  
3      int i;  
4      A(int n) : i(n) {}  
5  };  
6  
7  class B {  
8  public:  
9      int i;  
10     B(int n) : i(n) {}  
11 };  
12  
13 void f(A a) {}  
14 void f(B b) {} // overload  
15
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

Consider the following situation:

```
2 public:
3     int i;
4     A(int n) : i(n) {}
5 };
6
7 class B {
8 public:
9     int i;
10    B(int n) : i(n) {}
11 };
12
13 void f(A a) {}
14 void f(B b) {} // overload
15
16 int main() {
17
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

Consider the following situation:

```
5  };
6
7  class B {
8  public:
9      int i;
10     B(int n) : i(n) {}
11 };
12
13 void f(A a) {}
14 void f(B b) {} // overload
15
16 int main() {
17     f(10); // compile error!
18     return 0;
19 }
20
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

Consider the following situation:

```
5  };
6
7  class B {
8  public:
9      int i;
10     B(int n) : i(n) {}
11 };
12
13 void f(A a) {}
14 void f(B b) {} // overload
15
16 int main() {
17     f(10); // compile error!
18     return 0;
19 }
1~
```

6.7 CONSTRUCTORS FOR TYPE CONVERSION

6.7 CONSTRUCTORS FOR TYPE CONVERSION

- This situation is usually not needed

6.7 CONSTRUCTORS FOR TYPE CONVERSION

- This situation is usually not needed
- And it's harmful (implicit type conversion should be avoided as much as possible, as it can easily cause ambiguity)

6.7 CONSTRUCTORS FOR TYPE CONVERSION

- This situation is usually not needed
- And it's harmful (implicit type conversion should be avoided as much as possible, as it can easily cause ambiguity)
- Good programming style:

6.7 CONSTRUCTORS FOR TYPE CONVERSION

- This situation is usually not needed
- And it's harmful (implicit type conversion should be avoided as much as possible, as it can easily cause ambiguity)
- Good programming style:
 - If the constructor has only one parameter

6.7 CONSTRUCTORS FOR TYPE CONVERSION

- This situation is usually not needed
- And it's harmful (implicit type conversion should be avoided as much as possible, as it can easily cause ambiguity)
- Good programming style:
 - If the constructor has only one parameter
 - Then add the `explicit` keyword before the constructor

6.8 FURTHER READING

6.8 FURTHER READING

- In fact, function passing values by copy is a performance issue. Modern C++ introduced `std::move` to solve this problem.

6.8 FURTHER READING

- In fact, function passing values by copy is a performance issue. Modern C++ introduced `std::move` to solve this problem.
- Similarly, to solve this problem, the Rust language introduced the Ownership concept.

6.8 FURTHER READING

- In fact, function passing values by copy is a performance issue. Modern C++ introduced `std::move` to solve this problem.
- Similarly, to solve this problem, the Rust language introduced the Ownership concept.
- Reference materials:

6.8 FURTHER READING

- In fact, function passing values by copy is a performance issue. Modern C++ introduced `std::move` to solve this problem.
- Similarly, to solve this problem, the Rust language introduced the Ownership concept.
- Reference materials:
 - [lvalues and rvalues in C++ - Youtube](#)

6.8 FURTHER READING

- In fact, function passing values by copy is a performance issue. Modern C++ introduced `std::move` to solve this problem.
- Similarly, to solve this problem, the Rust language introduced the Ownership concept.
- Reference materials:
 - [lvalues and rvalues in C++ - Youtube](#)
 - [Understanding Ownership - The Rust Programming Language](#)

CHALLENGE

Implement your own vector

- Do not use generics, only for int type
- Initial memory size is 8
- If memory is insufficient, automatically expand memory (current memory quantity multiplied by 2)
- capacity returns memory size
- size returns the number of elements
- `int get(int index) const` and `std::optional<int> safe_get(int index) const`
- `bool set(int index, int value)`
- `std::string to_string() const`

CHALLENGE

Implement your own vector

ADVANCED

CHALLENGE

Implement your own vector

ADVANCED

- Copy constructor

CHALLENGE

Implement your own vector

ADVANCED

- Copy constructor
- Copy constructor for right value reference

CHALLENGE

Implement your own vector

ADVANCED

- Copy constructor
- Copy constructor for right value reference
- Test these two constructors using `std::move`

CHALLENGE

Implement your own vector

ADVANCED

- Copy constructor
- Copy constructor for right value reference
- Test these two constructors using `std::move`
- Implement `push_back`: automatically expand memory when capacity is insufficient