

Lab1 : back-propagation

Lab Objective:

In this lab, you will need to understand and write a simple neural networks with forward pass and backpropagation using two hidden layers. Noticed that you only can use Numpy and other python standard library, any other framework (ex : Tensorflow 、PyTorch) is not allowed in this lab.




Figure 1. Two layers neural network

Important Date:

1. Experiment Report Submission Deadline: 7/18 (Thu) 12:00 p.m.
2. Demo date: 7/18 (Thu)

Turn in:

1. Experiment Report (.pdf)
2. Source code

Notice: zip all files in one file and name it like 「**DLP_LAB1_your studentID_name.zip**」, ex: 「**DLP_LAB1_0756051_李仕柏.zip**」

Requirements:

1. Implement a simple neural networks with two hidden layers
2. You must use backpropagation in this neural network and only can use Numpy and other python standard library to implement
3. Plot your comparison figure that show the predict result and ground truth

Implementation Details:




Figure 2. Forward pass

- In the figure 2, we used the following definitions for the notations:
 - x_1, x_2 : *nerual network inputs*
 - X : $[x_1, x_2]$
 - y : *nerual network outputs*
 - \hat{y} : *ground truth*
 - $L(\theta)$: *loss function*
 - W_1, W_2, W_3 : *weight matrix of network layers*

- Here are the computations represented:


$$Z_1 = \sigma(XW_1) \quad Z_2 = \sigma(Z_1W_2) \quad y = \sigma(Z_2W_3)$$

- In the equations, the σ is sigmoid function that refers to the special case of the **logistic** function and defined by the formula:

$$\sigma(x) = \frac{1}{1+e^{-x}}$$

- Input / Test:**

The inputs are two kinds which showing at below.



You need to use the following `generate` function to create your inputs `x`, `y`.

```
def generate_linear(n=100):
    import numpy as np
    pts = np.random.uniform(0, 1, (n, 2))
    inputs = []
    labels = []
    for pt in pts:
        inputs.append([pt[0], pt[1]])
        distance = (pt[0]-pt[1])/1.414
        if pt[0] > pt[1]:
            labels.append(0)
        else:
            labels.append(1)
    return np.array(inputs), np.array(labels).reshape(n, 1)
```

```
def generate_XOR_easy():
    import numpy as np
    inputs = []
    labels = []

    for i in range(11):
        inputs.append([0.1*i, 0.1*i])
        labels.append(0)

        if 0.1*i == 0.5:
            continue

        inputs.append([0.1*i, 1-0.1*i])
        labels.append(1)

    return np.array(inputs), np.array(labels).reshape(21, 1)
```


Function usage

```
x, y = generate_linear(n=100)
x, y = generate_XOR_easy()
```

In the training, you need to print loss; In the testing, you need to show your predictions as shown below.

epoch 10000	loss : 0.16234523253277644	[0.01025062]
epoch 15000	loss : 0.2524336634177614	[0.99730607]
epoch 20000	loss : 0.1590783047540092	[0.02141321]
epoch 25000	loss : 0.22099447030234853	[0.99722154]
epoch 30000	loss : 0.3292173477217561	[0.03578171]
epoch 35000	loss : 0.40406233282426085	[0.99701922]
epoch 40000	loss : 0.43052897480298924	[0.04397049]
epoch 45000	loss : 0.4207525735586605	[0.99574117]
epoch 50000	loss : 0.3934759509342479	[0.04162245]
epoch 55000	loss : 0.3615008372106921	[0.92902792]
epoch 60000	loss : 0.33077879872648525	[0.03348791]
epoch 65000	loss : 0.30333537090819584	[0.02511045]
epoch 70000	loss : 0.2794858089741792	[0.94093942]
epoch 75000	loss : 0.25892812312991587	[0.01870069]
epoch 80000	loss : 0.24119780823897027	[0.99622948]
epoch 85000	loss : 0.22583656353511342	[0.01431959]
epoch 90000	loss : 0.21244497028971704	[0.99434455]
epoch 95000	loss : 0.2006912468389013	[0.01143039]
		[0.98992477]
		[0.00952752]
		[0.98385905]

Visualize the predictions and ground truth at the end of the training process.
The comparison figure should like example as below.



You can refer to the following visualization code

x: inputs (2-dimensional array)

y: ground truth label (1-dimensional array)

pred_y: outputs of neural network (1-dimensional array)

```
def show_result(x, y, pred_y):
    import matplotlib.pyplot as plt
    plt.subplot(1,2,1)
    plt.title('Ground truth', fontsize=18)
    for i in range(x.shape[0]):
        if y[i] == 0:
            plt.plot(x[i][0], x[i][1], 'ro')
        else:
            plt.plot(x[i][0], x[i][1], 'bo')

    plt.subplot(1,2,2)
    plt.title('Predict result', fontsize=18)
    for i in range(x.shape[0]):
        if pred_y[i] == 0:
            plt.plot(x[i][0], x[i][1], 'ro')
        else:
            plt.plot(x[i][0], x[i][1], 'bo')

    plt.show()
```

- **Sigmoid functions:**

1. A sigmoid function is a mathematical function having a characteristic "S"-shaped curve or sigmoid curve. It is a bounded, differentiable, real function that is defined for all real input values and has a non-negative derivative at each point. In general, a sigmoid function is monotonic, and has a first derivative which is bell shaped.
2. (hint) You may write the function like this:

```
def sigmoid(x):  
    return 1.0/(1.0 + np.exp(-x))
```

3. (hint) The derivative of sigmoid function

```
def derivative_sigmoid(x):  
    return np.multiply(x, 1.0 - x)
```

- **Back Propagation (Gradient computation)**

Backpropagation is a method used in artificial neural networks to calculate a gradient that is needed in the calculation of the weights to be used in the network. Backpropagation is a generalization of the delta rule to multi-layered feedforward networks, made possible by using the chain rule to iteratively compute gradients for each layer. The backpropagation learning algorithm can be divided into two parts; **propagation** and **weight update**.

Part 1: Propagation

Each propagation involves the following steps:

1. Propagation forward through the network to generate the output value
2. Calculation of the cost $L(\theta)$ (error term)
3. Propagation of the output activations back through the network using the training pattern target in order to generate the deltas (the difference between the targeted and actual output values) of all output and hidden neurons.

Part 2: Weight update

For each weight-synapse follow the below steps:

1. Multiply its output delta and input activation to get the gradient of the weight.
2. Subtract a ratio (percentage) of the gradient from the weight.

3. This ratio (percentage) influences the speed and quality of learning; it is called the **learning rate**. The greater the ratio, the faster the neuron trains; the lower the ratio, the more accurate the training is. The sign of the gradient of a weight indicates where the error is increasing, this is why the weight must be updated in the opposite direction.

Repeat part. 1 and 2 until the performance of the network is satisfactory.

Pseudocode:

```
initialize network weights (often small random values)
do
  forEach training example named ex
    prediction = neural-net-output(network, ex) // forward pass
    actual = teacher-output(ex)
    compute error (prediction - actual) at the output units
    compute  $\Delta w_h$  for all weights from hidden layer to output layer // backward pass
    compute  $\Delta w_i$  for all weights from input layer to hidden layer // backward pass continued
    update network weights // input layer not modified by error estimate
until all examples classified correctly or another stopping criterion satisfied
return the network
```

Report Spec

1. Introduction (20%)
2. Experiment setups (30%):
 - A. Sigmoid functions
 - B. Neural network
 - C. Backpropagation
3. Results of your testing (30%)
 - A. Screenshot and comparison figure
 - B. anything you want to present
4. Discussion (20%)
 - A. Anything you want to share

Score:

60% demo score (experimental results & questions) + 40% report
If the zip file name or the report spec have format error, you will be punished (-5)

Reference:

1. Logical regression:
http://www.bogotobogo.com/python/scikit-learn/logistic_regression.php
2. Python tutorial:
<https://docs.python.org/3/tutorial/>
3. Numpy tutorial:
<https://www.tutorialspoint.com/numpy/index.htm>
4. Python Standard Library:
<https://docs.python.org/3/library/index.html>
5. http://speech.ee.ntu.edu.tw/~tlkagk/courses/ML_2016/Lecture/BP.pdf
6. https://en.wikipedia.org/wiki/Sigmoid_function
7. <https://en.wikipedia.org/wiki/Backpropagation>