

CS 271 Computer Architecture and Assembly Language

Self-Check for Lecture #2 Solutions

1. Terms / Definitions

- “caching” is moving information from slower storage to faster storage, where it can be accessed more quickly.
- A “bus” is a set of parallel "wires" for transferring a set of electrical signals simultaneously.
- “vonNeumann architecture” refers to computer architectures that store programs in memory, and execute them under the control of the instruction execution cycle.

2. Inside the computer, machine instructions, memory addresses, numbers, characters, etc., are all represented as electrical signals.

3. In the simple CISC architecture discussed in Lecture #2, which register holds
- the current machine instruction? The Instruction Register (IR).
 - the current micro-instruction? The Control Register.

4. Number the order of steps in the instruction execution cycle.

3

Decode the instruction in the Instruction Register.

4

If the instruction requires memory access, determine the memory address, and fetch the operand from memory into a CPU register, or send the operand from a CPU register to memory.

2

Increment the Instruction Pointer to point to next instruction.

5

Execute the instruction.

1

Fetch the instruction at the address in the Instruction Pointer into the Instruction Register.

6

Repeat from step 1.

5. Consider the virtual machine levels in the diagram at the right. At each level (except 0 and 5), an interpreter accepts an instruction from the level above, converts the instruction to its own language, and passes the resulting instructions to the level below. Note that Level-0 has no interpreter; the instructions from the Micro-architecture level are sent directly to the hardware.

Suppose that the interpreters at each level (levels 1 - 4) generate n instructions in order to represent one instruction from the level above. Suppose also that each Level-0 instruction executes in c nanoseconds.

- a. How long does it take to execute a Level-3 instruction?

cn^2 ns. Going from level-3 to level-2 creates n instructions. For each of those n instructions, going from level-2 to level-1 creates n instructions, so there will be n^2 micro-instructions, each of which requires c nano-seconds to execute.

- b. How long does it take to execute a Level-5 instruction?

cn^4 ns.

