

# Mechanising Denotational Semantics in Agda

## Complete Code Listing

Peter D. Mosses<sup>a,1</sup> Jesper Cockx<sup>a,2</sup> Bernhard Reus<sup>b,3</sup>

<sup>a</sup> *Department of Computer Science  
Delft University of Technology  
Delft, Netherlands*

<sup>b</sup> *School of Engineering and Informatics  
University of Sussex  
Brighton, United Kingdom*

---

### Abstract

Formalisation of a semantic definition helps to ensure its wellformedness, and supports proofs about it. To minimise the effort required, formalisation should not involve significant reformulation or extension of the original definition. Here, we show how to formalise conventional Scott–Strachey denotational definitions by embedding them in Agda with almost no changes to  $\lambda$ -notation or domain equations.

We illustrate our approach with three examples: Scott’s  $D_\infty$  model of the untyped  $\lambda$ -calculus, Plotkin’s denotational semantics of PCF, and a semantics of a sublanguage of Scheme. Using appropriate postulates for domain constructors and their associated operations, the Agda type checker confirms the wellformedness of the embedded definitions. In previous work, such Agda formalisations have revealed several unsuspected wellformedness issues in published denotational definitions.

Some of our postulates are inconsistent with a classical set-theoretic interpretation of Agda. We conjecture that they would be consistent with an interpretation of Agda in the higher-order intuitionistic logic used by Alex Simpson in his work on synthetic domain theory.

*Keywords:* Denotational semantics, formalisation, mechanisation, Agda, postulates, synthetic domain theory

---

---

<sup>1</sup> Email: [p.d.mosses@tudelft.nl](mailto:p.d.mosses@tudelft.nl)

<sup>2</sup> Email: [j.g.h.cockx@tudelft.nl](mailto:j.g.h.cockx@tudelft.nl)

<sup>3</sup> Email: [bernhard@sussex.ac.uk](mailto:bernhard@sussex.ac.uk)

## Contents

|       |                                                      |    |
|-------|------------------------------------------------------|----|
| 3     | Postulated Domain Notation                           | 3  |
| 3.1   | Domains                                              | 3  |
| 3.2   | Function domains                                     | 3  |
| 3.3   | Recursive domains                                    | 4  |
| 3.4   | Flat domains                                         | 4  |
| 3.4.1 | Booleans                                             | 4  |
| 3.4.2 | Naturals                                             | 4  |
| 3.5   | Sum domains                                          | 5  |
| 3.6   | Product domains                                      | 5  |
| 3.6.1 | Tuples                                               | 6  |
| 3.6.2 | Sequences                                            | 6  |
| 3.7   | Updates                                              | 6  |
| 4     | Illustrative Examples                                | 7  |
| 4.1   | Untyped Lambda-Calculus                              | 7  |
| 4.1.1 | Abstract Syntax                                      | 7  |
| 4.1.2 | Domain Equations                                     | 7  |
| 4.1.3 | Semantic Functions                                   | 7  |
| 4.2   | PCF: A Programming Language for Computable Functions | 8  |
| 4.2.1 | Abstract Syntax                                      | 8  |
| 4.2.2 | Domain Equations                                     | 8  |
| 4.2.3 | Semantic functions                                   | 9  |
| 4.3   | Scm: A Sublanguage of Scheme                         | 10 |
| 4.3.1 | Abstract Syntax                                      | 10 |
| 4.3.2 | Domain Equations                                     | 10 |
| 4.3.3 | Auxiliary Functions                                  | 11 |
| 4.3.4 | Semantic Functions                                   | 12 |
| 5     | Postulated Properties                                | 13 |
| 6     | Illustrative Tests                                   | 14 |
| 6.1   | LC Tests                                             | 14 |
| 6.2   | PCF Tests                                            | 14 |
|       | References                                           | 15 |

### 3 Postulated Domain Notation

This section postulates Agda notation for the domain constructors and associated functions used in the [illustrative examples](#) (Section 4). See the accompanying website [2] for hyperlinked, highlighted listings of the complete Agda code for elided details such as module imports, fixity declarations, and declarations of the types of meta-variables. In the PDF, references to names of sections are links to the website.

#### 3.1 Domains

Domains are embedded in Agda as elements of the type `Domain`. A domain  $D$  is not itself a type, but it has a *carrier* type  $\ll D \gg : \text{Set}$ , which always contains an element  $\perp\{D\}$  (written  $\perp$  when Agda can infer  $D$ ).

```
module Domains where
  postulate
    Domain : Set          -- Domain is the type of all domains
     $\ll\_ \gg$  : Domain  $\rightarrow$  Set --  $\ll D \gg$  is the carrier type of D
     $\perp$  :  $\{D : \text{Domain}\} \rightarrow \ll D \gg$  --  $\perp\{D\}$  is the 'bottom' element of D
```

Some previous papers on embedding denotational semantics in Agda [3,4,5] defined domains to be types: `Domain = Set`. However, postulating  $\perp : D$  for all  $D : \text{Domain}$  was then *inconsistent* with the existence of an empty type in Agda. Postulating `Domain : Set` avoids that inconsistency.

The notation for domains postulated in this section supports type-checking embeddings of denotational semantics in Agda such as those in the [illustrative examples](#) (Section 4). It does *not* define or constrain the *mathematical structure* of domains, nor the algebraic and universal properties of the associated functions.

#### 3.2 Function domains

The conventional notation in denotational definitions for the domain of continuous functions from  $D$  to  $E$  is  $D \rightarrow E$  or  $[D \rightarrow E]$ . However, Agda reserves the notation  $D \rightarrow E$  for the *type* of *all* (total) functions from type  $D$  to type  $E$ ; instead, we use the notation  $D \rightarrow^c E$  for embedding continuous function domains:

```
module Functions where
  postulate  $\_ \rightarrow^c \_$  : Domain  $\rightarrow$  Domain  $\rightarrow$  Domain
```

Both  $\lambda$ -abstraction and application preserve continuity. In conventional denotational semantics, functions between domains are defined using  $\lambda$ -abstraction and application from primitive continuous functions associated with specific domain constructors, so they are *automatically* continuous.

This motivates treating the carrier  $\ll D \rightarrow^c E \gg$  of the embedding of a function domain as a type of continuous functions. In particular, embeddings of *endofunctions*  $\varphi$  on a domain  $D$  should always have fixed points  $\text{fix } \varphi$ , with  $\text{fix}$  itself also being continuous:

```
postulate fix :  $\ll (D \rightarrow^c D) \rightarrow^c D \gg$ 
```

In Agda, it appears that proving specific functions defined in  $\lambda$ -notation to be continuous requires pairing each  $\lambda$ -abstraction with an explicit proofs of its continuity, which is quite impractical (especially when embedding denotations defined in continuation-passing style).

However, to support type-checking the *direct* embedding of  $\lambda$ -notation from conventional denotational definitions in Agda, it appears to be necessary to *rewrite* the carriers of function domains to ordinary function types:

```
postulate dom-cts :  $\ll D \rightarrow^c E \gg \equiv (\ll D \gg \rightarrow \ll E \gg)$ 
{-# REWRITE dom-cts #-}
```

Similarly, the notation  $A \rightarrow^s D$  is the embedding of the domain of all functions from an ordinary type  $A$  to a domain  $D$  (which are trivially continuous, ordered pointwise):

```

postulate  $\_ \rightarrow^s \_ : \text{Set} \rightarrow \text{Domain} \rightarrow \text{Domain}$ 
postulate set-cts :  $\langle\langle A \rightarrow^s D \rangle\rangle \equiv (A \rightarrow \langle\langle D \rangle\rangle)$ 
{-# REWRITE set-cts #-}

```

### 3.3 Recursive domains

Conventional denotational semantics often involves groups of mutually recursive domain definitions. In Agda, recursive type definitions lead to non-termination of the type-checker. To avoid non-termination, it is sufficient to break the recursion by leaving (one or more) domains as *postulated*. The following operations can then be used to map values from a postulated domain to its structure and *vice versa* (as in [1]).

```

module Recursion where
postulate
   $\_ \cong \_ : \text{Domain} \rightarrow \text{Domain} \rightarrow \text{Set}$ 
  -- an instance of  $D \cong E$  declares that the structure of D is the same as E
  unfold :  $\{\{D \cong E\}\} \rightarrow \langle\langle D \rightarrow^c E \rangle\rangle$ 
  fold    :  $\{\{D \cong E\}\} \rightarrow \langle\langle E \rightarrow^c D \rangle\rangle$ 

```

The *instance parameter*  $\{\{D \cong E\}\}$  of the above operations restricts them to domains  $D$  and  $E$  such that  $\text{instance } \_ : D \cong E$  has been declared. (Instance parameters do not correspond to arguments of embedded functions on domains.)

### 3.4 Flat domains

Lifting an ordinary set  $A$  by adding a  $\perp$  element gives a flat domain, usually written  $A_\perp$ . The Agda module `Flat` postulates a corresponding domain constructor  $A + \perp$ , together with a function  $\uparrow$  for injecting elements of  $A$  into  $A + \perp$ , and an operator  $f^\#$  for extending a function  $f$  on  $A$  to a continuous function on  $A + \perp$ .

```

module Flat where
postulate
   $\_ + \perp : \text{Set} \rightarrow \text{Domain}$  --  $A + \perp$  constructs a flat domain
   $\uparrow : \langle\langle A \rightarrow^s (A + \perp) \rangle\rangle$  --  $(\uparrow a)$  injects  $a$  into  $A + \perp$ 
   $\_^\# : \langle\langle (A \rightarrow^s D) \rightarrow^c (A + \perp) \rightarrow^c D \rangle\rangle$  --  $f^\#$  extends  $f$  to map  $\perp$  to  $\perp$ 

```

#### 3.4.1 Booleans

The McCarthy conditional operation  $\beta \rightarrow \delta_1, \delta_2$  extends the usual ternary conditional choice to domains. It returns  $\perp$  whenever its first argument is  $\perp$ .

```

module Booleans where
  Bool $\perp$  = Bool +  $\perp$ 
   $\_ \rightarrow \_, \_ : \langle\langle \text{Bool}\perp \rightarrow^c D \rightarrow^c D \rightarrow^c D \rangle\rangle$  --  $\beta \rightarrow \delta_1, \delta_2$  is conditional choice
   $\_ \rightarrow \_, \_ = (\lambda b \delta_1 \delta_2 \rightarrow \text{if } b \text{ then } \delta_1 \text{ else } \delta_2)^\#$ 

```

The `Booleans` module also defines `Eq A` for use as an instance parameter restricting to types  $A$  such that  $\_ == \_ : A \rightarrow A \rightarrow \text{Bool}$ , and postulates an operation  $\delta_1 == \perp \delta_2$  on  $A + \perp$ .

#### 3.4.2 Naturals

Agda allows decimal notation for natural numbers, as well as unary notation using `zero` and `suc`.

```

module Naturals where
  Nat $\perp$  = Nat +  $\perp$ 

```

### 3.5 Sum domains

The separated sum  $D + E$  of two domains corresponds to lifting the disjoint union of their carrier sets. The following operations can be used directly for binary sums, and iterated for domains with more than two summands.

```

module Sums where
  postulate
    _+_      : Domain → Domain → Domain -- D + E is separated sum
    inj1    : ⟨⟨ D →c (D + E) ⟩⟩          -- inj1 δ is injection from D
    inj2    : ⟨⟨ E →c (D + E) ⟩⟩          -- inj2 ε is injection from E
    [_,_]    : ⟨⟨ (D →c F) →c (E →c F) →c ((D + E) →c F) ⟩⟩
    -- [ φ , ψ ] applies φ to arguments in D, and ψ to arguments in E
    
```

Agda also supports type-checking the notation explained in §2.1. However, instead of defining the summands  $D$  of a separated sum domain  $E$  by an equation  $E = \dots + D + \dots$ , the domain  $E$  is merely *postulated*, and each summand is declared separately by *instance*  $\_ : E \gtrsim n \mapsto D$  (where  $n$  should be a different natural number for each summand). The inherently *dependent* types of the summand operations are as follows.

```

postulate
  _~→_ : Domain → Nat → Domain → Set
  _in⊥_ : ⟨⟨ D ⟩⟩ → (E : Domain) → { { E ~ n → D } } → ⟨⟨ E ⟩⟩ -- δ in⊥ E injection
  _|⊥_ : ⟨⟨ E ⟩⟩ → (D : Domain) → { { E ~ n → D } } → ⟨⟨ D ⟩⟩ -- ε |⊥ D projection
  _∈⊥_ : ⟨⟨ E ⟩⟩ → (D : Domain) → { { E ~ n → D } } → ⟨⟨ Bool⊥ ⟩⟩ -- ε ∈⊥ D test
    
```

The operations are defined only for  $D$  and  $E$  where an instance of type  $E \gtrsim n \mapsto D$  is declared for some  $n$ .

### 3.6 Product domains

The carrier of the binary cartesian product of two domains consists of all pairs of elements of the carriers of the argument domains. Neither the product nor pairing is associative. The following operations can be used directly for binary products, and iterated for products of more than two domains.

module **Products** where

postulate

```

_×_ : Domain → Domain → Domain -- D × E is cartesian product
_,_ : ⟨⟨ D →c E →c (D × E) ⟩⟩ -- (δ , ε) is a pair of elements
_↓1 : ⟨⟨ (D × E) →c D ⟩⟩ -- (δ , ε)↓1 is δ
_↓2 : ⟨⟨ (D × E) →c E ⟩⟩ -- (δ , ε)↓2 is ε
    
```

### 3.6.1 Tuples

The domain  $D^n$  of  $n$ -tuples of elements of a domain  $D$  is conventionally written  $D^n$ , but Agda does not support the use of variables as superscripts.

module **Tuples** where

```

_ ^ n : Domain → Nat → Domain -- D ^ n is the domain of n-tuples (n ≥ 0)
    
```

### 3.6.2 Sequences

The domain  $D^*$  of finite sequences of elements of a domain  $D$  is conventionally written  $D^*$ .

The following notation for the various operations on sequences was introduced and extensively used by Strachey and his colleagues in the early 1970s. (The single angle-brackets  $\langle \dots \rangle$  used to form sequences are unrelated to the double angle-brackets  $\langle\langle D \rangle\rangle$  used for the carrier of domain  $D$ .)

module **Sequences** where

postulate

```

_ * _ : Domain → Domain -- D * is the finite sequence domain
⟨⟩ : ⟨⟨ D * ⟩⟩ -- ⟨⟩ is the empty sequence
⟨_⟩ : ⟨⟨ (D ^ suc n) →c D * ⟩⟩ -- ⟨ δ1 , ... ⟩ is a non-empty sequence
# : ⟨⟨ D * →c Nat ⊥ ⟩⟩ -- # δ* is the length of sequence δ*
_ § _ : ⟨⟨ D * →c D * →c D * ⟩⟩ -- δ*1 § δ*2 is sequence concatenation
_ ↓ _ : ⟨⟨ D * →c Nat →s D ⟩⟩ -- δ* ↓ n is the nth element
_ † _ : ⟨⟨ D * →c Nat →s D * ⟩⟩ -- δ* † n is the nth tail
    
```

### 3.7 Updates

When an ordinary Agda type  $A$  has an equality operation  $_ == _ : A \rightarrow A \rightarrow \text{Bool}$ , environments  $\rho : \langle\langle A \rightarrow^s D \rangle\rangle$  can be ‘updated’ (i.e., extended or overridden) using the conventional notation  $\rho [ \delta / a ]$ , defined as follows.

module **Updates** where

```

_ [ _ / _ ] : { {Eq A}} → ⟨⟨ (A →s D) →c D →c A →s (A →s D) ⟩⟩
-- ρ [ δ / a ] maps a to δ, and other arguments a' to ρ a'
ρ [ δ / a ] = λ a' → if a == a' then δ else ρ a'
    
```

Similarly for stores  $\sigma : \langle\langle (A + \perp) \rightarrow^c D \rangle\rangle$ :

```

_ [ _ / _ ] ⊥ : { {Eq A}} → ⟨⟨ ((A + ⊥) →c D) →c D →c (A + ⊥) →c ((A + ⊥) →c D) ⟩⟩
-- σ [ δ / α ] ⊥ maps α to δ, and other arguments α' to σ α'
σ [ δ / α ] ⊥ = λ α' → (α == ⊥ α') → δ , σ α'
    
```

Defining an operation  $_ [ \_ \leftarrow \_ ]$  for extension or overriding of *dependent* maps is [less straightforward](#), as it involves a function that returns an *equivalence proof* instead of a truth value.

## 4 Illustrative Examples

This section illustrates mechanisation of denotational semantics in Agda with three examples, all using the [postulated notation](#) (Section 3) for domains and their associated operations: the [Untyped Lambda-Calculus](#) (Section 4.1), [PCF: A Programming Language for Computable Functions](#) (Section 4.2), and [Scm: A Sublanguage of Scheme](#) (Section 4.3).

### 4.1 Untyped Lambda-Calculus

This section presents an Agda formalisation of a denotational semantics of the untyped  $\lambda$ -calculus. Elided module imports are included in the [complete code listing](#).

#### 4.1.1 Abstract Syntax

Abstract syntax is *not* regarded as a domain. In conventional Scott–Strachey style denotational semantics, abstract syntax is generally first-order: terms are finite, totally-defined elements.

A variable is written  $x\ n$ . The argument  $n$  merely distinguishes between variables – it is *not* a De Bruin index. The term constructor `var` below includes variables in terms.

In Agda, mixfix notation requires argument positions `_` to be separated by characters other than spaces. The term constructors for function abstraction and application use the Unicode character `⌊` as a separator.

```
module Examples.LC.Abstract-Syntax where
data Var : Set where
  x : Nat → Var
data Exp : Set where
  var _      : Var → Exp      -- variable reference
  (λ _ ⌊ _ ⌋) : Var → Exp → Exp -- function abstraction
  (⌊ _ ⌋ _ ) : Exp → Exp → Exp -- function application
```

#### 4.1.2 Domain Equations

The postulate `eqD $\infty$`  below declares `unfold` :  $\ll D_{\infty} \rightarrow^c (D_{\infty} \rightarrow^c D_{\infty}) \gg$  and `fold` :  $\ll (D_{\infty} \rightarrow^c D_{\infty}) \rightarrow^c D_{\infty} \gg$ , corresponding to a bijection between the domain  $D_{\infty}$  and the domain of continuous endofunctions on  $D_{\infty}$ . (Simply defining  $D_{\infty} = (D_{\infty} \rightarrow^c D_{\infty})$  would lead to non-termination of the Agda type-checker.)

```
module Examples.LC.Domain-Equations where
postulate
  D $\infty$  : Domain                -- corresponds to Scott's domain
  instance eqD $\infty$  : D $\infty$   $\cong$  (D $\infty$   $\rightarrow^c$  D $\infty$ ) -- bijection
  Env = Var  $\rightarrow^s$  D $\infty$  -- environments
```

Use of the conventional notation  $\rho \ [ \ \delta \ / \ v \ ]$  for updating an environment  $\rho$  to map  $v$  to  $d$  requires an equality test for variables (see the [complete code listing](#)).

#### 4.1.3 Semantic Functions

The semantic equations below correspond closely to those found in textbooks on denotational semantics (e.g., [7]).

```
module Examples.LC.Semantic-Functions where
[ _ ] : Exp →  $\ll$  Env  $\rightarrow^c$  D $\infty$   $\gg$ 
[ var v ]  $\rho$       =  $\rho\ v$ 
[ (λ v ⌊ e ⌋) ]  $\rho$  = fold ( λ  $\delta$  → [ e ] ( $\rho\ [ \ \delta \ / \ v \ ]$ ) )
[ (⌊ e1 ⌋ e2 ⌋) ]  $\rho$  = unfold ( [ e1 ]  $\rho$  ) ( [ e2 ]  $\rho$  )
```

## 4.2 PCF: A Programming Language for Computable Functions

PCF and its denotational semantics were originally defined by Dana Scott in 1969 [9] with combinators (S, K) instead of  $\lambda$ -abstraction. Gordon Plotkin subsequently defined a denotational semantics for PCF including  $\lambda$ -abstraction [6]. The Agda modules presented below are an embedding of the latter definition.

PCF is an intrinsically typed language: every well-formed term has a unique type. The following grammar summarises the context-free abstract syntax of types  $\sigma, \tau$  and terms  $M, N$  with variables  $\alpha_i^\sigma$  ( $i \geq 0$ ) and constants  $c$ . In §4.1.1 we reflect Plotkin’s presentation of PCF more accurately by exploiting Agda’s support for dependent types.

$$\sigma, \tau ::= \iota \mid o \mid (\sigma \rightarrow \tau) \quad (1)$$

$$c ::= tt \mid ff \mid \top \mid \mathbf{Y} \mid k_n \mid (+1) \mid (-1) \mid \mathbf{Z} \quad (2)$$

$$M, N ::= \alpha_i^\sigma \mid c \mid (M N) \mid (\lambda \alpha_i^\sigma M) \quad (3)$$

### 4.2.1 Abstract Syntax

The following abstract syntax of well-formed PCF terms in Agda uses indexed datatype definitions. PCF function types  $\sigma \rightarrow \tau$  are written  $\sigma \Rightarrow \tau$ , and variables  $\alpha_i^\sigma$  are written  $\alpha \text{ i } \sigma$  (where the argument  $i$  merely distinguishes between variables – it is *not* a De Bruin index).

module Examples.PCF.Abstract-Syntax where

```

data Types : Set where
   $\iota$       : Types                -- type terms
  o        : Types                -- individuals
  o        : Types                -- truth-values
   $\_ \Rightarrow \_$  : Types  $\rightarrow$  Types  $\rightarrow$  Types -- functions

data Vars : Types  $\rightarrow$  Set where
   $\alpha$       : Nat  $\rightarrow$  ( $\sigma$  : Types)  $\rightarrow$  Vars  $\sigma$  -- typed variables
  --  $\alpha \text{ i } \sigma$  is a variable of type  $\sigma$ 

data  $\mathcal{L}^A$  : Types  $\rightarrow$  Set where
  tt      :  $\mathcal{L}^A$  o                -- typed constants
  ff      :  $\mathcal{L}^A$  o                -- true
   $\top$      :  $\mathcal{L}^A$  (o  $\Rightarrow$   $\sigma \Rightarrow \sigma \Rightarrow \sigma$ ) -- false
  Y       :  $\mathcal{L}^A$  (( $\sigma \Rightarrow \sigma$ )  $\Rightarrow \sigma$ ) -- conditional
  k       : Nat  $\rightarrow$   $\mathcal{L}^A$   $\iota$         -- fixed point
   $\langle +1 \rangle$  :  $\mathcal{L}^A$  ( $\iota \Rightarrow \iota$ )    -- numerals
   $\langle -1 \rangle$  :  $\mathcal{L}^A$  ( $\iota \Rightarrow \iota$ )    -- successor
  Z       :  $\mathcal{L}^A$  ( $\iota \Rightarrow o$ )      -- predecessor
  -- zero test

data Terms : Types  $\rightarrow$  Set where
  V_      : Vars  $\sigma \rightarrow$  Terms  $\sigma$  -- typed terms
  L_      :  $\mathcal{L}^A$   $\sigma \rightarrow$  Terms  $\sigma$  -- variable
   $\langle \_ \_ \_ \rangle$  : Terms ( $\sigma \Rightarrow \tau$ )  $\rightarrow$  Terms  $\sigma \rightarrow$  Terms  $\tau$  -- constant
   $\langle \lambda \_ \_ \_ \rangle$  : Vars  $\sigma \rightarrow$  Terms  $\tau \rightarrow$  Terms ( $\sigma \Rightarrow \tau$ ) -- function application
  -- function abstraction

```

### 4.2.2 Domain Equations

The domains  $\mathcal{D} \sigma$  form a “standard collection of domains for arithmetic” in PCF, written  $\mathcal{D}_\sigma$  in [6]. As PCF is a simply-typed language, the domains  $\mathcal{D} \sigma$  are not reflexive, so their formalisation in Agda can use ordinary type definitions, not involving bijections or embeddings.



```
module Examples.PCF.Domain-Equations where
```

```
 $\mathcal{D}$  : Types → Domain      -- standard domains
 $\mathcal{D} \iota$       = Nat⊥        -- natural numbers
 $\mathcal{D} \circ$        = Bool⊥       -- truth-values
 $\mathcal{D} (\sigma \Rightarrow \tau) = \mathcal{D} \sigma \rightarrow^c \mathcal{D} \tau$  -- functions
```

Environments  $\rho$  are type-preserving maps from variables to values. They are naturally modeled by a dependent type:  $\text{Env } \sigma$  consists of type-preserving maps from variables in  $\text{Vars } \sigma$  to their values in the domain  $\mathcal{D} \sigma$ . The environment  $\rho \perp$  maps all variables to  $\perp$ .

```
Env = ( $\sigma$  : Types) → ⟨⟨ Vars  $\sigma \rightarrow^s \mathcal{D} \sigma \rangle \rangle$  -- typed environments
 $\rho \perp$  : Env                                           -- initial environment
 $\rho \perp \_ \_ = \perp$ 
```

Extension or overriding environments requires instances of the equality tests for both variables and types. The definition of the latter [2] is somewhat tedious.

#### 4.2.3 Semantic functions

The notation  $\rho \llbracket \alpha \text{ i } \sigma \rrbracket$  gives the value of the variable  $\alpha \text{ i } \sigma$  in  $\rho$  by applying  $\rho \sigma$  to the variable.

```
module Examples.PCF.Semantic-Functions where
```

```
 $\_ \llbracket \_ \rrbracket$  : Env → Vars  $\sigma \rightarrow \langle \langle \mathcal{D} \sigma \rangle \rangle$  -- typed variable denotations
 $\rho \llbracket \alpha \text{ i } \sigma \rrbracket = \rho \sigma (\alpha \text{ i } \sigma)$ 
```

The semantic function  $\mathcal{A} \llbracket c \rrbracket$  gives the standard interpretation of the constant  $c$ . The corresponding definitions in [6] use case analysis on the domain  $\mathcal{D} \iota$ , which is not supported in our Agda formalisation (partly because it can express non-continuous functions).

```
 $\mathcal{A} \llbracket \_ \rrbracket$  :  $\mathcal{L}^A \sigma \rightarrow \langle \langle \mathcal{D} \sigma \rangle \rangle$  -- typed constant denotations
 $\mathcal{A} \llbracket \text{tt} \rrbracket$       =  $\uparrow \text{true}$ 
 $\mathcal{A} \llbracket \text{ff} \rrbracket$       =  $\uparrow \text{false}$ 
 $\mathcal{A} \llbracket \supset \rrbracket$       =  $\lambda \beta \delta_1 \delta_2 \rightarrow (\beta \longrightarrow \delta_1, \delta_2)$ 
 $\mathcal{A} \llbracket \text{Y} \rrbracket$        = fix
 $\mathcal{A} \llbracket \text{k n} \rrbracket$      =  $\uparrow n$ 
 $\mathcal{A} \llbracket (+1) \rrbracket$     =  $(\lambda n \rightarrow \uparrow (n + 1))^\#$ 
 $\mathcal{A} \llbracket (-1) \rrbracket$     =  $(\lambda n \rightarrow \uparrow (n ==^N 0) \longrightarrow \perp, \uparrow (n - 1))^\#$ 
 $\mathcal{A} \llbracket Z \rrbracket$        =  $(\lambda n \rightarrow \uparrow (n ==^N 0))^\#$ 
```

The semantic function  $\mathcal{A}' \llbracket M \rrbracket$  is written  $\hat{\mathcal{A}} \llbracket M \rrbracket$  in [6]. It gives the denotation of the term  $M$  as a function of the environment  $\rho$ .

```
 $\mathcal{A}' \llbracket \_ \rrbracket$  : Terms  $\sigma \rightarrow \langle \langle \text{Env} \rightarrow^s \mathcal{D} \sigma \rangle \rangle$  -- typed term denotations
 $\mathcal{A}' \llbracket V \alpha \text{ i } \sigma \rrbracket \rho$       =  $\rho \llbracket \alpha \text{ i } \sigma \rrbracket$ 
 $\mathcal{A}' \llbracket L c \rrbracket \rho$              =  $\mathcal{A} \llbracket c \rrbracket$ 
 $\mathcal{A}' \llbracket (\text{M } \sqcup \text{N}) \rrbracket \rho$       =  $\mathcal{A}' \llbracket M \rrbracket \rho (\mathcal{A}' \llbracket N \rrbracket \rho)$ 
 $\mathcal{A}' \llbracket (\lambda \alpha \text{ i } \sigma \sqcup M) \rrbracket \rho \times$  =  $\mathcal{A}' \llbracket M \rrbracket (\rho [x / \alpha \text{ i } \sigma]')$ 
```

Comparison with Plotkin's original definition of PCF [6] confirms the directness of our Agda formalisation.

### 4.3 Scm: A Sublanguage of Scheme

Scm is a particularly basic sublanguage of the core Scheme expression language whose denotational semantics is defined in the Scheme reports [8]. The domains and auxiliary functions declared in this section are explained in the presentation of the conventional denotational semantics of Scm [4]; they involve the notation for sequences summarised in §2.1 of the present paper.

#### 4.3.1 Abstract Syntax

The following grammar [4] summarises the abstract syntax of Scm expressions  $E : \text{Exp}$  with integers  $Z : \text{Int}$ , constants  $K : \text{Con}$  and identifiers  $I : \text{Ide}$ . The meta-variable  $E^* : \text{Exp}^*$  implicitly ranges over arbitrary sequences of expressions.

$$K ::= Z \mid \#t \mid \#f \quad (4)$$

$$E ::= K \mid I \mid (E_0 E^*) \mid (\text{lambda } I E) \mid (\text{if } E_0 E_1 E_2) \mid (\text{set! } I E) \quad (5)$$

In the following Agda formalisation of the above grammar, the abstract syntax of sequences  $E^* : \text{Exp}^*$  is made explicit: the empty sequence is represented by  $\_\_\_\_\_\_$ , and sequence prefixing by  $E \_\_\_\_\_\_ E^*$ .

```

module Examples.Scm.Abstract-Syntax where

Ide = String      -- identifiers

data Con : Set where -- constants
  int    : Int → Con -- integer numerals
  #t     : Con       -- true
  #f     : Con       -- false

mutual
data Exp      : Set where -- expressions
  con        : Con → Exp -- constants
  ide        : Ide → Exp -- identifiers
  (|_|)      : Exp → Exp* → Exp -- procedure application
  (|lambda_|) : Ide → Exp → Exp -- procedure abstraction
  (|if_|_|)  : Exp → Exp → Exp → Exp -- conditional choice
  (|set!_|)  : Ide → Exp → Exp -- assignment
data Exp*    : Set where -- expression sequences
  \_\_\_\_\_\_ : Exp* -- empty sequence
  _|_|_       : Exp → Exp* → Exp* -- sequence prefix
    
```

#### 4.3.2 Domain Equations

The domains for Scm are somewhat simpler than for the denotational semantics in the Scheme standards [8], but still involve all our postulated domain constructors. Using definitional equations instead of postulated domain equivalences  $D \cong E$  avoids the need for the functions `fold` and `unfold`.

```

module Examples.Scm.Domain-Equations where

postulate Loc : Set
L  = Loc + ⊥      -- locations
N  = Nat ⊥        -- natural numbers
T  = Bool ⊥       -- booleans
R  = Int + ⊥      -- numbers
    
```

```

P = L × L          -- pairs
U = Ide →s L       -- environments
data Misc : Set where null unallocated undefined unspecified : Misc
M = Misc + ⊥       -- miscellaneous
    
```

The conventional denotational semantics of Scm [4] defines the domain  $\mathbf{E}$  of expression values by the equation  $\mathbf{E} = \mathbf{T} + \mathbf{R} + \mathbf{P} + \mathbf{M} + \mathbf{F}$ , and the domain  $\mathbf{F}$  of procedure values by  $\mathbf{F} = \mathbf{E}^* \rightarrow (\mathbf{E} \rightarrow \mathbf{C}) \rightarrow \mathbf{C}$ . Mutually recursive groups of domain equations have well-defined solutions, but in Agda, defining both the corresponding domains  $\mathbf{E}$  and  $\mathbf{F}$  by equations would cause the type checker to diverge. Postulating one (or both) of these domains avoids divergence; postulating  $\mathbf{E}$  also has the benefit that the embeddings and projections for its summands subsume the bijection between  $\mathbf{E}$  and its intended structure.

```

postulate E : Domain      -- expressed values
S = L →c E               -- stores
postulate A : Domain      -- answers
C = S →c A               -- command continuations
F = E * →c (E →c C) →c C -- procedure values
    
```

The following postulates instantiate embedding ( $\delta \text{ in } \perp \mathbf{E}$ ), inspection ( $\varepsilon \in \perp \mathbf{D}$ ), and projection ( $\varepsilon \mid \perp \mathbf{D}$ ) for each summand  $\mathbf{D}$  of  $\mathbf{E}$ .

```

postulate instance
  E+=T : E ≃ 1 ↦ T
  E+=R : E ≃ 2 ↦ R
  E+=P : E ≃ 3 ↦ P
  E+=M : E ≃ 4 ↦ M
  E+=F : E ≃ 5 ↦ F
    
```

#### 4.3.3 Auxiliary Functions

The  $\lambda$ -notation in the Agda definitions of auxiliary functions for Scm corresponds closely to that in its conventional denotational semantics [4]. The main difference is the explicit application here of the function  $\uparrow$  to inject elements of sets into the carriers of flat domains, cf. the definition of `truish` below.

```

module Examples.Scm.Auxiliary-Functions where

assign : ⟨ L →c E →c C →c C ⟩ -- assign  $\alpha \in \text{stores } \epsilon$  at location  $\alpha$ 
assign  $\alpha \in \theta \sigma = \theta (\sigma [\epsilon / \alpha] \perp)$ 

hold : ⟨ L →c (E →c C) →c C ⟩ -- hold  $\alpha$  gives the value stored at  $\alpha$ 
hold  $\alpha \kappa \sigma = \kappa (\sigma \alpha) \sigma$ 
    
```

In the continuation-passing style used to define auxiliary functions for Scm, giving explicit continuity proofs would be particularly tedious. For example, the function `hold` is simply a combination of  $\lambda$ -abstraction and application, which is wellknown to ensure continuity.

```

postulate new : ⟨ (L →c C) →c C ⟩ -- new gives an unallocated location

alloc : ⟨ E →c (L →c C) →c C ⟩ -- alloc  $\epsilon$  allocates a location for  $\epsilon$ 
alloc  $\epsilon \kappa = \text{new } (\lambda \alpha \rightarrow \text{assign } \alpha \epsilon (\kappa \alpha))$ 

postulate initial-store : ⟨ S ⟩ -- may have initialised locations
    
```

```

truish : ⟨ E →c T ⟩ -- truish ε is true for all ε except false
truish ε = (ε ∈⊥ T) → (((ε |⊥ T) ==⊥ ↑ false) → ↑ false , ↑ true) ,
           ↑ true

```

The remaining auxiliary function definitions shown here involve the operations for (finite) sequences  $\epsilon^*$  declared in the module [Notation.Products.Sequences](#) (Section 3.6.2).

```

cons : ⟨ F ⟩ -- cons ⟨ ε1 , ε2 ⟩ allocates and initialises a pair
cons ε* κ = (# ε* ==⊥ ↑ 2) →
            alloc (ε* ↓ 1) (λ α1 →
            alloc (ε* ↓ 2) (λ α2 → κ ((α1 , α2) in⊥ E))) ,
            ⊥

```

In [4] the auxiliary function *list* is defined by recursion on  $\epsilon^*$ . Agda accepts recursive definitions only when it can mechanically prove that the recursion terminates, which is not the case for arguments in postulated types. The following definition uses the postulated operation *fix* to avoid recursion.

```

list : ⟨ F ⟩ -- list ε* allocates and initialises a list
list = fix λ (list' : ⟨ F ⟩) → λ ε* κ →
        (# ε* ==⊥ ↑ 0) → κ (↑ null in⊥ E) ,
        list' (ε* † 1) (λ ε → cons ⟨ (ε* ↓ 1) , ε ⟩ κ)

```

#### 4.3.4 Semantic Functions

The  $\lambda$ -notation in the Agda definitions of semantic functions for Scm corresponds closely to that in its conventional denotational semantics [4].

```

module Examples.Scm.Semantic-Functions where

```

```

K[ ]      : ⟨ Con →s E ⟩ -- constant denotations
E[ ]      : ⟨ Exp →s U →c (E →c C) →c C ⟩ -- expression denotations
E*[ ]     : ⟨ Exp* →s U →c (E* →c C) →c C ⟩ -- sequence denotations

K[ int Z ] = ↑ Z in⊥ E
K[ #t ]    = ↑ true in⊥ E
K[ #f ]    = ↑ false in⊥ E

E[ con K ] ρ κ = κ (K[ K ])
E[ ide I ] ρ κ = hold (ρ I) κ
E[ (E1 ⊔ E2) ] ρ κ = E[ E1 ] ρ (λ ε → E*[ E2 ] ρ (λ ε* → (ε |⊥ F) ε* κ))
E[ (λ I . E) ] ρ κ = κ ( (λ ε* κ' →
                        list ε* (λ ε → alloc ε (λ α → E[ E ] (ρ [ α / I ] κ'))
                        ) in⊥ E )
E[ (if E1 ⊔ E2) ] ρ κ = E[ E1 ] ρ (λ ε → truish ε → E[ E1 ] ρ κ , E[ E2 ] ρ κ)
E[ (set! I ⊔ E) ] ρ κ = E[ E ] ρ (λ ε → assign (ρ I) ε (κ (↑ unspecified in⊥ E)))

E*[ ⊔⊔ ] ρ κ = κ ⟨ ⟩
E*[ E1 ⊔ E2 ] ρ κ = E[ E1 ] ρ (λ ε → E*[ E2 ] ρ (λ ε* → κ (⟨ ε ⟩ § ε*)))

```

## 5 Postulated Properties

This module declares some properties of the conventional notation for Scott domains and the associated functions on their carrier sets. Postulated equivalences between terms are used for testing denotations of terms; adding them as rewrite rules allows implicit use in proofs.

```

module Properties where

module Functions where
postulate
  apply-fix : { $\varphi : \langle\langle D \rightarrow^c D \rangle\rangle\} \rightarrow \text{fix } \varphi \equiv \varphi \text{ (fix } \varphi)$ 
  -- apply-fix{ $\varphi$ } unfolds fix  $\varphi$  once
  {-# REWRITE apply-fix #-}

module Recursion where
postulate
  elim-unfold-fold : { $\{ \_ : D \cong E \} \} \rightarrow \{e : \langle\langle E \rangle\rangle\} \rightarrow \text{unfold (fold e)} \equiv e$ 
  {-# REWRITE elim-unfold-fold #-}

module Flat where
postulate
  elim- $\#$ - $\uparrow$  : ( $f \#$ ) ( $\uparrow a'$ )  $\equiv f a'$ 
  elim- $\#$ - $\perp$  : ( $f \#$ )  $\perp \equiv \perp$ 
  {-# REWRITE elim- $\#$ - $\uparrow$  elim- $\#$ - $\perp$  #-}

module Naturals where
postulate
  elim- $=$ - $\perp$  : ( $\uparrow n_1 = \perp \uparrow n_2$ )  $\equiv \uparrow (n_1 =^N n_2)$ 
  {-# REWRITE elim- $=$ - $\perp$  #-}

module Sums where
postulate
  elim-inj1 : [ $\varphi, \psi$ ] (inj1  $\delta$ )  $\equiv \varphi \delta$ 
  elim-inj2 : [ $\varphi, \psi$ ] (inj2  $\varepsilon$ )  $\equiv \psi \varepsilon$ 
  elim-[]- $\perp$  : [ $\varphi, \psi$ ]  $\perp \equiv \perp$ 
  {-# REWRITE elim-inj1 elim-inj2 #-}

postulate
  elim- $\in \perp$  : { $\{ \_ : E \gtrsim n \mapsto D \} \} \rightarrow \{ \{ \_ : E \gtrsim n' \mapsto D' \} \} \rightarrow (\delta : \langle\langle D \rangle\rangle) \rightarrow$ 
    ( $\delta \text{ in } \perp E$ )  $\in \perp D' \equiv \uparrow (n =^N n')$ 
  elim- $|\perp$  : { $\{ \_ : E \gtrsim n \mapsto D \} \} \rightarrow (\delta : \langle\langle D \rangle\rangle) \rightarrow (\delta \text{ in } \perp E) |\perp D \equiv \delta$ 
  elim- $\in \perp$ - $\perp$  : { $\{ \_ : E \gtrsim n \mapsto D \} \} \rightarrow \{ \{ \_ : E \gtrsim n' \mapsto D' \} \} \rightarrow (\delta : \langle\langle D \rangle\rangle) \rightarrow$ 
    { $n \neq n'$ }  $\rightarrow (\delta \text{ in } \perp E) |\perp D' \equiv \perp$ 
  {-# REWRITE elim- $\in \perp$  elim- $|\perp$  #-}

module Products where
postulate
  elim- $\downarrow_1$  : ( $\delta, \varepsilon$ )  $\downarrow_1 \equiv \delta$ 
  elim- $\downarrow_2$  : ( $\delta, \varepsilon$ )  $\downarrow_2 \equiv \varepsilon$ 
  {-# REWRITE elim- $\downarrow_1$  elim- $\downarrow_2$  #-}
    
```

## 6 Illustrative Tests

### 6.1 LC Tests

module Tests.LC where

```
check-convergence : -- (λx1.x42)((λx0.x0 x0)(λx0.x0 x0)) = x42
  [ ( (λ x 1 ⊔ var x 42 ⊔
    ( (λ x 0 ⊔ ( var x 0 ⊔ var x 0 ⊔ ) ⊔ (λ x 0 ⊔ ( var x 0 ⊔ var x 0 ⊔ ) ⊔ ) )
  ≡ [ var x 42 ]
check-convergence = refl

check-abs : -- (λx1.x1)(λx1.x42) = λx2.x42
  [ ( (λ x 1 ⊔ var x 1 ⊔ ) ⊔ (λ x 1 ⊔ var x 42 ⊔ ) ) ≡ [ (λ x 1 ⊔ var x 42 ⊔ ) ]
check-abs = refl

check-free : -- (λx1.(λx42.x1)x2)x42 = x42
  [ ( (λ x 1 ⊔ ( (λ x 42 ⊔ var x 1 ⊔ ) ⊔ var x 2 ⊔ ) ⊔ ) ⊔ var x 42 ⊔ ) ≡ [ var x 42 ]
check-free = refl
```

### 6.2 PCF Tests

module Tests.PCF where

```
check-fix-const :
  A'[ ( (L Y ⊔ (λ e ⊔ L k 42 ⊔ ) ) ) ρ⊥ ≡ ↑ 42
check-fix-const = refl

-- fix (λg. λa. 42) 2 ≡ 42
check-fix-lambda :
  A'[ ( ( (L Y ⊔ (λ g ⊔ (λ a ⊔ L k 42 ⊔ ) ⊔ ) ⊔ L k 2 ⊔ ) ) ) ρ⊥ ≡ ↑ 42
check-fix-lambda = refl

-- fix (λg. λa. ifz a then 42 else g (pred a)) 5 ≡ 42
check-countdown :
  A'[ ( ( (L Y ⊔ (λ g ⊔ (λ a ⊔
    ( ( (L ⊃ ⊔ (L Z ⊔ V a ⊔ ) ⊔ ) ⊔ L k 42 ⊔ ) ⊔
    ( V g ⊔ (L (−1) ⊔ V a ⊔ ) ⊔ ) ⊔ ) ⊔
    ⊔ L k 5 ⊔ ) ) ) ) ρ⊥ ≡ ↑ 42
check-countdown = refl

-- fix (λh. λa. λb. ifz a then b else h (pred a) (L (+1) b)) 4 38 ≡ 42
check-sum-42 :
  A'[ ( ( ( (L Y ⊔ (λ h ⊔ (λ a ⊔ (λ b ⊔
    ( ( (L ⊃ ⊔ (L Z ⊔ V a ⊔ ) ⊔ ) ⊔ V b ⊔ ) ⊔
    ( ( V h ⊔ (L (−1) ⊔ V a ⊔ ) ⊔ ) ⊔ (L (+1) ⊔ V b ⊔ ) ⊔ ) ⊔ ) ⊔
    ⊔ L k 4 ⊔ ) ⊔ L k 38 ⊔ ) ) ) ) ρ⊥ ≡ ↑ 42
check-sum-42 = refl
```

## References

- [1] Abramsky, S. and A. Jung, *Domain theory*, pages 1–168, Oxford University Press, Inc., USA (1995), ISBN 019853762X.  
<https://achimjungbham.github.io/pub/papers/handy1.pdf>
- [2] *Mechanising denotational semantics in Agda: Code* (2026).  
<https://pdmosses.github.io/mfps2026-agda/>
- [3] Mosses, P. D., *Checking a denotational semantics of Scheme in Agda*, in: *Proceedings of the 26th ACM SIGPLAN International Workshop on Scheme and Functional Programming*, Scheme ’25, pages 3–15, Association for Computing Machinery, New York, NY, USA (2025), ISBN 9798400721625.  
<https://doi.org/10.1145/3759537.3762694>
- [4] Mosses, P. D., *A compositional semantics for `eval` in Scheme*, in: *Proceedings of the Workshop Dedicated to Olivier Danvy on the Occasion of His 64th Birthday*, OLIVIERFEST ’25, pages 72–81, Association for Computing Machinery, New York, NY, USA (2025), ISBN 9798400721502.  
<https://doi.org/10.1145/3759427.3760369>
- [5] Mosses, P. D., *Lightweight Agda formalization of denotational semantics*, in: F. Nordvall Forsberg, editor, *Proceedings of the 31st International Conference on Types for Proofs and Programs*, TYPES 2025, pages 286–290, University of Strathclyde, Glasgow, Scotland (2025).  
[https://msp.cis.strath.ac.uk/types2025/abstracts/TYPES2025\\_paper11.pdf](https://msp.cis.strath.ac.uk/types2025/abstracts/TYPES2025_paper11.pdf)
- [6] Plotkin, G. D., *LCF considered as a programming language*, Theoretical Computer Science **5**, pages 223–255 (1977), ISSN 0304-3975.  
[https://doi.org/10.1016/0304-3975\(77\)90044-5](https://doi.org/10.1016/0304-3975(77)90044-5)
- [7] Reynolds, J. C., *Theories of Programming Languages*, Cambridge Univ. Press, Cambridge, UK (1998), ISBN 9780521106979.  
<https://doi.org/10.1017/CB09780511626364>
- [8] *Scheme standards*.  
<https://standards.scheme.org>
- [9] Scott, D. S., *A type-theoretical alternative to ISWIM, CUCH, OWHY*, Theoretical Computer Science **121**, pages 411–440 (1993), ISSN 0304-3975.  
[https://doi.org/10.1016/0304-3975\(93\)90095-B](https://doi.org/10.1016/0304-3975(93)90095-B)