

# ULC.All

April 13, 2025

```
{-# OPTIONS --rewriting --confluence-check #-}
```

```
module ULC.All where
```

```
import ULC.Variables
import ULC.Terms
import ULC.Domains
import ULC.Environments
import ULC.Semantics
import ULC.Checks
```

---

```
module ULC.Variables where
```

```
open import Data.Bool using (Bool)
open import Data.Nat using (ℕ;  $\equiv^b$  _)
```

```
data Var : Set where
  x : ℕ → Var -- variables
```

```
variable v : Var
```

```
 $\_ == \_$  : Var → Var → Bool
x n == x n' = (n  $\equiv^b$  n')
```

---

```
module ULC.Terms where
```

```
open import ULC.Variables
```

```
data Exp : Set where
  var_ : Var → Exp      -- variable value
  lam_ : Var → Exp → Exp -- lambda abstraction
  app_ : Exp → Exp → Exp -- application
```

```
variable e : Exp
```

---

```

module ULC.Domains where

open import Relation.Binary.PropositionalEquality.Core using (_≡_; refl) public

Domain = Set

postulate ⊥      : {D : Domain} → D

postulate fix    : {D : Domain} → (D → D) → D

postulate fix-fix : ∀ {D} → (f : D → D) → fix f ≡ f (fix f)

postulate fix-app : ∀ {P D} → (f : (P → D) → (P → D)) (p : P) → fix f p ≡ f (fix f) p

open import Function using (Inverse; _↔_) public

postulate D∞ : Domain
postulate instance iso : D∞ ↔ (D∞ → D∞)
open Inverse {{ ... }} using (to; from) public

variable d : D∞

```

---

```

module ULC.Semantics where

open import ULC.Variables
open import ULC.Terms
open import ULC.Domains
open import ULC.Environments

[[_]] : Exp → Env → D∞
-- [ e ] ρ is the value of e with ρ giving the values of free variables

[ var v ] ρ      = ρ v
[ lam v e ] ρ    = from ( λ d → [ e ] (ρ [ d / v ]) )
[ app e1 e2 ] ρ = to ( [ e1 ] ρ ) ( [ e2 ] ρ )

```

---

```

module ULC.Environments where

open import ULC.Variables
open import ULC.Domains
open import Data.Bool using (if _ then _ else _)

Env : Domain
Env = Var → D∞
-- the initial environment for a closed term is λ v → ⊥

variable ρ : Env

[_ / _] : Env → D∞ → Var → Env
ρ [ d / v ] = λ v' → if v == v' then d else ρ v'

```

---

```

{-# OPTIONS --rewriting --confluence-check #-}

open import Agda.Builtin.Equality
open import Agda.Builtin.Equality.Rewrite

module ULC.Checks where

open import ULC.Domains
open import ULC.Variables
open import ULC.Terms
open import ULC.Environments
open import ULC.Semantics

open Inverse using (inversel; inverser)

to-from : (f : D∞ → D∞) → to (from f) ≡ f
from-to : (d : D∞)       → from (to d) ≡ d

to-from f = inversel iso refl
from-to f = inverser iso refl

{-# REWRITE to-from from-to #-}

-- The following proofs are potentially unsound, due to unsafe postulates.

-- (λx1.x1)x42 = x42
check-id :
  [ app (lam (x 1) (var x 1))
    (var x 42) ] ≡ [ var x 42 ]
check-id = refl

-- (λx1.x42)x0 = x42
check-const :
  [ app (lam (x 1) (var x 42))
    (var x 0) ] ≡ [ var x 42 ]
check-const = refl

-- (λx0.x0 x0)(λx0.x0 x0) = ...
-- check-divergence :
--   [ app (lam (x 0) (app (var x 0) (var x 0)))
--     (lam (x 0) (app (var x 0) (var x 0))) ]
--   ≡ [ var x 42 ]
-- check-divergence = refl

-- (λx1.x42)((λx0.x0 x0)(λx0.x0 x0)) = x42
check-convergence :
  [ app (lam (x 1) (var x 42))
    (app (lam (x 0) (app (var x 0) (var x 0)))
      (lam (x 0) (app (var x 0) (var x 0)))) ]
  ≡ [ var x 42 ]
check-convergence = refl

```

```

-- (λx1.x1)(λx1.x42) = λx2.x42
check-abs :
  [[ app (lam (x 1) (var x 1))
      (lam (x 1) (var x 42)) ]]
    ≡ [[ lam (x 2) (var x 42) ]]
check-abs = refl

-- (λx1.(λx42.x1)x2)x42 = x42
check-free :
  [[ app (lam (x 1)
      (app (lam (x 42) (var x 1))
        (var x 2)))
      (var x 42) ]] ≡ [[ var x 42 ]]
check-free = refl

```

---