

Tarea Módulo 20

Pedro Eduardo De
la Puente Rodríguez

Index

Initialization

Tracking

Modifying

Branch Management

Deployment

Initialization

The initialization phase began with the creation of the local development environment and the formal startup of the version control system. By executing the `git init` command within the project directory, the folder was successfully transformed into a functional Git repository, enabling the systematic tracking of all subsequent code changes.

Once the repository was active, the three core application files—`index.html`, `style.css`, and `script.js`—were moved to the staging area using the `git add` command. This process culminated in the execution of the first commit, which officially recorded all of the lines of the code and established a stable technical baseline for the remainder of the project's development lifecycle.

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL  PORTS

PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git init
Initialized empty Git repository in C:/Users/Usuario/Documents/Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez/.git/
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git add .
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git commit -m "Primer commit"
[main (root-commit) a9685f4] Primer commit
 3 files changed, 208 insertions(+)
 create mode 100644 index.html
 create mode 100644 script.js
 create mode 100644 style.css
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> 
```

Tracking

The tracking phase focused on defining the primary branch and establishing a secure link between the local environment and the cloud infrastructure. By utilizing the `git branch -M main` command, the default development line was explicitly renamed to "main" to align with modern industry standards and ensure compatibility with the remote hosting platform.

To complete the synchronization setup, the local repository was connected to the GitHub servers using the `git remote add origin` command. This step established a bridge to the public repository hosted at the specified URL, providing a centralized destination for the project's version history and enabling the collaborative tracking of all future updates.

```
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git branch -M main
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git remote add origin https://github.com/pdr0014/Tarea-Modulo-20-Pedro-Eduardo-De-La-Puente-Rodriguez.git
```

Modifying

The modifying phase involved updating the project files and synchronizing the local workspace with the remote server. After editing the core files, the git add command was applied individually to index.html, style.css, and script.js to prepare these specific changes for versioning, ensuring that every design and logic adjustment was accurately captured in the staging area.

To maintain consistency across environments, a git pull was initiated to integrate any existing data from the GitHub repository. Although the command initially identified a need to specify tracking information, this step highlighted the importance of branch synchronization, ensuring that the local development process remained aligned with the remote version before finalizing further updates.

```
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git add index.html
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git add style.css
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git add script.js
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git pull
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (3/3), 900 bytes | 180.00 KiB/s, done.
From https://github.com/pdr0014/Tarea-Modulo-20-Pedro-Eduardo-De-La-Puente-Rodriguez
* [new branch]      main      -> origin/main
There is no tracking information for the current branch.
Please specify which branch you want to merge with.
See git-pull(1) for details.
```

Branch Management

The branch management phase utilized a dedicated workflow to isolate new developments from the stable codebase. As seen in the image, a feature branch named feature-update was used to modify script.js and commit specific changes. After completing the work, a git checkout main was performed to return to the primary branch, followed by a git merge feature-update to integrate the improvements through a seamless fast-forward process.

```
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git branch
* feature-update
  main
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git add script.js
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git commit -m "Comentarios corregidos"
[feature-update e98166d] Comentarios corregidos
 1 file changed, 1 insertion(+), 1 deletion(-)
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git checkout main
D      README.md
Switched to branch 'main'
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git merge feature-update
Updating 16127b4..e98166d
Fast-forward
 script.js | 2 +-
 1 file changed, 1 insertion(+), 1 deletion(-)
```

Branch Management

Following the successful local integration, the finalized project was uploaded to the cloud repository to ensure accessibility and backup. As demonstrated in the image, the `git push origin main` command synchronized all local commits, including the merged features and updated documentation, with the remote GitHub server. This finalized the deployment cycle, making the World Time Calculator fully live and documented for the end-user.

```
PS C:\Users\Usuario\Documents\Tarea Modulo 20 Pedro Eduardo De La Puente Rodriguez> git push origin main
Enumerating objects: 6, done.
Counting objects: 100% (6/6), done.
Delta compression using up to 12 threads
Compressing objects: 100% (5/5), done.
Writing objects: 100% (5/5), 3.16 KiB | 3.16 MiB/s, done.
Total 5 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/pdr0014/Tarea-Modulo-20-Pedro-Eduardo-De-La-Puente-Rodriguez.git
719ffce..c3c4060  main -> main
```

Deployment

The deployment phase culminated in the successful publication of the project to a public GitHub repository. As illustrated in the image, the final structure includes all essential application files—`index.html`, `script.js`, and `style.css`—alongside a professionally updated `README.md`. The commit history reflects the iterative nature of the project, showing milestones ranging from the initial setup to the most recent documentation updates and logic refinements performed across different branches.

To ensure global accessibility and ease of use, the repository was configured with a standard HTTPS clone URL, allowing any user to replicate the environment locally or within GitHub Codespaces. This final stage of the workflow confirms that the World Time Calculator is no longer just a local script, but a fully deployed open-source project that adheres to modern web development and version control standards.

