```java
 1: // $Id: hellothread.java,v 1.2 2018-05-17 16:08:47-07 - - $
 2:
 3: // Hello World example using two threads.
 4: // class greeter extends Thread.
 5:
 6: import static java.lang.System.*;
 7: import static java.lang.String.*;
 8:
 9: class hellothread {
10:    static long nanostart = nanoTime();
11:
12:    static void print (String fmt, Object... args) {
13:       Thread self = Thread.currentThread();
14:       double millisec = (nanoTime() - nanostart) / 1e6;
15:       String ident = format ("%10.3f: %s(%d): ",
16:                              millisec, self.getName(), self.getId());
17:       String message = format (fmt, args);
18:       out.println (ident + message);
19:       out.flush();
20:    }
21:
22:    static class greeter extends Thread {
23:       long delay_msec;
24:       greeter (String threadname, int delay) {
25:          super (threadname);
26:          delay_msec = delay;
27:       }
28:       public void run() {
29:          print ("starting");
30:          for (int count = 0; count < 10; ++count) {
31:             try {
32:                sleep (delay_msec);
33:             }catch (InterruptedException exn) {
34:                print ("interrupted: %s", exn.getMessage());
35:             }
36:             print ("slept %d msec, cycle %d", delay_msec, count);
37:          }
38:          print ("finished");
39:       }
40:    }
41:
42:    public static void main (String[] args) {
43:       print ("starting");
44:       greeter hello = new greeter ("Hello", 500);
45:       greeter world = new greeter ("World", 800);
46:       hello.start();
47:       world.start();
48:       print ("finished");
49:    }
50:
51: }
52:
53: //TEST// ./hellothread >hellothread.out
54: //TEST// mkpspdf hellothread.ps hellothread.java* hellothread.out
55:
```

```
1: @@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@ mkc: starting hellothread.java
2: hellothread.java:
3:       $Id: hellothread.java,v 1.2 2018-05-17 16:08:47-07 - - $
4: javac -Xlint hellothread.java
5: jar cfm hellothread Manifest hellothread$greeter.class hellothread.class
6: chmod +x hellothread
7: rm -f hellothread$greeter.class hellothread.class
8: @@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@ mkc: finished hellothread.java
```

```
 1:      0.046: main(1): starting
 2:      8.555: main(1): finished
 3:      8.913: Hello(8): starting
 4:      9.705: World(9): starting
 5:    509.595: Hello(8): slept 500 msec, cycle 0
 6:    810.111: World(9): slept 800 msec, cycle 0
 7:   1010.163: Hello(8): slept 500 msec, cycle 1
 8:   1516.162: Hello(8): slept 500 msec, cycle 2
 9:   1619.163: World(9): slept 800 msec, cycle 1
10:   2016.747: Hello(8): slept 500 msec, cycle 3
11:   2419.810: World(9): slept 800 msec, cycle 2
12:   2517.414: Hello(8): slept 500 msec, cycle 4
13:   3018.137: Hello(8): slept 500 msec, cycle 5
14:   3220.501: World(9): slept 800 msec, cycle 3
15:   3518.828: Hello(8): slept 500 msec, cycle 6
16:   4019.427: Hello(8): slept 500 msec, cycle 7
17:   4021.369: World(9): slept 800 msec, cycle 4
18:   4519.979: Hello(8): slept 500 msec, cycle 8
19:   4821.841: World(9): slept 800 msec, cycle 5
20:   5020.574: Hello(8): slept 500 msec, cycle 9
21:   5020.989: Hello(8): finished
22:   5622.450: World(9): slept 800 msec, cycle 6
23:   6423.022: World(9): slept 800 msec, cycle 7
24:   7223.663: World(9): slept 800 msec, cycle 8
25:   8024.264: World(9): slept 800 msec, cycle 9
26:   8024.654: World(9): finished
```