

REMIND Lab - MVP Use Cases

Version 0.1 | Actor capabilities and authority boundaries

1. User Use Cases

- Edit own profile information.
- Create an EmergencyReport.
- View a specific report authored by the user.
- View the history of reports authored by the user.
- Change the severity of an active report authored by the user.
- Cancel an OPEN or IN_PROGRESS report authored by the user.

2. Company Use Cases

- Edit company information.
- View OPEN reports compatible with the company's emergency categories.
- View details of an eligible report.
- Assume an OPEN eligible report, changing it to IN_PROGRESS.
- Follow/conduct the response to an assigned occurrence.
- Resolve an IN_PROGRESS report for which the company is responsible.
- Record response information/report after handling an occurrence.
- View history of reports handled by the company.

3. Admin Use Cases

- Create, retrieve, edit, and administratively manage Users.
- Create, retrieve, edit, and administratively manage Companies.
- Physical deletion of emergency history is not implied by generic administrative CRUD and requires a separate business decision.

4. Authorization vs. Domain Authority

A role alone is insufficient to authorize domain operations. A USER may change severity or cancel only reports authored by that user. A COMPANY may resolve only a report assigned to that company. A COMPANY must also be eligible for the report category before it can assume the occurrence.

Action	Role requirement	Domain requirement
Change severity	USER	Must be the report author; report must be active.
Cancel report	USER	Must be the report author; state must be OPEN or IN_PROGRESS.
Assume report	COMPANY	Company must handle the category; report must still be OPEN.
Resolve report	COMPANY	Must be the assigned company; report must be IN_PROGRESS.

5. Primary MVP Flow

User creates report -> report becomes OPEN -> compatible companies can discover it -> one eligible company assumes it -> report becomes IN_PROGRESS -> responsible company conducts response -> company resolves it -> report becomes RESOLVED.

6. Alternative Terminal Flow

The author may cancel the report while it is OPEN or IN_PROGRESS. Cancellation does not erase the occurrence or its history; it changes the domain state to CANCELLED.

7. MVP Boundary

These use cases describe application behavior, not endpoint design or class structure. HTTP routes, controllers, services, repositories, persistence choices, and architectural patterns are intentionally deferred until the domain and MVP are stable.