LAN Security Concepts

Networks Attacks

- **Distributed Denial of Service (DDoS)**
- **Data Breach**
- **Malware** (e.g. WannaCry)

Network Security Devices

- **Virtual Private Network (VPN) enabled router**: Can be integrated into firewall.
- **Next-Generation Firewall (NGFW)**: stateful packet inspection, application visibility and control, Next-Generation IPS (NGIPS), advanced malware protection (AMP), and URL filtering.
- **Network Access Control (NAC)**: Includes AAA services. Cisco ISE (Identity Services Engine)

Endpoint Protection

- Best protected with combination of: NAC + AMP + ESA + WSA
  - **Cisco ESA** (Email Security Appliance): monitors SMTP
  - **Cisco WSA** (Web Security Appliance): advanced malware protection (AMP), application visibility and control, acceptable use policy controls, and reporting.

Access Control - AAA Components

- **Authentication**: **who is permitted to access** a network
  - **Local Authentication:** SSH in Cisco Routers. Small networks.
  - **Server-Based Authentication:** router accesses (via **RADIUS** or **TACACS+** protocols) a central AAA server that contains usernames and passwords for all users
- **Authorization**: **what they can do** while they are there. Uses a set of attributes that describe the user's access to the network.
- **Accounting**: **audit what actions they performed** while accessing the network. Collects and reports usage.

Access Control - 802.1X

- Port-based access control and authentication protocol.
- Restricts unauthorized workstations from connecting to a LAN throught publicly accessible switch ports.

802.1x Roles:

- **Client (Supplicant)**: Requires access and responds to request from switch
- **Switch (Authenticator)**: Controls physical access to the network based on client authentication status
- **Authentication Server**: Performs client authentication.

Layer 2 Vulnerabilities - Switch Attack Categories

- **MAC Table Attacks**: MAC address flooding attacks

- **VLAN Attacks**: VLAN hopping and VLAN double-tagging attacks

- **DHCP Attacks**: DHCP starvation and DHCP spoofing attacks

- **ARP Attacks**: ARP spoofing and ARP poisoning attacks

- **Address Spoofing Attacks**: MAC address and IP address spoofing attacks

- **STP Attacks**: Spanning Tree Protocol manipulation atacks

Layer 2 Vulnerabilities - Switch Attack Mitigation

- **Port Security**: Prevents MAC address flooding and DHCP starvation attacks

- **DHCP Snooping**: Prevents DHCP starvation and DHCP spoofing attacks

- **Dynamic ARP Inspection (DAI)**: Prevents ARP spoofing and ARP poisoning attacks

- **IP Source Guard**: Prevents MAC and IP address spoofing attacks

Also recommended:

SSH, SCP, SFTP, SSL/TLS, dedicated management VLAN, ACLs

MAC Address Table Flooding Attack

- **Attacker bombards the switch with fake source MAC addresses** ➡️ switch MAC address table full ➡️ **switch floods all incoming traffic out all ports on the same VLAN** ➡️ **attacker captures all of the frames sent from one host to another** on the local LAN or local VLAN.

Mitigation

- **Implement port security.**

VLAN Hopping Attacks

- **Enables traffic from one VLAN to be seen by another VLAN without the aid of a router.**
- The threat actor **configures a host to act like a switch** to take advantage of the automatic trunking port feature enabled by default on most switch ports ➡️ **establishes a trunk** ➡️ **can access all the VLANs on the switch.**

VLAN Double-Tagging Attacks

- **Attacker embeds a hidden 802.1Q tag inside the frame that already has an 802.1Q tag:**
    - **1st 802.1 tag** ➡️ **Native VLAN:** Switch forwards the packet out all native VLAN ports after stripping the VLAN tag ➡️ Attacker must be in a native VLAN port.
    - **2nd inner 802.1 tag** ➡️ The second switch looks only at the inner 802.1Q tag ➡️ frame is destined to the target VLAN.
- **The attacker gets the ability to communicate with devices on the normally blocked VLAN.**

Mitigation

- **Disable trunking on all access ports, disable auto trunking on trunk links** (if needed enabled manually) and be **sure that native VLAN is only used for trunks.**

10

DHCP Attacks

- **DHCP Starvation Attack:** create a DoS for connecting clients. Attacking tools look at the entire scope of leasable IP addresses and try to lease them all.

- **DHCP Spoofing Attack:** a rogue DHCP server is connected to the network and provides false IP configuration parameters to legimitate clients:

  - **Wrong default gateway:** MiTM attack
  - **Wrong DNS server:** points the user to a nefarious website.
  - **Wrong IP address:** DoS attack on the DHCP client.

ARP Attacks

- An attacker can send a gratuitous ARP message containing a spoofed MAC address to a switch, and the switch would update its MAC table accordingly.

- **A threat actor sends unsolicited ARP Replies to other hosts on the subnet with the MAC Address of the threat actor and the IP address of the default gateway**, effectively setting up a **man-in-the-middle attack**.

Mitigation

- **Implement Dynamic ARP Inspection (DAI).**

Address Spoofing Attacks

- **IP address spoofing:** when a threat actor hijacks a valid IP address of another device on the subnet or uses a random IP address.

- **MAC address spoofing:** when a threat actor alters the MAC address of their host to match another known MAC address of a target host.

Mitigation

- **Implement IP Source Guard (IPSG).**

STP Attack

Network attackers can manipulate the Spanning Tree Protocol to conduct an attack:

- **Spoofing the Root Bridge:**
  - **Attacker broadcasts BPDUs with lower bridge priority** to be elected as the **Root Bridge**
  - Changing the topology of the network
- Capturing all traffic for the immediate switched domain

Mitigation

- **Implement BPDU Guard on all access ports.**

CDP Reconnaissance Attack

- **CDP enabled by default** on all Cisco devices.
- CDP information includes the IP address of the device, IOS software version, platform, capabilities and the native VLAN.

Mitigation

- **Limit the use of CDP on devices or ports:**
  - Disable CDP globally on a **device**: `no cdp run`
  - Disable CDP on a **port**: `no cdp enable`