Ethernet Switching

📕 CCNA1v7 Module 7 Ethernet Switching

👩‍🏫 Pedro Durán

Data Link Sublayers

- **LLC Sublayer:** Places information in the frame to identify which network layer protocol is used for the frame.
- **MAC Sublayer:** Responsible for:
  - **Data encapsulation:** Ethernet frame, Addressing (MAC), Error detection
  - **Media access control:** CSMA/CD, CSMA/CA



Ethernet Frame

- Ethernet frame size (preamble not included):
  - **Minimum = 64 bytes. Maximum = 1518 bytes**
- Frame < **64 bytes** ➡️ "collision fragment" or **"runt frame"** (discarded)
- Frame > **1500 bytes of data** ➡️ **"jumbo"** or "baby giant frames".
- Minimum > Size of transmitted frame > Maximum ➡️ device drops the frame



Ethernet MAC Address

Ethernet MAC Address = 48 bits expressed in 12 hexadecimal digits

All MAC addresses must be unique to the Ethernet device or Ethernet interface.



Frame Processing

- Ethernet header include a **Source MAC address** and a **Destination MAC address**.
- Device receives frame ➡️ **examine Destination MAC address**
  - Frame received Destination MAC address ≠ Device NIC MAC ➡️ Discard frame
  - Frame received Destination MAC address = Device NIC MAC ➡️ Accept

Types of MAC Adresses

- **Unicast:** Determine MAC Address with an IP: IPv4 (ARP), IPv6 (ND)
- **Broadcast: FF-FF-FF-FF-FF-FF**
- **Multicast:**
  - **Multicast IPv4: 01-00-5E**
  - **Multicast IPv6: 33-33**

Switch Fundamentals

Switch makes its forwarding decisions based on the Layer 2 Ethernet MAC addresses.

1️⃣ **LEARN.** Frame enters switch. Switch examines frame **Source MAC address**

🤔 Source MAC address **unkwown** ➡️ Adds Source MAC to table with incoming port

🤔 Source MAC address **known** ➡️ Refresh timer for that entry (default: 5 min)

2️⃣ **FORWARD.** Find the **Destination MAC Address**

🤔 Destination is **Unicast MAC known** ➡️ Forwards out the specified port

🤔 Destination is **Unicast MAC unknown** ➡️ Forwards out all ports except incoming port

🤔 Destination is **Multicast or Broadcast**? ➡️ Forwards out all ports except incoming port

Frame Forwarding Methods on Cisco Switches

- **Store-and-forward switching:**
  Receives the entire frame and computes the CRC.
  🤔 CRC valid? ➡️ Forwards frame
  🤔 CRC invalid? ➡️ Discards frame
- **Cut-through switching:**
  - **Fast-forward switching:** forwards after reading the destination address.
  - **Fragment-free switching:** switch stores and performs an error check on the first 64 bytes of the frame before forwarding.

Duplex and Speed Settings

- **Full-duplex:** Both ends of the connection can send and receive simultaneously.
- **Half-duplex:** Only one end of the connection can send at a time.

⚠️ Gigabit Ethernet ports only operate in full-duplex.

Best practice: configure both Ethernet switch ports as full-duplex.

Auto-MDIX

Most switch devices now support the **Auto**matic **M**edium-**D**ependent **I**nterface crossover (**X**) feature. When enabled `mdix auto`, the switch automatically detects the type of cable attached to the port and configures the interfaces accordingly.