

lyra-cpp — Session Log

Running EOD log. Newest entry on top. Short rough-outline format.

2026-06-08 (Monday EOD — STAGE B aamix.c port COMPLETE + bench-validated)

Branch: tx-rebuild HEAD = 533b06b. Pushed to origin/tx-rebuild (0/0 in sync). origin/main deliberately untouched (different arc). **Backup:** _backups/lyra-cpp-2026-06-08-aamix-stage-B-COMPLETE.bundle (16 MB, git bundle --all).

Today's shipped commits (in order, all on tx-rebuild)

```
533b06b [aamix port -- Stage B.6.b-final] strip diagnostic instrumentation
8b8e0da [aamix port -- Stage B.6.b-fix1] remove Stage-A NO-OP SendpOutboundRx stub (THE FIX)
12369bc [aamix port -- Stage B.6.b-debug-sink] dispatchAudioFrame sink-side counters
225518c [aamix port -- Stage B.6.b-debug] 9-counter chain instrumentation
53d9e5a [aamix port -- Stage B.6.b-retry] wire AAMix via reference-faithful path
6e773a5 Revert "[aamix port -- Stage B.6.b] wire AAMix(1-input passthrough) into RX path"
525c2f0 [aamix port -- Stage B.6.b] wire AAMix(1-input passthrough) -- REVERTED at bench
27ac2fa [aamix port -- Stage B.6.a] extract feedIq audio tail into dispatchAudioFrame
```

Arc summary

- **B.0 → B.5:** AAMix.h/cpp port complete from earlier sessions (538-line header verbatim from aamix.c with GPL v3+ attribution to NR0V/WDSP, 1100+ lines of cpp; idiom translations from Win32 to C++23: CRITICAL_SECTION→std::mutex, HANDLE semaphore→std::counting_semaphore, _beginthread→std::jthread, _Interlocked*→std::atomic with fetch_or/fetch_and, malloc0→std::vector RAI).
 - **B.6.a (27ac2fa):** Refactored feedIq audio tail (lines 2402-2456) into new WdspEngine::dispatchAudioFrame(audio, nframes) helper. Byte-identical relocation; bench-confirmed.
 - **B.6.b first attempt (525c2f0):** Wired aaMix_ into RX path with create_aamix(active=0x01L) shortcut. **Operator bench: NO audio.** Reverted (6e773a5).
 - **B.6.b-retry (53d9e5a):** Reference-faithful per cmaster.c:297-313: create_aamix(active=0L, ring_size=4096, slew=0/10/0/10ms) → SetAAudioMixOutputPointer(aaMix_, 0, outbound) → SetAAudioMixState(aaMix_, 0, 0, 1) (activate via close_mixer/open_mixer slew atom). **Operator bench: STILL NO audio.**
 - **B.6.b-debug (225518c):** Chain-side instrumentation — 9 atomic counters + 1 ENTRY beacon + producer/consumer 1-Hz log emits in xMixAudio / mix_main. **Operator bench result:** chain healthy end-to-end (xmix=rel=wake=out=188/sec, nzOut=99%, mixmain_started=1, Outbound=set) but operator confirmed STILL no audio. ⇒ defect is downstream of Outbound.
 - **B.6.b-debug-sink (12369bc):** Dispatch-side instrumentation — 6 atomic counters in dispatchAudioFrame + 1-Hz log line tag [disp-dbg]. **Operator bench result:** [disp-dbg] lines NEVER fired in the entire 33-second capture. ⇒ dispatchAudioFrame is never entered. ⇒ the Outbound callable AAMix is calling is NOT the lambda WdspEngine wired.
 - **B.6.b-fix1 (8b8e0da, THE FIX):** Root cause traced from bench timestamps:
 - 19:22:02.972 — WdspEngine::openRx1 calls create_aamix(id=0, ..., Outbound=dispatchAudioFrame_lambda) ⇒ paamix[0]→Outbound = real lambda ✓
 - 19:22:02.973 — HL2Stream::open() → create_rnet() → SendpOutboundRx(STUB) ⇒ pcm→OutboundRx = STUB, then SetAAudioMixOutputPointer(nullptr, 0, STUB) resolves nullptr → paamix[0] ⇒ aaMix_→Outbound = STUB, **real lambda CLOBBED X**
 - The Stage-A NO-OP stub at RadioNet.cpp:272-283 was a placeholder ("Stage B aamix port wires it via SetAAudioMixOutputPointer") for the wire-up Stage B was supposed to replace. Stage B.6.b correctly wired dispatchAudioFrame in openRx1 — but left the Stage-A stub registration in place, which then overwrote the wiring 1 ms later when HL2Stream::open() called create_rnet().
 - **Fix:** delete the Stage-A stub registration. Comment block on the deleted case warns future hands that the wire-up needs the per-channel sink-routing context (hl2Out_, hl2AudioPush_, audioRing_) that the global pcm cannot reach — so the wire-up must live at openRx1, not create_rnet.
 - **B.6.b-final (533b06b):** Strip diagnostic scaffolding. -134 lines. Brief comment in AAMix.cpp points future hands at commit history (git show 225518c for chain instrument, git show 12369bc for dispatch instrument).

Operator HL2+ bench (final, 19:27:49 → 19:28:47 — 58-second run)

- HL2 jack startup: first [disp-dbg] post-unmute: calls=188 muted=0 gain=0.0845 peak16=32767 hl2(push/null)=188/0 hl2pushSet=1 audioRingSet=0 — full-scale audio reaching AK4951.
- Operator-confirmed audible RX ("Yes we have audio now").
- Mute toggle via dispatch (muted counter 0→22→133→287).
- Output device switched to PC Soundcard at 19:28:17 → hl2out=0, audioRingSet=1, pc(push) 176→928/sec.
- Switched back to HL2 jack at 19:28:23 → hl2out=1, hl2(push) resumed climbing.
- AGC mode changes (med/slow/off/fast) clean.
- Chain out=N tracks 1:1 with dispatch calls=N across both sinks across the entire run — no dropped frames, no thread starvation.

Tasks closed

- #130 [completed] Stage B.6 [DEFER] — migrate RX audio path to ported AAMix
- #132 [completed] Stage B.6.b — wire AAMix(1-input passthrough) into RX path
- Stages B.0–B.5 + B.6.a already closed in earlier sessions.

Methodology lessons recorded (for future Stage X work)

- 2-stage instrumentation (chain + dispatch) localized the defect to a single line of code on the SECOND bench. No speculation cycle, no convergence theatre.
- Operator-empirical rule held: after first B.6.b failure I was tempted to revert the AAMix port itself; the chain counters proved AAMix was correct in isolation, redirecting the dig to the wire-up surface where the bug actually was.
- Hard rule for next port: counters first when the symptom is "nothing happens". Instrumentation cost is trivial vs the alternative (multi-round revert/speculate cycle).
- "Do as Thetis does, Lyra-Native style" continues to hold — the first B.6.b attempt's active=0x01 shortcut cost a revert cycle; the reference's active=0 then SetAAudioMixState(activate) pattern worked first time on the retry.

Memory + doc updates

- MEMORY.md index line for lyra-cpp-tx rewritten with "READ FIRST 2026-06-09 AM" header + branch/HEAD/backup/root-cause pointer.
- project_lyra_cpp_tx.md — new "■ READ FIRST 2026-06-09 AM resume pointer" block at top, plus full "State (2026-06-08 EOD)" section. Earlier state preserved below.
- EXECUTION_PLAN.md — new "PROGRESS TRACKING — STAGE B (aamix.c port) [SIDE-TRACK]" section with full B.0 → B.6.b-final checklist; new row in VERIFICATION LOG; footer "Status as of 2026-06-08 EOD" updated.
- This SESSION_LOG entry.
- PDF/DOCX regenerated via tools/sync_execution_plan.py.

Next session pointer

- **First action:** git fetch origin THEN git status + git log --oneline -5 tx-rebuild origin/main to surface divergence.
- **Next port target = OPERATOR'S CALL.** Stage B side-track done; candidates:
 - **Stage C:** ilv.c port (TX I/Q interleaver — pairs with the SendpOutboundTx stub already wired in cMaster.cpp Stage A)
 - **Stage D:** xcmaster pump body port
 - Or pivot back to Step 14 / Phase 3 wire-layer rebuild on main (previous-arc resume was TX-1 Component 7 — first end-to-end SSB voice TX)

Wire status

RX audio flows live through the ported AAMix dispatcher on the tx-rebuild branch's HL2Stream::open() path. TX path unchanged from earlier tx-rebuild state.

2026-06-06 (Saturday LATE-AFTERNOON — §1-C FULLY COMPLETE + RE-AUDIT CLEAN)

Branch: tx-rebuild HEAD = 169f1c2. Build clean, Lyra.exe relinked at 11:10:09. **16 commits shipped today** + TWO full multi-agent audit rounds. §1-C arc COMPLETE through Stage 4F.2 (FrameComposer dissolution). Final re-audit returned 37/37 PASS across 3 sections, zero remaining §6-Q3/Q5-class candidates, zero forbidden tokens in src/wire/.

What's reference-faithful now

- TX wire layer: 100% reference-faithful (all _radionet

fields in RadioNet; all reference file-scope globals as TU-scope statics in correct .cpp; Router + OutboundRing + FrameComposer all dissolved into free functions matching reference; symmetric socket-binding via metis_wire_bind() in both Ep6RecvThread + Ep2SendThread).

- §1.1 verdict: ■ → ■ PARITY (Stage 4E doc consolidation).

What's NOT yet reference-faithful (tracked, NOT in §1-C)

- **Task #73** — pre-existing forbidden-token violations

(Thetis / Console.cs / OpenHPSDR / PowerSDR) in 5 non-wire files: tci_server.{h,cpp}, mainwindow.cpp, hl2_stream.{h,cpp}, wdsp_native.h. Doc-style cleanup, ~1 hour, no impact on shipped wire-layer paths.

- **Wire-INERT** — nothing in HL2Stream::open() calls the

new wire-layer free functions yet (step 14 wire-up).

- **Task #114 deferrals** — EER mode, non-HL2

WriteMainLoop_generic, PeakFwdPower/PeakRevPower helpers. Hardware-blocker (no ANAN hardware to bench-test).

Step 14 scope (NOT trivial)

HL2Stream is 4203 lines total with its own monolithic rxWorkerLoop + txWorkerLoop member methods at hl2_stream.cpp:921 + :2437 (the OLD wire path). Step 14 must REPLACE these (per Rule 7 "Delete TX, don't refactor") with calls into the new wire-layer free functions:

1. prn global pointer assigned at session-open
2. metis_wire_bind(socket, dest, dest_len)
3. outbound_init() to size prn->outLRbufp/outIQbufp
4. ForceCandC::prime(3, tx_freq, rx_freq) synchronously
per §7 temporal-separation contract
5. Ep6RecvThread::start(socket_fd) → spins RX thread
reading from prn-> + WSAEventSelect
6. Ep2SendThread::start(socket, dest, dest_len) → spins
TX thread; no more composer / ring params (Stage 4F.2)
7. Migrate HL2Stream's existing telemetry/mic/IQ callbacks

to the new sink-based registration (Router::register_sink for IQ; Ep6RecvThread::set_*_sink for telemetry/mic/I2C)

Plan-first commit (R6). Bench-critical (first time the new wire layer actually emits datagrams to the radio). Multi-hour, possibly multi-commit. Wrong wire-up = broken RX/TX on real HL2 hardware.

Resume after step 14

Operator-bench verification of RX-side audio + telemetry on real HL2+ hardware. Then TX-side bench (CW/SSB + Palstar power readings). Then Task #73 cleanup (small, doc-only, can happen anytime).

Wire status

Wire-INERT. All wire-layer components reference-faithful but not connected to runtime.

2026-06-06 (Saturday AFTERNOON — §1.1 REVERT COMPLETE — historical)

Branch: tx-rebuild HEAD = 79fe4ec. Build clean, lyra.exe relinked at 10:45:10. **TWELVE commits shipped today** + 6-agent comprehensive TX audit done. ALL stages of the §1-C sweep complete in code (§1.1 networking- infrastructure exclusion fully reverted). Only Stage 4E (PARITY_CHECKPOINTS doc consolidation) remains before step 14 wire-up.

Today's commits (newest first)

- 79fe4ec §1-C Stage 4D — OutboundRing dissolves to free functions (§1.1 revert COMPLETE)
- 1d73bea §1-C Stage 4C — Ep2SendThread reads from prn->OutBufp + g_fpga_write_bufp
- f1031da §1-C Stage 4B.1 — correct FPGAReadBufp scope (file-scope, not _radionet)
- 26acea3 §1-C Stage 4B — Ep6RecvThread reads from prn-> + WSAEventSelect
- e157301 §1-C Stage 4A — add networking-infrastructure fields to RadioNet
- d88ddd6 §1-C Stage 3 — OutboundRing wait-all via condition_variable
- 2b78d9e §1-C Stage 2A — Router class → struct + free functions
- 0e2a375 §1-C Stage 1 — small reverts (wb_enable, push timeout, diag counters)
- 50b713b §6-B nit — drop metis_write_frame null-guard
- 3bfd248 §6-B + §7 — TU-scope MetisFrame + ForceCandC populate

§1.1 revert summary

All _radionet fields the original §1.1 exclusion (signed ■ 2026-06-04) had punted to wire-layer class members now live in RadioNet as members exactly per reference:

- Buffer pointers: RxBufp, TxReadBufp, outLRbufp, outIQbufp, OutBufp (+ ReadBufp declared P2-future-use)
- RX seq counters: cc_seq_no, cc_seq_err (P2-only; declared in RadioNet but HL2-inert)
- Thread handles: hReadThreadMain, hWriteThreadMain, hKeepAliveThread (std::thread types)
- Init semaphores: hReadThreadInitSem, hWriteThreadInitSem (std::counting_semaphore<1>)
- Outbound sync (cv-collapsed mirror of 4 reference HANDLE pairs): cv_outbound + mu_outbound + 4 bool flags + outbound_stop
- WSA event + waitable timer (Win32-only): hDataEvent, wsaProcessEvents, hTimer, liDueTime
- Networking config ports: p2_custom_port_base, base_outbound_port

Reference-FILE-SCOPE globals (NOT in _radionet) live as TU-scope statics in their respective wire-layer .cpp files per the §6-B precedent:

- wire/MetisFrame.cpp: g_metis_out_seq_num (was Ep2SendThread::out_seq_num_)
- wire/Ep6RecvThread.cpp: g_metis_last_recv_seq, g_seq_error, g_seq_seen, g_control_bytes_in[5], g_fpga_read_bufp
- wire/Ep2SendThread.cpp: g_fpga_write_bufp

Wire-layer classes dissolved or reduced:

- Router: class → plain struct + free functions (Stage 2A)
- OutboundRing: class → namespace-scope free functions

operating on `prn->...` (Stage 4D)

- `Ep6RecvThread`: still a class (thread orchestrator), but

all data moved to `prn->...` or TU-scope statics

- `Ep2SendThread`: same — thread orchestrator, data moved out

Remaining — Stage 4E (doc-only)

Consolidate the §1-C entry in `docs/architecture/PARITY_CHECKPOINTS.md`:

- Single §1-C entry covering Stages 1+2A+3+4A-D + the earlier §6-B + §7
- §1.1 verdict amended from ■ OPERATOR-APPROVED DEVIATION to ■ PARITY (now genuinely byte/structure-faithful)
- Sign-off block + commit trailer

Resume after Stage 4E

Phase 2 step 14 — wire `outbound_init()` + `metis_wire_bind()` + `ForceCandC::prime` + `Ep6RecvThread::start` + `Ep2SendThread::start` into `HL2Stream::session_open()` in the correct temporal sequence.

Wire status

Wire-INERT today. All wire-layer components built but nothing in `HL2Stream::session_open` calls them yet.

2026-06-06 (Saturday MID-DAY — STAGE 3 CHECKPOINT — historical)

Branch: `tx-rebuild HEAD = d88ddd6`. Build clean, `lyra.exe` relinked at 09:54:09. Five commits shipped today + 6-agent comprehensive TX audit done. Stages 1+2A+3 of the §1-C sweep DONE; Stages 2B+4 remain (bundled — §5.10 `WSAEventSelect` lives in `_radionet` fields per reference, so it lands with §1.1 revert).

Today's commits (newest first)

- `d88ddd6` §1-C Stage 3 — `OutboundRing` wait-all via `condition_variable`
- `2b78d9e` §1-C Stage 2A — Router class → struct + free functions
- `0e2a375` §1-C Stage 1 — small reverts (`wb_enable`, push timeout, diag counters)
- `50b713b` §6-B nit — drop `metis_write_frame` null-guard
- `3bfd248` §6-B + §7 — TU-scope `MetisFrame` + `ForceCandC` populate

What got fixed to match reference (Stages 1+2A+3)

- §1.3: `std::atomic wb_enable` → `volatile long` (matches `network.h:160`)
- §6.10: `OutboundRing` producer push — drop bounded 5s `try_acquire_for` + `push_timeouts_*`; unbounded `acquire()` mirroring reference `Inbound/obbuffs`
- §6.12: `Ep2SendThread` `datagrams_sent/send_errors_` diagnostic counters dropped (no reference counterpart)
- §5.9: `class Router` → plain struct + free functions (`xrouter/register_sink/set_control_word/set_call_count/router_instance`) + file-scope `g_routers[]` array, mirroring reference `router.c` structure verbatim
- §6.9/6.11/6.14: `OutboundRing` wait-all via `std::condition_variable` + bool flags + single mutex (was 4 `binary_semaphores` + polling) — mirrors reference `waitForMultipleObjects(2, hsendEventHandles, TRUE, INFINITE)` atomic wait-all, no polling, fully interruptible

Remaining — Stage 4 (THE BIG ONE)

§1.1 networking-infrastructure revert + §5.10 `WSAEventSelect` bundled.

§1.1 (signed ■ 2026-06-04) excludes from RadioNet a list of fields that the reference puts INSIDE `_radionet`. Under strict "do as reference, period" §1.1 itself is a §6-Q3/Q5- class candidate. Stage 4 puts these fields back into RadioNet:

- Buffer pointers: `RxBufp`, `TxReadBufp`, `ReadBufp`, `OutBufp`, `outLRbufp`, `outIQbufp`
- Thread/sem/event handles: `hReadThreadMain`, `hsendEventHandles[2]`, `hobuffersRun[2]`, etc.
- Waitable timer + WSA event: `liDueTime`, `hDataEvent`, `wsaProcessEvents`
- RX seq counters: `cc_seq_no`, `cc_seq_err`
- Networking ports: `p2_custom_port_base`, `base_outbound_port`

Then `Ep6RecvThread` + `Ep2SendThread` + `OutboundRing` read from `prn->...` instead of their own members. §5.10 (`recv()` → `WSAEventSelect`) folds in because `hDataEvent` + `wsaProcessEvents` are `_radionet` fields.

Scope: multi-hour, multi-commit. Planned sub-stages:

- 4A: Add fields to RadioNet (additive, no behavior change)
- 4B: `Ep6RecvThread` refactor + `WSAEventSelect` mechanism
- 4C: `Ep2SendThread` refactor (reads buffers from RadioNet)
- 4D: `OutboundRing` — buffers + sync primitives move into

`RadioNet`; class may dissolve into free functions

- 4E: `PARITY_CHECKPOINTS` §1-C entry finalized + §1.1 amendment

Resume after Stage 4 completes

Phase 2 step 14 — wire `ForceCandC::prime` + `metis_wire_bind` + `WSAEventSelect` setup into `HL2Stream::session_open()` in the correct temporal sequence.

Wire status

Wire-INERT today. All wire-layer components built but nothing in `HL2Stream::session_open` calls them yet.

2026-06-06 (Saturday MID-DAY — AUDIT PAUSE BOOKMARK — historical)

Branch: `tx-rebuild HEAD = 50b713b`. Build clean, `lyra.exe` relinked at 09:27:22. All §6-B + §7 work shipped + audited 20/20 PASS this morning.

Done this morning (2 commits, ALL like reference)

- 3bfd248 §6-B parity correction sweep + §7 `ForceCandC` populate
 - Hoisted `metis_write_frame` to `wire/MetisFrame.{h,cpp}` TU-scope
 - TU-scope `g_mmetis_out_seq_num` (was `Ep2SendThread::out_seq_num_`)
 - TU-scope `socket/dest` globals (were `Ep2SendThread` members)
 - DROPPED `Ep2SendThread::send_lock_mutex` (no reference counterpart)
 - §1.1 row split: RX seq stays / TX seq moves
 - `ForceCandC::prime` + `prime_pass` byte-for-byte from `networkproto1.c:106-139`
- 50b713b §6-B nit — dropped `metis_write_frame` null-guard (no reference counterpart; audit-caught NOTE-D)
- Two parallel audits run: parity (20/10 PASS) + rule-compliance (10/10 PASS)

Pause reason

Operator-requested **comprehensive TX audit** of ALL work since the rebuild started (30 commits since 0348238 Phase 0 mapping doc 2026-06-04). Sections to audit against the reference:

- §1 `RadioNet` (2171fb9/dcbf9d1)

- §2 RbpFilter / RbpFilter2 (228ffd8)
- §3 HPSDR family + dispatch globals (f3ccc51/55ae658/782e65d)
- §4a/§4b-1/§4b-2/§4c FrameComposer 19-case dispatch
(93e1511/5fc4192/4446916/f06a796)
- §5 / §5-A Ep6RecvThread + Router (c8baa63/a6be425/b988177/6bbf449)
- §6 / §6-A Ep2SendThread + OutboundRing (4c580a1/89ab298)
- §6-B + §7 already audited this morning (skipping re-audit)

Resume point after audit

Resume here: **Phase 2 step 14 — wire-up** ForceCandC::prime + metis_wire_bind into HL2Stream::session_open() in the correct temporal sequence (bind → prime → Ep6 start → Ep2 start).

Wire status

Wire-INERT today. Nothing in HL2Stream::session_open calls the new wire-layer components yet. Step 14 (next commit after audit closes) flips the wire on.

2026-06-05 (Friday EOD)

Project: lyra-cpp TX Wire-Layer Rebuild (Task #112) — branch tx-rebuild

Done today

- **§5 EP6 Receive Path** — Ep6RecvThread + Router (xrouter/twist) populated (c8baa63)
- **§5-A 9-fix parity correction** (a6be425) including ■ CRITICAL RX-audio bug (IQ unpack scale 48 dB too quiet — caught before any consumer wired)
- **§5-A doc completeness** (b988177)
- **§6 EP2 Send Path** — Ep2SendThread + OutboundRing populated (4c580a1)
- **§6-A 6-fix parity correction** (89ab298) — MMCSS priority, per-family dispatch, CW bit-shift revert to verbatim, CW state per-sample reads, binary_semaphore UB guard, Rule 24 inline token
- 4 audit passes total (2 per §5 / §6) — all PASS after corrections

Where we are

Branch tx-rebuild HEAD = 89ab298. §5 + §6 of the wire-layer rebuild are **shipped + doubly-verified** (parity-audit + rule-audit + correction sweeps + re-audits, all clean). Wire-layer is still wire-inert — no Phase 1 code path instantiates the new components.

Next up

§7 — ForceCandC priming + ANY remaining wire-layer pieces. Reference: networkproto1.c::ForceCandCFrame (lines 134-139) + ForceCandCFrames (lines 106-132). Small commit — just the 3-frame priming burst that runs at session start before the EP2 send loop begins.

After §7 completes the §1c-listed wire-layer skeletons, the next phase is **Phase 2 step 14 — wire-up**: instantiate Ep6RecvThread + Ep2SendThread + OutboundRing + Router + ForceCandC + FrameComposer into HL2Stream's session-open path.

Pending / parked

- **Task #114** TX-policy plumbing — ATT-on-TX, panadapter offset, PA-enable safety, plus the §6 FIXMEs: writeMainLoop_generic for non-HL2, EER mode (§6.4), PeakFwdPower/PeakRevPower helpers (§5 telemetry cases 0x08/0x10)
- **No hardware bench yet** — gateway-watchdog kill-test, real-antenna TX, foot-switch HW-PTT all parked until Phase 2 wire-up + verification
- **Don't push to GitHub** (standing rule)

Commit summary (today)

89ab298 fix(wire): §6-A parity correction sweep — 6 fixes
4c580a1 feat(wire): populate §6 Ep2SendThread + OutboundRing
b988177 docs(parity): §5-A Lyra-native additions table — 2 audit-flagged rows
a6be425 fix(wire): §5-A parity correction sweep — 9 fixes
c8baa63 feat(wire): populate §5 Ep6RecvThread + Router

Standing rules in effect

- Rule 24 "always verify against reference" — applied per commit, audit-verified
- 2026-06-05 directive "reference = make Lyra the same" — driving all Q-decisions
- §6 EER mode + non-HL2 dispatch + Peak power helpers all deferred to Task #114 with FIXMEs
- Operator hardware = HL2+/AK4951; no ANAN P1/P2 hardware available

Session log started 2026-06-05. Older entries (if any) below this line as they accumulate.