

# CSSS508, Lecture 6

## Loops

Michael Pearce

(based on slides from Chuck Lanfear)

May 3, 2022



# Topics

Last time, we learned about,

1. Importing and exporting data
2. Cleaning and reshaping data
3. Dates and times

Today, we will cover,

1. Why Loops?
2. `for()` loops
3. `while()` loops

# 1. Why Loops?

# Bad Repetition

If someone doesn't know better, they might find the means of variables in the `swiss` data by typing in a line of code for each column:

```
mean1 <- mean(swiss$Fertility)
mean2 <- mean(swiss$Agriculture)
mean3 <- mean(swiss$Examination)
mean4 <- mean(swiss$Fertility)
mean5 <- mean(swiss$Catholic)
mean5 <- mean(swiss$Infant.Mortality)
c(mean1, mean2, mean3, mean4, mean5, mean6)
```

Can you spot the problems?

How upset would they be if the `swiss` data had 200 columns instead of 6?

# Good Repetition

You will learn a better way to calculate column means today using loops!

```
means <- rep(NA, ncol(swiss))
for(i in 1:ncol(swiss)){
  means[i] <- mean(swiss[,i])
}
data.frame(Variable=names(swiss),Mean=means)
```

```
##           Variable Mean
## 1      Fertility 70.1
## 2   Agriculture 50.7
## 3   Examination 16.5
## 4      Education 11.0
## 5      Catholic 41.1
## 6 Infant.Mortality 19.9
```

Don't worry about the details yet!

# Don't Repeat Yourself (DRY)!

The **DRY** idea: Computers are much better at doing the same thing over and over again than we are.

- Writing code to repeat tasks for us reduces the most common human coding mistakes.
- It also *substantially* reduces the time and effort involved in processing large volumes of data.
- Lastly, compact code is more readable and easier to troubleshoot.

## 2. `for()` Loops

# The `for()` Loop

`for()` loops are the most general kind of *loop*, found in pretty much every programming language.

"**For** each of these values -- in order -- **do this**"

*Given a set of values...*


1. Set an index variable (often `i`) equal to the first value
2. Do something (perhaps depending on `i`)
3. Is there a next value?
  - *YES*: Update to next value, go back to 2.
  - *NO*: Exit loop

We are *looping* through values and repeating some actions.



# for( ) Loop: Diagram

*Given a set of values...*



# for( ) Loop: Example

```
for(i in 1:5) {  
  # inside for, output won't show up without print()  
  print(i^2)  
}
```

```
## [1] 1  
## [1] 4  
## [1] 9  
## [1] 16  
## [1] 25
```

Note this runs *5 separate print commands*, which is why each line starts with `[1]`.

# These Do the Same Thing

```
for(i in 1:3) {  
  print(i^2)  
}
```

```
## [1] 1  
## [1] 4  
## [1] 9
```

```
i <- 1  
print(i^2)  
i <- 2  
print(i^2)  
i <- 3  
print(i^2)
```

```
## [1] 1  
## [1] 4  
## [1] 9
```

# Iteration Conventions

- We call what happens in the loop for a particular value one **iteration**.
- Iterating over indices `1:n` is *very* common. `n` might be the length of a vector, the number of rows or columns in a matrix or data frame, or the length of a list.
- Common notation: `i` is the object that holds the current value inside the loop.
  - If loops are nested, you will often see `j` and `k` used for the inner loops.
  - This notation is similar to indexing in mathematical symbols (e.g.  $\sum_{i=1}^n$ )
- Note `i` (and `j`, `k`, etc) are just normal objects. You can use any other names you want.
  - Ex: When iterating over rows and/or columns, I often use `row` and/or `col`!

# Iterate Over Characters

What we iterate over doesn't have to be numbers `1:n` or numbers at all! You can also iterate over a character vector in R:

```
for(i in letters[1:3]) {  
  print(i)  
}
```

```
## [1] "a"  
## [1] "b"  
## [1] "c"
```

```
i # in R, this will exist outside of the loop!
```

```
## [1] "c"
```

# Pre-Allocation

Usually in a `for()` loop, you aren't just printing output, but want to store results from calculations in each iteration somewhere.

To do that, figure out what you want to store, and **pre-allocate** an object of the right size as a placeholder (typically with missing values as placeholders).

Examples of what to pre-allocate based on what you store:

- Single numeric value per iteration:
  - `rep(NA, num_iter_iters)`
- Numeric vector per iteration:
  - `matrix(NA, nrow = num_of_iters, ncol = length_of_vector)`

# Pre-Allocation: Numeric

```
iters <- 10 # Set number of iterations
output <- rep(NA,iters) # Pre-allocate numeric vector
output
```

```
## [1] NA NA NA NA NA NA NA NA NA NA
```

```
for(i in 1:iters) { # Run code below iters times
  output[i] <- (i-1)^2 + (i-2)^2
}
output # Display output
```

```
## [1] 1 1 5 13 25 41 61 85 113 145
```

Steps:

1. Set a number of iterations
2. Pre-allocate a numeric vector of that length
3. Run ten iterations where the output is a mathematical function of each iteration number.

# Pre-Allocation: Numeric Vector per Iteration Matrix

```
rownums <- 3
colnums <- 6
output <- matrix(NA,nrow=rownums,ncol=colnums)

for(i in 1:rownums){
  for(j in 1:colnums){
    output[i,j] <- i + j
  }
}
output
```

```
##      [,1] [,2] [,3] [,4] [,5] [,6]
## [1,]    2    3    4    5    6    7
## [2,]    3    4    5    6    7    8
## [3,]    4    5    6    7    8    9
```



# Aside: If/Else Statements

To test a logical statement and then conditionally execute a set of actions, use `if()` and `else`. The structure is:

```
if(CONDITION){  
    SOME CALCULATION  
} else{  
    A DIFFERENT CALCULATION  
}
```

**Warning!** `else` needs to be on same line as the closing brace `}` of previous `if()`.

# If/Else Simple Example

```
if(8 < 10){  
    print("Less than 10!")  
}else{  
    print("Not less than 10!")  
}
```

```
## [1] "Less than 10!"
```

# More Complex If/Else

We can nest together multiple if/elses! if we wish:

```
i <- 13
if(i <= 10) {
  print("i is less than or equal to 10!")
} else if(i <= 14) {
  print("i is greater than 10, less than or equal to 14")
} else {
  print("i is greater than or equal to 15")
}
```

```
## [1] "i is greater than 10, less than or equal to 14"
```

# Loops with If/Else Statements

Suppose we want to take the numbers between 1 and 5, and divide the evens by 2 and multiply the odds by 2. We could do that using a loop with if/else statements!

```
for(i in 1:5){  
  if(i %% 2 == 0){ #check for even numbers  
    print(i / 2)  
  }else{  
    print(i * 2)  
  }  
}
```

```
## [1] 2  
## [1] 1  
## [1] 6  
## [1] 2  
## [1] 10
```

# Handling Special Cases

Aside from the previous toy example, `if()` statements are useful when you have to handle special cases.

`if()` statements can be used to make a loop ignore or fix problematic cases.

They are also useful for producing error messages, by generating a message *if* an input value is not what is expected.

### 3. `while()` Loops

# while()

A lesser-used looping structure is the `while()` loop.

Rather than iterating over a predefined vector, the loop keeps going until some condition is no longer true.

Here is the structure:

```
while(COND IS MET){  
  RUN CODE  
}
```

If you're not careful, the while loop will run **forever!!**

# Simple `while()` loop example:

```
x <- 0
while(x < 3){
  x <- x + 1
  print(x)
}
```

```
## [1] 1
## [1] 2
## [1] 3
```

What happened in each iteration?



# These Do the Same Thing

```
x <- 0
while(x < 3){
  x <- x + 1
  print(x)
}
```

```
## [1] 1
## [1] 2
## [1] 3
```

```
x <- 0
x <- x+1
print(x)
x <- x+1
print(x)
x <- x+1
print(x)
```

```
## [1] 1
## [1] 2
## [1] 3
```

# More Complex Example

Let's see how many times we need to flip a coin to get 4 heads:

```
num_heads <- 0
num_flips <- 0

while(num_heads < 4) {
  # simulating a coin flip
  coin_flip <- rbinom(n = 1, size = 1, prob = 0.5)

  # keep track of heads
  if (coin_flip == 1) {
    num_heads <- num_heads + 1
  }

  # update number of coin flips
  num_flips <- num_flips + 1
}

num_flips # follows negative binomial distribution
```

```
## [1] 10
```

# Summary

## 1. Why Loops?

- To make our lives easier!

## 2. `for()` loops:

- For iterating over a fixed number of items

## 3. `while()` loops:

- For iterating until some condition is met

*Let's take a 10 minute break, then return for some activities!*

# Activity 1

1. Create a `for` loop to calculate the maximum value of each variable in the `swiss` data. What are the maximum values of each variable?
2. Using your previous answer as a starting point, create a nested `for` loop to calculate the maximum value for each variable in the `swiss` data (outer loop), and then divide that maximum by 1, 2, and 4 (inner loop). Print the output after each step.
3. Using your previous answer as a starting point, write a loop that does the same calculations as before but stores the values in a matrix with `ncol(swiss)` columns and 3 rows. How will you "pre-allocate" space for the results?

# Activity 1: My Answers!

Question 1:

```
for(i in 1:ncol(swiss)) {  
  curr_max <- max(swiss[,i])  
  print(curr_max)  
}
```

```
## [1] 92.5  
## [1] 89.7  
## [1] 37  
## [1] 53  
## [1] 100  
## [1] 26.6
```

# Activity 1: My Answers!

Question 2:

```
for(i in 1:ncol(swiss)) {  
  curr_max <- max(swiss[,i])  
  for(j in c(1,2,4)){  
    print(curr_max/j)  
  }  
}
```

```
## [1] 92.5  
## [1] 46.2  
## [1] 23.1  
## [1] 89.7  
## [1] 44.9  
## [1] 22.4  
## [1] 37  
## [1] 18.5  
## [1] 9.25  
## [1] 53  
## [1] 26.5  
## [1] 13.2  
## [1] 100
```

# Activity 1: My Answers!

Question 3:

```
results <- matrix(NA, ncol=ncol(swiss),nrow=3)
for(i in 1:ncol(swiss)) {
  curr_max <- max(swiss[,i])
  for(j in 1:3){
    curr_divisor <- c(1,2,4)[j]
    results[j,i] <- curr_max/curr_divisor
  }
}
results
```

```
##      [,1] [,2] [,3] [,4] [,5] [,6]
## [1,] 92.5 89.7 37.00 53.0  100 26.60
## [2,] 46.2 44.9 18.50 26.5   50 13.30
## [3,] 23.1 22.4  9.25 13.2   25  6.65
```

# Activity 2

1. Consider the vector `vec <- c(1,2,NA,3,NA)`. Write a `for` loop that includes an `if/else` function so that for each value `x` in `vec`, we print "Missing!" if `x` is NA, and `x^3` otherwise.

2. What will happen if I run the following loop:

```
x <- 1
while(x < 10){
  print(x + 1)
}
```

3. Write a `while()` loop that starts with `x <- 1` and doubles `x` each iteration, while `x < 100`. Print `x` after each iteration.



# Activity 2: My Answers

1.

```
for(x in c(1,2,NA,3,NA)){  
  if(is.na(x)){  
    print("Missing!")  
  } else{  
    print(x^3)  
  }  
}
```

```
## [1] 1  
## [1] 8  
## [1] "Missing!"  
## [1] 27  
## [1] "Missing!"
```

# Activity 2: My Answers

2. What will happen if I run the following loop:

```
x <- 1
while(x < 10){
  print(x + 1)
}
```

- **Answer:** The while loop will run forever printing 1, since we are not updating x!!

# Activity 2: My Answers

3. Write a `while()` loop that starts with `x <- 1` and doubles `x` each iteration, while `x < 100`. Print `x` after each iteration.

```
x <- 1
while(x < 100){
  x <- x * 2
  print(x)
}
```

```
## [1] 2
## [1] 4
## [1] 8
## [1] 16
## [1] 32
## [1] 64
## [1] 128
```

*Why does `x` reach 128?!*

# Homework

HW 6 will be posted on the website shortly! Remember that it is a continuation of HW 5!