



Data manipulation in R

A program to use when size matters

Peter Shaw

September 24, 2015



Why use R?

Why not use a spreadsheet?



Why not use a spreadsheet?

- Data manipulation in Excel is VERY risk and time consuming
- A range of software packages are available for Excel
- Large data sets can exceed the size limits of standard programs
- Spreadsheets don't have the inherent understanding of statistics that R has
- For example handling of NA's
- R is hot!



Why use R?



Why use R?

- Its free
- Its available on most operating systems Windows, OS X, Linux
- There are huge numbers of packages available
- Its becoming the international standard for statistics



Getting Started I

Some References



James P. Howard.

R Cookbook.

O'Reilly Media, Inc, 2011.



Phil Spector.

Data Manipulation with R.

Use R series

Springer, 2008



Getting Started

Installing R!



Download it

- Open <http://www.r-project.org>
- Click CRAN (Under download on Top Left)
- Click <http://cran.ms.unimelb.edu.au/> University of Melbourne

Windows

- Select Windows
- Select Base
- Download R (suggest latest version)

OS X

- Select Select OS X
- Select R-3.2.2.pkg (or the version that matches your OS version)



Getting Started

Installing a GUI



How about RStudio

<https://www.rstudio.com/products/rstudio/download/>



Getting Started

Basic steps



```
2+5
```

```
## [1] 7
```

```
# Create a sequence of numbers
```

```
X = 2:10
```

```
# Display basic statistical measures
```

```
summary(X)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##         2         4         6         6         8         10
```

```
# use q() to quit
```



Getting Started

Help Functions



To access the documentation type

```
help.start()  
help(summary)  
args(summary)  
example(sd)
```




Help Functions

Search the Web



To search R documentation

```
RSiteSearch("key phrase") help(adf.test,package="tseries")
```

Custom Google search focused on R-specific websites

```
http://rseek.org
```

Coding Q&A site

```
http://stackoverflow.com http://stats.stakexchange.com
```



Iterative development

Working Creatively



Some discussion recently on how to work creatively. Research out of successful R&D projects developed into Agile

- Keep the managages away
- work sustainably
- people over process
- iterative development



R Data types

Lists, frames and tables



Lists

- $l = c(1, 3, 4)$
- *bbb*



Lets read the table

Check the current directory



Where are we

```
getwd()  
setwd("/Users/pcru")  
dir() #This lists the files  
ls()  #This lists the variables
```

<http://www.statmethods.net/input/contents.html>



Lets read the table

Reading a table



To read a csv table as a table try

```
tab1 <- as.matrix(read.csv(file="filetable.csv", sep="," , header=FALSE))
```

But our table is an excel file

- What about a package?
- <http://www.thertrader.com/2014/02/11/a-million-ways-to-connect-r-and-excel/>
- Lets use the R package xlsx



Where from

- install command
- `install.packages(pkgs)`

Citing Packages

<https://cran.r-project.org/web/packages/RefManagerR/vignettes/TestRmd.html>

```
x<-citation()  
toBibtex(x)  
  
## @Manual{,  
##   title = {R: A Language and Environment for Statistical Computing},  
##   author = {{R Core Team}},  
##   organization = {R Foundation for Statistical Computing},  
##   address = {Vienna, Austria},  
##   year = {2014},  
##   url = {http://www.R-project.org/},  
## }
```



Lets read the table

An example

```
table1<-read.xlsx2("1_R Wkshp_dummy data_OTU table.xlsx", sheetName =  
"Sheet1", header=FALSE, rowNames=FALSE, transpose=TRUE, endRow=18)
```

Loading the xlsx package

```
## Loading required package: xlsx  
## Warning: package 'xlsx' was built under R  
version 3.1.3  
## Loading required package: rJava  
## Warning: package 'rJava' was built under R  
version 3.1.3  
## Loading required package: methods  
## Loading required package: xlsxjars  
## Loading required package: xtable
```



Lets read the table

The columns are wrong



	X1	X2	X3	X4	X5	X6	X7
1	Group	Contaminated					
2	Site	1			2		
3	Sample ID	10000	10001	10002	10003	10004	10005
4	Rep	1	2	3	1	2	3
5	phormidiaceae	24872	24872	5822	7538	7201	7538
6	streptococcaceae	11	7	14	8	10	8



Lets read the table

Transpose the table



Transposing

We need to transpose the table and set the column names correctly

```
table1t=setNames(data.frame(t(table1[, -1])), table1[, 1])
```

http://rgm3.lab.nig.ac.jp/RGM/R_rdfile?f=Ecdat/man/read.transpose.Rd&d=R_CC <http://stackoverflow.com/questions/17288197/reading-a-csv-file-organized-horizontally>



Fields across many columns

Replicating first column



Lets do it the easy way first

```
ctridx<-which(table1t$Group=="Control")
table1t$Group[1:48]<-"Contaminated"
table1t$Group[(ctridx+1):48]<-"Control"
```

```
ttt<-table1t$Site
for(i in c(2:length(table1t$Site)))
{
  temp<-as.character(table1t$Site[i])
  tempb<-as.character(ttt[i-1])
  if (table1t$Site[i]=="")
  {
    ttt[i]<-tempb
  }
  if (!table1t$Site[(i)]=="")
  {
    ttt[i]<-temp
  }
}
table1t$Site<-ttt
```

```
## X3
## 1
## Levels: 1 2 3 4 FALSE TRUE
```



How to work with strings

stringr package

■ `require(stringr)`

Lets look at this package

■ `stri_c(str1, str2)`

concatenates two string

■ `str_len(str)`

```
require(stringr)
```

```
## Loading required package: stringr
```

```
table1t$Rep<-str_replace(table1t$Rep, "[rep]{3}?", "\\1")  
table1t$Rep<-str_replace(table1t$Rep, "A", "1")  
table1t$Rep<-str_replace(table1t$Rep, "B", "2")  
table1t$Rep<-str_replace(table1t$Rep, "C", "3")  
table1t$Rep<-as.factor(table1t$Rep)
```



Lets read the table

Reading a table of other types



- `http://www.statmethods.net/input/importingdata.html`
- `http://stackoverflow.com/questions/17288197/reading-a-csv-file-organized-horizontally`
- `http://rgm3.lab.nig.ac.jp/RGM/R_rdfileread?f=Ecdat/man/read.transpose.Rd&d=R_CC`
- Input files from Stata

```
library(foreign)
mydata <- read.dta("c:/mydata.dta")
```



Lets read the next table

Reading a table using xlsx



```
setwd("/Users/pcru/SizeDoesMatter1")  
#dir()  
table2<-read.xlsx2("2_R Wkshp_dummy data_Env Data_incl2outliersMK.xls
```

	Group	Site	Sample.ID	Rep	Spill.date
1	Contaminated	1	10000	1	14-May-14
2	Contaminated	1	10001	2	14-May-14
3	Contaminated	1	10002	3	14-May-14
4	Contaminated	2	10003	1	14-May-14
5	Contaminated	2	10004	2	14-May-14
6	Contaminated	2	10005	3	14-May-14



Lets read the next table

Reading a table



Oh NO All columns have been set to factors

```
str(table2[,1:11])
```

```
## 'data.frame': 48 obs. of  11 variables:
##  $ Group          : Factor w/ 2 levels "Contaminated",...: 1
##  $ Site            : Factor w/ 4 levels "1","2","3","4": 1 1
##  $ Sample.ID       : Factor w/ 18 levels "10000","10001",...:
##  $ Rep             : Factor w/ 9 levels "1","2","3","A",...:
##  $ Spill.date       : Factor w/ 2 levels "14-May-14","N/A": 1
##  $ Sample.collection.date: Factor w/ 4 levels "15.5.14","17/5/14",
##  $ labnum           : Factor w/ 36 levels "2000","2001",...: 1
##  $ phosphate..ppb.  : Factor w/ 39 levels "10","105","108",...:
##  $ ammonia..ppb.    : Factor w/ 41 levels "10","103","1042",...:
##  $ chlorophyll..ug.L : Factor w/ 38 levels "1","10","11",...: 2
##  $ DO....           : Factor w/ 31 levels "100","120","31",...:
```

lets break it down

First lets reed a few rows only

```
table2<-read.xlsx2("2 R Wkshp dummyv data Env Data incl2outliersMK.xls")
```



Lets read the next table I

Setting the data types



colClasses

- The variable colClasses can be used to specify the row types.
- We need to set stringsAsFactor=FALSE or all columns will be loaded as factors
- The dates are in a non standard format so we need to read them as chars first

```
table2b<-read.xlsx2("2_R Wkshp_dummy data_Env Data_incl2outliersMK.xlsx",
sapply(table2,class))
```

```
##           Group           Site      Sample.ID           Rep      Spill.d
## "character"      "numeric"    "numeric"      "character"    "character"
##      rowNames as.Data.frame
##      "logical"      "logical"
```



Lets read the next table II

Setting the data types





Lets read the next table

Setting the Date Type



```
table2f<-table2
table2f$Spill.date<-as.Date(table2f$Spill.date,"%d-%b-%y")
table2f$Sample.collection.date<-as.Date(table2f$Sample.collection.date)
```

```
## Error in
```

```
as.Date.default(table2f$Sample.collection.date,
"%d.%m.%y"): do not know how to convert
'table2f$Sample.collection.date' to class "Date"
```

```
#sapply(table2f,mode)
```

```
sapply(table2f,class)
```

```
##          Group          Site      Sample.ID          Rep      Spill.d
##  "character"      "numeric"    "numeric"    "character"    "Da
##      rowNames as.Data.frame
##      "logical"      "logical"
```



Lets read the next table

Setting the Date Type



colClasses

- The as.Date method can take a format string as the second variable
- The format strings are described in help on strptime
- But Spill.data has **two formats**
- We can use the if else function to combine them

```
table2bf<-table2b
table2bf$Spill.date<-as.Date(table2bf$Spill.date,"%d-%b-%y")
cdate1<-as.Date(table2bf$Sample.collection.date,"%d.%m.%y")
cdate2<-as.Date(table2bf$Sample.collection.date,"%d/%m/%y")
table2bf$Sample.collection.date<-as.Date(ifelse(!is.na(cdate1),as.Date(cdate1),as.Date(cdate2)))
table2bf$Group<-as.factor(table2bf$Group)
table2bf$Rep<-as.factor(table2bf$Rep)
na_count <-sapply(table2bf, function(y) sum(length(which(is.na(y)))))
na_count
```

```
##          Group          Site          Sample.
##          0          0
##          Rep          Spill.date Sample.collection.da
##          0          24
```



How to work with strings

merge command

- `require(stringr)`
- `str_c(str1, str2)` concatenates two string
- `str_len(str)`

```
require(stringr)
table2bf$Rep<-str_replace(table2bf$Rep, "[rep]{3}?", "\\1")
table2bf$Rep<-str_replace(table2bf$Rep, "A", "1")
table2bf$Rep<-str_replace(table2bf$Rep, "B", "2")
table2bf$Rep<-str_replace(table2bf$Rep, "C", "3")
table2bf$Rep<-as.factor(table2bf$Rep)
str(table2bf)
```

```
## 'data.frame': 48 obs. of 13 variables:
## $ Group : Factor w/ 2 levels "Contaminated",...: 1
## $ Site : num 1 1 1 2 2 2 1 1 1 2 ...
## $ Sample.ID : num 10000 10001 10002 10003 10004 ...
## $ Rep : Factor w/ 3 levels "1","2","3": 1 2 3 1
## $ Spill.date : Date, format: "2014-05-14" "2014-05-14"
## $ Sample.collection.date: Date, format: "2014-05-15" "2014-05-15"
## $ labnum : num 2000 2001 2002 2003 2004 ...
## $ phosphate_ppb : num 3020 3253 3169 2999 2879
```



How to merge two data sets

Using the merge command



The inbuilt command merge

- R has a command merge
- Lets start looking at the first 9 lines of the tables and merge them using the Sample ID
- Because otherwise its not uniques

```
merge(x, y, by = intersect(names(x), names(y)),
      by.x = by, by.y = by, all = FALSE, all.x = all, all.y = all,
      sort = TRUE, suffixes = c(".x", ".y"),
      incomparables = NULL, ...)
```

```
tab1c<-table1t[1:9,]
tab2c<-table2b[1:9,]
m1<-merge(tab1c,tab2c,by.x="Sample ID",by.y="Sample.ID")
m2<-merge(table1t,table2bf,by.x=c("Group","Site","Sample ID"),by.y=c(
m3<-merge(table1t,table2bf,by.x=c("Group","Site","Sample ID","Rep"),by
```



How to Append two data sets

Lets load a third data set



Follow up data from contaminated site

```

table3<-read.xlsx2("3_Follow up data from contaminated site_MK.xlsx", sheetName = "
table3f<-table3
table3f$Spill.date<-as.Date(table2f$Spill.date,"%d.%m.%y")
table3f$Sample.collection.date<-as.Date(table2f$Sample.collection.date,"%d.%m.%y")
sapply(table3f,mode)
sapply(table3f,class)

```

```

## Error in
as.Date.default(table2f$Sample.collection.date,
"%d.%m.%y"): do not know how to convert
'table2f$Sample.collection.date' to class "Date"

```

```

##           Group           Site           R
##           "numeric"         "numeric"      "numeri
##           Spill.date Sample.collection.date      labn
##           "numeric"         "numeric"      "numeri
##           phosphate..ppb. ammonia..ppb. chlorophyll..ug.
##           "numeric"         "numeric"      "numeri
##           DO.... phormidiaceae streptococcace
##           "numeric"         "numeric"      "numeri
##           vibriaceae enterobacteriaceae verrucimicrobiaceae

```



How to append two data sets

Lets load a third data set



Joining table 3 to are merged tables

- We need to be careful to match everything

3

```

Sample.ID←rep(20000,3)
table3fi←cbind(table3f, Sample.ID)
#how many columns I can't count
ncol(table3fi)
ncol(m3)
#now get the cols all right
table3fii←table3fi[c(1,2,24,3,4:23)]
m3i←m3[c(1:4,19:20,5:18,21:26)]
setdiff(names(m3i),names(table3fii))
m3ii←rename(m3i,c("Sample.ID"="Sample.ID"))
table3fiii←cbind(table3fii, corynebacteriaceae, porphyromonadaceae)
setdiff(names(m3ii),names(table3fiii))

m3ii[,c(7:24)] ← sapply(m3ii[,c(7:24)],as.numeric)
m3ii[,c(1:4)] ←sapply(m3ii[,c(1:4)],as.character)
#m3ii[,c("Site")] ←sapply(m3ii[,c("Site")],as.character)

table3fiii[,c(1:4)] ← sapply(table3fiii[,c(1:4)],as.character)
table3fiii[,c(7:24)] ← sapply(table3fiii[,c(7:24)],as.numeric)
table4←rbind(m3ii, table3fiii)
table4[,1] ← sapply(table4[,1],as.factor)

```

[1] 24



Another Break





RSQLite

- Suppose merge is not enough? I know about SQL and want to do joins
- Lets Install RSQLite
- We also need to install DBI

```
## Loading required package: RSQLite
## Loading required package: gsubfn
## Loading required package: proto
## Warning in doTryCatch(return(expr), name,
parentenv, handler): unable to load shared object
'/Library/Frameworks/R.framework/Resources/modules//R_X11.so':
##
dlopen(/Library/Frameworks/R.framework/Resources/modules//R_X11.so,
6): Library not loaded: /opt/X11/lib/libSM.6.dylib
## Referenced from:
/Library/Frameworks/R.framework/Resources/modules//R_X11.so
## Reason: image not found
## Could not load tcltk. Will use slower R code
instead.
## Loading required package: chron
```




Reshaping Tables

reshape2



```
reshape2
```

```
vignette(reshape)
```



Another important component of TDD is refactoring and unit tests

- Refactoring <http://refactoring.com/>
- <http://www.r-bloggers.com/my-experience-of-learning-r-from-basic-graphs-to-performance-tuning/>
- TDD in R <http://www.slideserve.com/andrew/test-driven-development-in-r>
- Version Control tortoiseSVN <http://tortoisesvn.net/>
- GitHub <https://github.com/>



Morning Tea Time

Back in 20min



Need coffee



Lunch Time

Back in 30 min



Provided



Dropping row and columns

Dropping selected variables



dropping variables



Adding a new column

Calculating the number of days



Using the *is.Date* command



centering data

Normalizing data



supply



Now lets have some fun

Making a heat map





What next

Proposed future talks



Your feedback on some ideas

- Using Sweave or Knitr
- Advanced Data Cleaning
- Network Centric data analysis



Resources

If you want to improve this style



LaTeX Beamer

<http://latex-beamer.sourceforge.net/>



Sharelatex Site

<https://www.sharelatex.com>



A Data Cleaning Mooc

<https://www.sharelatex.com>



The chunk below will not be printed