

# Smart Contract

- 陳博宇 @ 東吳大學 -

# 關於我

- 資工系 @ 交通大學
- 學術長 @ 清華大學區塊鏈研究社
- 核心成員 @ 台灣密碼龐克
- 區塊鏈工程師 @ 密碼貨幣交易所



# 目錄

- 1 什麼是智能合約
- 2 智能合約開發環境介紹
- 3 智能合約架構簡介
- 4 撰寫第一個智能合約
- 5 作業公布

```
pragma solidity ^0.6.0;

contract SimpleStorage {
    uint storedData;

    function set(uint x) public {
        storedData = x;
    }

    function get() public view returns (uint) {
        return storedData;
    }
}
```

# - 什麼是智能合約？ -

---

# 區塊鏈上的智能合約

## ● Bitcoin

- 支援條件判斷
- 不支援迴圈
- 不保存狀態
- 無法做複雜的計算設計

## ● Ethereum

- 支援條件判斷
- 支援迴圈
- 狀態儲存
- 可模擬任何程式執行
- 如何避免無窮迴圈？

# Gas的設計

- 每種運算都有其相對應的成本

- Gas Price

- 每個單位 Gas 的價格
- $1 \text{ Gwei} = 0.000000001 \text{ ETH}$

- Gas Limit

- 單筆交易所願意支付 Gas 單位的最大數量

- Tx Fee

- 最多為  $\text{Gas Limit} * \text{Gas Price}$

1. 礦工的選擇

2. 超鉅額手續費

## 合約的部署

- 1 寫好合約
- 2 編譯合約
  - Bytecode
  - ABI
- 3 透過線上 IDE 部署 or 其他

## 呼叫合約

- 1 Function 的識別碼
- 2 放上需要的參數

Function : setName(string)



Kecaak-256



c47f0027.....

## 優點

- 1 提供可信任應用
- 2 流程自動化
- 3 運行成本降低

## 缺點

- 1 安全性議題
- 2 交易處理速度
- 3 不可篡改的延伸問題



# - 開發環境介紹 -

---

- Remix - 線上 IDE

- <http://remix.ethereum.org>

- Solc (Solidity Compiler) - localhost

- <https://www.npmjs.com/package/solc>

# Remix - 線上 IDE

The screenshot displays the Remix IDE interface. On the left, the 'FILE EXPLORERS' sidebar shows a 'browser' view with four files: '1\_Storage.sol', '2\_Owner.sol', '3\_Ballot.sol', and '4\_Ballot\_test.sol'. Below this, two green callout boxes highlight 'Solidity Compiler' and 'Deploy & run tx'. The main workspace features a blue header with the Remix logo and buttons for 'Learn more' and 'Use previous version'. The central area is divided into three sections: 'Environments' with 'Solidity' and 'Vyper' buttons; 'File' with options like 'New File', 'Open Files', and 'Connect to Localhost'; and 'Featured Plugins' with 'Pipeline', 'Debugger', and 'Workshops'. A 'Resources' section on the right lists 'Documentation', 'Gitter channel', 'Medium Posts', and 'Tutorials'. At the bottom, a search bar prompts 'Search with transaction hash or address', and a console area shows two function definitions: 'remix.call(message: {name, key, payload}): Call a registered plugins' and 'remix.getFile(path): Returns the content of the file located at the given path'.

FILE EXPLORERS

▼ browser

- 1\_Storage.sol
- 2\_Owner.sol
- 3\_Ballot.sol
- 4\_Ballot\_test.sol

**Solidity Compiler**

**Deploy & run tx**

Home

1 tabs

Learn more Use previous version

Environments

Solidity Vyper

File

New File

Open Files

Connect to Localhost

Import From:

Gist GitHub Swarm Ipfs https Resolver-engine

Featured Plugins

Pipeline

Debugger

Workshops

See all Plugins

Resources

Documentation

Gitter channel

Medium Posts

Tutorials

listen on network

Search with transaction hash or address

```
remix.call(message: {name, key, payload}): Call a registered plugins
```

```
remix.getFile(path): Returns the content of the file located at the given path
```

# Remix - 線上 IDE

The screenshot displays the Remix online IDE interface. On the left, the 'SOLIDITY COMPILER' panel is open, showing various configuration options. The 'Compiler' dropdown is set to '0.6.1+commit.e6f7d5a4'. Below it, the 'Language' is set to 'Solidity' and the 'EVM Version' is set to 'compiler default'. A 'Compile <no file selected>' button is highlighted with an orange border. Under the 'Compiler Configuration' section, there are three checkboxes: 'Auto compile', 'Enable optimization', and 'Hide warnings', all of which are currently unchecked. At the bottom of this panel, an orange button reads 'No Contract Compiled Yet'. The main workspace on the right is empty, with a tab indicator showing '1' file. At the bottom of the interface, there is a search bar with the placeholder text 'Search with transaction hash or address' and a 'listen on network' checkbox. Below the search bar, there is a list of registered plugins: 'remix.call(message: {name, key, payload}): Call a registered plugins' and 'remix.getFile(path): Returns the content of the file located at the given path'.

SOLIDITY COMPILER

Compiler 0.6.1+commit.e6f7d5a4

Language Solidity

EVM Version compiler default

Compile <no file selected>

Compiler Configuration

☐ Auto compile

☐ Enable optimization

☐ Hide warnings

No Contract Compiled Yet

Search with transaction hash or address

remix.call(message: {name, key, payload}): Call a registered plugins

remix.getFile(path): Returns the content of the file located at the given path

# Remix - 線上 IDE

DEPLOY & RUN TRANSACTIONS

Environment: JavaScript VM

Account: 0xCA3...a733c (100 eth)

Gas limit: 3000000

Value: 0 wei

No compiled contracts  
or

At Address Load contract from Address

Transactions recorded: 0

Deployed Contracts

Currently you have no contract instances to interact with.

0 listen on network Search with transaction hash or address

remix.call(message: {name, key, payload}): Call a registered plugins

remix.getFile(path): Returns the content of the file located at the given path

# - 智能合約架構簡介 -

---

# 基礎架構

```
pragma solidity ^0.6.0;
```

```
contract SimpleStorage {
```

```
    uint256 storedData; ← 變數宣告
```

```
    function set(uint256 x) public { ← 很多函數
```

```
        storedData = x;
```

```
    }
```

```
    function get() public view returns (uint256) { ← 很多函數
```

```
        return storedData;
```

```
    }
```

```
}
```

# 變數宣告

## ● 變數型態

- bool
- int / uint
- bytes
- address
- string
- array
- mapping

+

## ● 能見度

- public
- private
- internal

+

## ● 變數名稱

```
int8 public age;  
bool private hack;  
string name;
```



# 變數宣告

## ● address

```
address payable public bank;
```

## ● mapping

```
mapping(address => uint256) public balances;  
balances[address] = 10;  
uint256 balance = balances[address];
```

## ● array

○ push

○ pop

○ length

```
uint256[4] fixArr;  
uint256[] dynamicArr;
```

# 特殊變數

## ● Coin

- ☐ wei
- ☐ gwei
- ☐ finney
- ☐ ether

## ● Time

- ☐ now
- ☐ seconds
- ☐ weeks
- ☐ years

## ● Tx

- ☐ tx.orgin
- ☐ tx.gasPrice

## ● msg

- ☐ msg.sender
- ☐ msg.value

User → Contract A → Contract B

# 特殊變數

## ● Address

- ☐ address.balance
- ☐ address.tranfser
- ☐ address.send
- ☐ address.call
- ☐ address.delegatecall

## ● Block

- ☐ block.number
- ☐ block.timestamp
- ☐ block.difficulty
- ☐ blockhash ( uint )

# 函數宣告

● 函數名稱(參數)    +    ● 能見度    +    ● 回傳值

☐ public

☐ private

☐ internal

☐ external

```
function funName() private {...}  
function funName2(uint num) external returns(uint8) {...}  
function deposit() public payable {...}
```

# 函數宣告

## ● View function

## ● Pure function

- 不改變合約狀態
- 函數執行不消耗 gas
- 不需經過礦工驗證
- 函數執行不消耗 gas

```
function viewFun(uint256 a, uint256 b) public view returns (uint256) {  
    return a * (b + 42) + now;  
}  
  
function pureFun(uint256 a, uint256 b) public pure returns (uint256) {  
    return a * (b + 42);  
}
```

# 特殊函數

## ● Assert

- 燒掉所有 gas
- 常用於處理非變量
- 常用於處理溢位
- 驗證改變後的狀態
- 一般用於函數結尾

## ● Require

- 退回剩餘 gas
- 常用於驗證 input
- 常用於驗證條件狀態
- 一般用於函數開頭
- 允許 error message

## ● Revert

- 退回剩餘 gas
- 搭配 if / else
- 允許 error message

# 特殊函數

revert →

```
function buy(uint amount) public payable {  
    if (amount > msg.value / 2 ether)  
        revert("Not enough Ether provided.");  
}
```

require、assert



```
function sendHalf(address payable addr) public payable returns (uint256 balance) {  
    require(msg.value % 2 == 0, "Even value required.");  
    uint256 balanceBeforeTransfer = address(this).balance;  
    addr.transfer(msg.value / 2);  
    assert(address(this).balance == balanceBeforeTransfer - msg.value / 2);  
    return address(this).balance;  
}
```

# 特殊函數

## ● Constructor

- 合約建構子
- 只會執行一次
- 非必須

## ● Selfdestruct

- 合約自殺
- 唯一參數為地址
- 把合約剩餘的錢給該地址

```
contract shop {  
    address payable owner;  
  
    constructor() public {  
        owner = msg.sender;  
    }  
  
    function close() public {  
        require(owner == msg.sender);  
        selfdestruct(owner);  
    }  
}
```



# 特殊函數

## ● Fallback / Receive [payable]

- 沒有 function 宣告
- 沒有參數與回傳值
- 必須是 external
- 預設只有 2300 gas
- 非必要
- 觸發條件：
  1. 單純的轉帳
  2. 呼叫合約沒有的函數

```
contract StandardFallback {  
    receive() external payable {}  
    fallback() external {}  
}
```

- 撰寫第一個智能合約 -

---

- Demo Time -

---

- 作業公布 -

---

# 作業公布

## ● 實作一個銀行合約

### ○ 函數功能要有：

- 存錢
- 提錢
- 轉帳
- 查詢餘額
- 查詢銀行餘額
- 帳戶註冊

### ○ 要有 Fallback (捲款潛逃)

### ○ 要有 Constructor

### ○ 基本防呆 ( with error message )

### ○ 使用 mapping 存取帳本

# 函數詳細內容

- Constructor → 設定合約擁有者
- 存錢 → `function deposit()`
- 提錢 → `function withdraw(uint withdrawAmount)`
- 轉帳 → `function tnasfer(uint transerAmount)`
- 餘額查詢 → `function getBalance()`
- 銀行餘額查詢 → `function getBankBalance()`
- 帳戶註冊 → `function enroll(string accountName)`
- Fallback → 確認是 Owner 卷款錢逃
- Constructor → 設定 Owner
- 防呆說明 → Error message