Designing a Custom AXI-lite Slave Peripheral

LECTURE 9

IOULIIA SKLIAROVA

Custom Hardware

Custom hardware blocks are used to:

- Delegate to hardware time-critical functions
- Save MicroBlaze resources

Two examples will be considered:

- A custom coprocessors with no output ports
- A custom peripheral with output ports

Next lab (lab. 7) will be dedicated to the design and use of a custom peripheral IP – Display Driver.

Block Design (BD)



AXI4 Protocol

Consult **Vivado AXI Reference Guide** and **AMBA AXI Protocol Specification**

There are three types of AXI4 interfaces:

- **AXI4**: For high-performance memory-mapped requirements.
- **AXI4-Lite**: For simple, low-throughput memory-mapped communication (for example, to and from control and status registers).
- **AXI4-Stream**: For high-speed streaming data.

AXI-Lite:

- all transactions are of burst length 1
- all data accesses use the full width of the data bus
- AXI4-Lite supports a data bus width of 32-bit or 64-bit
- all accesses are non-modifiable, non-bufferable

Global	Write address channel	Write data channel	Write response channel	Read address channel	Read data channel
ACLK	AWVALID	WVALID	BVALID	ARVALID	RVALID
ARESETn	AWREADY	WREADY	BREADY	ARREADY	RREADY
–	AWADDR	WDATA	BRESP	ARADDR	RDATA
–	AWPROT	WSTRB	–	ARPROT	RRESP

AXI4-lite Handshaking Signals

Consistent across the five channels.

Based on a simple “Ready” and “Valid” principle:

- “Ready” is used by the recipient to indicate that it is ready to accept a transfer of a data or address value.
- “Valid” is used to clarify that the data (or address) provided on that channel by the sender is valid so that the recipient can then sample it.



Example 1 – Adder with 3 Operands

Import Block Design

Create and Package new IP (*CustomCopr*)

Add IP

Edit in IP Packager

CustomCopr:

- Adds the contents of 3 registers (written by software)
- Puts the result in the 4th register (read by software)

Apply options from T6 (Problems and Results)

Generate output products

Create HDL Wrapper

Generate Bitstream

Export Hardware

Launch Vitis

Vitis

If build errors do appear, update **all the makefiles** related to the custom IP:





Correct Makefile

```
COMPILER=
ARCHIVER=
CP=cp
COMPILER_FLAGS=
EXTRA_COMPILER_FLAGS=
LIB=libxil.a

RELEASEDIR=../../../lib
INCLUDEDIR=../../../include
INCLUDES=-I./. -I${INCLUDEDIR}

INCLUDEFILES=*.h
LIBSOURCES=*.c
OBJECTS = $(addsuffix .o, $(basename $(wildcard *.c)))
ASSEMBLY_OBJECTS = $(addsuffix .o, $(basename $(wildcard *.S)))

libs:
	echo "Compiling CustomCopr..."
	$(COMPILER) $(COMPILER_FLAGS) $(EXTRA_COMPILER_FLAGS) $(INCLUDES) $(LIBSOURCES)
	$(ARCHIVER) -r ${RELEASEDIR}/${LIB} ${OBJECTS} ${ASSEMBLY_OBJECTS}
	make clean

include:
	${CP} $(INCLUDEFILES) $(INCLUDEDIR)

clean:
	rm -rf ${OBJECTS} ${ASSEMBLY_OBJECTS}
```


After Correcting the Makefiles

1. Clean the projects
2. Build the hardware platform
3. Analyze the file xparameters.h (correct the main code if necessary)
4. Build the software application
5. Run the application (source code available on eLearning)

Example 2 – triple PWM Generator

PWM – Pulse Width Modulation



PWM

Frequency – how many times per second the LED is switched on and off:

- Cannot be very slow to avoid flicker

Resolution - indicates how many intermediate steps (also called „units“) a PWM cycle has:

- In 8 bit mode, there are 256 levels of brightness

One easy way to build a PWM generator is to use two counters:

- Counter 1 (*s_clkEnbCnt*) limits the frequency of PWM pulses
- Counter 2 (*s_pwmCounter*) controls duty-cycle of PWM pulses (pulse width) within the chosen resolution
- PWM frequency =

  = system clock / (resolution * counter_1_MaxValue)

Lab. 7 – parts 1-3

Direct the display refresh functions to custom hardware

The custom display driver will receive from the MicroBlaze (through AXI-Lite interface):

- Digit enables – 8 bits
- Decimal point enables - 8 bits
- Digit values - 32 bits (8 x 4 bits)

The custom display driver will produce on its outputs:

- an – 8 bits
- seg – 7 bits
- dp – 1 bit

The original GPIO_Displays must be deleted



Final Remarks

At the end of this lecture you should be able to:

- Design custom hardware modules interacting with the MicroBlaze through AXI-Lite interface
- write C programs that make use of custom hardware

To do:

- Construct the considered hardware platforms
- Test the given applications in Vitis