

Manual Test Cases _ Graph Phone Book (Q-Test)

Authentication and registration

TC-AUTH-03 _ Duplicate email on sign-up

Register one user, then try sign_up again with a different username but the same email. The brief implies email should be unique. Without this check, a registration integrity gap can go unnoticed. There is no unique email constraint in the schema.

Search and response shape

TC-SRCH-06 _ Field consistency across lookups

Create a contact that includes an explanation. Call get_all_phone_users and get_phone_user_by_name for the same person, then compare the fields for phones and explanation. Callers and docs break if the two paths disagree. In particular, watch for phone_number versus phone_numbers, and whether by-name drops the explanation. Judge the result against the brief.

Protocol and client CLI

TC-ZMQ-02 _ Full sample file end to end

With the server running, run the real client against samples/commands.json. This is the official vendor happy path and confirms real client-server batch behavior. Inspect the printed response shape by eye, including whether the payload looks double encoded. A strict goldenfile assert is blocked until the encoding bug is fixed, so this stays a manual walkthrough for now.

TC-ZMQ-04 _ Bad or missing --file

Point the client at a missing file or invalid JSON. The client should fail fast so an operator is not left hanging on ZeroMQ. Review the CLI error wording and experience as a human would brittle exception text asserts are less useful here than confirming the tool fails clearly and early.

Negative and edge cases

TC-NEG-01 _ Empty username on sign-up

Call sign_up with an empty username. Empty identity is a common abuse or typo path, unprotected sign-up can pollute the database. The brief does not define the expected message yet, so record the observed behavior: rejection, cryptic error, or silent acceptance.

TC-NEG-02 _ SQL injection in username

Put crafted attacker controlled strings into username and related fields. Auth and contact fields are attacker controlled, the system must not crash or wipe tables. This is a security spot check: look for crashes, unexpected side effects, or corrupted data rather than a single pass criterion.

TC-NEG-03 _ Very long explanation

Add a contact with an extremely long explanation string. Large text can hit database or column limits and break add or list under real use. Whether the system accepts, truncates, or errors is undefined in the brief.

TC-NEG-004 _ Unicode names (Persian / emoji)

Create and look up contacts whose names include Persian text and emoji. These names matter for this locale, and encoding bugs are easy to ship. Confirm a readable names by eye not only that no exception was raised.

TC-NEG-005 _ Concurrent sign-in for the same user

Sign the same user in from two clients (or two ports) at once. This stresses session and online_users semantics. Note whether both sessions stay active, one replaces the other, or something else happens.

TC-NEG-006 _ Port out of range

Start the server with a --port value outside the allowed range. A wrong port must not silently bind the wrong endpoint in operations. Confirm interactively whether the process rejects the value or falls back to 9090 (valid ports are range(1000, 9998)).