

Python

Lists

Loops let us do things many times

Loops let us do things many times

Collections let us store many values together

Loops let us do things many times

Collections let us store many values together

Most popular collection is a *list*

Create using `[value, value, ...]`

Create using `[value, value, ...]`

Get/set values using `var[index]`

Create using [value, value, ...]

Get/set values using var[index]

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(gases)  
['He', 'Ne', 'Ar', 'Kr']
```

Create using [value, value, ...]

Get/set values using var[index]

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(gases)  
['He', 'Ne', 'Ar', 'Kr']
```

```
print(gases[1])  
Ne
```


Index from 0, not 1

Index from 0, not 1

Reasons made sense for C in 1970...

Index from 0, not 1

Reasons made sense for C in 1970...

It's an error to try to access out of range

Index from 0, not 1

Reasons made sense for C in 1970...

It's an error to try to access out of range

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(gases[4])
```

IndexError: list index out of range

Use `len(list)` to get length of list

Use `len(list)` to get length of list

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(len(gases))  
4
```

Use `len(list)` to get length of list

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(len(gases))  
4
```

Returns 0 for the *empty list*

```
etheric = []  
print(len(etheric))  
0
```

Some negative indices work

Some negative indices work

`values[-1]` is last element, `values[-2]` next-to-last, ...

Some negative indices work

`values[-1]` is last element, `values[-2]` next-to-last, ...

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

Some negative indices work

`values[-1]` is last element, `values[-2]` next-to-last, ...

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(gases[-1], gases[-4])  
Kr He
```

Some negative indices work

`values[-1]` is last element, `values[-2]` next-to-last, ...

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(gases[-1], gases[-4])  
Kr He
```

`values[-1]` is much nicer than `values[len(values)-1]`

Some negative indices work

`values[-1]` is last element, `values[-2]` next-to-last, ...

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(gases[-1], gases[-4])  
Kr He
```

`values[-1]` is much ~~nicer~~ than `values[len(values)-1]`

less error prone

Mutable : can change it after it is created

Mutable : can change it after it is created

```
gases = ['He', 'Ne', 'Ar', 'K'] # last entry misspelled
```

Mutable : can change it after it is created

```
gases = ['He', 'Ne', 'Ar', 'K'] # last entry misspelled  
gases[3] = 'Kr'
```


Mutable : can change it after it is created

```
gases = ['He', 'Ne', 'Ar', 'K']    # last entry misspelled
gases[3] = 'Kr'
print(gases)
['He', 'Ne', 'Ar', 'Kr']
```

Mutable : can change it after it is created

```
gases = ['He', 'Ne', 'Ar', 'K']    # last entry misspelled
gases[3] = 'Kr'
print(gases)
['He', 'Ne', 'Ar', 'Kr']
```

Location must exist before assignment

Mutable : can change it after it is created

```
gases = ['He', 'Ne', 'Ar', 'K']    # last entry misspelled
gases[3] = 'Kr'
print(gases)
['He', 'Ne', 'Ar', 'Kr']
```

Location must exist before assignment

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

Mutable : can change it after it is created

```
gases = ['He', 'Ne', 'Ar', 'K']    # last entry misspelled
gases[3] = 'Kr'
print(gases)
['He', 'Ne', 'Ar', 'Kr']
```

Location must exist before assignment

```
gases = ['He', 'Ne', 'Ar', 'Kr']
gases[4] = 'Xe'
```

IndexError: list assignment index out of range

Heterogeneous : can store values of many kinds

Heterogeneous : can store values of many kinds


```
helium = ['He', 2]
```

```
neon = ['Ne', 8]
```

Heterogeneous : can store values of many kinds

```
helium = ['He', 2]  
neon = ['Ne', 8]
```


[string, int]



Heterogeneous : can store values of many kinds

```
helium = ['He', 2]
```

```
neon = ['Ne', 8]
```




Heterogeneous : can store values of many kinds

```
helium = ['He', 2]  
neon = ['Ne', 8]  
gases = [helium, neon]
```


Heterogeneous : can store values of many kinds

```
helium = ['He', 2]  
neon = ['Ne', 8]  
gases = [helium, neon]
```



Heterogeneous : can store values of many kinds

```
helium = ['He', 2]  
neon = ['Ne', 8]  
gases = [helium, neon]
```



Devote a whole
episode to this

Loop over elements to "do all"

Loop over elements to "do all"

Use `while` to step through all possible indices

Loop over elements to "do all"

Use `while` to step through all possible indices

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
i = 0  
while i < len(gases):  
    print(gases[i])  
    i += 1
```

Loop over elements to "do all"

Use `while` to step through all possible indices

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
i = 0
```

← First legal index

```
while i < len(gases):  
    print(gases[i])  
    i += 1
```

Loop over elements to "do all"

Use `while` to step through all possible indices

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
i = 0  
while i < len(gases):  
    print(gases[i])  
    i += 1 ← Next index
```


Loop over elements to "do all"

Use `while` to step through all possible indices

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
i = 0
```

```
while i < len(gases):
```

———— Defines set of legal indices

```
    print(gases[i])
```

```
    i += 1
```

Loop over elements to "do all"

Use `while` to step through all possible indices

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
i = 0  
while i < len(gases):  
    print(gases[i])  
    i += 1
```

He

Ne

Ar

Kr

Loop over elements to "do all"

Use `while` to step through all possible indices

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
i = 0  
while i < len(gases):  
    print(gases[i])  
    i += 1
```

He

Ne

Ar

Kr

Tedious to type in over and over again

Loop over elements to "do all"

Use `while` to step through all possible indices

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
i = 0  
while i < len(gases):  
    print(gases[i])  
    i += 1
```

He

Ne

Ar

Kr

Tedious to type in over and over again

And it's easy to forget the "`+= 1`" at the end

Use a **for** loop to access each value in turn

Use a `for` loop to access each value in turn

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
for gas in gases:  
    print(gas)
```

He

Ne

Ar

Kr

Use a `for` loop to access each value in turn

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
for gas in gases:  
    print(gas)
```

He

Ne

Ar

Kr

Loop variable assigned each *value* in turn

Use a `for` loop to access each value in turn

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
for gas in gases:  
    print(gas)
```

He

Ne

Ar

Kr

Loop variable assigned each *value* in turn

Not each index

Use a `for` loop to access each value in turn

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
for gas in gases:  
    print(gas)
```

He

Ne

Ar

Kr

Loop variable assigned each *value* in turn

Not each index

Because that's the most common case

Can delete entries entirely (shortens the list)

Can delete entries entirely (shortens the list)

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

Can delete entries entirely (shortens the list)

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
del gases[0]
```

Can delete entries entirely (shortens the list)

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
del gases[0]  
print(gases)  
['Ne', 'Ar', 'Kr']
```

Can delete entries entirely (shortens the list)

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
del gases[0]  
print(gases)  
['Ne', 'Ar', 'Kr']  
del gases[2]
```

Can delete entries entirely (shortens the list)

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
del gases[0]  
print(gases)  
['Ne', 'Ar', 'Kr']  
del gases[2]  
print(gases)  
['Ne', 'Ar']
```

Can delete entries entirely (shortens the list)

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
del gases[0]  
print(gases)  
['Ne', 'Ar', 'Kr']  
del gases[2]  
print(gases)  
['Ne', 'Ar']
```

Yes, deleting an index that doesn't exist is an error

Appending values to a list lengthens it

Appending values to a list lengthens it

```
gases = []
```

Appending values to a list lengthens it

```
gases = []  
gases.append('He')
```

Appending values to a list lengthens it

```
gases = []  
gases.append('He')  
gases.append('Ne')
```

Appending values to a list lengthens it

```
gases = []  
gases.append('He')  
gases.append('Ne')  
gases.append('Ar')
```

Appending values to a list lengthens it

```
gases = []  
gases.append('He')  
gases.append('Ne')  
gases.append('Ar')  
print(gases)  
['He', 'Ne', 'Ar']
```

Appending values to a list lengthens it

```
gases = []  
gases.append('He')  
gases.append('Ne')  
gases.append('Ar')  
print(gases)  
['He', 'Ne', 'Ar']
```

Most operations on lists are *methods*

Appending values to a list lengthens it

```
gases = []  
gases.append('He')  
gases.append('Ne')  
gases.append('Ar')  
print(gases)  
['He', 'Ne', 'Ar']
```

Most operations on lists are *methods*

A function that belongs to (and usually operates on)
specific data

Appending values to a list lengthens it

```
gases = []  
gases.append('He')  
gases.append('Ne')  
gases.append('Ar')  
print(gases)  
['He', 'Ne', 'Ar']
```

Most operations on lists are *methods*

A function that belongs to (and usually operates on)
specific data

`thing . method (args)`

Some useful list methods

Some useful list methods

```
gases = ['He', 'He', 'Ar', 'Kr'] # 'He' is duplicated
```

Some useful list methods

```
gases = ['He', 'He', 'Ar', 'Kr'] # 'He' is duplicated
print(gases.count('He'))
2
```

Some useful list methods

```
gases = ['He', 'He', 'Ar', 'Kr'] # 'He' is duplicated
print(gases.count('He'))
2
print(gases.index('Ar'))
2
```

Some useful list methods

```
gases = ['He', 'He', 'Ar', 'Kr'] # 'He' is duplicated
print(gases.count('He'))
2
print(gases.index('Ar'))
2
gases.insert(1, 'Ne')
```

Some useful list methods

```
gases = ['He', 'He', 'Ar', 'Kr'] # 'He' is duplicated
print(gases.count('He'))
2
print(gases.index('Ar'))
2
gases.insert(1, 'Ne')
print(gases)
['He', 'Ne', 'He', 'Ar', 'Kr']
```

Two that are often used incorrectly

Two that are often used incorrectly

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

Two that are often used incorrectly

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(gases.sort())  
None
```

Two that are often used incorrectly

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(gases.sort())  
None  
print(gases)  
['Ar', 'He', 'Kr', 'Ne']
```

Two that are often used incorrectly

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
print(gases.sort())
```

None

```
print(gases)
```

['Ar', 'He', 'Kr', 'Ne']

```
print(gases.reverse())
```

None

Two that are often used incorrectly

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
print(gases.sort())
```

None

```
print(gases)
```

['Ar', 'He', 'Kr', 'Ne']

```
print(gases.reverse())
```

None

```
print(gases)
```

['Ne', 'Kr', 'He', 'Ar']

Two that are often used incorrectly

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
print(gases.sort())
```

None

```
print(gases)
```

['Ar', 'He', 'Kr', 'Ne']

```
print(gases.reverse())
```

None

```
print(gases)
```

['Ne', 'Kr', 'He', 'Ar']

A common bug

Two that are often used incorrectly

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
print(gases.sort())
```

None

```
print(gases)
```

['Ar', 'He', 'Kr', 'Ne']

```
print(gases.reverse())
```

None

```
print(gases)
```

['Ne', 'Kr', 'He', 'Ar']

A common bug

`gases = gases.sort()` assigns `None` to `gases`

There is an alternative built-in function for sorting:

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
s_gases = sorted(gases)  
r_gases = sorted(gases, reverse=True)
```

```
print(gases)  
['He', 'Ne', 'Ar', 'Kr']
```

```
print(s_gases)  
['Ar', 'He', 'Kr', 'Ne']
```

```
print(r_gases)  
['Ne', 'Kr', 'He', 'Ar']
```


Use `in` to test for membership

Use `in` to test for membership

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

Use **in** to test for membership

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print('He' in gases)  
True
```

Use **in** to test for membership

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print('He' in gases)  
True  
if 'Pu' in gases:  
    print('But plutonium is not a gas!')  
else:  
    print('The universe is well ordered.')
```

Use `in` to test for membership

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print('He' in gases)  
True  
if 'Pu' in gases:  
    print('But plutonium is not a gas!')  
else:  
    print('The universe is well ordered.')  
The universe is well ordered.
```

Use `range` to construct a range of numbers

Use `range` to construct a range of numbers

```
print (range (5) )  
range (0, 5)
```

Use `list(range)` to construct lists of numbers

Use `list(range)` to construct lists of numbers

```
print(list(range(5)))  
[0, 1, 2, 3, 4]
```

Use `list(range)` to construct lists of numbers

```
print(list(range(5)))  
[0, 1, 2, 3, 4]  
print(list(range(2, 6)))  
[2, 3, 4, 5]
```

Use `list(range)` to construct lists of numbers

```
print(list(range(5)))
```

```
[0, 1, 2, 3, 4]
```

```
print(list(range(2, 6)))
```

```
[2, 3, 4, 5]
```

```
print(list(range(0, 10, 3)))
```

```
[0, 3, 6, 9]
```

Use `list(range)` to construct lists of numbers

```
print(list(range(5)))  
[0, 1, 2, 3, 4]  
print(list(range(2, 6)))  
[2, 3, 4, 5]  
print(list(range(0, 10, 3)))  
[0, 3, 6, 9]  
print(list(range(10, 0)))  
[]
```

So `list(range(len(list)))` is all indices for the list

So `list(range(len(list)))` is all indices for the list

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

So `list(range(len(list)))` is all indices for the list

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
print(len(gases))
```

4

So `list(range(len(list)))` is all indices for the list

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
print(len(gases))
```

```
4
```

```
print(list(range(len(gases))))
```

```
[0, 1, 2, 3]
```


So `list(range(len(list)))` is all indices for the list

```
gases = ['He', 'Ne', 'Ar', 'Kr']  
print(len(gases))  
4  
print(list(range(len(gases))))  
[0, 1, 2, 3]  
for i in range(len(gases)):  
    print(i, gases[i])
```

So `list(range(len(list)))` is all indices for the list

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
print(len(gases))
```

```
4
```

```
print(list(range(len(gases))))
```

```
[0, 1, 2, 3]
```

```
for i in range(len(gases)):
```

```
    print(i, gases[i])
```

```
0 He
```

```
1 Ne
```

```
2 Ar
```

```
3 Kr
```

So `list(range(len(list)))` is all indices for the list

```
gases = ['He', 'Ne', 'Ar', 'Kr']
```

```
print(len(gases))
```

```
4
```

```
print(list(range(len(gases))))
```

```
[0, 1, 2, 3]
```

```
for i in range(len(gases)):
```

```
    print(i, gases[i])
```

```
0 He
```

```
1 Ne
```

```
2 Ar
```

```
3 Kr
```

A very common *idiom* in Python