

E-Commerce SaaS Platform

This document describes the functional and non-functional requirements of the e-commerce platform as agreed during the discovery phase. Each section corresponds to a distinct deliverable module.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request.

The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request.

The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request.

The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request.

The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak.

metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as

--- Module: ZephyrAuth ---

Description: Authentication and authorisation subsystem.

The ZephyrAuth module is responsible for handling all aspects of authentication and authorisation subsystem. It exposes a dedicated REST API surface and integrates with the core platform via internal service-to-service calls. All ZephyrAuth operations are logged at INFO level for audit trails. Performance SLA: p99 latency < 200 ms at 100 rps.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and

[illegible]

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under `/api/v1` and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and

[illegible]

[illegible]

degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates

--- Module: AuroraCache ---

Description: Distributed caching layer backed by redis.

The AuroraCache module is responsible for handling all aspects of distributed caching layer backed by Redis. It exposes a dedicated REST API surface and integrates with the core platform via internal service-to-service calls. All AuroraCache operations are logged at INFO level for audit trails. Performance SLA: p99 latency < 200 ms at 100 rps.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request.

The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request.

The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request.

[illegible]

is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exc

--- Module: CosmosSearch ---

Description: Full-text search integration via elasticsearch.

The CosmosSearch module is responsible for handling all aspects of full-text search integration via Elasticsearch. It exposes a dedicated REST API surface and integrates with the core platform via internal service-to-service calls. All CosmosSearch operations are logged at INFO level for audit trails. Performance SLA: p99 latency < 200 ms at 100 rps.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance

[illegible]

is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability

Description: Analytics and kpi reporting dashboard.

The OrionMetrics module is responsible for handling all aspects of analytics and KPI reporting dashboard. It exposes a dedicated REST API surface and integrates with the core platform via internal service-to-service calls. All OrionMetrics operations are logged at INFO level for audit trails. Performance SLA: p99 latency < 200 ms at 100 rps.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance

[illegible]

[illegible]

separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively t

--- Module: PulsarNotify ---

Description: Real-time notification engine (email + push).

The PulsarNotify module is responsible for handling all aspects of real-time notification engine (email + push). It exposes a dedicated REST API surface and integrates with the core platform via internal service-to-service calls. All PulsarNotify operations are logged at INFO level for audit trails. Performance SLA: p99 latency < 200 ms at 100 rps.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability

[illegible]

separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates

--- Module: VegaExport ---

Description: Data export module - csv, excel, and pdf reports.

The VegaExport module is responsible for handling all aspects of data export module - CSV, Excel, and PDF reports. It exposes a dedicated REST API surface and integrates with the core platform via internal service-to-service calls. All VegaExport operations are logged at INFO level for audit trails. Performance SLA: p99 latency < 200 ms at 100 rps.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability

[illegible]

Description: Administrative back-office and user management panel.

The SiriusAdmin module is responsible for handling all aspects of administrative back-office and user management panel. It exposes a dedicated REST API surface and integrates with the core platform via internal service-to-service calls. All SiriusAdmin operations are logged at INFO level for audit trails. Performance SLA: p99 latency < 200 ms at 100 rps.

[illegible]

separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak.

peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend

--- Module: LyraCI ---

Description: Ci/cd pipeline and deployment automation.

The LyraCI module is responsible for handling all aspects of CI/CD pipeline and deployment automation. It exposes a dedicated REST API surface and integrates with the core platform via internal service-to-service calls. All LyraCI operations are logged at INFO level for audit trails. Performance SLA: p99 latency < 200 ms at 100 rps.

The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with

separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at peak. The system must handle concurrent requests from multiple tenants without performance degradation. Each service component is independently scalable via Kubernetes horizontal pod autoscaling. Database migrations are managed through Alembic with zero-downtime strategies. All API endpoints are versioned under /api/v1 and protected by JWT bearer tokens. Observability is implemented with structured JSON logs (structlog), distributed tracing (OpenTelemetry), and metrics exported to Prometheus. The infrastructure is defined as code using Terraform modules targeting AWS ECS Fargate. Staging and production environments are fully isolated with separate VPCs and IAM roles. Automated security scans (Trivy, Bandit) run on every pull request. The frontend communicates exclusively through the API gateway, never directly with backend microservices. Load testing is performed with Locust targeting 500 concurrent virtual users at