

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	01	ADDED .75 NPT RTD CONN("BB"); 87.58 DIM WAS 86.83; ECN08802283	19NOV08	KMD/BAB

A) 12.00"–900# FF FLANGE CONN–INLET/TOP AND DISCHARGE/BOTTOM
20X–1.375 STUDS ON ø21.000 B.C. ø24.00 FLANGE
B) .25 NPT PACKING LUBE CONN ---------- TOP
C) .25 NPT PACKING VENT/DRAIN CONN ---------- BOTTOM
D) .75 NPT YOKE DRAIN/PURGE CONN ---------- BOTTOM
E) .25 NPT CYLINDER LUBE CONN (4X)---------- TOP
G) .75 NPT YOKE VENT CONN ---------- TOP
U) .25 NPT UNLOADER AIR CONN
V) .25 NPT UNLOADER VENT TO NON–HAZARDOUS AREA -- TOP
AD) .50 NPT OUTER END INDICATOR CONN ---------- TOP
AE) .50 NPT FRAME END INDICATOR CONN ---------- TOP
AJ) .750–10UNC–3B THD CYL. SUPPORT ---------- BOTTOM SIDE
AP) .625–11UNC–3B THD YOKE SUPPORT ---------- BOTTOM
BB) .75 NPT RTD CONN. (IF REQUIRED) (MAX. INSERTION DEPTH–16.50")







64.25(HOS) FOR 5" STROKE
63.25(HOS) FOR 6" STROKE
64.09(HOSS) FOR 6" STROKE
62.25(HOS) FOR 7" STROKE
63.09(HOSS) FOR 7" STROKE
REQUIRED FOR REMOVAL
OF PISTON & ROD
(NOT TO SCALE)

FARSIDE ALSO

71.00 (HOSS)
67.75 (HOS)
TO COMPR. SHAFT AND FRAME
CENTERLINE
(NOT TO SCALE)





TOTAL WEIGHT: APPROX 6500 LBS.

CHG TO: 149

THIRD ANGLE PROJECTION

DRAWN DL SYMONS	DATE 17APR08	SIZE 11.00–13.50	STROKE 5.0/6.0/7.0	TYPE HOS/HOSS
CHECKED R.A. BENNITT	DATE 17APR08	NAME OF PART OUTLINE – HP/PIPELINE CYLINDER		
APPROVED R.A. BENNITT	DATE 18APR08	SIZE C	FEDERAL SUPPLY CODE -----	DWG NO. HHH01174 REV. 01
UG PART		SCALE 3:32	WT. ABOVE	SHEET 1 OF 1

DWG NO HHH01174 SH 1

NON FLANGE-08/02