

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

Dimensions:

- Overall width: 66.06
- Overall height: 24.50
- Flange diameter: 12.50 BC
- Stroke length: 19.00
- Clearance required for valve removal: 22.00

Callouts: A, B, C, D, E, F, G, H, J, K, L, N, S, T, W, X, AE, AD, AJ, AP, BB.

Legend:

- A) 6.00"-900# FF FLANGE CONN-INLET TOP & DISCH BOTTOM
- B) .25 NPT -- PACKING LUBE CONN ----- TOP
- C) .25 NPT -- PACKING VENT/DRAIN CONN ----- BOTTOM
- D) .75 NPT -- YOKE DRAIN CONN ----- BOTTOM
- E) .25 NPT -- CYL BORE LUBE CONN ----- TOP
- F) .25 NPT -- CYL BORE LUBE CONN ----- BOTTOM
- G) .75 NPT -- YOKE VENT/PURGE CONN (IF REQUIRED)----- TOP
- H) .38 NPT -- PACKING COOLANT OUT CONN (IF REQUIRED)- TOP
- J) .38 NPT -- PACKING COOLANT IN CONN (IF REQUIRED)-- BOTTOM
- K) .75 NPT -- CYL COOLANT INLET CONN (IF REQUIRED)-- BOTTOM
- L) .75 NPT -- CYL COOLANT DISCH CONN (IF REQUIRED)-- TOP
- N) .75 NPT -- SPARE CONN ----- BOTTOM
- S) .125 NPT -- VVCP ROD PKG VENT TO NON-HAZ AREA ---- TOP
- T) .125 NPT -- GREASE FITTING ----- TOP
- W) .25 NPT -- SCRAPER PURGE CONN (IF REQUIRED)----- TOP
- X) .25 NPT -- PACKING PURGE CONN (IF REQUIRED)----- TOP
- AE) .50 NPT -- OUTER END INDICATOR CONN ----- BOTH SIDES
- AD) .50 NPT -- FRAME END INDICATOR CONN ----- BOTH SIDES
- AJ) .750-10UNC-3B THD, CYLINDER SUPPORT ----- BOTTOM END
- AP) .625-11UNC-3B THD, YOKE SUPPORT ----- BOTTOM
- BB) .75 NPT -- RTD CONN. (IF REQUIRED)

Notes:

- REQUIRED FOR REMOVAL OF PISTON & ROD
- CLEARANCE REQUIRED FOR VALVE REMOVAL-TYPICAL
- TOTAL WEIGHT: APPROX. 3300 LBS.

CHG TO: 72 124 149			
THIRD ANGLE PROJECTION		SIZE	STROKE
DRAWN K.DAVISON		9.00/9.50 NI	ALL
CHECKED B.NIESSING		TYPE HOS	
NAME OF PART OUTLINE-CYLINDER W/VVCP & 13" DPC			
APPROVED B.NIESSING		SIZE	FEDERAL SUPPLY CODE
DATE 22OCT08		C	H1H00964
UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES		DRAWING NO.	REV.
SCALE 1:12		WT.	SH 1

FORM PL-1002-08/102