

Packager Guidelines

Section 10: Metric Conversions

METRIC CONVERSION EQUIVALENTS

— U.S. TO METRIC —

The metric conversion equivalents listed below represent the more commonly used measuring units in the engine and compressor industry.

Multiply	By	To Obtain
inches (in)	25.4	millimetres (mm)
pounds (lbs)	0.454	kilograms (kg)
gallons (gals)	3.785	litres (L)
horsepower (HP)	0.746	kilowatts (kW)
British Thermal Units (Btu)	1055	joules (j)
degrees Fahrenheit (°F)	0.556 (°F - 32)	degrees Celsius (°C)
pounds per square inch (psi)	0.0703	kilograms per square centimetre (kg/cm ²)
	6.895	kilopascal (kPa)
	0.069	bar
cubic feet per minute (CFM)	0.0283	cubic metres per minute (m ³ /min)
gallons per minute (GPM)	3.785	litres per minute (L/min)
torque in foot-pounds (ft-lbs)	1.356	newton metres (N•m)
	0.138	kilogram metres (kg-m)
Saybolt Seconds Universal (SSU): 50-100 SSU 100-350 SSU over 350 SSU @ 100°F (40°C) over 350 SSU @ 210°F (100°C)	(0.226 x SSU) - (205.3 ÷ SSU) (0.22 x SSU) - (147.7 ÷ SSU) SSU x 0.21576 SSU x 0.21426	kinematic viscosity, centistokes (cSt)