

Product information requirements according to COMMISSION REGULATION (EU) No 548/2014

Type designation:	4GY6364-1EC (Sr. B382978)
Design:	GEAFOL Neo® Three-phase cast-resin rectifier transformer
Transformer acc. to	IEC 60076-11:2018 / VDE 0532
Environmental class	E2
Climatic class	C2
Fire behavior class	F1
Installation	indoor
Altitude installation	1000 m
Ambient temperature	40 °C
Temp. rise windings HV / LV	100 K / 100 K
Thermal class HV / LV	F / F
Frequency	50 Hz
Type of duty	continuous
Type of cooling	AN
Protection	IP00
Rated power	2000 kVA
Vector group	Dyn11
High voltage (U1)	20000 V
tappings	±2,5; ±5%
insulation level (kV)	LI 95 AC 50
Low voltage (U2)	480 V
Insulation level (kV)	LI - AC 10
No load losses (guaranteed)	2340 W +0 %
No load losses (measured)	1974 W
Load losses (Pk75)	14000 W +0 %
Load losses (Pk120, guaranteed)	16000 W +0 %
Load losses (Pk120, measured)	15174 W
Impedance voltage	6 % ±10 %
Winding material LV	Aluminium
Winding material mass LV	314 kg
Winding material HV	Aluminium
Winding material mass HV	508 kg
Core material	grain-oriented electrical steel
Core material mass	3215 kg
Dimensions, approximately	
Length x width x height	1920 mm x 1280 mm x 2100 mm
Distance between rollers	1070 mm
Total mass	4740 kg
Painting scheme	
Color, thickness	RAL 7016, 80 µm
Accessories:	
Thermal protection	
Thermal protection relay	PT 100 built-in sensors in coils and on the core in the middle phase one T154 thermal protection relay, 24-240 V, AC / DC for 4 sensors with 4 contacts
Other accessories	Electrostatic shield between LV and HV windings.
Documentation	Spanish

Remark(s):

The guaranteed values are valid in case of sinusoidal induction.