

Ex 2: Modelagem e Análise de desempenho

$$D_i = 200, 190, 230, 220, 210 \text{ ms/req}$$

$$1) \text{ Sat}_{\min} = \frac{1}{190} = 3,26$$

$$\frac{190 + 200 + 210 + 220 + 230}{5} = 210$$

$$\text{Sat}_{\max} = \frac{1}{230} = 4,35$$

$$\text{Sat}_{\text{med}} = \frac{1}{210} = 4,76$$

$$2) \lambda^{\min} = \frac{800 - 190}{800 \cdot 190} = \frac{610}{152.000} = 0,004 \text{ ms/req}$$

$$\lambda_{\text{med}} = \frac{800 - 210}{800 \cdot 210} = \frac{590}{168.000} = 0,0035 \text{ ms/req}$$

$$\lambda_{\max} = \frac{800 - 230}{800 \cdot 230} = \frac{570}{184.000} = 0,0030 \text{ ms/req}$$

$$3) \lambda_d = \frac{0,05}{1,05 \times 10^6} \quad \lambda_{\text{atm}} = \frac{0,65}{1,65 \times 190} = 0,00025 \text{ ms/req}$$

$$\lambda_{\text{at med}} = \frac{0,05}{1,05 \times 210} = 0,00022 \text{ ms/req}$$

$$\lambda_{\text{at max}} = \frac{0,05}{1,05 \times 230} = 0,00020 \text{ ms/req}$$

2) A carga máxima de saturação que deve ser é 4,35 ms/req