

Imperial College London
Department of Computing

Automatic Cell Tracking in Noisy Images for Microscopic Image Analysis

Pedro Damian Kostelec

September 2014

Supervised by Ben Glocker

Submitted in part fulfilment of the requirements for the degree of
Master of Science in Computing (Artificial Intelligence) of Imperial
College London

Abstract

Acknowledgement

I offer my sincerest gratitude to life,

The copyright of this thesis rests with the author and is made available under a Creative Commons Attribution Non-Commercial No Derivatives licence. Researchers are free to copy, distribute or transmit the thesis on the condition that they attribute it, that they do not use it for commercial purposes and that they do not alter, transform or build upon it. For any reuse or redistribution, researchers must make clear to others the licence terms of this work.



Contents

1	Introduction	NEW	7
1.1	Motivation	NEW	7
1.2	Objectives	NEW	7
1.3	Contributions	NEW	7
1.4	Thesis structure	NEW	8
2	Related work	NEW	12
2.1	Cell detection	NEW	12
2.2	Cell tracking	NEW	12
2.2.1	Tracking by detection	NEW	12
2.2.2	Tracking by model evolution	NEW	12
2.2.3	Tracking by global data association	NEW	12
3	Detection of cells	NEW	13
3.1	Overview	NEW	13
3.2	Learning to detect non-overlapping cells	NEW	13
3.2.1	Extremal regions	NEW	13
3.2.2	The non-overlap constraint	NEW	13
3.2.3	Formulation of the model	NEW	13
3.2.4	Learning the model	NEW	13
3.2.5	Implementation details	NEW	14
3.2.6	Summary	NEW	14
3.3	Speeding up the algorithm	NEW	14
3.4	Feature selection	NEW	15

4	Tracking of cells	DRAFT I	17
4.1	Cell tracking overview	DRAFT I	17
4.2	Joining cell detections into robust tracklets	DRAFT I	19
4.3	Global data association	DRAFT I	21
4.4	Implementation using linear programming	DRAFT I	23
4.5	Hypotheses likelihood definitions	DRAFT I	24
4.6	Computing the likelihoods	DRAFT I	26
4.7	Features for the linking classifier	OUTLINE	29
4.7.1	Estimating the velocity with Kalman filters	NEW	31
4.7.2	Gaussian broadening feature	DRAFT I	31
4.7.3	Best feature selection	NEW	32
5	Quantitative measurements of cell behaviour	NEW	19
6	Data acquisition and annotation	NEW	20
6.0.6	Cell culture conditions and imaging modality	NEW	20
6.0.7	Annotating cell images	NEW	20
7	Experimental results	NEW	22
7.1	Cell detector	NEW	22
7.1.1	Performance	NEW	22
7.1.2	Detection accuracy	NEW	22
7.2	Cell tracker	NEW	22
7.2.1	Performance metrics	NEW	24
7.2.2	Performance	NEW	24
7.2.3	Tracking accuracy		24
8	Discussion and conclusion	NEW	25
8.1	Future work	NEW	25
	Bibliography		26

1 Introduction NEW

1.1 Motivation NEW

To develop methods for cell tracking

explain what is a the neukocyte

what is its function

why is it still important to track them (what we don't know)

section todo describes the imaging modality

1.2 Objectives NEW

Describe the different modules of the system - detector, tracker, stat computation

- create a robust pipeline for tracking neukocytes in image sequences of noisy images obtained throught that ventilator method

- the system should be able to accept an image sequence, detect the cell in each frame, and uset hem to compute the trajectories of the cells.

- A basic system to return metrics about the trajectories

1.3 Contributions NEW

Machine learning based cell tracker system

that is able to work on highly noisy datasets, where several frames can come out of focus, cells dissapear and reappear, etc.

Dot Annotation GUI

to ease the annotation of datasets of point objects, as well as link them to create trajectories in a frame by frame basis

**1.4 Thesis structure** NEW

The remained of the thesis is structured as follows.

chapter 2 is a brief literature survey outlining the exesting methods for cell detection and tracking

chapter 3 describes the cell detection module and its implementation

chapter 4 describes the tracking module

chaapter 5 represents the biological statistics module, and we focus on listing the different types of metrics that it computes

chapter 6 represents the image annotation tool that was created to facilitate image annoations

chapter 7 evaluates the cell detector and cell tracker

chapter 8 is reserved for some concluding remarks and ideas that could be used to enhance this work.

3 Detection of cells NEW

3.1 Overview NEW

3.2 Learning to detect non-overlapping cells NEW

Check both Arteta's papers on the subject

Subsection with the changes that were made to Arteta's work

3.2.1 Extremal regions NEW

3.2.2 The non-overlap constraint NEW

3.2.3 Formulation of the model NEW

3.2.4 Learning the model NEW

Info about the binary/structural classifier

Rewrite: Several of these subsections are directly taken from Arteta's paper. They are meant as guidance, but should be adapted appropriately.

3.2.5 Implementation details NEW

Dynamic programming for inference NEW

3.2.6 Summary NEW

3.3 Speeding up the algorithm NEW

[review this section](#)

The main drawback of the algorithm presented by Arteta [1] is the poor performance. The original algorithm took about 30 seconds to detect cells in a 400x400 image. Because we will be processing hours of microscopy video it was important to reduce the detection time as much as possible. The major performance improvements were achieved by addressing three things.

The algorithm needs to extract a set of features on every single detected MSER. First, we have first fine-tuned the MSER detector to detect less cells, more robustly.

Second, we have identified features that are slow to compute and improved their algorithmic behaviour. One such feature is the Contour Points Distribution Histogram implemented in *cpdh.m*. The function was performing excessive calls to slow functions to extract region characteristics, and was rewritten to call these functions less often, while negligibly affecting its optimality.

Second, several MATLAB builtin functions were modified to remove excessive parameter checking, which in several cases represented an overhead of over 30%. These parameter checks are welcome when developing the algorithm, but once the algorithm is complete, several of these checks can be safely removed.

These optimizations resulted in a significant performance boost. Instead of 30 seconds, the algorithm can now detect cells on the same images in about .

Measure the number of seconds it takes to process one of these 400x400 images

3.4 Feature selection NEW

The effectiveness of the machine learning method to detect cells depends on the quality of features. Good features have a lot of discriminative power between cells and non cells. The used approach classifies extremal regions as cell/non-cell. The regions are extracted using the MSER detector. Then each region is processed and features are extracted from it. We have evaluated several combinations of these features:

1. the area A of the region represented by a 10-dimensional binary vector with the entry $\lceil \log A \rceil$ set to 1.
2. 10-dimensional histogram of intensities within the region
3. the position of the descriptor in the image in terms of x-y coordinates of a centroid fitted to the descriptor.
4. two 6-dimensional histograms of differences in intensities between the region border and a dilation of it for two different dilation radii
5. a shape descriptor represented by a 60-dimensional histogram of the distribution of the boundary of the region on a size-normalized polar coordinate system
6. The orientation of the descriptor after attempting to normalize its orientation
7. The proportion of edge-pixels in the region.

Each of these features has different discriminative power, and takes some time to compute. The application of the cell detector requires that images are processed within a time limit. For this reason, we have trained and tested the algorithm with all the $2^7 - 1$ possible combinations of these features.

We have also developed a function that helps select the most appropriate set of features given specific constraints, for example a maximum

computation time, minimal precisiona and recall values, etc. A graph generated by the function is shown in figure 3.1.




Figure 3.1: The plots helps the user to select the most appropriate feature, given a combination of computation time per image, mean precision and recall. This example, which was obtained by selecting only within feature sets that compute in less than 1 CPU-second, have at least 0.5 precision and 0.9 recall have resulteds in a feature set containing features 1, 3 and 4. Most importance was given to precision followed by computation time and recall. The selected feature set computes in 0.414 cpu-seconds (Intel(R) Core(TM) i7-2600 CPU @ 3.40GHz) per image, with mean precision of 0.836 and mean recall of 0.9363.

Bibliography

- [1] C. Arteta, V. Lempitsky, J. A. Noble, and A. Zisserman, “Learning to detect cells using non-extremal regions,” in *Proceedings of the 15th International Conference on Medical Image Computing and Computer-Assisted Intervention - Volume Part I, MICCAI’12*, (Berlin, Heidelberg), pp. 348–356, Springer-Verlag, 2012. 14, 20
- [2] R. Bise, T. Kanade, Z. Yin, and S. il Huh, “Automatic cell tracking applied to analysis of cell migration in wound healing assay,” in *Engineering in Medicine and Biology Society, EMBC, 2011 Annual International Conference of the IEEE*, pp. 6174–6179, Aug 2011. 18
- [3] R. Bise, Z. Yin, and T. Kanade, “Reliable cell tracking by global data association,” in *ISBI*, pp. 1004–1010, IEEE, 2011. 21, 25
- [4] L. Zhang, Y. Li, and R. Nevatia, “Global data association for multi-object tracking using network flows,” in *Computer Vision and Pattern Recognition, 2008. CVPR 2008. IEEE Conference on*, pp. 1–8, June 2008. 21
- [5] C. Huang, B. Wu, and R. Nevatia, “Robust object tracking by hierarchical association of detection responses,” in *Computer Vision - ECCV 2008* (D. Forsyth, P. Torr, and A. Zisserman, eds.), vol. 5303 of *Lecture Notes in Computer Science*, pp. 788–801, Springer Berlin Heidelberg, 2008. 21
- [6] J. Schindelin, I. Arganda-Carreras, E. Frise, V. Kaynig, M. Longair, T. Pietzsch, S. Preibisch, C. Rueden, S. Saalfeld, B. Schmid, J.-Y. Tinevez, D. J. White, V. Hartenstein, K. Eliceiri, P. Tomancak,

and A. Cardona, “Fiji: an open-source platform for biological-image analysis,” *Nature Methods*, vol. 9(7), pp. 676–682, 2012. 20

- [7] S. F. I. o. T. L. Philippe Thévenaz, Biomedical Imaging Group, “Point picker: An interactive imagej plugin that allows storage and retrieval of a collection of landmarks,” May 2014. 20