



Computer Security Foundations
11/11/2022

Duration: 1H

LEIC
Midterm

This is a multiple-choice test that will be corrected automatically. Please follow these rules:

- Mark your answer using only **blue** and **black** pen. No pencil or light-coloured pens.
- Check only inside each box and be generous on ink. Erased boxes will not be detected automatically.
- Only the boxes matter for the automatic correction. You may underline text or take notes on the sides.

The test is marked for 20 points. There are 30 questions in total, each with 4 options. Each question is worth 20/30 points. Students can check one or two choices per question. The scoring for each question is as follows:

- One checked correct answer (100%).
- One checked incorrect answer (-20%).
- No checked answers (0%).
- Two checked answers, one correct (50%).
- Two checked answers, none correct (-20%).
- More than two checked answers (-20%).

<input type="checkbox"/> 0	<input checked="" type="checkbox"/> 0	<input type="checkbox"/> 0	<input checked="" type="checkbox"/> 0	<input checked="" type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0
<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input checked="" type="checkbox"/> 1
<input checked="" type="checkbox"/> 2	<input type="checkbox"/> 2	<input checked="" type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2
<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input checked="" type="checkbox"/> 3	<input type="checkbox"/> 3
<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4
<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input checked="" type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5
<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6
<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input checked="" type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7
<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8
<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9

← code your 9-digit upYYYYXXXXX student number horizontally on the left, and replicate it below. Write also your first and last name below.

Student Number:

up

2	0	2	0	0	7	5	3	4
---	---	---	---	---	---	---	---	---

First and Last Name:

Pedro...Macedo.....

Group 1 Introduction (4 questions)

Question 1.1 ♣ Which of the following concepts is not associated with the risk management approach to security?

- ☒ Security proof. ←
- ☐ Cost/benefit analysis. ✕
- ☒ Threat analysis.
- ☐ Mitigation. ✕

Question 1.2 ♣ Which of the following is not a common reason for an attacker to compromise a server that answers to requests from a large number of clients/users?

- ☒ To make the machine part of a botnet.
- ☐ Geo-political and strategic motivation. ✕
- ☒ As part of a supply-chain attack.
- ☐ To cause a data breach. ✕

0.5/1

0.5/1



Question 1.3 ♣ Pick the incorrect statement or indicate that all are correct.

- ☐ A security goal is stated in terms of avoiding loss of value to an asset.
- ☐ A security policy describes how security mechanisms are used to realize a security model.
- ☒ All are correct.
- ☐ A trust model describes which assumptions we can rely on to build security. ✓

Question 1.4 ♣ Which of the following options is not usually categorised as an exploit?

- ☐ Message that triggers an array access out of bounds.
- ☐ Text filled into edit box that contains JavaScript.
- ☐ JavaScript performing heap spraying.
- ☒ Overflow in an integer computation. ✓

Group 2 Software Security (10 questions)

Question 2.1 ♣ One can bypass Address Space Layout Randomization (ASLR) protections by:

- ☒ All of the other choices. ✗
- ☐ Jumping to system code using Return Oriented Programming.
- ☒ Extracting addresses using other vulnerabilities. ✓
- ☐ Trial and error. ✗

→ The addresses are always changing, so Trial and Error does not work.

→ It's harder to make ROP, when it's used ASLR. The ROP needs the exact address.

Question 2.2 ♣ Certain format strings can make a program crash (with very high probability). Which of the following `printf` commands is very likely to crash the program?

- ☒ `int n=0; printf("%f%d",n);`
- ☐ `int n=1; printf("%n%f",&n);` ✗
- ☒ `int n=1; printf("%s%d",n);` ✗
- ☒ `int n=0; printf("%s%x",&n);` ✓

Question 2.3 ♣ Recall the buffer overflow lab. You explored a buffer overflow vulnerability by creating a malicious input that overwrites the return address of the vulnerable function with an address within your buffer where you stored shellcode to be executed. Which security technique had to be disabled during compilation to allow you to overwrite the return address of the vulnerable function?

- ☐ Data Execution Prevention
- ☐ None of the other choices
- ☒ Stack Canary ✓
- ☐ Address Space Layout Randomisation ✗

→ Always verifies if the value of the canary was overwritten (if it didn't change)

Question 2.4 ♣ A canary built from string terminating bytes offers better security than a random canary because:

- ☐ It is harder to guess than a random canary.
- ☐ They can be generated much more efficiently.
- ☒ It makes it more difficult to overwrite the stack.
- ☐ Random bytes can be all 0.

→ In my opinion, if a canary has a str terminating bytes, if we put `printf("%s")`, the read will stop in the canary, and not overwriting the return address



$f() \{ \dots \}$

$g() \{ \dots \}$
 $f()$

+100/3/46+

Question 2.5 ♣ Recall what you have studied about the classical configuration of the stack region managed by a function f that is called by a function g . Indicate which of the following options is correct for the positioning of the following data pieces: ① local variables of f , ② frame pointer of g , ③ parameters passed by g , ④ return address back to g .

- ☒ ③ ⇒ A, ④ ⇒ B, ② ⇒ C, ① ⇒ D
☐ ④ ⇒ A, ③ ⇒ B, ① ⇒ C, ② ⇒ D ✗
☒ ① ⇒ A, ③ ⇒ B, ② ⇒ C, ④ ⇒ D
☐ ③ ⇒ A, ② ⇒ B, ① ⇒ C, ④ ⇒ D ✗

High address

A
B <i>parameters</i>
C
D. <i>local var. of f</i>

Low address

Question 2.6 ♣ *Information-flow analysis* encompasses a class of program analysis techniques beyond safety. The C-like program on the right illustrates an example of:

- ☐ Dynamic taint analysis.
☐ Control-flow integrity. ←
☒ Static taint analysis.
☐ Constant-time analysis.

```
int printf(untainted char *fmt, ...);
tainted char *fgets(...);

tainted char *name = fgets(..., network_fd);
printf(name); // FAIL: tainted not untainted
```

Question 2.7 ♣ Consider the code below, which introduced a critical vulnerability in openSSH. An attacker that controls the value of `nresp` can cause a memory management problem because:

- ☒ It can lead to allocating too much memory. *X*
☐ None of the other choices.
→ ☒ It can lead to not allocation enough memory.

```
nresp = packet_get_int();
if (nresp > 0) {
    response = xmalloc(nresp * sizeof(char *));
    for (i = 0; i < nresp; i++)
        response[i] = packet_get_string(NULL); }
```


Question 2.8 ♣ Suppose you intend to use Return Oriented Programming to execute the instructions of functions f_1, f_2, f_3, f_4, f_5 (in some order) and you have placed their addresses in the stack as illustrated below. Which of the following functions could take parameters and the ROP strategy would still work without any changes to the part of the stack shown in the figure?

- ☐ All functions could take parameters.
☐ Function f_2 .
☐ It is not possible to pass any parameters.
☒ Function f_3 .

High address	$\&f_3$
	$\&f_1$
	$\&f_5$
	$\&f_4$
Low address	$\&f_2$

Question 2.9 ♣ Recall the buffer overflow lab that you have performed, where a buffer in a local variable receives an untested input. For the exploitation strategy where the injected code (*shellcode*) is placed at the end of the input bytes, you should:

- ☒ In the place of the vulnerable function's return address, write another address pointing to a lower place in the stack.
→ ☒ In the place of the vulnerable function's return address, write another address pointing to a higher place in the stack.
☐ In the place of the vulnerable function's return address, write the address of the buffer. ✗
☐ None of the other options.



Group 3 Systems Security (10 questions)

Question 3.1 ♣ Virtual machines are commonly used as a security mechanism. Which of the following sentences is not true?

- ☒ An advantage of virtual machines is that software may be transparently executed as in a non-virtualised operating system.
- ☐ An advantage of virtual machines is that acquiring root in the virtual machine does not grant root in a host operating system. ✓
- ☐ A disadvantage of virtual machines is that malware may exploit the virtualisation layer to remain undetected.
- ☐ A disadvantage of virtual machines is that malware may detect that it is being virtualised. ✗

Question 3.2 ♣ Which of the above is not a systems security principle that we have studied in the classes?

- ☒ Closed design
- ☐ Separation of privilege ✗
- ☐ Economy of mechanism ✗
- ☒ Compromise recording

Question 3.3 ♣ The Android operating system is a particular distribution built on top of Linux. Which is not an additional domain-specific restriction that Android implements?

- ☒ There is no root user, to prevent applications from escalating privileges.
- ☐ It isolates different applications by registering each application with a different UNIX user. ✗
- ☐ It implements a form of Mandatory Access Control, so that no application can change its permissions. ✗
- ☒ It enforces Manifest Permissions per application, to restrict its system capabilities.

Question 3.4 ♣ Many modern operating systems require system support for a hardware component called a Trusted Platform Module (TPM). Which is the main rationale for that requirement?

- ☐ To store user's cookies when browsing the web. ✗
- ☐ To guarantee that the user only installs official software.
- ☐ To protect the user login process.
- ☒ To prevent malicious bootloaders from compromising the operating system's boot process.

Question 3.5 ♣ Which fundamental mechanism does a UNIX operating system have in place to enforce isolation?

- ☒ System call interposition, by virtualising the address space of different user processes, monitoring all virtual address translations.
- ☒ Software fault isolation, by virtualising the address space of different user processes, monitoring all virtual address translations.
- ☐ Software fault isolation, by ensuring that the control-flow of user processes never accesses invalid virtual memory regions.
- ☐ System call interposition, by preventing different user processes to communicate via system calls.



Question 3.6 ♣ The UNIX filesystem can be seen as an instance of:

- ☒ Capability lists, since each file enumerates the permissions for all the users who may read, write or execute it.
- ☒ Role-based access control, since each file has an access control list for three fixed roles (owner, group, others) and the association between users and groups may be modified independently.
- ☐ Attribute-based access control, since users may change their group membership without the need to change file permissions. ✗
- ☐ Access control lists, since only the owner of each file (or root) may read, write or execute it. ✗

Question 3.7 ♣ For efficiency reasons, the address space of the Linux kernel is not completely independent from that of user processes due to *kernel mapping*. Which of the following is correct?

- ☐ Part of each user process's memory is mapped into the kernel memory space, to reduce the size of the address translation tables.
- ☐ Part of the kernel memory space is mapped into the memory space of each user process, to reduce the number of cache misses.
- ☐ Since the discovery of speculative execution attacks such as Meltdown and Spectre, Linux no longer uses *kernel mapping*, as it violates the principle of *separation of privilege*.
- ☒ Part of the kernel memory space is mapped into the memory space of each user process, to speed up system calls. ✗

Question 3.8 ♣ In the environment variable and setuid program lab we have experimented with environment variables and `setuid` programs. Which of the following sentences is **not** true?

- ☐ If the shell detects that it is being run under a `setuid` process, it may drop its privilege.
- ☒ When a process forks a child process, it passes on its environment, excluding some critical variables if the fork is a system call.
- ☐ When the shell forks a child process, it passes on its environment, excluding some critical variables if it has a different effective user id.
- ☐ The `system` function allows calling a shell function within a program with the program's environment.

Question 3.9 ♣ Remember the environment variable and `setuid` program lab. The Linux file system associates a `owner`, a `group`, and 12 permission bits with each entry. For a file with the 12th bit (the Set-UID bit) active, it can be executed:

- ☐ Only by a user belonging to the group.
- ☒ Only by users whose set (owner, group, others) in the permission bits, has the executable bit active.
- ☐ Only by the owner.
- ☐ Only by the owner or by a user belonging to the group.

$\begin{matrix} r & w & x & r & w & x & r & w & x \\ \hline \text{owner} & \text{group} & \text{others} \end{matrix}$



Question 3.10 ♣ Under Linux, Docker crucially relies on `seccomp-bpf` to confine containers. Select the incorrect choice or mark that all choices are correct.

- ☒ If an attacker has access to certain system calls inside a container, it can exploit Docker to acquire root in the host OS.
- ☒ Users can manually configure `seccomp-bpf` filters to block various system calls inside the container.
- ☒ All choices are correct.
- ☐ Using the default Docker `seccomp-bpf` filters, an attacker that acquires root in the container does not directly acquire root in the host OS. ✓

Group 4 Web Security (6 questions)

Question 4.1 ♣ Cookies may be used for various purposes. Name the incorrect one below.

- ☒ Managing user sessions.
- ☐ Personalising user experience. ✓
- ☒ Encrypting user communication. ✓
- ☒ Tracking user activity.

Question 4.2 ♣ Which sentence best characterises a Cross-Site Request Forgery (CSRF) attack? "When a malicious origin can send requests to a server in another origin ...";

- ☒ ... and trigger a side-effect on the server.
- ☐ ... and measure side-channels such as response time. ✗
- ☐ ... where the user is already logged in.
- ☐ ... and read its response.

Question 4.3 ♣ A classical protection against Cross-Site Scripting (XSS) attacks is for the site to adopt a Content Security Policy (CSP). Which of the following statements is true?

- ☐ Stored XSS attacks cannot be prevented with a CSP because the malicious payloads are already stored in the server.
- ☐ Preventing reflected XSS attacks requires both CSP and SRI (Subresource Integrity).
- ☒ XSS attacks using inline scripts are blocked by a default CSP.
- ☐ DOM-based XSS attacks cannot be prevented with a CSP because they occur on the server-side when processing a user request.

Question 4.4 ♣ Which assignment can be seen as a valid analogy in the table below?

- ☐ ①=Pages, ②=HTML, ③=JavaScript, ④=Popups
- ☒ ①=DOM, ②=Cookies, ③=iFrames, ④=Fetch
- ☒ ①=Pages, ②=Cookies, ③=HTTP, ④=Frames
- ☐ ①=Frames, ②=DOM, ③=Images, ④=Sub-frames

Systems Security	Web Security
Processes	①
Files	②
Sockets	③
Sub-processes	④



Question 4.5 ♣ Consider the following SQL query, written in some server-side library, that is vulnerable to SQL injection. Which of the following statements is true?

```
uName = getQueryString("username");
uPass = getQueryString("userpassword");
sql = 'SELECT_*_FROM_Users_WHERE_Name_=' + uName + ' _AND_Pass_=' + uPass + ' '
```

- ☐ A SQL injection attack would not be possible if the clauses for the `Name` and `Pass` fields did not enclose strings with double quotes (`"`).
- ☒ A SQL injection attack may be able to delete the `USERS` table.
- ☐ A SQL injection attack will only be able to read existing data from the `USERS` table.
- ☐ A SQL injection attack that bypasses authentication is only possible because the clause for the `Name` field appears before the clause for the `Pass` field. ✗

Question 4.6 ♣ According the Same-Origin Policy (SOP), which of the following is allowed?

- ☒ HTML code in a page from origin A can send a POST request to a page from origin B.
- ☐ HTML code in a page from origin A can send and read the response of a GET request to a page from origin B.
- ☐ JavaScript code in a frame from origin A can exchange data with a frame from origin B.
- ☐ JavaScript code in a page from origin A can inspect the HTML code of a frame from origin B.