

Lab Assignment 1 - Sampling and Quantisation of media signals

Task 1 - (Optional) Introductory part that may be developed outside the classroom

After applying the different sampling rates to the same audio file (in this case, we used the *audioCluck.wav* file), we got 3 files (the original file - *audioCluck.wav*, another file with 11025 Hz of sampling rate - *audioCluck2.wav*, and another file with 44100 Hz of sampling rate - *audioCluck3.wav*).

After carefully analysing the 3 audio files, we got to these conclusions:

1. The audio files *audioCluck.wav* and *audioCluck3.wav* were both sampled at 44100 Hz of sampling rate, while *audioCluck2.wav* was sampled at 11025 Hz of sampling rate. The lower sampling rate of *audioCluck2.wav* is noticeable in the audio quality compared to the other two files, since it exhibits less clarity.

Task 2 - Variation of sampling frequency with or without filters

1. After executing the command
`amostragemInterp_semFiltro("./resources/audios/Mozart20sec.wav","./outputFiles/Mozart20sec/without_filter/outputMozart20sec_factor_4.wav",4)`, we got the following output:

```
>>
amostragemInterp_semFiltro("./resources/audios/Mozart20sec.wav","./outputFiles/Mozart20sec/without_filter/outputMozart20sec_factor_4.wav",4)

Importing the original audio

info =

struct with fields:

    Filename: '/Users/pedromacedo/Desktop/Desktop - MacBook Air de
Pedro/Study/Year 4/Semester2/SAM-
Year4Semester2/Project/source/resources/audios/Mozart20sec.wav'
CompressionMethod: 'Uncompressed'
  NumChannels: 1
   SampleRate: 44100
TotalSamples: 882000
    Duration: 20
        Title: []
    Comment: []
    Artist: []
  BitsPerSample: 16
```

```
the number of samples in the original audio:  
N = 882000
```

Press a key to continue

The subsampled audio

```
the number of samples in the subsampled audio:  
ans = 220500
```

Carregue numa tecla para continuar

The interpolated sound


```
the number of samples in the interpolated audio:  
ans = 882000
```



Carregue numa tecla para continuar

Erro entre o sinal original e o interpolado = $5.66584e-06$

PSNR do sinal interpolado = 33.7013


This were the graphics of the 3 types of waves (original, subsampled and interpolated).







2. Comparison of the original sound and the processed sounds in terms of perceptual quality, waveform and spectrum

- **Factor of 4 ($k = 4$):** Comparing the original sound *Mozart20sec.wav* with the interpolated sound *outputMozart20sec_factor_4.wav* (the file inside the directory `/outputFiles/Mozart20sex/without_filter` directory), we can notice some differences.





1. **Perceptual quality:** The perceptual quality can be measured with two properties: **loudness** (used to quantify the sound intensity) and **pitch** (used to quantify the sound tonality). Hearing both of the audios, we can notice that the second audio (the audio result of the interpolation process) has more noise than the original audio, and it also seems louder than the original audio even when the audio volumes were at the same level during the testing phase. By analysing the formula to calculate the magnitude of a wave using its amplitude, $x(t) = A * \cos(w * t)$, for the same $\cos(w * t)$ value, we can conclude that if the magnitude increases, $x(t)$, the amplitude of the wave, A will also increase. Because in the interpolated audio, the amplitude interval decreased from $[0, \approx 525]$ to $[0, \approx 180]$, we can say that the interpolated wave has a high rate of variation in time (frequency), because for small variation in amplitude, there is a high rate of variation in time (frequency). So, we can conclude that the interpolated audio increased in terms of **pitch** (higher frequency means higher **pitch**). For the **loudness** parameter, it depends a lot on the person is listening, but the interpolated sound appears to sound louder than the original sound, and it also presents lower amplitude than the original sound. To conclude, comparing the original and the interpolate sounds, we could realize that the audio became more harsh.
2. **Waveform:** Looking to the sound waves (the original, the subsampled and the interpolated), we can see that the original waveform show the most detail, while the subsampled show less detail due to the reduced data points. Since the interpolated form as more data points, it shows a smoother version of the original waveform, potentially, missing some of the finer details. Additionally, we can notice that the y-axis range in the interpolated waveform is bigger than the one in the original waveform. This can be due

to the interpolation process which could have affected the dynamic range of the audio signal. Because the range is higher, the "quiet" parts might be quieter, and the "loud" parts might be louder than the original sound. By listening to the audio, we could confirm that the lower parts are lower and the higher parts are louder in the interpolated sound.

3. *Spectrum*: We can see that after subsampling the original audio, the range of magnitude decreased. This can happen because of the reduction of the number of samples (by specifying a number for the k parameter). For example, in this case, $k = 4$, when applying the subsample process, only one sample will be selected to be part of the subsample, so this could lead to data loss. Following this, we verified that by applying the interpolation process to this subsample, we are trying to approximate the subsample sound/waveform to the original sound/waveform.
- **Factor of 2 ($k = 2$)**: Now moving on to the second part of the problem. We are going to apply the interpolation but this time with a factor of 2 instead of 4.

After executing the command

```
amostragemInterp_semFiltro("./resources/audios/Mozart20sec.wav","./outputFiles/Mozart20sec/without_filter/outputMozart20sec_factor_2.wav",2),
```

we got the following output:

```
>>
amostragemInterp_semFiltro("./resources/audios/Mozart20sec.wav",
"./outputFiles/Mozart/Mozart20sec_interpolated_without_filter_factor_2.wav",2)
```

Importing the original audio

```
info =
```

struct with fields:

```

        Filename: '/Users/pedromacedo/Desktop/Desktop - MacBook
Air de Pedro/Study/Year 4/Semester2/SAM-
Year4Semester2/Project/source/resources/audios/Mozart20sec.wav'
CompressionMethod: 'Uncompressed'
    NumChannels: 1
    SampleRate: 44100
    TotalSamples: 882000
        Duration: 20
            Title: []
        Comment: []
        Artist: []
    BitsPerSample: 16
```

```
the number of samples in the original audio:
N = 882000
```

Press a key to continue

The subsampled audio

the number of samples in the subsampled audio:
ans = 441000

Carregue numa tecla para continuar

The interpolated sound


the number of samples in the interpolated audio:
ans = 882000

Carregue numa tecla para continuar


Erro entre o sinal original e o interpolado = 8.17638e-07

PSNR do sinal interpolado = 42.1083


This were the graphics of the 3 types of waves (original, subsampled and interpolated).



Original wave results



Subsampled wave results



Interpolated wave results

Comparing the three different types of results (the original, subsamples and interpolated wave results), we can see that the differences are similar to the ones mentioned in the previous experience (no filter and a factor of 4).

1. *Perceptual quality*: By hearing both of the original audio and the interpolated audio with a factor of 2, we can notice that there is not much of the differences to the original audio, that are noticeable in a human hearing.
 2. *Waveform*: Looking to the sound waves (the original, the subsampled and the interpolated), we can see that the subsampled waveform shows less detail due to the fact that it has less data points to compute the sound wave ($60 / 2 = 30$ data points). To recover data loss, we used the interpolation process. After applying it, we can see that the interpolated process has 60 data points and the lost data points that were recreated in this process are a good approximation to the ones in the original waveform.
 3. *Spectrum*: We can see that after subsampling the original audio, the range of magnitude decreased. This situation is similar to what happened in the soundwave with no filters and a factor of 4.
- **Comparison between the two factors, 2 and 4**: When comparing both of the approaches (with 2 and 4 of factor), some conclusions were pointed:
 1. *Sample data loss*: We can see, both in the interpolated waveforms and in the graphics representing the wave with filters and factors of 2 and 4, that the graphic with factor of 4 had more sample data loss than the one with factor of 2. This happens because with a bigger factor, less samples will be selected in the subsampling process, which will cause less information for the interpolation process to work on. A factor of 4 means that from 4 samples of the original waveform, only 1 will enter in the subsample, while with a factor of 2 means that from 2 samples of the original waveform, only 1 will enter in the subsample.
 2. *Magnitudes*: In the situation with a factor of 2, there were no reports of magnitudes in the frequencies between 1Hz and 1.5Hz. This can happen to similar reasons referenced

in the previous point. Due to the loss of samples due to the high factor, this could had lead to a loss of high-frequency content and introduce aliasing.

3. *Mean Square Error (MSE)*: The *MSE* is a mesaure of an estimator. It is often used to quantify the amount of error between a reference signal and the interpolated signal. The *PSNR (Peak signal-to-noise Ratio)* is used to measure the quality of the reconstruction of samples lost during the subsampled process. As we can see from the results obtained, the Mean Square Error (MSE) is 5.66584e-06 for a factor of 2, and 8.17638e-7 for a factor of 4. For the sample with factor of 4, because the MSE is relatively low, we can conclude that the difference between the original sound and the interpolated sound wiht facator of 4 is small, which generally indicates that the interpolation process was done successfully.

Factor	MSE	PSNR
k = 2	5.66584e-6	33.7013
k = 4	8.17638e-7	42.1083

3. Interpolation with filters and two different factors, 2 and 4

- For $k = 2$, the results obtained were the following ones:

```
>> amostragemInterp_comFiltro("./resources/audios/Mozart20sec.wav",  
"./outputFiles/Mozart20sec/with_filter/outputMozart20sec_factor_2.  
wav",2)
```

Importar o sinal original para a variavel y

frequencia de amostragem = 44100 ; numero de amostras = 882000
Numero original de amostras no sinal de entrada = 882000

Prima uma tecla para continuar

0 som sub-amostrado

Prima uma tecla para continuar

0 pre-filtro utilizado

Prima uma tecla para continuar

0 som interpolado

Prima uma tecla para continuar

0 filtro utilizado na interpolacao

Prima uma tecla para continuar

Erro entre o sinal original e o interpolado = $4.55849e-10$

PSNR do sinal interpolado = 74.6457

1. *Perceptual quality*: By earing both of the original audio and the inteprolated audio with filter and a factor of 2, we can really notice much differences, that are noticeable in a human earing, between the audios.
 2. *Waveform*: Looking to the sound waves (the original, the subsampled and the interpolated), we can see that the inteprolated graph is really similar to the original sound waveform. This could happen because of the implementation of filters in the interpolation process.
 3. *Spectrum*: In the inteprolate graphic, we can see that there are now suddently high peaks as the the subsampled graphic.
- And, for $k = 4$, the results obtained were the following ones:

```
>> amostragemInterp_comFiltro("./resources/audios/Mozart20sec.wav",  
"./outputFiles/Mozart20sec/with_filter/outputMozart20sec_factor_4.  
wav",4)
```

Importar o sinal original para a variavel y

frequencia de amostragem = 44100 ; numero de amostras = 882000
Numero original de amostras no sinal de entrada = 882000

Prima uma tecla para continuar

0 som sub-amostrado

Prima uma tecla para continuar

0 pre-filtro utilizado

Prima uma tecla para continuar

0 som interpolado

Prima uma tecla para continuar

0 filtro utilizado na interpolacao

Prima uma tecla para continuar

Erro entre o sinal original e o interpolado = $3.00164e-09$

PSNR do sinal interpolado = 66.4603


1. *Perceptual quality*: By hearing both of the original audio and the interpolated audio with filter and a factor of 2, we can really notice much differences, that are noticeable in a human hearing, between the audios.
 2. *Waveform*: Looking to the sound waves (the original, the subsampled and the interpolated), we can see that the interpolated graph is really similar to the original sound waveform. This could happen because of the implementation of filters in the interpolation process.
 3. *Spectrum*: In the interpolate graphic, we can see that there are now suddenly high peaks as the the subsampled graphic.
- **Comparison between the two factors, 2 and 4, with filters**: By comparing the results obtained from both the experiences with filter, we can see some differences:
 1. *Sample data loss*: This case is similar to the the observations pointed out in the previous experience, experience without filters with factor of 2 and 4. Actually, as we can see in the graphic obtained in the experience with filters and factor of 2, we see that this graphic is closer to the original wave form than the one generated by the the graphic with filters with factor of 4. This can be justified by the fact that the subsampling with a factor of 4 has less data points (less information available) than the subsampling with factor of 2.
 2. *Magnitudes*: In the situation with a factor of 2, the magnitudes in each sample were closer to the original sound samples frequencies than the ones registered in the experience with filters and factor of 4.
 3. *Mean Square Error (MSE)*: As we can see from the results obtained, the Mean Square Error (MSE) is $4.55849e-10$ for a factor of 2, and $3.00164e-9$ for a factor of 4. For the sample with factor of 4, because the MSE is relatively low, we can conclude that the difference between the original sound and the interpolated sound with factor of 4 is small, which generally indicates that the interpolation process was done successfully. Similar to what happened in the previous experience (the experience without filters and with both factors, 2 and 4), the case with filters and factor of 2 has lower error rate and a higher PSNR when compared to the case with filters and factor of 4. This means that the case with filters and factor of 2 is more accurate than the case with filters and factor of 4 to predict and approximate the sound wave to the original sound.

Factor	MSE	PSNR
k = 2	$4.55849e-10$	74.6457
k = 4	$3.00164e-9$	66.4603


- **Comparison between the two programs**: By comparing the results obtained from both the programs (the first one that the filters were not use, and the last one that the filters were applied), we can confirm that from the 4 experiences made (2 without filters and 2 with filters), the one that lead to better results for the same value of k was the experience with filters and factor of 2. This experience registered, as we can see in the last topic table, the high PSNR (74.6457) and the lowest MSE/error rate ($4.55849e-10$). This means that the experience with

filters and factor of 2 was the one. Additionally, we can see that, in each program, from the two experiences made (one with factor of 2, and another with factor of 4), the experience with factor of 2 always registered a higher PSNR than the experience with factor of 4. In conclusion, the filtered method lead to better results in the end, resulting in smoother sounds and better audio quality.

- **Frequency response of the used filters:** In order to analyse the frequency response of the filters used in these two experiences, for each of them, we will need to compare the graphics obtained (the pre-filter response - file *response_pre_filter_impulse.png* - and the graphic obtained at the end of each experience after applying the filters - file *response_filter_impulse.png*).
1. **Factor of 2:** As we can see, in the filter response graph, the response seems smoother when compared to the pre-filter graph, because it has less magnitude peaks. This means that the filter has attenuated the sound, resulting in a more uniform attenuation across the frequency spectrum. Both of these situations are very similar despite that for some frequency ranges, the last filter response has less applied filters (less magnitude peaks) than the graphic obtained in the pre-filter phase.




Pre filter response with filters and factor of 2




Filter response with filters and factor of 2

2. *Factor of 4*: As we can see in this experiment, the graphics of pre-filter (the *response_pre_filter_impulse*) and the last graph (the *response_filter_impulse*) are different. We can see, on the *response_filter_impulse* graph, that at higher frequencies there are higher magnitudes, specially around the frequency of 0.75Hz. This could indicate that the filters allow more of the high frequencies to pass through with less attenuation.



Pre filter response with filters and factor of 4



Filter response with filters and factor of 4

- In this task, we will quantatize an audio signal by changing the number of quantisation levels or bits per sample.

1. After executing the command

`quant_uniform("./resources/audios/sound.wav","./outputFiles/Mozart20sec/quant_uniform/sound_256_levels.wav",256)`, we got the following output for 256 levels:

```
>>
quant_uniform("./resources/audios/sound.wav","./outputFiles/Mozart20sec/quant_uniform/sound_256_levels.wav",256)
```

```
info =
```

```
struct with fields:
```

```
    Filename: '/Users/pedromacedo/Desktop/Desktop – MacBook Air de
Pedro/Study/Year 4/Semester2/SAM-
Year4Semester2/Project/source/resources/audios/sound.wav'
CompressionMethod: 'Uncompressed'
    NumChannels: 1
    SampleRate: 8000
    TotalSamples: 8492
        Duration: 1.0615
            Title: []
            Comment: []
            Artist: []
    BitsPerSample: 8
```

```
xmin      xmax      N      Q
-1.0000    1.0000  256.0000  0.0078
```


Prima uma tecla para continuar

Let now look at the signal in the interval [0.25 – 0.275]sec


Prima uma tecla para continuar

Erro entre o sinal original e o interpolado = 1.52588e-05

PSNR do sinal interpolado = 32.889



1/500 samples of the total number of the signal samples of the original audio and quantised



200 samples of the total number of the signal samples of the original audio and quantised

- **Comparing the results obtained with the original audio:** The obtained audio has some differences from the original audio. There are:
 1. *Perceptual quality:* This audio, quantized with 256 levels, was the closer to the original audio sound. The quantization process resulted in a reduction of audible noise and distortion.
 2. *Objective quality:* The waveform shows a closer match between the original and the quantized signals.

2. We also executed the command

```
quant_uniform("./resources/audios/sound.wav","./outputFiles/Mozart20sec/quant_uniform/sound_16_levels.wav",16)
```

to get the quantization of the same audio at 16 levels of quantization:


```
>>
quant_uniform("./resources/audios/sound.wav","./outputFiles/Mozart20sec/quant_uniform/sound_16_levels.wav",16)

info =

struct with fields:

    Filename: '/Users/pedromacedo/Desktop/Desktop – MacBook Air de
Pedro/Study/Year 4/Semester2/SAM–
Year4Semester2/Project/source/resources/audios/sound.wav'
CompressionMethod: 'Uncompressed'
  NumChannels: 1
  SampleRate: 8000
  TotalSamples: 8492
    Duration: 1.0615
      Title: []
    Comment: []
    Artist: []
  BitsPerSample: 8

xmin      xmax      N      Q
-1.0000    1.0000   16.0000  0.1250


Prima uma tecla para continuar

Let now look at the signal in the interval [0.25 – 0.275]sec


Prima uma tecla para continuar

Erro entre o sinal original e o interpolado = 0.00101933

PSNR do sinal interpolado = 2.59984
```



1/500 samples of the total number of the signal samples of the original audio and quantised



200 samples of the total number of the signal samples of the original audio and quantised

- **Comparing the results obtained with the original audio:** The obtained audio has some differences from the original audio. There are:
 1. *Perceptual quality:* The sound shows noticeable distortion when compared to the original audio. This was expected because the quantization algorithm reduces significantly the level of noise in the audio.
 2. *Objective quality:* Is evident that there are a lot of quantosation errors in this scenario. For example, in the firs graph (1/500 samples), the steps between quantization levels are wider, causing a poor approximation of the waveform.
- 3. **Comparing the quantization errors obtained:** To comapre the quantization errors between the two experiences, below is the table with all the values referent to the results obtain in the *MSE* and *PSNR* attributes.

Quantization levels	MSE	PSNR
---------------------	-----	------

Quantization levels	MSE	PSNR
16	0.00101933	2.59984
256	1.52588e-05	32.889

As we can see, the quantization at 256 levels of quantization has the lowest MSE and the highest PSNR.

4. **Comparing quantization graphs at 16 levels and at 256 levels of quantization:** By increasing the number of quantization levels, the difference between the audio signal and the nearest quantization level (quantizational error) is reduced. This results in a better approximation of the original sign. In both graphs, we can see this by checking the distance of the original sound data points (red points) to the quantatized audio signal (blue line), and in the graph with 256 quantization levels, the difference is smaller than the one in the graph with 16 quantization levels. In summary, increasing the number of quantization levels generally improves the quality of the audio signal.