GEAR DATA
NUMBER OF TEETH: 120
DIAMETRAL PITCH: 38.00
MODULE (mm, REF): 0.668
PRESSURE ANGLE: 14.5 DEG
PITCH DIAMETER (mm, REF): 80.21
OUTSIDE DIAMETER (mm): 81.55 +0/-0.10
WHOLE DEPTH (mm): 1.44 REF
FACE WIDTH (mm): 3.00
TOOTH FORM: INVOLUTE, FULL DEPTH



CUT TEETH PER GEAR DATA.
THIN DISC GEAR; GEAR TEETH: CIRCULAR RUNOUT 0.05 MAX ABOUT DATUM A, MEASURED AT THE TOOTH TIPS.
DRIVEN 12:120 BY THE TRANSGEAR PINION (MHA-080).
LOCKED COAXIAL TO THE 12T FEED PINION (MHA-110).

UNLESS OTHERWISE SPECIFIED, TOLERANCES

.XX	.XXX	DRILLED HOLES	∠	Ra 3.2
±0.51	±0.13	+0.10 / 0	±1°	

REMOVE BURRS AND BREAK SHARP EDGES R0.25 OR CHAMFER 0.25 MAX

FINISH
gear teeth cut; polished brass

MATERIAL
Brass

INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5-2018

DO NOT SCALE DRAWING

Albert Michelson's Harmonic Analyzer
A Project For Hobby Machinists

PART
rack-pinion

DWG. NO. MHA-070v

REV 32

SCALE: 1:1

UNIT: mm