

D

C

B

A

D

C

B

A

GEAR DATA
NUMBER OF TEETH: 120
DIAMETRAL PITCH: 38.00
MODULE (mm, REF): 0.668
PRESSURE ANGLE: 14.5 DEG
PITCH DIAMETER (mm, REF): 80.21
OUTSIDE DIAMETER (mm): 81.55 +0/-0.10
WHOLE DEPTH (mm): 1.44 REF
FACE WIDTH (mm): 3.00
TOOTH FORM: INVOLUTE, FULL DEPTH

+0.05
Ø 5.00 +0.03
THRU - REAM

A

⊥ 0.05 A

Ra 1.6

CUT TEETH PER GEAR DATA.
THIN DISC GEAR; GEAR TEETH: CIRCULAR RUNOUT 0.05 MAX ABOUT DATUM A, MEASURED AT THE TOOTH TIPS.
DRIVEN 12:120 BY THE TRANSGEAR PINION (MHA-080).
LOCKED COAXIAL TO THE 12T FEED PINION (MHA-110).

UNLESS OTHERWISE SPECIFIED, TOLERANCES				Albert Michelson's Harmonic Analyzer A Project For Hobby Machinists		
.XX ±0.51	.XXX ±0.13	DRILLED HOLES +0.10 / 0				
REMOVE BURRS AND BREAK SHARP EDGES R0.25 OR CHAMFER 0.25 MAX						
FINISH gear teeth cut; polished brass						
MATERIAL Brass						
INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5-2018						
DO NOT SCALE DRAWING						
PART						rack-pinion
DWG. NO.		REV		SCALE: 1:1		
MHA-070v		32		UNIT: mm		
© 2026 Pedro Paulo Vezza Campos						