

Algoritmo		Latência do Handshake [ms]					
Troca de Chave	Assinatura	Desligado	Padrão(3x)	5x	10x	15x	20x
ML-KEM-512	ML-DSA-44	2.9±0.7	3.0±1.2	-	-	2.6±0.4	2.4±0.4
ML-KEM-512	FALCON-512	2.6±0.2	4.4±1.7	-	-	2.6±0.0	2.6±0.1
ML-KEM-512	FALCON-PADDED-512	2.5±0.2	2.9±0.2	-	-	2.6±0.1	2.6±0.0
ML-KEM-512	SPHINCS-SHA2-128-F-SIMPLE	8.9±0.5	14.1±2.2	-	-	10.3±0.1	10.3±0.1
ML-KEM-512	SPHINCS-SHA2-128-S-SIMPLE	119.1±0.2	191.4±67.2	-	-	149.3±0.1	149.0±0.1
ML-KEM-512	SPHINCS-SHAKE-128-F-SIMPLE	15.9±0.5	31.0±3.0	-	-	19.0±0.1	19.0±0.1
ML-KEM-512	SPHINCS-SHAKE-128-S-SIMPLE	254.0±0.4	314.2±74.0	-	-	318.2±0.2	318.2±0.2
BIKE-L1	ML-DSA-44	3.9±0.5	4.9±0.5	-	-	4.9±0.3	4.9±0.4
BIKE-L1	FALCON-512	3.8±0.2	5.0±0.7	-	-	5.1±0.1	5.1±0.0
BIKE-L1	FALCON-PADDED-512	3.6±0.1	5.5±0.3	-	-	5.1±0.1	5.1±0.1
BIKE-L1	SPHINCS-SHA2-128-F-SIMPLE	9.8±0.4	17.3±1.9	-	-	12.7±0.1	12.7±0.1
BIKE-L1	SPHINCS-SHA2-128-S-SIMPLE	120.3±0.3	297.8±4.0	-	-	281.6±0.4	281.2±0.5
BIKE-L1	SPHINCS-SHAKE-128-F-SIMPLE	17.0±0.6	34.5±1.1	-	-	21.3±0.2	21.3±0.1
BIKE-L1	SPHINCS-SHAKE-128-S-SIMPLE	255.0±0.4	-	-	-	450.8±0.5	450.0±0.2
FRODO-640-AES	ML-DSA-44	3.9±0.5	5.5±2.0	-	-	4.3±0.4	4.4±0.4
FRODO-640-AES	FALCON-512	3.9±0.2	5.9±1.9	-	-	4.4±0.0	4.4±0.1
FRODO-640-AES	FALCON-PADDED-512	4.0±0.4	5.7±0.3	-	-	4.4±0.0	4.4±0.1
FRODO-640-AES	SPHINCS-SHA2-128-F-SIMPLE	10.0±0.3	17.5±1.2	-	-	12.0±0.1	12.0±0.1
FRODO-640-AES	SPHINCS-SHA2-128-S-SIMPLE	120.6±0.4	-	-	-	-	-
FRODO-640-AES	SPHINCS-SHAKE-128-F-SIMPLE	17.1±0.5	25.9±7.8	-	-	20.9±0.0	20.9±0.1
FRODO-640-AES	SPHINCS-SHAKE-128-S-SIMPLE	254.6±0.2	-	-	-	-	-
FRODO-640-SHAKE	ML-DSA-44	5.4±0.3	7.1±1.9	-	-	6.2±0.2	6.2±0.2
FRODO-640-SHAKE	FALCON-512	5.5±0.2	6.9±1.2	-	-	6.5±0.1	6.5±0.1
FRODO-640-SHAKE	FALCON-PADDED-512	5.4±0.2	6.3±0.8	-	-	6.5±0.0	6.5±0.1
FRODO-640-SHAKE	SPHINCS-SHA2-128-F-SIMPLE	11.4±0.2	18.2±3.4	-	-	-	-
FRODO-640-SHAKE	SPHINCS-SHA2-128-S-SIMPLE	122.3±0.4	-	-	-	-	-
FRODO-640-SHAKE	SPHINCS-SHAKE-128-F-SIMPLE	18.6±0.5	25.4±8.3	-	-	-	-
FRODO-640-SHAKE	SPHINCS-SHAKE-128-S-SIMPLE	256.6±0.6	-	-	-	-	-
HQC-128	ML-DSA-44	26.0±0.3	37.1±9.0	-	-	32.2±0.4	32.3±0.4
HQC-128	FALCON-512	26.2±0.2	27.9±0.8	-	-	32.3±0.1	32.3±0.0
HQC-128	FALCON-PADDED-512	26.2±0.1	31.4±5.4	-	-	32.3±0.1	32.3±0.0
HQC-128	SPHINCS-SHA2-128-F-SIMPLE	32.1±0.3	39.3±3.7	-	-	40.0±0.1	39.9±0.1
HQC-128	SPHINCS-SHA2-128-S-SIMPLE	142.7±0.1	-	-	-	-	-
HQC-128	SPHINCS-SHAKE-128-F-SIMPLE	39.4±0.4	51.8±10.4	-	-	48.7±0.1	48.6±0.1
HQC-128	SPHINCS-SHAKE-128-S-SIMPLE	277.0±0.1	-	-	-	-	-