

| Algoritmo        |                            | Latência do Handshake [ms] |                 |    |     |            |            |
|------------------|----------------------------|----------------------------|-----------------|----|-----|------------|------------|
| Troca de Chave   | Assinatura                 | Desligado                  | Padrão(3x)      | 5x | 10x | 15x        | 20x        |
| ML-KEM-1024      | ML-DSA-87                  | 3.1±0.3                    | 5.4±1.9         | -  | -   | 4.2±0.5    | 4.3±0.6    |
| ML-KEM-1024      | FALCON-1024                | 2.8±0.3                    | 4.3±0.4         | -  | -   | 4.1±0.2    | 4.0±0.2    |
| ML-KEM-1024      | FALCON-PADDED-1024         | 3.1±0.3                    | 4.0±0.9         | -  | -   | 4.1±0.2    | 4.1±0.2    |
| ML-KEM-1024      | SPHINCS-SHA2-256-F-SIMPLE  | 23.2±0.4                   | 47.1±4.6        | -  | -   | 29.4±0.1   | 29.4±0.1   |
| ML-KEM-1024      | SPHINCS-SHA2-256-S-SIMPLE  | 193.9±0.3                  | 232.6±12.0      | -  | -   | -          | -          |
| ML-KEM-1024      | SPHINCS-SHAKE-256-F-SIMPLE | 45.9±0.4                   | 80.1±15.8       | -  | -   | 57.7±0.1   | 57.6±0.1   |
| ML-KEM-1024      | SPHINCS-SHAKE-256-S-SIMPLE | 387.4±0.5                  | 406.8±18.0      | -  | -   | -          | -          |
| BIKE-L5          | ML-DSA-87                  | 8.3±0.5                    | 9.7±1.6         | -  | -   | 10.2±1.0   | 9.4±0.2    |
| BIKE-L5          | FALCON-1024                | 8.0±0.3                    | 9.6±1.4         | -  | -   | 9.5±0.2    | 9.4±0.1    |
| BIKE-L5          | FALCON-PADDED-1024         | 8.0±0.4                    | 8.8±1.1         | -  | -   | 9.5±0.1    | 9.4±0.1    |
| BIKE-L5          | SPHINCS-SHA2-256-F-SIMPLE  | 28.3±0.3                   | 52.4±6.2        | -  | -   | -          | -          |
| BIKE-L5          | SPHINCS-SHA2-256-S-SIMPLE  | 199.4±0.3                  | 230.8±22.4      | -  | -   | -          | -          |
| BIKE-L5          | SPHINCS-SHAKE-256-F-SIMPLE | 51.5±0.6                   | 81.1±16.8       | -  | -   | -          | -          |
| BIKE-L5          | SPHINCS-SHAKE-256-S-SIMPLE | 392.3±0.7                  | 419.5±19.6      | -  | -   | -          | -          |
| FRODO-1344-AES   | ML-DSA-87                  | 7.0±1.1                    | 9.1±1.0         | -  | -   | 1006.9±0.7 | 1006.7±0.5 |
| FRODO-1344-AES   | FALCON-1024                | 6.9±0.9                    | 9.1±0.3         | -  | -   | 1006.2±0.1 | 1006.2±0.1 |
| FRODO-1344-AES   | FALCON-PADDED-1024         | 6.8±0.6                    | -               | -  | -   | 1006.2±0.2 | 1006.2±0.1 |
| FRODO-1344-AES   | SPHINCS-SHA2-256-F-SIMPLE  | 38.4±10.0                  | 54.7±2.4        | -  | -   | -          | -          |
| FRODO-1344-AES   | SPHINCS-SHA2-256-S-SIMPLE  | 199.9±1.2                  | 241.3±1.7       | -  | -   | -          | -          |
| FRODO-1344-AES   | SPHINCS-SHAKE-256-F-SIMPLE | 50.0±1.7                   | -               | -  | -   | -          | -          |
| FRODO-1344-AES   | SPHINCS-SHAKE-256-S-SIMPLE | 391.1±1.5                  | -               | -  | -   | -          | -          |
| FRODO-1344-SHAKE | ML-DSA-87                  | 16.2±3.5                   | -               | -  | -   | 1014.3±0.6 | 1014.4±0.6 |
| FRODO-1344-SHAKE | FALCON-1024                | 15.8±3.0                   | 21.0±0.4        | -  | -   | 1013.9±0.1 | 1013.9±0.1 |
| FRODO-1344-SHAKE | FALCON-PADDED-1024         | 15.9±2.4                   | -               | -  | -   | 1013.9±0.1 | 1014.1±0.1 |
| FRODO-1344-SHAKE | SPHINCS-SHA2-256-F-SIMPLE  | 42.4±11.0                  | -               | -  | -   | -          | -          |
| FRODO-1344-SHAKE | SPHINCS-SHA2-256-S-SIMPLE  | 204.3±2.5                  | -               | -  | -   | -          | -          |
| FRODO-1344-SHAKE | SPHINCS-SHAKE-256-F-SIMPLE | 57.1±3.2                   | -               | -  | -   | -          | -          |
| FRODO-1344-SHAKE | SPHINCS-SHAKE-256-S-SIMPLE | 396.9±1.8                  | 441.7±5.6       | -  | -   | -          | -          |
| HQC-256          | ML-DSA-87                  | 133.0±1.6                  | 69887.3±10154.3 | -  | -   | -          | -          |
| HQC-256          | FALCON-1024                | 134.0±1.5                  | -               | -  | -   | -          | -          |
| HQC-256          | FALCON-PADDED-1024         | 132.1±0.8                  | -               | -  | -   | -          | -          |
| HQC-256          | SPHINCS-SHA2-256-F-SIMPLE  | 169.3±13.7                 | -               | -  | -   | -          | -          |
| HQC-256          | SPHINCS-SHA2-256-S-SIMPLE  | 354.8±2.1                  | 70838.2±1625.3  | -  | -   | -          | -          |
| HQC-256          | SPHINCS-SHAKE-256-F-SIMPLE | 203.4±5.7                  | 71865.3±2380.2  | -  | -   | -          | -          |
| HQC-256          | SPHINCS-SHAKE-256-S-SIMPLE | 546.7±15.5                 | -               | -  | -   | -          | -          |