

COMPARISON CHART

Model	MDB-1P	MDB-2P	MDB-1A	MDB-USB
				
FEATURES				
Input	1/4 inch	2 x 1/4 inch	1/4 inch	USB
Output	XLR	2 x XLR	XLR	Headphone, 2-XLR
Ground Lift	Yes	Yes	Yes	—
Input Pad	-15 dB	2 @ -15 dB each	-20 dB	—
Additional Features	—	Stereo I/O	Merge Switching	Stereo/Mono switching
			Polarity	Volume control
			Low Cut	Ground Lift
Supported Audio Formats	—	—	—	WDM, MME, WAV, CoreAudio, DirectSound
Sample Rate	—	—	—	Up to 96kHz/24-bit
SPECIFICATIONS				
Frequency Response	20Hz–20kHz +/-0.2dB		20Hz–20kHz +/-0.5dB	20Hz–20kHz +/-0.5dB
Power	Passive		48V Phantom	Via USB
THD	0.002% THDF @ 1kHz		0.02% THDF @ 1Khz	<0.01% THDF @ 1kHz



MDB-1P MDB-2P MDB-1A MDB-USB

FEATURES

PREMIUM ANALOG CIRCUITRY

MDB Series direct boxes offer excellent noise performance and transparency. Whether you are performing on stage or in the studio, your instruments will always sound as good as they do at the source.

ESSENTIAL TOOLS FROM A BRAND YOU TRUST

Mackie has been at the heart of live sound and studio setups for decades. And now musicians and engineers that rely on our gear can get affordable, high-quality direct boxes from their favorite brand.

BUILT-LIKE-A-TANK™

From the inside out, MDB Series direct boxes are built to last. Thick steel chassis, impact resistant corners, and long-wearing jacks will keep these in your bag for years to come.



MDB-1P Passive Direct Box

An essential tool for every musician and engineer, the **MDB-1P Passive DI** has everything you need to adapt unbalanced, high-impedance audio to a balanced, low-impedance output with minimal noise. Featuring a 1/4" high-impedance input and thru with -15db pad and a balanced XLR output with ground lift.

FEATURES

- Perfect for guitars, basses, and more for stage and studio
- High-impedance 1/4" input with Thru output
- Balanced male XLR output connector with Ground Lift
- Ultra-low noise and distortion
- -15dB pad ensures distortion-free performance when connecting to high-output sources
- Built-Like-A-Tank™ construction

MDB-2P Passive Stereo Direct Box

Great for stereo sources like keyboards and synthesizers, the **MDB-2P** is an essential tool for electronic musicians, live sound venues, and recording studios. The **MDB-2P Stereo Passive DI** features dual 1/4" high-impedance inputs with Thru outputs and -15db pads, and dual low-impedance XLR outputs with ground lift.

FEATURES

- Perfect for stereo sources like keyboards and media players
- High-impedance 1/4" inputs with Thru outputs
- Balanced XLR outputs with Ground Lift
- Ultra-low noise and distortion
- -15dB pads ensure distortion-free performance when connecting to high-output sources
- Built-Like-A-Tank™ construction

MDB-1A Active Direct Box

Great for active instruments like guitars and basses with active pickups and preamps, the **MDB-1A Active DI** features increased headroom and distortion-free operation. Featuring a 1/4" high-impedance input and thru with -20dB pad plus a Merge switch that turns the Thru jack into a second input, perfect for summing a stereo source to a mono output. The balanced XLR output features switches for Polarity, Low Cut, and Ground Lift. For maximum convenience, the **MDB-1A** is powered by 48v phantom power.

FEATURES

- Active circuitry offers higher headroom for ultra-low noise and distortion-free performance
- High-impedance 1/4" input with Thru output
- Balanced XLR output with Ground Lift
- Low Cut and Polarity switches
- Merge switch allows connection of stereo sources which are then summed to mono at the output, perfect for stereo sources like keyboards and media players
- -20dB pad ensures distortion-free performance when connecting to high-level sources
- Powered via 48v Phantom Power
- Built-Like-A-Tank™ construction

MDB-USB USB Stereo Direct Box

With the bus-powered **MDB-USB Stereo DI**, the days of relying on your headphone jack to get audio from a computer into analog gear are over. Combining a high-resolution audio interface with a noise and distortion-free stereo DI, **MDB-USB** converts your digital audio into clean, balanced, stereo output. Featuring an output level control, headphone output, and mono sum for maximum versatility. Analog outputs are dual XLR with ground lift.

FEATURES

- Connect your computer directly via USB
- High-resolution 24bit/96kHz interface
- Balanced, low-impedance XLR outputs with Ground Lift
- Output level control with Mono switch
- Headphone output for easy monitoring
- Noise-free operation
- Powered by your computer
- Plug and play operation, no driver required
- Built-Like-A-Tank™ construction

