# Security of Networks, Services, and Systems Quick Intro to Vulnerabilities

Ricardo Morla

FEUP – SSR/M.EEC, SR/M.EIC



#### Definition

- Weaknesses that allow an attacker to gain access to information, control over a system, or deny service access to others
  - Set of vulnerabilities is known as attack surface
- Successful exploitation requires:
  - Susceptibility or flaw of a system (vulnerability)
  - Attacker access to the vulnerability
  - Attacker capability to exploit the vulnerability

- Flaws in algorithms and protocols
  - When the cipher is known to be vulnerable to cryptanalysis
  - When the block operation or network protocol is not secure (e.g. key) exchange)
- Implementation bugs
- Accessible attack points
- User-related
- Denial of service

- Flaws in algorithms and protocols
- Implementation bugs
  - Incorrect implementation of crypto algorithm that reduces brute force attack space
  - Memory safety violations buffer overflow, dangling pointers
  - Input validation SQL injection, cross-side scripting
  - Race conditions time of check to time of use
  - Privilege confusion cross-site request forgery
  - Privilege escalation horizontal, vertical & jailbreak
- Accessible attack points
- User-related
- Denial of service



- Flaws in algorithms and protocols
- Implementation bugs
- Accessible attack points
  - TCP ports opened by default system services not firewalled
  - Sharing services with no authentication and access control
  - Operating system access control limitations (e.g. no root password)
- User-related
- Denial of service



- Flaws in algorithms and protocols
- Implementation bugs
- Accessible attack points
- User-related
  - Poorly chosen or not securely stored passwords
  - Email viruses, phishing, social network
- Denial of service



- Flaws in algorithms and protocols
- Implementation bugs
- Accessible attack points
- User-related
- Denial of service
  - This vulnerability is always present
  - As long as the service can be accessed by potential attackers
  - Can also see it as threat



# References to databases of types, instances, and exploits of vulnerabilities

- CWE Common Weakness Enumeration (type of vulnerability) https://cwe.mitre.org/
- CVE Common Vulnerabilities and Exposures (instance of vulnerability, exploit)

https://cve.mitre.org

• CPE – Common Platform Enumeration (id platform subject to vulnerability)

https://nvd.nist.gov/products/cpe

#### CPE example


https://nvd.nist.gov/products/cpe/search/results?namingFormat=2.3&keyword=SurfControl

```
cpe:2.3:a:surfcontrol:soap_runtime:2.0:sp2:*:*:*:*:
cpe:2.3:a:surfcontrol:superscout:-:*:*:*:*:*: View CVEs
cpe:2.3:a:surfcontrol:superscout_email_filter:-:*:*:*:*:*
                                                           View CVEs
cpe:2.3:a:surfcontrol:superscout_email_filter:3.5:*:*:*:*:*
                                                             View CVEs
cpe:2.3:a:surfcontrol:superscout_email_filter:4.0:*:*:*:*:*:
                                                             View CVEs
                                                                                   CVE-2002-1532
cpe:2.3:a:surfcontrol:superscout_web_filter:-:*:*:*:*:*
                                                          View CVEs
cpe:2.3:a:surfcontrol:web_filter:-:*:*:*:*:*: View CVEs
```

#### CVE example

http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1532

The administrative web interface (STEMWADM) for SurfControl SuperScout Email Filter allows remote attackers to cause a denial of service (resource exhaustion) via a GET request without the terminating /r/n/r/n (CRLF) sequence, which causes the interface to wait for the sequence and blocks other users from accessing it.





#### CWE example

https://cwe.mitre.org/data/definitions/166.html

- CWE-166: Improper Handling of Missing Special Element
- Special case of:
  - Improper Check or Handling of Exceptional Conditions (CWE703)
- Relevant to the weakness view:
  - Research Concepts
  - Software Development (Data processing Errors)
- Observed example:
  - CVE-2002-1532
  - HTTP GET without \r\n\r\n CRLF sequences causes product to wait indefinitely and prevents other users from accessing it



# Security of Networks, Services, and Systems Quick Intro to Vulnerabilities

Ricardo Morla

FEUP – SSR/M.EEC, SR/M.EIC

