

Knowledge Compilation with Continuous Random Variables Applied to Probabilistic Logic Programming

KU LEUVEN

Pedro Zuidberg Dos Martires, Anton Dries, Luc De Raedt



The Goal

1. Determine probability of SMT formula being true
2. Apply result to Probabilistic Logic Programming

Consider the SMT Formula


$\text{broken} \leftrightarrow (\text{no_cool} \wedge (t > 20)) \vee (t > 30)$

What Is Its Probability Given That:

$$p(\text{no_broken}) = 0.01$$

$$t \sim \mathcal{N}(20, 5)$$

Graphical Representation of Compiled Formula:



How to Calculate the Probability from the Graphical Representation

1. Symbolically evaluate the arithmetic circuit:

$$0.01[t > 20][t \leq 30] + [t > 30]$$

2. Multiply with probability densities:

$$(0.01[t > 20][t \leq 30] + [t > 30]) \mathcal{N}(20, 5)$$

3. Carry out integration over free continuous variables

$$0.01 \int_{20 < t \leq 30} \mathcal{N}(20, 5) dt + \int_{t > 30} \mathcal{N}(20, 5) dt$$

Keywords

Knowledge Compilation - Algebraic Model Counting
- Weighted Model Integration - Hybrid Probabilistic Logics

Symbolic Inference Engine used:
Gehr T., et. al PSI: Exact Symbolic Inference for Probabilistic Programs.

Hybrid Logic Program

$0.2 :: h.$

$0.01 :: \text{no_cool}.$

$\text{normal}(20, 5) :: t \leftarrow \neg h.$

$\text{normal}(27, 5) :: t \leftarrow h.$

$\text{broken} \leftarrow \text{valS}(t, T), \text{conS}(T > 30).$

$\text{broken} \leftarrow \text{no_cool}, \text{valS}(t, T), \text{conS}(T > 20).$

Grounded Hybrid Logic Program

$0.2 :: h. \quad 0.01 :: \text{no_cool}.$

$(t | \neg h > 20, \text{normal}_{t | \neg h}(20, 5)) :: \text{conS}(t > 20) \leftarrow \neg h.$


$(t | h > 20, \text{normal}_{t | h}(27, 5)) :: \text{conS}(t > 20) \leftarrow h.$

$(t | \neg h > 30, \text{normal}_{t | \neg h}(20, 5)) :: \text{conS}(t > 30) \leftarrow \neg h.$

$(t | h > 30, \text{normal}_{t | h}(27, 5)) :: \text{conS}(t > 30) \leftarrow h.$

$\text{broken} \leftarrow \text{conS}(t > 30). \text{broken} \leftarrow \text{no_cool}, \text{conS}(t > 20).$

Graphical Representation of Compiled Program



Experimental Results (in milliseconds)

Benchmark	KC	Evaluation	PSI	Domain
BurglarAlarm	31.4	0.8	190.1	Discrete
CoinBias	41.9	7.9	12.9	Hybrid
Grass	31.2	1.2	228.0	D
NoisyOR	35.8	11.2	12.7	D
TwoCoins	27.0	2.1	57.8	D
ClickGraph	4300	—	10500	H
ClinicalTrial	54.6	25.7	3400	H
AddFun/max	25.2	4.4	53.1	H
AddFun/sum	27.1	2.1	84.9	H
MurderMystery	27.6	0.3	65.4	D