

Table 21. validation_logs

Tamper-evident audit trail of user and system actions; each row is hash-chained to the previous one.

#	Field name	Data type	Key	Null	Default	Description
1	id	integer	PK	No	auto-increment	Unique identifier of the record.
2	entity_type	text		No		Kind of record acted on.
3	entity_id	integer		No		ID of the record acted on.
4	action	text		No		Action code (e.g. LOGIN, TRANSACTION_APPROVED).
5	details_json	jsonb		Yes		Additional details (JSON).
6	user_id	integer	FK	No		Account the record belongs to. → users.id · on delete restrict
7	ip_address	text		Yes		IP address of the request.
8	user_agent	text		Yes		Browser or app user-agent string.
9	status	text		No	'SUCCESS'	Current status of the record.
10	timestamp	timestamp(3)		No	CURRENT_TIMESTAMP	When the action happened.
11	category	text		Yes		Audit category (Authentication, Documents, ...).
12	severity	text		Yes	'INFO'	INFO, WARNING or CRITICAL.
13	outcome	text		Yes	'SUCCESS'	SUCCESS, FAILURE or DENIED.
14	action_label	text		Yes		Readable action name.
15	target_type	text		Yes		Kind of target record.
16	target_id	integer		Yes		ID of the target record.
17	target_reference	text		Yes		Readable reference of the target.
18	actor_email	text		Yes		Email of the actor at the time.
19	actor_role	text		Yes		Role of the actor at the time.
20	actor_station	text		Yes		Station of the actor at the time.
21	client_source	text		Yes	'web'	web or mobile.
22	request_id	text		Yes		ID tying entries from one request together.

#	Field name	Data type	Key	Null	Default	Description
23	failure_reason	text		Yes		Why the action failed.
24	record_hash	text		Yes		Hash of this audit entry.
25	previous_hash	text		Yes		Hash of the previous entry (chain link).
26	hash_version	integer		Yes		Version of the hashing scheme.