


https://vinyl-rack.herokuapp.com/contact/





Performance



Values are estimated and may vary. The <u>performance score is calculated</u> directly from these metrics. <u>See calculator.</u>



Show audits relevant to: All FCP LCP TBT CLS

Opportunity Estimated Savings

Opportunities — These suggestions can help your page load faster. They don't directly affect the Performance score.

Eliminate render-blocking resources

1.65 s ^

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. Learn more. FCP (LCP)

Show 3rd party resources (8)

URL

Transfer Size Potential Savings

URL	Transfer Size	Potential Savings
css/bootstrap.min.css (stackpath.bootstrapcdn.com)	24.3 KiB	1,230 ms
/css?family=Lato&display=swap (fonts.googleapis.com)	0.5 KiB	780 ms
css/base.css (vinyl-rack.s3.amazonaws.com)	8.2 KiB	910 ms
/jquery-3.4.1.min.js (code.jquery.com)	30.1 KiB	1,360 ms
umd/popper.min.js (cdn.jsdelivr.net)	7.6 KiB	1,050 ms
js/bootstrap.min.js (stackpath.bootstrapcdn.com)	16.2 KiB	300 ms
/2c410f4ae7.js (kit.fontawesome.com)	4.0 KiB	930 ms
/v3/ (js.stripe.com)	63.0 KiB	1,680 ms
Reduce unused JavaScript Reduce unused JavaScript and defer loading scripts until they are required to d	lecrease bytes consumed by ne	0.47 s
Learn more. LCP	ooroadd bytod doribarnoa by hol	work douvity.
	Show 3rd party	resources (2)
URL	Transfer Size	Potentia Savings
/v3/ (js.stripe.com)	63.0 KiB	48.5 KiB
/jquery-3.4.1.min.js (code.jquery.com)	30.1 KiB	20.7 KiB
Reduce unused CSS		0.15 s ^
Reduce unused rules from stylesheets and defer CSS not used for above-the-for network activity. <u>Learn more</u> . <u>FCP</u> <u>LCP</u>	old content to decrease bytes co	onsumed by
	✓ Show 3rd-party	resources (1)
URL	Transfer Size	Potentia Savings
css/bootstrap.min.css (stackpath.bootstrapcdn.com)	24.3 KiB	23.3 KiB
/*! * Font Awesome Free 5.15.4 by <code>@fontawesome</code> - <code>https://fontawesome.com</code> * <code>https://fonta</code>	* License - 12.0 KiB	11.9 KiB
agnostics — More information about the performance of your application. These rformance score.	e numbers don't <u>directly affect</u> the	e
Serve static assets with an efficient cache policy — 3 resources found		^
A long cache lifetime can speed up repeat visits to your page. <u>Learn more</u> .		
	Show 3rd-party	resources (3)
URL	Cache TTL	Transfer Size
/v3/ (js.stripe.com)	1 m	63 KiB

...js/m-outer-2a901ea....js (js.stripe.com)

1 KiB

1 m

URL Cache TTL Transfer Size

/out-4.5.40.js (m.stripe.network)

5 m 28 KiB

Avoid chaining critical requests — 10 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn more. FCP (LCP)

Maximum critical path latency: 480 ms

Initial Navigation

/contact/ (vinyl-rack.herokuapp.com)

...css/bootstrap.min.css (stackpath.bootstrapcdn.com) - 40 ms, 24.33 KiB

/css?family=Lato&display=swap (fonts.googleapis.com)

...v20/S6uyw4BMU....woff2 (fonts.gstatic.com) - 30 ms, 13.78 KiB

...css/base.css (vinyl-rack.s3.amazonaws.com) - 130 ms, 8.16 KiB

...webfonts/free-fa-brands-400.woff2 (ka-f.fontawesome.com) - 160 ms, 75.76 KiB

...webfonts/free-fa-solid-900.woff2 (ka-f.fontawesome.com) - 200 ms, 77.19 KiB

/jquery-3.4.1.min.js (code.jquery.com) - 30 ms, 30.07 KiB

...umd/popper.min.js (cdn.jsdelivr.net) - 20 ms, 7.57 KiB

...js/bootstrap.min.js (stackpath.bootstrapcdn.com) - 40 ms, 16.15 KiB

/2c410f4ae7.js (kit.fontawesome.com) - 40 ms, 3.96 KiB

/v3/ (js.stripe.com) - 40 ms, 63.01 KiB

Keep request counts low and transfer sizes small — 21 requests • 387 KiB

To set budgets for the quantity and size of page resources, add a budget.json file. Learn more.

Resource Type	Requests	Transfer Size
Total	21	386.6 KiB
Font	3	166.7 KiB
Script	7	150.0 KiB
Stylesheet	3	32.9 KiB
Other	5	21.0 KiB
Document	3	15.9 KiB
Image	0	0.0 KiB
Media	0	0.0 KiB
Third-party	20	372.4 KiB

Largest Contentful Paint element — 1 element found

This is the largest contentful element painted within the viewport. Learn More [LCP]

URL

 $/jquery-3.4.1.min.js \ ({\tt code.jquery.com})$

Element	
h4.logo-font.my-1	
Avoid large layout shifts — 5 elements found	^
These DOM elements contribute most to the CLS of the page. CLS	
Element CLS (div.col.banner-bg.text-white	Contribution
	0.002
ul.d-lg-none.pl-2	0.001
ul.d-lg-none.pl-2	0.001
p.my-0	0.001
p.my-0	0
Avoid long main-thread tasks — 1 long task found	^
Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. <u>Learn more</u> (TBT)	

Duration

140 ms

Show 3rd-party resources (1)

Start Time

2,783 ms

Passed audits (28)		^
Properly size images		^
Serve images that are appropriately-sized to save cellular data and improve load time	e. <u>Learn more</u> .	
Defer offscreen images		^
Consider lazy-loading offscreen and hidden images after all critical resources have finteractive. Learn more.	inished loading to lower time	to
Minify CSS — Potential savings of 3 KiB		^
Minifying CSS files can reduce network payload sizes. <u>Learn more</u> . <u>FCP</u> <u>LCP</u>		
	Show 3rd-party re	esources (1)
URL	Transfer Size	Potential Savings
css/base.css (vinyl-rack.s3.amazonaws.com)	8.2 KiB	2.6 KiB
Minify JavaScript		^
Minifying JavaScript files can reduce payload sizes and script parse time. Learn mor	e. FCP LCP	
Efficiently encode images		^
Optimized images load faster and consume less cellular data. <u>Learn more</u> .		
Serve images in next-gen formats		^
Image formats like WebP and AVIF often provide better compression than PNG or JI and less data consumption. <u>Learn more</u> .	PEG, which means faster dov	vnloads
Enable text compression — Potential savings of 16 KiB		^
Text-based resources should be served with compression (gzip, deflate or brotli) to ramore. FCP \Box CP	ninimize total network bytes.	<u>Learn</u>
	Show 3rd-party re	esources (1)
URL	Transfer Size	Potential Savings
/contact/ (vinyl-rack.herokuapp.com)	13.8 KiB	10.8 KiB
css/base.css (vinyl-rack.s3.amazonaws.com)	7.7 KiB	5.5 KiB
Preconnect to required origins		^
Consider adding `preconnect` or `dns-prefetch` resource hints to establish early con_ Learn more. FCP LCP	nections to important third-pa	rty origins.
Initial server response time was short — Root document took 60 ms		^
Keep the server response time for the main document short because all other reque-	sts depend on it. <u>Learn more</u> .	FCP
	Show 3rd party re	esources (0)

URL	Time Spent
/contact/ (vinyl-rack.herokuapp.com)	60 ms
Avoid multiple page redirects	^
Redirects introduce additional delays before the page can be loaded. <u>Learn more</u> . FCP [L	CP
Preload key requests	^
Consider using ` k rel=preload>` to prioritize fetching resources that are currently requemore. FCP LCP	ested later in page load. <u>Learn</u>
Use HTTP/2	^
HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Le	<u>earn more</u> .
Use video formats for animated content	^
Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM PNG/WebP for static images instead of GIF to save network bytes. <u>Learn more</u> <u>LCP</u>	videos for animations and
Remove duplicate modules in JavaScript bundles	^
Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes of TBT	onsumed by network activity.
Avoid serving legacy JavaScript to modern browsers — Potential savings of 0 KiB	^
Polyfills and transforms enable legacy browsers to use new JavaScript features. However, modern browsers. For your bundled JavaScript, adopt a modern script deployment strateg detection to reduce the amount of code shipped to modern browsers, while retaining support More (TBT)	y using module/nomodule feature
	☐ Show 3rd-party resources (2)
URL	Potential Savings
Preload Largest Contentful Paint image	^
Preload the image used by the LCP element in order to improve your LCP time. <u>Learn mo</u>	re. LCP
Avoids enormous network payloads — Total size was 387 KiB	^
Large network payloads cost users real money and are highly correlated with long load tim	nes. <u>Learn more</u> . <u>LCP</u>
	✓ Show 3rd-party resources (9)
URL	Transfer Size
webfonts/free-fa-solid-900.woff2 (ka-f.fontawesome.com)	77.2 KiB
webfonts/free-fa-brands-400.woff2 (ka-f.fontawesome.com)	75.8 KiB
/v3/ (js.stripe.com)	63.0 KiB
/jquery-3.4.1.min.js (code.jquery.com)	30.1 KiB
/out-4.5.40.js (m.stripe.network)	27.8 KiB
css/bootstrap.min.css (stackpath.bootstrapcdn.com)	24.3 KiB

,			T (0
JRL			Transfer S
js/bootstrap.min.js (stackpath.bootstrapcdn.c	com)		16.2 K
/contact/ (vinyl-rack.herokuapp.com)			14.2 K
v20/S6uyw4BMUwoff2 (fonts.gstatic.com	1)		13.8 K
css/free.min.css?token=2c410f4ae7 (ka-f.f.	fontawesome.com)		13.2 K
Avoids an excessive DOM size — 139 eleme	ents		
A large DOM will increase memory usage, cau	use longer <u>style calculations</u> , and produ	uce costly <u>layout reflows</u> .	<u>Learn more</u> .
Statistic	Element		Va
Total DOM Elements			1
Maximum DOM Depth	i.fas.fa-search		
	form#contact-forn	n.form.mb-2	
Maximum Child Elements			
User Timing marks and measures Consider instrumenting your app with the Use	er Timing API to measure your app's rea	al-world performance duriı	ng key user
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, con			yloads helps
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, conwith this. Learn more. TBT		d delivering smaller JS pa	yloads helps ty resources
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, conwith this. Learn more. TBT	mpiling, and executing JS. You may find	d delivering smaller JS par Show 3rd-part	yloads helps ty resources Script Pa
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, con	mpiling, and executing JS. You may find Total CPU Time	d delivering smaller JS part Show 3rd-part Script Evaluation	yloads helps ty resources Script Pa
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, conwith this. Learn more. TBT JRL /contact/ (vinyl-rack.herokuapp.com)	mpiling, and executing JS. You may find Total CPU Time 155 ms	d delivering smaller JS part Show 3rd-part Script Evaluation 6 ms	yloads helps ty resources Script Pa 2 r
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, conwith this. Learn more. (TBT) JRL /contact/ (vinyl-rack.herokuapp.com)	mpiling, and executing JS. You may find Total CPU Time 155 ms 137 ms	d delivering smaller JS part Show 3rd-part Script Evaluation 6 ms 12 ms	yloads helps ty resources of Script Pa 2 r 0 r 13 r
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, conwith this. Learn more. TBT JRL /contact/ (vinyl-rack.herokuapp.com) Unattributable /v3/ (js.stripe.com)	Total CPU Time 155 ms 137 ms	d delivering smaller JS part Show 3rd-part Script Evaluation 6 ms 12 ms 58 ms	yloads helps ty resources Script Pa
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, conwith this. Learn more. TBT JRL /contact/ (vinyl-rack.herokuapp.com) Unattributable /v3/ (js.stripe.com) /jquery-3.4.1.min.js (code.jquery.com)	Total CPU Time 155 ms 137 ms 71 ms 60 ms	Show 3rd-part Script Evaluation 6 ms 12 ms 58 ms 32 ms	yloads helps ty resources (Script Pa 2 r 0 r 13 r
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, conwith this. Learn more. TBT JRL /contact/ (vinyl-rack.herokuapp.com) Unattributable /v3/ (js.stripe.com) /jquery-3.4.1.min.js (code.jquery.com) Minimizes main-thread work — 0.5 s Consider reducing the time spent parsing, con	Total CPU Time 155 ms 137 ms 71 ms 60 ms	Show 3rd-part Script Evaluation 6 ms 12 ms 58 ms 32 ms	yloads helps ty resources of the second sec
Consider instrumenting your app with the Use experiences. Learn more. JavaScript execution time — 0.1 s Consider reducing the time spent parsing, conwith this. Learn more. TBT JRL /contact/ (vinyl-rack.herokuapp.com) Unattributable /v3/ (js.stripe.com) /jquery-3.4.1.min.js (code.jquery.com) Minimizes main-thread work — 0.5 s Consider reducing the time spent parsing, conwith this. Learn more TBT	Total CPU Time 155 ms 137 ms 71 ms 60 ms	Show 3rd-part Script Evaluation 6 ms 12 ms 58 ms 32 ms	yloads helps ty resources (Script Pa 2 r 0 r 13 r 5 r

Category	Time Spent
Style & Layout	71 ms
Parse HTML & CSS	44 ms
Script Parsing & Compilation	25 ms
Rendering	22 ms
All text remains visible during webfont loads	^
Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. <u>Learn more</u> . <u>FCP</u>	LCP
Minimize third-party usage — Third-party code blocked the main thread for 0 ms	^

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. <u>Learn more</u>. (TBT)

Show 3rd-party resources (0)

Third-Party	Transfer Size	Main-Thread Blocking Time
FontAwesome CDN	176 KiB	0 ms
webfonts/free-fa-solid-900.woff2 (ka-f.fontawesome.com)	77 KiB	0 ms
webfonts/free-fa-brands-400.woff2 (ka-f.fontawesome.com)	76 KiB	0 ms
css/free.min.css?token=2c410f4ae7 (ka-f.fontawesome.com)	13 KiB	0 ms
Other resources	10 KiB	0 ms
<u>Stripe</u>	95 KiB	0 ms
/v3/ (js.stripe.com)	63 KiB	0 ms
/out-4.5.40.js (m.stripe.network)	28 KiB	0 ms
Bootstrap CDN	40 KiB	0 ms
css/bootstrap.min.css (stackpath.bootstrapcdn.com)	24 KiB	0 ms
js/bootstrap.min.js (stackpath.bootstrapcdn.com)	16 KiB	0 ms
jQuery CDN	30 KiB	0 ms
/jquery-3.4.1.min.js (code.jquery.com)	30 KiB	0 ms
Google Fonts	14 KiB	0 ms
v20/S6uyw4BMUwoff2 (fonts.gstatic.com)	14 KiB	0 ms
Amazon Web Services	10 KiB	0 ms
css/base.css (vinyl-rack.s3.amazonaws.com)	8 KiB	0 ms
JSDelivr CDN	8 KiB	0 ms
umd/popper.min.js (cdn.jsdelivr.net)	8 KiB	0 ms

Lazy load third-party resources with facades

Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. <u>Learn more.</u> <u>TBT</u>

Uses passive listeners to improve scrolling performance

Consider marking your touch and wheel event listeners as 'passive' to improve your page's scroll performance. Learn more.

Avoids document.write()

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. <u>Learn more</u> .	
Avoid non-composited animations	^
Animations which are not composited can be janky and increase CLS. <u>Learn more</u> <u>CLS</u>	
Image elements have explicit width and height	^
Set an explicit width and height on image elements to reduce layout shifts and improve CLS. Learn more CLS	



Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Additional items to manually check (10) — These items address areas which an automated testing tool cannot cover. Learn ^ more in our guide on conducting an accessibility review.

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. Learn more. Interactive controls are keyboard focusable Custom interactive controls are keyboard focusable and display a focus indicator. Learn more. Interactive elements indicate their purpose and state Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn more. The user's focus is directed to new content added to the page If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more. User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more.		
Interactive controls are keyboard focusable Custom interactive controls are keyboard focusable and display a focus indicator. Learn more. Interactive elements indicate their purpose and state Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn more. The user's focus is directed to new content added to the page If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more. User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order	The page has a logical tab order	^
Custom interactive controls are keyboard focusable and display a focus indicator. Learn more. Interactive elements indicate their purpose and state Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn more. The user's focus is directed to new content added to the page If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more. User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more.	Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more</u> .	
Interactive elements indicate their purpose and state Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn more. The user's focus is directed to new content added to the page If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more. User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order	Interactive controls are keyboard focusable	^
Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn more. The user's focus is directed to new content added to the page If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more. User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order	Custom interactive controls are keyboard focusable and display a focus indicator. Learn more.	
elements. Learn more. The user's focus is directed to new content added to the page If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more. User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order	Interactive elements indicate their purpose and state	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more. User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order		
User focus is not accidentally trapped in a region A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order	The user's focus is directed to new content added to the page	^
A user can tab into and out of any control or region without accidentally trapping their focus. Learn more. Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order	If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more.	
Custom controls have associated labels Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order	User focus is not accidentally trapped in a region	^
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more. Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order	A user can tab into and out of any control or region without accidentally trapping their focus. Learn more.	
Custom controls have ARIA roles Custom interactive controls have appropriate ARIA roles. Learn more. Visual order on the page follows DOM order	Custom controls have associated labels	^
Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> . Visual order on the page follows DOM order	Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <u>Learn more</u> .	
Visual order on the page follows DOM order	Custom controls have ARIA roles	^
	Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	
DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	Visual order on the page follows DOM order	^
	DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	

Offscreen content is hidden from assistive technology Offscreen content is hidden with display: none or aria-hidden=true. Learn more. HTML5 landmark elements are used to improve navigation Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. Learn more. Passed audits (18) [aria-*] attributes match their roles Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. Learn [aria-hidden="true"] is not present on the document <body> Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. Learn more. [aria-hidden="true"] elements do not contain focusable descendents Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn more. [aria-*] attributes have valid values Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more. [aria-*] attributes are valid and not misspelled Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more. Buttons have an accessible name When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. Learn more. The page contains a heading, skip link, or landmark region Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more. Background and foreground colors have a sufficient contrast ratio Low-contrast text is difficult or impossible for many users to read. Learn more. Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more. ARIA IDs are unique The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn more. Heading elements appear in a sequentially-descending order

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. <u>Learn more</u>.

<html> element has a [lang] attribute

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. <u>Learn more</u>.

<html> element has a valid value for its [lang] attribute

Specifying a valid BCP 47 language helps screen readers announce text properly. Learn more.

Form elements have associated labels

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more.

Links have a discernible name

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. <u>Learn more</u>.

Lists contain only elements and script supporting elements (<script> and <template>).

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. <u>Learn more</u>.

List items () are contained within or parent elements

Screen readers require list items (``) to be contained within a parent `` or `` to be announced properly. <u>Learn more</u>.

[user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5.

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. <u>Learn more</u>.

Not applicable (26)

[accesskey] values are unique

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more.

button, link, and menuitem elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

ARIA input fields have accessible names

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

ARIA meter elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

ARIA progressbar elements have accessible names When a 'progressbar' element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. [role]s have all required [aria-*] attributes Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more. Elements with an ARIA [role] that require children to contain a specific [role] have all required children. Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more. [role]s are contained by their required parent element Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more. [role] values are valid ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more. ARIA toggle fields have accessible names When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA tooltip elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA treeitem elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. <dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements. When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn more. Definition list items are wrapped in <dl> elements Definition list items ('<dt>' and '<dd>') must be wrapped in a parent '<dl>' element to ensure that screen readers can properly announce them. Learn more. [id] attributes on active, focusable elements are unique All focusable elements must have a unique 'id' to ensure that they're visible to assistive technologies. Learn more. No form fields have multiple labels Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn more. <frame> or <iframe> elements have a title Screen reader users rely on frame titles to describe the contents of frames. Learn more. Image elements have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more</u>.

<input type="image"> elements have [alt] text

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. <u>Learn more</u>.

The document does not use <meta http-equiv="refresh">

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more</u>.

<object> elements have [alt] text

Screen readers cannot translate non-text content. Adding all text to `<object>` elements helps screen readers convey meaning to users. <u>Learn more</u>.

No element has a [tabindex] value greater than 0

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u>.

Cells in a element that use the [headers] attribute refer to table cells within the same table.

Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. <u>Learn more</u>.

elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <u>Learn more</u>.

[lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn more</u>.

<video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more.



Best Practices

Trust and Safety

Includes front-end JavaScript libraries with known security vulnerabilities — 2 vulnerabilities detected

Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. <u>Learn more</u>.

Library Version **Vulnerability Count Highest Severity** jQuery@3.4.1 2 Medium Ensure CSP is effective against XSS attacks A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. Learn more Description Directive Severity No CSP found in enforcement mode High Passed audits (16) **Uses HTTPS** All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more. Links to cross-origin destinations are safe Add `rel="noopener"` or `rel="noreferrer"` to any external links to improve performance and prevent security vulnerabilities. Learn more. Avoids requesting the geolocation permission on page load Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more. Avoids requesting the notification permission on page load Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more. Allows users to paste into password fields Preventing password pasting undermines good security policy. Learn more. Displays images with correct aspect ratio Image display dimensions should match natural aspect ratio. Learn more. Serves images with appropriate resolution Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn more. Page has the HTML doctype Specifying a doctype prevents the browser from switching to quirks-mode. Learn more. Properly defines charset A character encoding declaration is required. It can be done with a '<meta>' tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more.

Avoids unload event listeners	^
The `unload` event does not fire reliably and listening for Consider using the `pagehide` or `visibilitychange` ever	or it can prevent browser optimizations like the Back-Forward Cache. Its instead. Learn more
Avoids Application Cache	^
Application Cache is deprecated. <u>Learn more</u> .	
Detected JavaScript libraries	^
All front-end JavaScript libraries detected on the page.	Learn more.
Name	Version
Bootstrap	4.4.1
jQuery	3.4.1
Avoids deprecated APIs	^
Deprecated APIs will eventually be removed from the b	rowser. <u>Learn more</u> .
No browser errors logged to the console	^
Errors logged to the console indicate unresolved proble concerns. <u>Learn more</u>	ms. They can come from network request failures and other browser
Page has valid source maps	^
·	rce code. This helps developers debug in production. In addition, deploying source maps to take advantage of these benefits. <u>Learn</u>
	Show 3rd-party resources (2)
URL	Map URL
js/bootstrap.min.js (stackpath.bootstrapcdn.com)	js/bootstrap.min.js.map (stackpath.bootstrapcdn.com)
umd/popper.min.js (cdn.jsdelivr.net)	umd/popper.min.js.map (cdn.jsdelivr.net)
No issues in the Issues panel in Chrome Devtools	^
	s indicate unresolved problems. They can come from network request r concerns. Open up the Issues panel in Chrome DevTools for more
Not applicable (1)	^
Fonts with font-display: optional are preloaded	^
Preload `optional` fonts so first-time visitors may use the	em. <u>Learn more</u>



These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on Core Web Vitals. Learn more.

Additional items to manually check (1) — Run these additional validators on your site to check additional SEO best practices.	^
Structured data is valid	^
Run the <u>Structured Data Testing Tool</u> and the <u>Structured Data Linter</u> to validate structured data. <u>Learn more</u> .	
Passed audits (11)	^
Has a <meta name="viewport"/> tag With width Or initial-scale	^
Add a ` <meta name="viewport"/> ` tag to optimize your app for mobile screens. Learn more.	
Document has a <title> element</td><td>^</td></tr><tr><td>The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if page is relevant to their search. <u>Learn more</u>.</td><td>а</td></tr><tr><td>Document has a meta description</td><td>^</td></tr><tr><td>Meta descriptions may be included in search results to concisely summarize page content. Learn more.</td><td></td></tr><tr><td>Page has successful HTTP status code</td><td>^</td></tr><tr><td>Pages with unsuccessful HTTP status codes may not be indexed properly. <u>Learn more</u>.</td><td></td></tr><tr><td>Links have descriptive text</td><td>^</td></tr><tr><td>Descriptive link text helps search engines understand your content. <u>Learn more</u>.</td><td></td></tr><tr><td>Links are crawlable</td><td>^</td></tr><tr><td>Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor elements to an appropriate destination, so more pages of the site can be discovered. Learn More</td><td>links</td></tr><tr><td>Page isn't blocked from indexing</td><td>^</td></tr><tr><td>Search engines are unable to include your pages in search results if they don't have permission to crawl them. Learn r</td><td>nore.</td></tr><tr><td>Document has a valid hreflang</td><td>^</td></tr><tr><td>hreflang links tell search engines what version of a page they should list in search results for a given language or region Learn more.</td><td>n.</td></tr><tr><td>Document uses legible font sizes — 100% legible text</td><td>^</td></tr><tr><td>Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Str</td><td>ive to</td></tr></tbody></table></title>	

have >60% of page text ≥12px. <u>Learn more</u>.

				Show 3rd party resources (0)
	Source	Selector	% of Page Text	Font Size	
	Legible text		100.00%	≥ 12px	
	Document avoids plugins				^
	Search engines can't index plugin content, and many devices restrict plugins or don't support them. <u>Learn more</u> .				
	Tap targets are sized appropriately — 100% appropriately sized tap targets				
	Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. <u>Learn more</u> .				
Not applicable (3)					^
	robots.txt is valid				^
	If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. <u>Learn more</u> .				
	Image elements have [alt]	attributes			^
	Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty a attribute. <u>Learn more</u> .				
	Document has a valid rel=c	anonical			^
	Canonical links suggest whi	ch URL to show in search results 1	earn more		



Progressive Web App

These checks validate the aspects of a Progressive Web App. Learn more.

Installable

Web app manifest or service worker do not meet the installability requirements — 4 reasons

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn more</u>.

Failure reason

Manifest start URL is not valid

Manifest does not contain a 'name' or 'short_name' field

Failure reason

No matching service worker detected. You may need to reload the page, or check that the scope of the service worker for the current page encloses the scope and start URL from the manifest.

Downloaded icon was empty or corrupted

PWA Optimized

Does not register a service worker that controls page and start_url The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. Learn more. Does not redirect HTTP traffic to HTTPS If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. Learn more. Is not configured for a custom splash screen Failures: Manifest does not have `name`. A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. Learn more. Does not set a theme color for the address bar. Failures: No `<meta name="theme-color"> `tag found. The browser address bar can be themed to match your site. Learn more. Content is sized correctly for the viewport If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. Learn more. Has a <meta name="viewport"> tag with width or initial-scale Add a `<meta name="viewport">` tag to optimize your app for mobile screens. Learn more. Provides a valid apple-touch-icon For ideal appearance on iOS when users add a progressive web app to the home screen, define an 'apple-touch-icon'. It must point to a non-transparent 192px (or 180px) square PNG. Learn More. Manifest doesn't have a maskable icon A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. Learn more.

Additional items to manually check (3) — These checks are required by the baseline <u>PWA Checklist</u> but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

Site works cross-browser

To reach the most number of users, sites should work across every major browser. Learn more.

Page transitions don't feel like they block on the network

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. <u>Learn more</u>.

Each page has a URL

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. <u>Learn more</u>.

Runtime Settings

URL https://vinyl-rack.herokuapp.com/contact/

Fetch Time Oct 17, 2021, 10:57 AM GMT+1

Device Emulated Moto G4

Network throttling 150 ms TCP RTT, 1,638.4 Kbps throughput (Simulated)

CPU throttling 4x slowdown (Simulated)

Channel devtools

User agent (host) Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like

Gecko) Chrome/94.0.4606.81 Safari/537.36

User agent (network) Mozilla/5.0 (Linux; Android 7.0; Moto G (4)) AppleWebKit/537.36 (KHTML, like

Gecko) Chrome/94.0.4590.2 Mobile Safari/537.36 Chrome-Lighthouse

CPU/Memory Power 1490

Axe version 4.2.3

Generated by **Lighthouse** 8.3.0 | File an issue