

rough notebook that had some experimenting for a two parameter surface illustration. This notebook was not left in a useful looking state.

```
<< peeters` ;
peeters`setGitDir[ "../project/figures/GAelectrodynamics" ]
/Users/pjoot/project/figures/GAelectrodynamics

ClearAll[o, f, triple, bold, fs, bx0fa, dxa, dxb,
  bx0faDa, bx0faDb, p, p2, pa, pb, g, x, y, dx, pay, pbx]
o = {0, 0, 0};
f[x_, y_] = -4 + Sin[5 x + y] + (x - 2 y)^2 ;
triple[x_, y_] = {x, y, f[x, y]} ;
bold = Style[#, Bold] &;
fs = 14;
bx0fa = Style[Row[{bold[x], "(u1, u2)"}], FontSize → fs] ;
bx0faDa = Style[Row[{bold[x], "(u1 + Δu1, u2)"}], FontSize → fs] ;
bx0faDb = Style[Row[{bold[x], "(u1, u2 + Δu2)"}], FontSize → fs] ;

t = Style[#, FontSize → fs] &;
dx[v_, e_ : "", s_ : ""] :=
  Row[{s // t, t["d"], Subscript[bold[x] // t, v // t], e // t}] ;
dxa = dx["u1"];
dxb = dx["u2"];

p = Plot3D[
  f[x, y], {x, 0, 1}, {y, 0, 1},
  PlotTheme → "ThickLines",
  Axes → None, Mesh → None, PlotStyle → Directive[Opacity[0.8] ]
] ;


pay[l_, h_, a_] := ParametricPlot3D[ triple[a, y], {y, l, h},
  PlotTheme → "ThickLines", PlotStyle → Directive[Green // Darker // Darker]];
pbx[l_, h_, b_] := ParametricPlot3D[ triple[x, b], {x, l, h},
  PlotTheme → "ThickLines", PlotStyle → Directive[Green // Darker // Darker]];
pa = pay[0.5, 1, 0.5];
pb = pbx[0.5, 1, 0.5];

low = 0.5;
high = 1.5;
lowlow = triple[low, low];
lowhigh = triple[low, high];
```

```
highlow = triple[high, low];
highhigh = triple[high, high];
```

```
(*Callout doesn't appear to work for 3D plot*)
p2 = ListPointPlot3D[{
  (*Callout[lowlow,bx0fa, Above],
  Callout[highlow,bx0faDa, Above],
  Callout[lowhigh,bx0faDb, Above]*)
  lowlow,
  highlow,
  lowhigh,
  o
},
PlotStyle → Directive[Black, PointSize[Large]]
];
```

```
g = Show[p, p2, pa, pb,
Graphics3D[{
  Thick, Arrowheads[0.001],
  Arrow[{o, lowlow}],
  Arrow[{o, highlow}],
  Arrow[{o, lowhigh}],
  Blue // Darker,
  (*Arrowheads[0.01],*)
  Arrow[{lowlow, triple[0.5, 0.9]}],
  Arrow[{lowlow, triple[0.9, 0.5]}],
  (*Text[bx0fa,lowlow + {-1,1,0.1}0.2],*)
  Text[bx0faDa, highlow + {1, 1, 0} 0.3],
  Text[bx0faDb, lowhigh + {1, 1, 0} 0.3],
  Text[dxb, triple[0.5, 0.9] + {1, 0, 0} 0.15],
  Text[dxa, triple[0.9, 0.5] + {0, 1, 0} 0.15]
}]
]
```



```

pah = pay[0.5, 1.5, 1.5];
pbh = pbx[0.5, 1.5, 1.5];

g2 = Show[p, pa, pb, pah, pbh,
Graphics3D[{
  Thick, Arrowheads[0.001],

  Arrow[{lowhigh, triple[low + 0.3, high]}],
  Arrow[{highhigh, triple[high, high - 0.3]}],
  Arrow[{lowlow, triple[low, low + 0.3]}],
  Arrow[{highlow, triple[high - 0.3, low]}],

  Text[dx["a", "(b=1)"], triple[low + 0.3, high] + {0, 1, 0} 0.2],
  Text[dx["b", "(a=1)", "-"], triple[high, high - 0.3] - 0.3 {1, 0, 0}],
  Text[dx["b", "(a=0)", ""], triple[low, low + 0.3] + 0.3 {1, 0, 0}],
  Text[dx["a", "(b=0)", "-"], triple[high - 0.3, low] - 0.2 {0, 1, 0}]

}]
]

peeters`exportForLatex["twoParameterDifferentialFig1", g]
(*peeters`exportForLatex["twoParameterDifferentialBoundaryFig2", g2]*)
{twoParameterDifferentialFig1.eps, twoParameterDifferentialFig1pn.png}

```

```

ClearAll[z, r, rx, ry]
z[x_, y_] := y + 4 x^2;
r[x_, y_] := {x, y, z[x, y]};
rx[x_, y_] := {1, 0, 8 x};
ry[x_, y_] := {0, 1, 1};
surface = Plot3D[z[x, y], {x, 0, 1}, {y, 0, 1}, PlotRange -> Full];
plotAlong = ParametricPlot3D[{rx[x, y], ry[x, y]}, {x, 0, 1}, {y, 0, 1}];
(*plotAlongY[xv_] := ParametricPlot3D[{xv, y, z[xv, y]}, {y, 0, 1}]*
*)

(*Show[{surface,
  plotAlong
  (*plotAlongX[0.1],
  plotAlongY[0.3]*
}]*
*)

```

