CrowdStrike for SOC Analysts

Hailie Shaw
Blue Team Consulting, LLC
https://blueteamwins.com



Course Agenda

- Module 1 Console Overview
- Module 2 Where to Spend your Time
- Module 3 Triaging a Detection
- Module 4 Useful Open Source Tools to Use
- Module 5 Event Search / Splunk Queries
- Module 6 Real Time Response Features
- Module 7 Sandbox & Blocking Actions
- Module 8 Whitelisting / Exclusions
- Module 9 Putting it all together
- Module 10 Where to go next




Module 1

Console Overview




Be sure to do the following


- Set your time preference to UTC




Staying Signed In/Dark Theme




Different Subscriptions have different menu options







20 22 BLUE TEAM CONSULTING



Bookmarks

Updates





Demo: Overview of the console





Module 2


Where to Spend Your Time




Areas important to SOC Operations









Overview of Detections


Incidents Queue

Detections Queue

Regex Rules

Whitelisting

Hashes, IPs, Domains



CQL Searching of Raw Endpoint logs

IP, hash, domain, user quick lookups

Reports, Event searches, Prebuilt dashboards for hunting, host timelines, etc.

Demo: Areas of the console to focus on




Module 3

Triaging a Detection



Detections are present for a 90 day retention period
Indicators are present based on your CS retention period, more than likely this is 1 year



Icons & Color Coding




High

+9 others

If there is a white badge = a process was killed or an operation was blocked



Multiple detections, could be part of an Incident



If there is a green badge = a process was blocked











Malware - Informational





Overwatch Detection







Persistence, Defense Evasion, blocked/killed





Malware - High







Lots of Different Viewpoints in CS






Where to look first





Group your Detections, if it helps



Things to ask yourself when looking at a detection

Are we dealing with a Server or a Workstation?
Who was the user associated with the activity? What is their level of permissions?
What is the severity of the alert?
What is CS noting for MITRE Tactic & Technique?
Was anything blocked?
Is something still running? / Do I need to think about containment?
Any flags for indicators or known TA groups?
Do we recognize the file name or other processes involved?
Outbound active network connections seen?
Suspicious command line arguments?
Odd parent child process trees?
Hash, IP, Domain, URL analysis from OSINT?



What to include in a write up

At a minimum:
Host, timestamps (UTC), process involved, command lines, what happened on the host, what actions you took, OSINT research

Nice to have:
Root Cause Analysis, pictures of forensic artifacts you found, scoping steps taken, next steps/recommendations to the next tier in the SOC, sandbox sample/analysis, link to the detection

Best to develop your own “detection template” that you can use to just fill in each time you do a write up.
BTC has a free one available on our website store: BlueTeamWins.com



Demo: Detections Overview



Module 4

OSINT Tools to Leverage



Free Websites to Leverage




VirusTotal
AnyRun
Joes Sandbox Reports
Hybrid Analysis
Urlscan.io
Domain Tools whois
Shoadan.io
Mxtoolbox
*Just google it…

















Where they are in CS





Leverage other Companies Resources

SANS Sites ▾ Search Log In Join

SANS

Train and Certify Manage Your Team Security Awareness Resources Get Involved About

Home > Poster > Hunt Evil


Share:

Hunt Evil


Knowing what's normal on a Windows host helps cut through the noise to quickly locate potentia
malware. Use this information as a reference to know what's normal in Windows and to focus you
attention on the outliers.

February 7, 2023

Download



For Linux:




20 22 BLUE TEAM CONSULTING

Module 5

Endpoint Log Searching / CQL





SIEM > Advanced Event Search = Raw Logs




Fields to Call Out

event_simpleName
@timestamp
@rawsring
CommandLine
ComputerName
FileName
ImageFileName
UserName
SHA256HashData
DomainName
LocalIP / LPort
RemoteIP / RPort





Fields for Files




*tip: replace “\Device\HarddiskVolume#” with a drive letter (probably C)
Example: \Device\HarddiskVolume4\Program Files\PuTTY\putty.exe is actually
C:\Program Files\PuTTY\putty.exe




Searching tips: wildcard string search

/<insert string/i



Working with Time fields



Use @timestamp. Format it to human readable format and then put it in UTC (Zulu) time

Build your repeatable “Base Search”

```
| time := formatTime("%Y-%m-%d %H:%M:%S", field=@timestamp, locale=en_US, timezone=Z)
```

```
|select([time,UserName,ImageFileName,CommandLine,ParentBaseFileName,TargetProcessId,ContextProcessId,SHA256HashData,AuthenticodeHashData])
```


```
aid = febc1bda67924b70902e4de002b4e3fc
| #event_simpleName=CommandHistory
| time := formatTime("%Y-%m-%d %H:%M:%S", field=@timestamp, locale=en_US, timezone=Z)
| table([time,CommandHistory,ApplicationName,TargetProcessId])
```

```
aid = febc1bda67924b70902e4de002b4e3fc
| #event_simpleName = ScheduledTask*
| time := formatTime("%Y-%m-%d %H:%M:%S", field=@timestamp, locale=en_US, timezone=Z)
| table([time,#event_simpleName,UserName,TaskAuthor,TaskExecArguments,TaskExecCommand,TaskName,@rawstring], limit=20000)
```

How to groupBy

```
| groupBy([DomainName], function=[count(as=count)])
| sort([count], order=desc, limit=10000)
```


```
aid = febc1bda67924b70902e4de002b4e3fc
| "#event_simpleName" = NetworkConnectIP4
| RemotePort = /(80|3389|22)/
| groupBy([RemoteAddressIP4], function=[count(as=count)])
| sort([count], order=desc, limit=1000)
```





```
aid = febc1bda67924b70902e4de002b4e3fc
#event_simpleName = DnsRequest
| DomainName = /rclone/i
| groupBy([DomainName], function=[count(as=count)])
| sort([count], order=desc, limit=10000)
```

DomainName	count
rclone.org	2
weblog.rclone.org	2

If you refuse to learn CQL...



If you refuse to learn CQL…



@timestamp	CommandLine	ContextProcessId	ImageFileName	ParentBaseFileN	SHA256HashData	TargetProcessId	time	UserName
1.76356E+12							11/19/25 14:30	
1.76356E+12							11/19/25 14:30	
1.76356E+12		6.54048E+17			c05f0a5e7c239a2afb740afead85f7ea58ecb424954 5bfc11f225d		11/19/25 14:02	hailieshaw
1.76356E+12	ps -o pcpu,rss -p 6003				7323501f54d9771476d1a2ed94d8373ae61de680d12fc8eb133a		11/19/25 14:33	root
1.76356E+12							11/19/25 14:17	
1.76356E+12							11/19/25 13:44	
1.76356E+12		6.54109E+17					11/19/25 14:29	
1.76356E+12		6.54129E+17			735c3eecdf014edcf519713c79a810df52f07	6.54129E+17	11/19/25 14:33	
1.76356E+12							11/19/25 14:32	
1.76354E+12		6.54048E+17					11/19/25 9:20	
1.76356E+12							11/19/25 13:30	
1.76356E+12							11/19/25 14:00	
1.76356E+12		6.54048E+17			d288958e7d85cb925005e2b6f41d513eadabe68a908cb2877fc2f		11/19/25 14:02	hailieshaw
1.76356E+12	/Applications/Splunk/bin/python3.9/Applications/Splunk/etc/apps/search/bin/quarantine_files.py				e0a9f01af13df89fb87a5ae8e20ad74d90a7928b19919bd89aa7cc		11/19/25 14:33	root
1.76356E+12	splunk-optimize -d /Applications/Splunk/var/lib/splunk/_internaldb/db/hot_v1_71 -x 3613588992 --log-to--splunkd-log --write-level 3 --tsidx-target-size 1572864000 --msidx-com				735c3eecdf014edcf519713c79a810df52f07c9aaaae2b4133ae6e		11/19/25 14:24	root
1.76356E+12							11/19/25 13:44	
1.76356E+12		6.54109E+17					11/19/25 14:29	
1.76356E+12		6.54129E+17			735c3eecdf014edcf519713c79a810df52f07	6.54129E+17	11/19/25 14:33	
1.76356E+12							11/19/25 14:30	
1.76354E+12		6.54048E+17					11/19/25 9:20	
1.76356E+12		6.54048E+17					11/19/25 14:02	
1.76356E+12							11/19/25 13:30	
1.76356E+12		6.54048E+17			8f78b6c1ad66534cb27493 7b16f1e605962adfa04ea8bb4eaece1		11/19/25 14:02	hailieshaw
1.76356E+12	/bin/sh -c /Applications/Splunk/bin/python3.9/Applications/Splunk/etc/apps/search/bin/quarantine_files.py				b46e8d4eac541d79f77000550b4254b47599df8dd8c52cc5b0f37		11/19/25 14:32	root
1.76356E+12	splunk-optimize -d /Applications/Splunk/var/lib/splunk/_internaldb/db/hot_v1_71 -x 3615761920 --log-to--splunkd-log --write-level 3 --tsidx-target-size 1572864000 --msidx-com				735c3eecdf014edcf519713c79a810df52f07c9aaaae2b4133ae6e		11/19/25 14:22	root
1.76356E+12		6.54048E+17					11/19/25 13:44	root
1.76356E+12		6.54109E+17					11/19/25 14:29	
1.76356E+12		6.54129E+17			735c3eecdf014edcf519713c79a810df52f07	6.54129E+17	11/19/25 14:33	
1.76356E+12							11/19/25 14:28	
1.76354E+12		6.54048E+17					11/19/25 8:46	
1.76356E+12		6.54048E+17					11/19/25 14:02	
1.76356E+12		6.54048E+17			7f64c9116e7b3d768093edf187074dd36ce0669789170d45dd5f2		11/19/25 14:02	hailieshaw
1.76356E+12	/bin/sh -c /Applications/Splunk/bin/python3.9/Applications/Splunk/etc/apps/search/bin/quarantine_files.py				20c3a003f0bfd51c799e345be7598aa79cecce936ad7f2543e445		11/19/25 14:32	root
1.76356E+12	ps -o pcpu,rss -p 6003				7323501f54d9771476d1a2ed94d8373ae61de680d12fc8eb133a		11/19/25 14:22	root


Demo: Advanced Event Search




Module 6

Real Time Response





Falcon Real Time Response
Console
Search
Hostname
LAPTOP-J26AI80A
Platform
Windows
Connection status
Connected (Session start: Jul. 29, 2023 14:40:16)
End session
ipconfig Show network configuration information.
kill Kill a process.
ls Display the contents of the specified path.
map Map an SMB (network) share drive.
memdump Dump the memory of a process.
mkdir Create a new directory (access restricted to administrative groups).
mount List mounted filesystem volumes.
mv Move a file or directory. The command will block moving any symlinks or junctions unless the optional “FollowSymLinks” flag is specified.
netstat Display network statistics and active connections.
ps Display process information.
put Put a file from the CrowdStrike cloud onto the machine.
put-and-run Put an executable from the CrowdStrike cloud into a secure directory on the machine and run it.
reg Windows registry manipulation. Subcommands: delete, load, query, set, unload.
restart Restart target system.
rm Remove a file or directory. The command will block removing any symlinks or junctions unless the optional “FollowSymLinks” flag is specified.
run Warning: Consider using "put-and-run" to execute a file from a protected folder. Run an executable.
runscript Run a PowerShell script.
shutdown Shutdown target system.
unmap Unmap an SMB (network) share drive.
update Windows update manipulation. Subcommands: history, install, list, query.
xmemdump Dump the complete or kernel memory of a system.
zip Compress a file or directory into a zip file.
C:\>
Run commands
Edit & run scripts
Enter command
Run command


Difference in the Tabs




Dont forget the Side Menu



Online Status of Host Matters for RTR





Online = powered on and connected to the cloud console

A host can be both online and network contained

Commands to get comfortable with

mkdir
cd
cat
file hash / get-filehash (ps)
kill
help
netstat
ps
put
run
get
runscript
ls

No tab complete, to my knowledge

Get comfortable moving around the CLI, leverage double quotes

Files pulled off will have the password “infected” and will be zipped up


Some limitations for file sizes 2/4GB files max(?) to pull off

Leverage google or chatgpt for how tos with powershell commands or scripts or really anything




A few ways to get to Real Time Response (RTR) in the console


From Event Actions



From an Incident



Host management page, Detections page



Demo: Real Time Response




Module 7

Sandbox & Blocking Actions



Are there other EDRs that offer one?



100 files to submit per month, files that CS quarantines and sends automagically to the SB do not count against the 100



Submit for analysis

Single file | Archive file | URL | File from URL

Archive

malwaresample.zip

Password (optional)

infected

On Show password

Custom tags (optional)

Live interaction New

Only for Windows environments

Interact with sample

Detonation environment

- Windows 11 64 bit
- Windows 10 64 bit
- Windows 7 32 bit
- Windows 7 64 bit
- Android
- Linux Ubuntu 20 64 bit
- MacOS Catalina 10.15


Browser selection


For live interaction with URL only. Options may vary depending on the OS.

- Edge
- Google Chrome
- Internet explorer

Advanced settings About advanced settings

Customize your detonation settings







Counter Adversary Operations | Indicators

Search

Indicators 100 items (282,197,109 total)

Search indicators | Type | Last updated | Confidence | Adversary | Malware family | Threat type | Target | Vulnerability | Published date | Kill chain | Clear all

Type to filter

Clear | Apply

Create indicator graph | Export

		Type	Malware Families	Related Adversaries	Related Rep...	Kill Chain	Published Date	Last Updated
High	81383384e0c17853bfde040f...	SHA1 Hash	Tofsee	--	--	--	Nov. 19, 2025 14:43:29	Nov. 19, 2025 14:43:32
High	dcfb61e3ade3cdd410dfd95a...	MD5 Hash	Xworm	--	--	--	Nov. 19, 2025 14:43:21	Nov. 19, 2025 14:43:24



Seen in your environment

- | 0 | 0

Actors

BITWISE S...

See more about BITWISE SPIDER

Last active	Status	Origin
Jul 2023	Active	Unknown

Intel reports	Target industries	Target countries
-	42	93

Actor type	Motivation
eCrime	Criminal

Community identifiers

LockBit, LockBitSupp, StealBit



Seen in your environment

- | 0 | 0

Actors

PRIMITIVE ...

See more about PRIMITIVE BEAR

Last active	Status	Origin
Jul 2023	Active	Russian Federation

Intel reports	Target industries	Target countries
-	5	5

Actor type	Motivation
Targeted	State-Sponsored


Community identifiers

APT-C-53, SpiceyHoney Campaign, Operation Armagedd...



How to Block in CS

1) IOC Management Page
   a) Can block hashes
   b) Can alert on domains and IP addresses



IOC Management Page, Gotchas

IOC type	Block	Block and dont show a detection	Detect only, dont block	Allow	No action
Hashes*	✓	✓	✓	✓	✓
IPs			✓		✓
Domains			✓		✓


*exe files only…
So basically, you can only detect for IPs and Domains from here




So what if we want to block IPs and Domains

1) HBFW option for rule creations = IPS
2) Custom IOAs = IPs or Domain names







*always test your regex and rules

A note on Custom IOAs



	Windows	Mac	Linux
Domains	✓		
Process Creation	✓	✓	✓
File Creation	✓	✓	✓
Network Connection	✓	✓	

Demo: Sandbox & Blocking




Module 8

Whitelisting / Exclusions



4 Types of Exclusions in CS




Machine Learning and IOA: Made that option from a detection

Sensor Visibility: Complete exclusion from the sensor, won't even collect logs, everything in the path you specify will be allowed to ru. You manually put in the path to whitelist here.

Example: **ML based Exclusion**


Comes from CS machine learning repository of known malware, hashes, files, etc.



IOA NAME: Machine Learning Identified High Confidence Malicious File

IOA DESCRIPTION: A file written to the file system meets the on-sensor machine learning high confidence threshold for malicious files. Detection is based on a high degree of entropy, packing, anti-malware evasion, or other similarity to known malware.

DETECT TIME: Jul. 29, 2023 10:35:45





The buttons are dependent on the type of detection

Example: **IOA Based Exclusion**
-Detection comes from an IOA

IOA NAME: SuspiciousFileWritten


IOA DESCRIPTION: A process has written a suspicious file to disk. Adversaries may write a malicious file to a commonly trusted directory, use a benign name, or a mismatched file extension. This is done for the sake of evading defenses and observation. Check the activity and surrounding events are expected in your environment.





Sensor Visibility Exclusions


*complete visibility loss



*Glob pattern syntax


Example:
C:\Program Files\McAfee\

Program Files\McAfee**
OR
**\McAfee.exe






Some Side Notes



- Can always WL a hash in IOC Management
- Can always allow an IP from the HBFW
- Overwatch detections cannot be excluded
- Can't allow or WL from Custom IOAs



Demo: Exclusions



Module 9

Putting it All Together



Create your Detection Template

- Always best to have a clean, formal, professional alert template to work off of
  - Highlight important information at the top
  - Always report in UTC
  - Use your own words for summarizing what happened at the top of your report
- Use it as a repeatable process to follow
  - This will lower your triage time as you get more experience
- Does not have to be fancy, sublime text or notepad++ will do


If you need a template, download a free one from our store!
Use it as a starting point to customize it later



Bookmark all your favorite OSINT Tools



Demo: Lets Triage!



Module 10

Where to Go Next



My opinion doesn't matter…

- Go for an EDR certification
- SANS GCFE or GCFA for their workstudy program
- Lean Splunk fundamentals with our two new courses

SIEM & EDR go hand in hand for resumes

- IBM Qradar, Splunk, CS Next-Gen SIEM, S1, Carbon Black, Microsoft's EDR

OSINT Tools go hand in hand for SOC Positions

- Wireshark
- A Sandbox of choice
- Email header analysis
- Splunk
- AnyRun
- Velociraptor

