```php
<?php

return [

    /*
    |--------------------------------------------------------------------------
    | Messenger app name
    |--------------------------------------------------------------------------
    |
    | This value is the name of the app which is used in the views or elsewhere
    | in this app.
    |
    */

    'name' => env('CHATIFY_NAME', 'Chatify Messenger'),

    /*
    |--------------------------------------------------------------------------
    | Package path
    |--------------------------------------------------------------------------
    |
    | This value is the path of the package or in other meaning, it is the prefix
    | of all the registered routes in this package.
    |
    | e.g. : app.test/chatify
    */

    'path' => env('CHATIFY_PATH', 'chatify'),

    /*
    |--------------------------------------------------------------------------
    | Package's web routes middleware
    |--------------------------------------------------------------------------
    |
    | This value is the middleware of all routes registered in this package
    | which is by default : auth
    |
    */

    'middleware' => env('CHATIFY_MIDDLEWARE', 'auth'),

    /*
    |--------------------------------------------------------------------------
    | Pusher API credentials
    |--------------------------------------------------------------------------
    |
    | This array includes all the credentials that required to use pusher API
```

```php
48      | with Chatty package, which is used to broadcast events over websockets
   to
49      | create a real-time features.
50      |
51      */
52      'pusher' => [
53          'key' => env('PUSHER_APP_KEY'),
54          'secret' => env('PUSHER_APP_SECRET'),
55          'app_id' => env('PUSHER_APP_ID'),
56          'options' => [
57              'cluster' => env('PUSHER_APP_CLUSTER'),
58              'encrypted' => false,
59          ],
60      ],
61
62      /*
63      |----------------------------------------------------------------------
   --
64      | User Avatar
65      |----------------------------------------------------------------------
   --
66      |
67      | This is the user's avatar setting that includes :
68      | [folder]  which is the default folder name to upload and get
69      |           user's avatar from.
70      | [default] which is the default avatar file name for users stored
71      |           in database.
72      |
73      */
74      'user_avatar' => [
75          'folder' => 'users-avatar',
76          'default' => 'avatar.png',
77      ],
78
79      /*
80      |----------------------------------------------------------------------
   --
81      | Attachments By Default
82      |----------------------------------------------------------------------
   --
83      |
84      | This array contains the important default values that used in this
   package.
85      |
86      | The first value in this array is the default folder name in the storage
87      | which is all the attachments will be stored in.
88      | This is also going to be used in attachments urls in the views.
89      |
90      */
91      'attachments' => [
92          'folder' => 'attachments',
93          // Below is the route name to download attachments.
94          'route' => 'attachments.download',
95      ],
96
97
98      /*
99      |----------------------------------------------------------------------
   --
```

```
      | Route's controllers namespace
      |----------------------------------------------------------------
--
      |
      | You may need to change the namespace of the route's controllers of
      | this package after publishing the 'controllers' asset, from the
      | default one to your App's controllers namespace.
      |
      | By default: Chatify\Http\Controllers
      |
      */
     'namespace' => env('CHATIFY_ROUTES_NAMESPACE',
  'Chatify\Http\Controllers'),
];
```