

University of Idaho
College of Engineering

CS 466/566
PLC PROGRAMMING AND AUTOMATION
FALL 2024

LECTURE 14 – THE INTERNET

INSTRUCTOR: DR JOHN SHOVIC
LECTURER: JACOB FRIEDBERG

COMPUTER NETWORKING

OVERVIEW

- History of the Internet
- What is the Internet – a simplified version
- The Network Stack – also simplified
- Important protocols
- PLC Protocols
  - Modbus
  - EtherCAT
  - Ethernet/IP

THE INTERNET

- It’s ubiquitous nowadays
  - High speed wireless connections – 3G, 4G, 5G, WiFi 4, 5, 6, 7
  - Optic fiber
  - Cable
  - ADSL
  - Satellites – Starlink
- Used for entertainment
  - Social media, video streaming, music streaming, gaming, news
- Accessible from almost any device
  - Desktop, laptop, phone, gaming console, microcontrollers – Internet of Things
- Plays a big part of Industry 4.0

HISTORY OF THE INTERNET

ARPANET - 1968

- Established by Advanced Research Projects Agency and US Department of Defense
- Came about as part of the Cold War
- Enable access to remote computers
- Utilized Packet Switching
  - Circuit switching – dedicated electronic line
  - Think old telephone systems
  - Packet - smaller piece of a large amount of data
- Made use of leased communication lines
  - Telephone, optic fiber
- One of first implementations of TCP/IP (Transmission Control Protocol / Internet Protocol)




[1]

HISTORY OF THE INTERNET

ARPANET - 1968

- Consisted of 4 nodes initially
  - UCLA
  - UCSB
  - University of Utah School of Computing
  - Stanford Research Institute (SRI)
- East coast connected with Raytheon BBN in Cambridge, MA – 1970
- More nodes added later



[2]

HISTORY OF THE INTERNET


ARPANET - 1968


- First link established between UCLA and SRI 22:30, October 29, 1969
- Group of grad students and professor from UCLA connected to a computer at Stanford to send data
  - Wanted to type the word “login” and see if appeared on the monitor at the Stanford location
- "We set up a telephone connection between us and the guys at SRI…," Kleinrock … said in an interview: "We typed the L and we asked on the phone,
  - "Do you see the L?"
    "Yes, we see the L," came the response.
    "We typed the O, and we asked, "Do you see the O."
    "Yes, we see the O."
    "Then we typed the G, and the system crashed"…
  - Yet a revolution had begun"… [3]

HISTORY OF INTERNET

NSFNET – 1985-1988

- National Science Foundation Network
- Advanced research and education purposes – Government and Universities only
  - NASA, DoD, DCA, DoE, NSF
  - Princeton, Cornell, Carnegie Mellon, Pittsburgh, UIUC, UCSD
- Connected with 6x 56 Kb/s nodes







HISTORY OF INTERNET

NSFNET – 1988-1992

- Backbone upgraded to 1.5Mb/s - 1991
- 13 nodes
- Upgraded again to 45 Mb/s with 16 nodes - 1992





HISTORY OF INTERNET

INTERNET SERVICE PROVIDER (ISP) - 1989

- Originally NSFNET was for non-commercial purposes
- Companies formed to provide public access to NSFNET
- Connected via dial-up connection
  - Made use of telephone line
  - Couldn’t use the phone while connected
- Superseded with the modern internet in 1995



HISTORY OF INTERNET

WORLD WIDE WEB 1989 - 2004

- Commonly called “the internet”
- Information hosted on a web server
- Accessed via a web browser
  - Netscape Navigator, Internet Explorer, Mosaic
- Content (Web pages) were indexed by search engines
  - Yahoo, Lycos, Alta Vista, Ask Jeeves, Google
- Microsoft sued by the US government for the web browser monopoly bundling IE with Windows 95
  - Settled with MS sharing its Application Programming Interfaces (APIs) with third parties
  - Successfully killed off Netscape – source code used to start Mozilla Firefox

HISTORY OF INTERNET

DOTCOM BUBBLE 1996 - 2001

- X on the internet, Y online, Z.com
- Didn’t matter what it was, if it’s on the internet, it’s worth millions
- Most companies had no actual product or service backing it up
- Caused a major spike and then crash in the NASDAQ Composite index
- Survivors:
  - Amazon
  - Ebay
  - Google
  - Yahoo



HISTORY OF INTERNET

WI-FI 1997 - PRESENT

- Introduced personal wireless devices to the internet
  - Laptops, printers, desktops, speakers, TVs, consoles, fridges, toasters
- Greatly increased convenience
- Always a shared medium unlike a wire
  - Multiple devices on the same frequency causes collisions and greatly reduced throughput
- Signal drops off significantly indoors – brick, concrete, walls
- Operates in 2.4 GHz (120mm) and 5 GHz (60mm) bands

HISTORY OF INTERNET

WEB 2.0 2004 - PRESENT

- Web pages prior used to be mainly static and only changed when the webmaster updated it
  - Dynamically updated pages
  - Based on your web history – profiles, shadow profiles, digital fingerprints
- Big data collection on everything
- Interactive websites
  - Forums
  - Games
  - Video
  - Blogs
  - Image sharing
  - Social networks

HISTORY OF INTERNET

WEB 3.0 2014 - PRESENT

- Decentralization
  - Blockchain – cryptocurrencies and mining
    - The reason why graphics cards cost 3-5x MSRP
  - Non-Fungible Tokens (NFTs) – AKA a scam
- Debate whether it is a real thing yet

WHAT IS THE INTERNET?


PHYSICALLY

- A whole bunch of computers connected and able to communicate with one another
  - Peer-to-peer
  - Client-server
- Lots of hardware in between to make it happen
  - Network card – Ethernet/WiFi
  - Switches
  - Routers
  - Modems
  - Exchanges



WHAT IS THE INTERNET?


A LOT OF CABLES



WHAT IS THE INTERNET?


SUBMARINE CABLE

- 1) Polyethylene insulator, 2) Copper sheathing, 3) Steel wires, 4) Optical fibers in silicon gel



WHAT IS THE INTERNET?

END TO END SUBMARINE CABLE CONNECTION



WHAT IS THE INTERNET?


A LOT OF CABLES



WHAT IS THE INTERNET?

CONNECT TO GOOGLE.COM FROM HOME

- Open web browser, type google.com into the address bar
- Your laptop -> router via WiFi -> modem via network cable (can be same device as router) -> ISP (cable, ADSL, satellite, dial-up ☹ if you're stuck on this) -> Bigger routers and switches (the "cloud") -> Google's web server
- You get a web page with Google search



WHAT IS THE INTERNET?

ABSTRACTION EVERYWHERE

- The cloud is an abstraction
- Your ISP is an abstraction
- The example of going to google.com has multiple levels of abstraction
- Abstraction is hiding the lower-level details and presenting a simpler interface

NETWORK PROTOCOL STACK

OSI MODEL


Layer Number	Layer	Protocol Data Unit	Function
7	Application	Data	High level protocols - HTTP
6	Presentation	Data	Data translation
5	Session	Data	Communication sessions
4	Transport	Segment/Datagram	Transmission of data between points on network
3	Network	Packet	Addressing, routing, traffic control
2	Data Link	Frame	Transmission of frames between physical nodes
1	Physical	Bit	Transmission of bits over physical media

User



Application	User enters https://somesite.com
Presentation	Application data is decoded to machine language
Session	Start a TLS session over TCP
Transport	Destination port is TCP/443 The system network stack assigns a random ephemeral port as the source port
Network	The packet is stamped with the destination address of the server
Data Link	The destination IP address is not in the LAN. The packet is stamped with the MAC of the default gateway.
Physical	Transmit electrical pulses over the wire

Browser makes a request to the underlying network stack of the computer



Layer 2 Switch

Switch receives packet. Checks the CAM table and sees the destination MAC is on the trunk. Forward packet to gateway.

Router receives packet and sees IP address is foreign. Consults its routing table for next hop. Router changes the source IP to its own IP and keeps a record of the packet in its own cache, in order to redirect return packets to the requester based on source TCP or UDP port.



Router

The original packet is further encapsulated in routing protocols until it reaches its destination. All routers in between repeat this process until the packet reaches its destination



The application processes the user request and prepares a response to go back out over the wire	**Application**
The server application re-encodes the bits to content the application understands	**Presentation**
Initialize a TLS session with the client All data will be encrypted	**Session**
The TCP/IP stack receives a **SYN** packet on TCP/443	**Transport**
The destination IP address is stamped with the server's address	**Network**
Packet comes in on the WAN interface from the ISP. Destination MAC is correct.	**Data Link**
Server receives the electrical pulses -- or bits	**Physical**

Some Site Server



48 port Layer 2 Switch



Switch receives packet. Checks the CAM table and sees the destination MAC is on one of the physical ports. Forward the packet to the server.


Router receives packet and sees the destination IP is internal. Stamps the packet with the MAC address of one of the YouTube servers.



Router

NETWORK PROTOCOL STACK


OSI MODEL



How to Read an OSI Model Chart (cbtnuggets.com)

NETWORK PROTOCOL STACK

OSI MODEL



- GIF - Imgur

APPLICATION LAYER

LAYER 7 - ALL THE USER END APPLICATIONS

- Hypertext Transfer Protocol (HTTP) and Secure (HTTPS) – web pages
- Simple Mail Transfer Protocol (SMTP), Post Office Protocol (POP), Internet Message Access Protocol (IMAP) – email
- Network Time Protocol (NTP)
- File Transfer Protocol (FTP)
- Secure Shell (SSH)
- Telnet
- Domain Name System (DNS)
- Modbus, EtherCAT, Ethernet/IP

PRESENTATION LAYER

LAYER 6 - TRANSLATION AND FORMATTING OF DATA

- Character encoding
  - ASCII
  - Unicode
- Encryption and decryption of data – can be done at other layers too
- Serialization
  - JSON
  - XML
- Can be considered part of the application layer

SESSION LAYER

LAYER 5 - MAINTAINING COMMUNICATION

- Combining multiple data streams
- Synchronization
  - Video and audio streams for TV
  - ASCII
- Checkpointing
  - Saving application’s state for fault tolerance
- Can be considered part of the transport layer

TRANSPORT LAYER


LAYER 4 - TRANSMISSION CONTROL PROTOCOL (TCP)

- A 1GB file is too big to send in one piece
  - Your home internet connection may be “up to” 1Gbps (bits not Bytes – 125 MBps)
- TCP is the main protocol used at this layer
  - Establishes connections – 3-way handshake, connection-oriented
  - Reliable – uses an acknowledgement to confirm receipt of segments and sequencing to make sure segments are reassembled in the correct order and a checksum to ensure data isn’t corrupted
  - Flow control – dynamically chance the number of segments sent based on network conditions
  - Multiplexing – handle multiple separate data streams
- Uses port numbers
  - 80 for HTTP, used 8080 for the OpenPLC runtime

TRANSPORT LAYER

THREE-WAY HANDSHAKE

- SYN – Synchronize, client sends this to a server to establish a connection, uses random sequence number
- SYN-ACK – The server responds acknowledging the request, uses random sequence number
- ACK – The client sends an Acknowledgement to confirm the connection is now active



TRANSPORT LAYER

TCP SEGMENT – MINIMUM 26 BYTES IN SIZE

Bit Offset	0-3	4-7	8-15	16-31
0	Source Port			Destination Port
32	Sequence Number			
64	Acknowledgement Number			
96	Data Offset	Reserved	Flags	Window
128	Checksum			Urgent Pointer (Can be ignored)
160	Options (Optional)			
192	Data (6-536 bytes)			

TRANSPORT LAYER

LAYER 4 - USER DATAGRAM PROTOCOL (UDP)

- Doesn’t care about checking data
- Doesn’t set up a connection first - connectionless
- Send the data on its way without warning, if it gets there ok, if it doesn’t get there, ok
- Doesn’t care if data arrives in the wrong order
- Used when speed is more important than reliability
  - Live video streaming – it’s ok if a frame gets dropped here or there
  - Voice Over IP (VOIP)
  - Multiplayer games
- Can broadcast – send to everyone on a network
- Can multicast – send to multiple devices on a network

TRANSPORT LAYER

UDP DATAGRAM

Bit Offset	0-15	16-31
0	Source Port	Destination Port
32	UDP Length	Checksum
64	Data (8-548 bytes)	

NETWORK LAYER

LAYER 3 – NETWORK ADDRESSING

- Internet Protocol (IP) is the main layer 3 protocol now
  - IPv4 (32-bit) and IPv6 (128-bit)
- IPX, Appletalk are legacy
- Concerned with sending data from one device to another
- IP addresses are a way to identify devices publicly on the internet
  - Google.com – 142.251.33.110 – one of many
  - Uidaho.edu – 129.101.119.250 – type this in a web browser
- Routers are used at this layer to allow communication between different networks

NETWORK LAYER

DIFFERENT NETWORKS

- IPv4 addresses were divided into 5 classes – A, B, C, D and E
- They are a 32-bit stream divided into 4 octets and interpreted as unsigned 8-bit integer
  - 129.101.119.250
  - 32-bit unsigned would work too but good luck remembering 2,170,910,714
- First bit = 0 -> A -> 0.0.0.0
- First bit = 1 -> B -> 128.x.x.x
- First 2 bits = 1 ->C -> 192.x.x.x
- First 3 bits = 1 -> D -> 224.x.x.x
- First 4 bits = 1 -> E -> 240.x.x.x

NETWORK LAYER

IPV4 CLASSES

Class	Leading bits	Network Number Size	Rest of field	# Networks	Addrs per network	Total Addr	Start Addr	End Addr
A	0	8	24	128	16,777,216	2 Bill	0.0.0.0	127.255.255.255
B	10	16	16	16,384	65,536	1 Bill	128.0.0.0	191.255.255.255
C	110	24	8	2,097,152	256	0.5 Bill	192.0.0.0	223.255.255.255
D (Multicast)	1110	Undefined	Undefined	Undefined	Undefined	268 Mill	224.0.0.0	239.255.255.255
E (Reserved)	1111	Undefined	Undefined	Undefined	Undefined	268 Mill	240.0.0.0	255.255.255.255

NETWORK LAYER

SALE OF IP ADDRESSES

- Companies were able to buy a block of IP addresses in the 1990's from any of class A, B, C
- A class A network has 16 million addresses in it
  - Way too many for any single organization
  - Take a few addresses needed, then resell the unused ones to other companies
- All these addresses are publicly accessible
  - Need a way to prevent any device from accessing any network
  - As the number of devices connected increased, rapidly ran out of addresses
  - Only 3.5 billion addresses available on IPv4

NETWORK LAYER

PRIVATE NETWORKS

- A block of addresses in each class was designated as a private network
- Cannot access a device in a private network from outside without the device first establishing a connection – TCP handshake
  - Also why scammers, hackers etc. so desperately want you to download something or click a link
- These addresses can be reused over and over by any organization
- Can have millions of private IP addresses behind a single public IP address
- Network Address Translation (NAT) is used to handle the private to public IP conversion

NETWORK LAYER

SUBNETTING

- Class A – 16 million addresses per network
- Class B – 65,536 addresses per network
- Class C – 256 addresses per network
- Way too many per network
- A subnet mask divides up the network into smaller pieces – powers of 2
  - 2 devices are considered in the same network if their subnet mask matches along with their IP addresses being in the same network range
- Class A has a default subnet mask of 255.0.0.0
- Class B 255.255.0.0
- Class C 255.255.255.0

NETWORK LAYER

SUBNETTING

- Don’t have to use the default subnet masks for public IP addresses
  - Class A can use 255.255.255.0 for 256 addresses per network
  - Or 255.255.255.128 for 128 etc.
- IP address and its subnet mask can be written as 192.168.1.0/25 – 25 represents 25 1’s in the mask
  - 11111111 11111111 11111111 10000000 -> 255.255.255.128
- Two devices are determined to be on the same network by ANDing the IP address and the subnet mask
- The result is the network address, if they are equal – comparator, they are on the same network
- Example
  - Are 192.168.1.2 and 192.168.1.129 on the same network with a subnet mask of 255.255.255.128?

NETWORK LAYER

SUBNETTING

- Are 192.168.1.2 and 192.168.1.129 on the same network with a subnet mask 255.255.255.128?

Add	Octet 1	Octet 2	Octet 3	Octet 4
IP Address	11000000	10101000	00000001	00000010
Subnet Mask	11111111	11111111	11111111	10000000
AND	11000000	10101000	00000001	00000000

Add	Octet 1	Octet 2	Octet 3	Octet 4
IP Address	11000000	10101000	00000001	10000001
Subnet Mask	11111111	11111111	11111111	10000000
AND	11000000	10101000	00000001	10000000

- The results don't match therefore they are not in the same network

NETWORK LAYER

PRIVATE NETWORKS

- The mask bits and host bits for each network are defaults and can be changed to any size
- The number of IP addresses available to devices is always 2 less than the number of hosts
  - The first address is the network address
  - The last one is the broadcast address – send a message to every device
- A subnet with 255.255.255.0 has 2^8 -2 = 254 possible hosts

Start Address	End Address	Mask bits	Host bits	Number of Addresses
10.0.0.0	10.255.255.255	8	24	16,777,216
172.16.0.0	172.31.255.255	12	20	1,048,576
192.168.0.0	192.168.255.255	16	16	65,536

NETWORK LAYER

ANOTHER SPECIAL ADDRESS

- Your computer will have an IP address that you can lookup with ipconfig, ifconfig, going into networking options
- If you're not connected to a network, your network card still has an address
- 127.0.0.1 is the local loopback address
- We used this or localhost for OpenPLC and Factory IO communication
  - Your IP address changes between home and the university and would have caused issues
  - The "Home" address of your machine
- Can use it to determine if networking is working on your machine

NETWORK LAYER

CONNECTING TO SOMETHING OUTSIDE THE NETWORK

- Devices on the same subnet are part of a local network
- Devices outside the network are not directly accessible
- A device is needed to provide access
- This is the Gateway – usually a router
- The gateway connects to other networks and is hierarchical
  - Your local gateway may be a private IP address, the gateway itself then has a gateway which is another private address, that gateway then has a connection to a public IP

NETWORK LAYER

ROUTERS

- Routers provide connectivity between networks
- They maintain a routing table of known networks and where to send its packets to
  - This can be a specific interface it has connected via an Ethernet cable
  - Usually, a default route if it doesn't know where to send a packet – the gateway
- Multiple protocols exist to prevent routing loops
  - RIP, EIGRP, BGP, OSPF
- Your typical consumer router has WiFi and Ethernet connectivity
- Often look like spaceships nowadays



NETWORK LAYER

IP PACKETS – 20 BYTES + DATA


- An IP packet contains the data – the TCP segment/UDP datagram
- It encapsulates the segment with IP headers
- Parts we care about most are source and destination IP address

Bit	0-3	4-7	8-13	14-15	16-18	19-23	24-31
0	Version	IHL	DSCP	ECN	Total Length		
32	Identification				Flags	Fragment Offset	
64	Time To Live		Protocol		Header Checksum		
96	Source IP Address						
128	Destination IP Address						
160	Options (Optional, based on IHL)						
160-480	Data (TCP Segment/UDP Datagram)						

NETWORK LAYER

IPV6

- IPv6 is the proposed solution to running out of IPv4 addresses
- Uses 128 bits instead of 32, 2^128 = 3.4x10^38 addresses
- Officially released in 2012 but not backwards compatible with IPv4 directly
- About 40% of Google accesses are IPv6 today



DATA LINK LAYER

TRANSFERS DATA BETWEEN NETWORKS ACROSS THE PHYSICAL LAYER

- An IP address isn't specific enough to uniquely identify a device
- Media Access Control Address (MAC Address) is used to do this, 48-bit identifier
  - Expressed in hexadecimal e.g. 00:5f:3a:28:d6:12
  - The first 3 octets usually refers to a specific vendor/manufacturer of network cards
  - Can use this to identify potential vulnerabilities based on a device's MAC address
- Meant to uniquely identify a device but if two devices have the same MAC address on the same network = bad things happen
  - Mainly stuff just doesn't work
  - Very annoying if this happens

DATA LINK LAYER

ETHERNET – IEEE 802.3

- That cable you plug into your laptop or desktop
- Can provide power as well (PoE 802.3af)
- Coaxial cable, twisted pair, fiber optic
- Speeds 10 Mbps, 100 Mpbs (Fast Ethernet), 1 Gbps (Gigabit Ethernet), 2.5 Gbps, 10 Gbps, 100, 400



DATA LINK LAYER

WIFI – 802.11

- The way you connect to a network without a wire
- Uses 2.4-2.5 GHz and 5-6 GHz spectrums, also 6 GHz+
- Transmission distance is inversely proportional to the frequency
  - Proportional to wavelength – longer wavelength, further distance
- Signal attenuated by solids – brick, concrete, drywall
- Half duplex – you cannot send and receive at the same time
  - The medium used is air which is shared among all devices
  - Protocols needed for collision detection (CD) and avoidance (CA)
- Lots of wireless devices in an area greatly slows things down for everyone
  - Put it on wired if you can

DATA LINK LAYER

FRAMES

- The IP packet is encapsulated with frame headers
- The destination MAC is the MAC address of the adjacent device – e.g. the gateway

Bit Offset	0-7	8-15	16-23	24-31
0	Preamble (7 bytes)			
32	Preamble			SFD
64	MAC Destination (6 bytes)			
96	MAC Destination		MAC Source (6 bytes)	
128	MAC Source			
160	Ethernet Type (2 bytes)		Data (46-1500 bytes)	
206-1660	CRC (4 bytes)			
210-1664	Interpacket Gap (12 bytes)			

DATA LINK LAYER

NETWORK SWITCH

- Allows devices to communicate over the same network
- Maintains a table of MAC addresses and the corresponding ports
- If a device isn’t in the table (outside the network), it sends it to the router (if one is connected)
- Unmanaged (dumb) and managed (smart)
  - Unmanaged are just plug and play
  - Managed has a lot of extra features, mainly QoS, security and segregation of devices
- Unicast – sends data only to the intended recipient



DATA LINK LAYER

NETWORK HUB

- Same as a switch except it broadcasts
  - Sends data out every port
  - Only the intended recipient will keep it, the rest will drop it since it wasn't for them
- This leads to greatly increased network traffic and reduced speeds
- A security risk also since anyone can read any frame sent over the network

PHYSICAL LAYER

THE PROTOCOLS FOR SENDING AND RECEIVING BITS

- Serial, Parallel, USB, SPI, I2C, CANbus, LoRa, PCIE, Ethernet Physical Layer
- Bit rates
- Frequency
- Point-to-point, multi-point, point-to-multipoint
- Network topology
- Full duplex, half duplex, simplex
- Auto-negotiation
- Modulation
- Bit synchronization
- Electrical and Mechanical specifications

NETWORK TYPES


GEOGRAPHICAL SPAN OF THE NETWORK

- Interplanetary Network – Earth-Moon, Earth-Mars – rovers, Curiosity, Opportunity, Spirit, Perseverance
- Wide Area Network (WAN) – the internet is a WAN
- Metropolitan Area Network (MAN) – cities, neighboring cities, metro areas
- Campus Area Network (CAN) – multiple LANs, Uofl probably uses this in Moscow
- Local Area Network (LAN) – within a building, home
- Personal Area Network (PAN) - short distances (1-10’s of meters), Bluetooth, wireless USB
- Body Area Network (BAN) – medical devices
- Near Field Communication (NFC) – RFID chips, credit and debit cards

NETWORK TOPOLOGIES

POINT TO POINT

- Simplest type of network
- Two devices directly connected to each other via a network cable
- Can be two PC’s, switches, or routers using the cloud
- Very simple
- Single point of failure
- Factory IO and OpenPLC was implemented as a point to point network, the PCs just happened to be the same device




[2]

NETWORK TOPOLOGIES

STAR

- Multiple devices connect to a single point for communication – network switch, router, hub
- Devices communicate with one another via this device
- Usually connected to another device to access devices out of the network
- Has a single point of failure - switch
- If one of the PC-Switch connections goes down, the rest of the network is fine




[3]

NETWORK TOPOLOGIES

BUS

- All devices are connected to a common line
- Simple, less cable
- A message sent from a device gets sent to all devices
  - Like a hub
- Excess traffic slows transfer rate down
- Single fault can bring the network down




[4]

NETWORK TOPOLOGIES

MESH

- Every device is connected to every other device
- A single failure doesn't bring the network down – redundancy, fault tolerance
- Can load balance so a single device isn't overwhelmed
- Uses a lot more cables – Connections = n*(n-1)/2
  - 6 devices = 15 connections, 10 devices = 45, 20 devices = 190
- Requires more configuration to prevent loops




[5]

NETWORK TOPOLOGIES

RING

- Devices are connected to devices adjacent to it
- Data moves in one direction
- When data reaches a device that isn't the intended recipient, the device repeats the signal
- If any connection goes down, the entire network goes down




[6]

NETWORK TOPOLOGIES

HYBRID

- All the previous network topologies offer different advantages and disadvantages and have different purposes
- A network needs to be designed to take all these into account along with bandwidth requirements, reliability, cost and risk



[7]

IMPORTANT PROTOCOLS


DOMAIN NAME SYSTEM (DNS) – PORT 53 (TCP AND UDP)

- We've seen two ways to access a resource on the web
  - Typing in a name – URL
  - Typing in an IP address
- The name is much easier to remember
- DNS provides that translation between the URL and IP address
- A hierarchical tree structure exists where a home network/office maintains a DNS server
  - If it doesn't have the URL-IP mapping, it asks the DNS server above whether it knows what IP address belongs to a URL
- 13 Root Servers exist worldwide which maintain the DNS zones - .com, .org, .edu, .net

IMPORTANT PROTOCOLS

DOMAIN NAME SYSTEM (DNS) – PORT 53 (TCP AND UDP)

- Can use nslookup in Windows command line to find the ip address of a URL



IMPORTANT PROTOCOLS


DYNAMIC HOST CONTROL PROTOCOL (DHCP) - PORT 67, 68 (UDP)

- When you connect to your home network, uidaho network on AirVandalGold, there is a service running on the router, access point, or a server that provides you with the following:
  - IP address
  - Subnet mask
  - Gateway
  - DNS server
- If the DHCP server is down, you can set your IP address yourself in network settings
- Otherwise, you will default to an IP address in the 169.254.0.0/16 range – the “I don’t have an IP address” IP address
- If the Mini Factory isn’t connected to the network, you will need to set your IP address statically to avoid this problem

IMPORTANT PROTOCOLS

INTERNET CONTROL MESSAGE PROTOCOL (ICMP)


- Used by devices such as routers to send error messages and operational information
- Operates at the Network Layer – 3
- Ping
  - Sends an echo request and listens for an echo reply
  - Used as a basic troubleshooting step to see if a device is on a network



IMPORTANT PROTOCOLS

INTERNET CONTROL MESSAGE PROTOCOL (ICMP)

- Traceroute
  - Sends packets with increasing Time To Live (TTL) lengths to determine the route a packet takes
  - Can map out geographically where a packet goes to a destination
  - May not take the shortest path




IMPORTANT PROTOCOLS

URL STRUCTURE

- When you go to a website and start clicking on links, you'll notice that the address bar changes and can get longer and longer
- https://www.uidaho.edu/engr/departments/me/degrees/bs
  - https: - protocol, others include ftp, mailto, http, file
  - // - authority
  - www.uidaho.edu – host
  - /engr/… - path name of web page or folder
- Https://localhost:8080
  - Localhost – host, 127.0.0.1
  - :8080 – port number

PUTTING IT ALL TOGETHER

GOING TO GOOGLE.COM



2 DNS Query Segmented
Source Port xxxxx
Dest Port 53

3 Segment -> Packet
Source IP 129.101.98.200
Dest IP 129.101.119.223

4 Packet -> Frame
Source MAC F0-57-A5-D2-08-13
Dest MAC A1-63-DF-12-5C-64

7 Frame received, header removed
8 Looks at Packet and not for the router
9 Looks at routing table and sees interface that it should send packet out
10 Packet -> Frame
Source MAC A1-63-DF-12-5C-64
Dest MAC 00-03-A4-42-DD-98

12 Frame received, header removed
13 Looks at Packet, is for the DNS server
14 Looks at segment, sees it is for the DNS service
15 Looks at data and sees request for IP address corresponding to "www.google.com"
16 Creates Response with www.google.com = 142.251.215.238


PUTTING IT ALL TOGETHER

GOING TO GOOGLE.COM

27 Frame received, header removed
28 Looks at Packet, is for the PC
29 Looks at segment, sees it is a DNS response
29 Looks at data and sees that the IP address for www.google.com is 142.251.215.238

21 Frame received, header removed
22 Looks at Packet and not for the router
23 Looks at routing table and sees interface that it should send packet out
24 Packet -> Frame
Source MAC A1-63-DF-12-5C-64
Dest MAC F0-57-A5-D2-08-13

17 DNS Response Segmented
Source Port 53
Dest Port xxxx (same as source port from request)
18 Segment -> Packet
Source IP 129.101.119.223
Dest IP 129.101.98.200
19 Packet -> Frame
Source MAC 00-03-A4-42-DD-98
Dest MAC A1-63-DF-12-5C-64



PUTTING IT ALL TOGETHER

GOING TO GOOGLE.COM

- Your computer then initiates a 3-way handshake with the server at 142.251.215.238
- Once complete, the https request is made at layer 7 and layer 6
- This data goes down to layer 4 and a TCP segment is made, a random source port is generated (0-65535), destination port 443 is added, along with sequence numbers
- The segment then goes down to layer 3 and your computer's IP address is added to the source address, 172.217.14.206 is added as the destination address
- The packet then goes to layer 2 and your computer's network card's MAC address is added to the source
- The frame is then sent via ethernet cable/wifi as a bitstream to the gateway

PUTTING IT ALL TOGETHER

GOING TO GOOGLE.COM

- Each router along the way receives the frame and de-encapsulates it to look at the destination IP address of the packet
- When it sees that the IP address is not for the router, it looks at its routing table to determine where to send it next
- The packet is then encapsulated with frame headers with the source and destination MAC addresses added
- This continues until the server at 142.251.215.238 receives the packet and sees it is an https request, it then sends part of the HTML data back to your computer using the same method
- Your computer receives a piece of the web page then continues to request more of it until it is complete. When finished, the TCP connection is terminated

BACK TO PLCS

MODBUS

- Protocol developed by Schneider Electric in 1979 for its PLCs
- Is now a de facto standard communication protocol for industrial electronics
- Multiple versions exist
  - RTU – remote terminal unit – serial communication
  - ASCII – another serial
  - TCP/IP – used for TCP/IP networks, port 502, we will be using this
  - UDP

ETHERCAT

ETHERNET CONTROL AUTOMATION TECHNOLOGY

- Created by Beckhoff Automation in 2003
- IEC 61158
- Used for applications with short cycle times <100µs, Frequency = 1/T -> f >10,000Hz
- Low jitter – variance in the cycle period - <1 µs -> 99-101 µs -> f = 9900-10101Hz
- Modifies layer 2 – Data Link – layers in the network stack can be changed and not affect the operation of the rest of the layers******** (After lots and lots of testing)
- Layers 3, 4, 5 and 6 are also removed – greatly increases speed
- Frames are modified with a “telegram” that doesn’t get de-encapulated, read and processed at each device


ETHERCAT

ETHERNET CONTROL AUTOMATION TECHNOLOGY

- One Master sends a telegram out – up to 60 KB in size
- The telegram is addressed to multiple devices on the network and passes through each one (ring network)
- As the telegram is received by a Slave device, it processes the data in the frame addressed to it (MAC address), modifies data then passes onto the next device
  - This is done on the fly as the frame is received
  - The frame reaches its way back to the master device for processing
- A single frame can be used for multiple devices
  - In typical TCP/IP such as Modbus, a separate frame, packet, segment must be created for each device
- All devices must have an EtherCAT controller - $100's to $1,000's each

ETHERCAT

ETHERNET CONTROL AUTOMATION TECHNOLOGY



[7]

REFERENCES

- [1] Computer Networking Notes, Network Topologies Explain with Examples, 2022, https://www.computernetworkingnotes.com/networking-tutorials/network-topologies-explained-with-examples.html, Accessed 10/3/22
- [2] Computer Networking Notes, Network Topologies Explain with Examples, 2022, https://www.computernetworkingnotes.com/networking-tutorials/network-topologies-explained-with-examples.html, Accessed 10/3/22
- [3] Computer Networking Notes, Network Topologies Explain with Examples, 2022, https://www.computernetworkingnotes.com/networking-tutorials/network-topologies-explained-with-examples.html, Accessed 10/3/22
- [4] Computer Networking Notes, Network Topologies Explain with Examples, 2022, https://www.computernetworkingnotes.com/networking-tutorials/network-topologies-explained-with-examples.html, Accessed 10/3/22
- [5] Computer Networking Notes, Network Topologies Explain with Examples, 2022, https://www.computernetworkingnotes.com/networking-tutorials/network-topologies-explained-with-examples.html, Accessed 10/3/22
- [6] David Johnson, Karel Mathee, Dare Sokoya, Lawrence Mboweni, Ajay Makan, Henk Kotze, Building a Rural Wireless Mesh Network: A do-it-yourself guide to planning a building a Freifunk based mesh network, 2014, https://upload.wikimedia.org/wikipedia/commons/8/83/Wireless_mesh_network_diagram.jpg, Accessed 10/3/22

REFERENCES

- [7] Timmy Broling, EthercatOperatingPrinciple, Wikimedia Commons, https://commons.wikimedia.org/wiki/File:EthercatOperatingPrinciple.webm

  Accessed 10/24/22

REFERENCES

- [1] https://en.wikipedia.org/wiki/Telephone_switchboard#/media/File:Photograph_of_Women_Working_at_a_Bell_System_Telephone_Switchboard_(3660047829).jpg
- [2]
- [3] *Gromov, Gregory (1995). "Roads and Crossroads of Internet History"*