

## This is a WinBUGS program for the artificial example in Chapter 13, Section 13.6.

Model: Nonlinear Structural Equation Model with Exponential Family and Fixed Covariates (fc1)

Data Set Names: YO1.dat and fc1.dat

Sample Size: N=500

```
model {
  for(i in 1:N){
    #structural equation model
    xi[i,1:2]~dmnorm(zero2[1:2],phi[1:2,1:2])
    eta[i]~dnorm(etamu[i],psd)
    etamu[i]<-ubeta*x2[i,1]+gam[1]*xi[i,1]+gam[2]*xi[i,2]+gam[3]*xi[i,1]*xi[i,2]
    dthat[i]<-eta[i]-etamu[i]

    #measurement equation model
    for(j in 1:P){
      z[i,j]~dbin(pb[i,j],5)
      logit(pb[i,j])<-mu[i,j]
    }
    mu[i,1]<-uby[1]+eta[i]
    mu[i,2]<-uby[2]+lam[1]*eta[i]
    mu[i,3]<-uby[3]+lam[2]*eta[i]
    mu[i,4]<-uby[4]+xi[i,1]
    mu[i,5]<-uby[5]+lam[3]*xi[i,1]
    mu[i,6]<-uby[6]+lam[4]*xi[i,1]
    mu[i,7]<-uby[7]+xi[i,2]
    mu[i,8]<-uby[8]+lam[5]*xi[i,2]
    mu[i,9]<-uby[9]+lam[6]*xi[i,2]
  } # end of i

  for(i in 1:2){zero2[i]<-0}

  #priors on loadings and coefficients
  for (i in 1:P){ uby[i]~dnorm(0.8,4.0) }

  lam[1]~dnorm(0.6,4.0)      lam[2]~dnorm(0.6,4.0)
  lam[3]~dnorm(0.7,4.0)      lam[4]~dnorm(0.7,4.0)
  lam[5]~dnorm(0.6,4.0)      lam[6]~dnorm(0.6,4.0)

  ubeta~dnorm(0.6,4.0)

  var.gam<-4.0*psd
  gam[1]~dnorm(0.5,var.gam)  gam[2]~dnorm(0.5,var.gam)    gam[3]~dnorm(0.5,var.gam)

  #priors on precisions
  psd~dgamma(10,8)
  sgd<-1/psd
  phi[1:2,1:2]~dwish(R[1:2,1:2], 8)
  phx[1:2,1:2]<-inverse(phi[1:2,1:2])
} #end of model
```

## Data

```
list(N=500, P=9,  
     R=structure(.Data=c(5.0,2.5,2.5,5.0),.Dim=c(2,2)),  
     z=structure(.Data=c(paste YO1.dat here),.Dim=c(500,9)),  
     x2=structure(.Data=c(paste fc1.dat here),.Dim=c(500,1)))
```

## Three different initial values

```
list(  
  uby=c(0.8,0.8,0.8,0.8,0.8,0.8,0.8,0.8,0.8),  
  ubeta=0.6,  
  lam=c(0.6,0.6,0.7,0.7,0.6,0.6),  
  gam=c(0.5,0.5,0.5),  
  psd=1.4,  
  phi=structure(  
    .Data=c(1.3333, -0.6667, -0.6667, 1.3333),  
    .Dim=c(2,2)))
```

```
list(  
  uby=c(1.0,1.0,1.0,1.0,1.0,1.0,1.0,1.0,1.0),  
  ubeta=1.0,  
  lam=c(1.0,1.0,1.0,1.0,1.0,1.0),  
  gam=c(1.0,1.0,1.0),  
  psd=1.0,  
  phi=structure(  
    .Data=c(2.0, -1.0, -1.0, 2.0),  
    .Dim=c(2,2)))
```

```
list(  
  uby=c(0.0,0.0,0.0,0.0,0.0,0.0,0.0,0.0,0.0),  
  ubeta=0.0,  
  lam=c(0.0,0.0,0.0,0.0,0.0,0.0),  
  gam=c(0.0,0.0,0.0),  
  psd=0.36,  
  phi=structure(  
    .Data=c(0.6, -0.2, -0.2, 0.6),  
    .Dim=c(2,2)))
```