Coordinated multi-robot motion planning: An overview

Peik Etzell

School of Science

Bachelor's thesis Espoo February 12, 2023

Supervisor

Professor Eero Hyvönen

Advisor

Postdoctoral researcher Francesco d'Amore



Copyright © 2023 Peik Etzell



Aalto University, P.O. BOX 11000, 00076 AALTO www.aalto.fi Abstract of the bachelor's thesis

Keywords			
ΓODO			
Abstract			
Date February 12, 2023 Number of pages	S 9+1 Language	English	
Francesco d'Amore			
Advisor Postdoctoral researcher			
Teacher in charge Professor Eero Hyvönen			
Major Computer Science	Code of major SCI3028.kand		
Degree programme Computer Science			
Title Coordinated multi-robot motion planning: A	an overview		
Author Peik Etzell			
Author Peik Etzell			



Aalto-universitetet, PB 11000, 00076 AALTO www.aalto.fi Sammandrag av kandidatarbetet

Författare Peik Etzell		
Titel		
Utbildningsprogram Datateknik		
Huvudämne Datateknik	Huvudämnets kod SCI3028.kand	
Ansvarslärare		
Handledare TODO Swedish title	Francesco d'Amore	
Datum February 12, 2023	Sidantal $9+1$	Språk Engelska
Sammandrag		
TODO		
Nyckelord		

Preface

Espoo, February 12, 2023

Peik Etzell

Contents

A	bstra	act Control of the Co	3		
A	Abstract (in Swedish) Preface				
P					
\mathbf{C}	onter	nts	6		
1		roduction	7		
	1.1	General Overview	7		
	1.2	Thesis Objective	8		
	1.3	Getting in depth	8		
		1.3.1 Discrete Grid case	8		
		1.3.2 Continuous case	8		
	1 /	Considerations	0		

1 Introduction

1.1 General Overview

Robotic motion planning is a field of research in theoretical computer science which has been deeply studied. It focuses on designing and studying algorithms for making robots get from one point to another safely (without colliding) and efficiently (depending on the situation, minimizing time, resource usage or similar metrics) [1].

Robots are modeled in a vast variety of ways, which differ in terms of shapes, sizes and kinematics: some warehouse robots can be modeled to move in two dimensions only, while flying drones can be seen as moving in three dimensions.

Robotic arms that move an end-effector are often modeled in six dimensions: three spatial ones and three for orientation. These often have some so-called kinematic redundancy, meaning they have more degrees of freedom than strictly necessary. This means that the arm is able to re-adjust while holding the same end-effector pose, which helps dexterity and fault-tolerance, but also increases complexity in planning, as poses can have different alternative joint configurations. [2]

There are many different environments in which robots exist. Assembly line robots have a fairly static environment, well defined start and end positions, and a clear and safe path between them. Robotic vacuum cleaners on the other hand need to map their environment and make decisions dynamically, as furniture, people and pets can change places from time to time. Some robots need to work together; multi-robot systems can be found in warehouses [2], where parallel motion is highly desirable, but past research has focused mostly on algorithms moving robots one-by-one [3].

The many real world scenarios to be studied led to the formulation of different problems. The one we investigate in this thesis is *coordinated multi-robot motion planning:* making robots move effectively without colliding with other moving robots. The goal is to move the robots from a starting configuration to a target configuration,

The problem has multiple variations: In an unlabeled case, we do not care which robot gets to which target position, only that all target positions get occupied. Otherwise we have a labeled problem, where robots and target positions each have labels, such that target positions contain a robot with the same label at the end. Note that the labels can be unique or not, and some sources distinguish between these cases: for example, [3] uses *unlabeled*, *colored* and *labeled* as variations on the problem, such that labeled signifies unique labels.

The problem can also be modeled as continuous or discrete. The discrete variant is often handled using graph theory, while simple shapes like unit radius disks (see [3], [4]) or unit squares (see [5]) are often used in the continuous case.

Finding the minimum *makespan* solution to a discrete grid case of the problem is found to be NP-hard by [3]. NP-hardness implies approximation algorithms are justified [3], so research is focused on better approximations and faster computation.

1.2 Thesis Objective

The field of coordinated motion planning for parallel robotics has seen a lot of research in recent years, with different algorithms tackling different problems in the field. The scope is broad and the problems are varied but related. The goal will be to understand and explain current research in the field, what has been done and what is yet to be understood.

One of the key objectives will be to compare different algorithms in terms of their performance in computation and execution, strengths, weaknesses and scalability. How many robots can we support in a real system before motion planning becomes too slow?

1.3 Getting in depth

TODO start explaining a bit more in details these topics (definitions, results, difficulties)

There are two different types of motion problems: finding a collision free path from a starting configuration to a target configuration is called a *motion planning* problem, while determining if such a path exists is called the *mover's problem*. [6]

- 1.3.1 Discrete Grid case
- 1.3.2 Continuous case
- 1.4 Considerations

References

- [1] H. Choset, K. Lynch, S. Hutchinson, K. George, B. Wolfram, L. Kavraki, and S. Thrun, *Principles of Robot Motion Theory, Algorithms, and Implementation*. The MIT Press, Feb. 2005.
- [2] B. Siciliano and O. Khatib, eds., *Springer Handbook of Robotics*. Springer Handbooks, Cham: Springer International Publishing, 2016.
- [3] E. D. Demaine, S. P. Fekete, P. Keldenich, H. Meijer, and C. Scheffer, "Coordinated Motion Planning: Reconfiguring a Swarm of Labeled Robots with Bounded Stretch," *SIAM Journal on Computing*, vol. 48, pp. 1727–1762, Jan. 2019.
- [4] B. Banyassady, M. de Berg, K. Bringmann, K. Buchin, H. Fernau, D. Halperin, I. Kostitsyna, Y. Okamoto, and S. Slot, "Unlabeled Multi-Robot Motion Planning with Tighter Separation Bounds," May 2022.
- [5] H. Yang and A. Vigneron, "Coordinated Path Planning through Local Search and Simulated Annealing," *ACM Journal of Experimental Algorithmics*, vol. 27, pp. 1–14, Dec. 2022.
- [6] J. E. Hopcroft and G. T. Wilfong, "Reducing Multiple Object Motion Planning to Graph Searching," SIAM Journal on Computing, vol. 15, pp. 768–785, Aug. 1986.