

# INFO90002 Week 5 Lab Answers

## Objectives:

- This week the focus in labs is to write, execute and understand how SQL works.

## Section 1 SQL Learning by Example

### Sub Queries

Sometimes we need to find a value and then use it. For example if we wanted to find out the departmentid of the department which has the lowest salary.

First we would find the lowest salary across all of the department store.

You might be tempted to write a query like this

```
SELECT min(Salary), DepartmentID  
FROM Employee;
```

But if we check this result set we will see that this result is wrong.

```
SELECT min(salary)  
FROM Employee  
WHERE DepartmentID =1;
```

OR

```
SELECT min(Salary), DepartmentID  
FROM Employee  
GROUP BY DepartmentID;
```

Department 1 does not have the lowest salary! While we can use Limit keyword – it is not always wise to do so.

So we break the problem into two components. Find the lowest salary, then find the departmentid rows where the salary matches the value of the first query.

```
SELECT MIN(Salary)  
FROM Employee;
```

The result set is one value {41000} we then use that value in our next query

```
SELECT DepartmentID  
FROM Employee  
WHERE Salary = 41000;
```

This can be done in the one statement:

```

SELECT departmentid
FROM Employee
WHERE SALARY =
(SELECT MIN(Salary)
FROM Employee);

```

|  | departmentid |
|--|--------------|
|  | 4            |

The query in parenthesis is known as the "inner query" and the other query is known as the "outer query".

This is doing exactly the same as two SQL statements above it but in one statement. The query in parenthesis is run first and the result returned (41000) then each row in the outer query matches the salary value with the value returned in the inner query. The only match is where Department ID is 4.

*Important: if the subquery returns more than one result "=" will not work you must use "IN"*

How many employees work in departments are on the fifth floor?

To approach this question, we break it into separate components.

1. What departmentid's are on the fifth floor
2. Count the number of employees whose departmentid matches the results returned in the inner query who are in the same department as the first query

Query 1 The "inner" query

```

SELECT departmentid
FROM Department
WHERE Floor = 5;

```

|  | departmentid |
|--|--------------|
|  | 1            |
|  | 8            |
|  | 9            |
|  | 10           |
|  | 11           |

Returns the result set {1,8,9,10,11} that is five rows.

Now we need to count each row in the Employee table where the departmentID matches 1 or 8 or 9 or 10 or 11.

As the result set has more than one row we need to use the keyword IN

```

SELECT count(employeeid)
FROM Employee
WHERE departmentid IN
(SELECT departmentID
FROM Department
WHERE Floor = 5);

```

|  |                  |
|--|------------------|
|  | EMP_COUNT_FLOOR5 |
|  | 9                |

TRY: If you have time replace the keyword IN with " = " and observe the error in the query window

Error Code: 1242. Subquery returns more than 1 row

1.1 Find the item id's sold by at least two departments on the second floor

```
SELECT DISTINCT ItemID
FROM sale inner join saleitem inner join department
ON sale.SaleID = saleitem.SaleID and sale.DepartmentID =
department.DepartmentID
WHERE department.Floor=2
GROUP BY ItemID
HAVING Count(Distinct(department.Departmentid)) > 1;
```

Alternatively

```
SELECT DISTINCT ItemID
FROM sale inner join saleitem inner join department
ON Sale.SaleID = SaleItem.SaleID
AND department.DepartmentID = sale.DepartmentID
WHERE department.DepartmentID IN
(SELECT DepartmentID
FROM department
WHERE department.Floor=2)
GROUP BY ItemID
HAVING Count(Distinct(department.Departmentid)) > 1
ORDER by ItemID;
```

There are other ways of achieving the same result set.

|  |        |
|--|--------|
|  | ItemID |
|  | 14     |

Remember: If necessary review the slides from the week 3 lecture on the types of joins.

1.2 List the departments having an average salary of over 55000

```
SELECT DepartmentID, AVG(employee.Salary)
FROM employee
GROUP BY DepartmentID
HAVING AVG(employee.Salary) > 55000;
```

## 1.2 Continued

You can format the output for better readability:

```
SELECT DepartmentID,  
FORMAT(AVG(employee.Salary),2) AS AverageSalary  
FROM employee  
GROUP BY DepartmentID  
HAVING AVG(employee.Salary) > 55000;
```

|    | DepartmentID | AverageSalary |
|----|--------------|---------------|
| 1  |              | 125.000,00    |
| 8  |              | 60.000,00     |
| 9  |              | 79.500,00     |
| 10 |              | 75.000,00     |
| 11 |              | 64.000,00     |

*Remember that HAVING is the way to use a condition for any column that has an aggregate function used on it (e.g. AVG MAX SUM COUNT etc)*

## 1.3 Name the items which have only been delivered by exactly one supplier

*HINT: You will need to join three tables (Item, Sale and Department) together and make sure the ambiguous columns in your select statement are fully qualified e.g.:*

```
SELECT Employee.Lastname, Department.Name  
FROM Employee Natural Join Department
```

```
SELECT Item.Name, count(distinct(SupplierID)) as SupplierCount  
FROM deliveryitem inner join delivery inner join item  
ON deliveryitem.DeliveryID = delivery.DeliveryID  
AND deliveryitem.ItemID = item.ItemID  
Group by item.Name  
Having Count(distinct(supplierID)) = 1  
Order by SupplierID, Name;
```

| Name                   | SupplierID | SupplierCount |
|------------------------|------------|---------------|
| BBO - Jumbuk           | 102        | 1             |
| Camoino chair          | 102        | 1             |
| Tent - 2 person        | 102        | 1             |
| Tent - 4 person        | 102        | 1             |
| Tent - 8 person        | 102        | 1             |
| Boots - Mens Hikina    | 105        | 1             |
| Boots - Womens Goretex | 105        | 1             |
| Boots - Womens Hikina  | 105        | 1             |
| Boots Ridina           | 105        | 1             |
| Cowboy Hat             | 105        | 1             |
| Horse saddle           | 105        | 1             |
| Polar Fleece Beanie    | 105        | 1             |
| Sun Hat                | 105        | 1             |

1.4 List the suppliers that have delivered at least 10 distinct items. List the supplier name and id

```
SELECT Supplier.SupplierID, Supplier.Name  
FROM deliveryitem INNER JOIN supplier INNER JOIN delivery  
ON deliveryitem.DeliveryID = delivery.DeliveryID  
AND delivery.SupplierID = supplier.SupplierID  
GROUP BY supplier.SupplierID  
HAVING COUNT(DISTINCT deliveryitem.ItemID) >= 10;
```

|  | SupplierID | Name            |
|--|------------|-----------------|
|  | 102        | Neaolese Corp.  |
|  | 105        | All Points Inc. |

1.5 Type the SQL that for each item, gives its type, the departments that sell the item, and the floor location of these departments.

*HINT: You will need to join four tables (Item, SaleItem, Sale and Department) together and make sure each ambiguous column in your select statement is fully qualified e.g.:*

```
SELECT Employee.lastname, Department.Name
```

```
FROM Employee Natural Join Department
```

```
SELECT distinct(item.Name), item.Type, sale.DepartmentID, department.Floor  
FROM item INNER JOIN saleitem INNER JOIN sale INNER JOIN department  
on item.ItemID = saleitem.ItemID and saleitem.SaleID = sale.SaleID and  
sale.DepartmentID = department.DepartmentID  
ORDER BY item.Name, sale.DepartmentID;
```

Your result set should look something like this:

| Name                        | Type | DepartmentID | Floor |
|-----------------------------|------|--------------|-------|
| BBO - Jumbuk                | F    | 4            | 3     |
| Boots - Mens Hikina         | C    | 3            | 2     |
| Boots - Womens Goretex      | C    | 3            | 2     |
| Boots - Womens Hikina       | C    | 3            | 2     |
| Boots Ridina                | C    | 2            | 1     |
| Camino chair                | F    | 4            | 3     |
| Compass - Silva             | N    | 2            | 1     |
| Compass - Silva             | N    | 4            | 3     |
| Compass - Silva             | N    | 6            | 1     |
| Cowboy Hat                  | C    | 3            | 2     |
| Explorino in 10 Easy Les... | B    | 2            | 1     |
| Geo positioning system      | N    | 2            | 1     |
| Geo positioning system      | N    | 6            | 1     |
| Gortex Rain Coat            | C    | 2            | 1     |
| Gortex Rain Coat            | C    | 3            | 2     |
| Gortex Rain Coat            | C    | 4            | 3     |
| Gortex Rain Coat            | C    | 5            | 4     |
| Gortex Rain Coat            | C    | 6            | 1     |
| How to Win Foreign Frie...  | B    | 2            | 1     |
| How to Win Foreign Frie...  | B    | 6            | 1     |
| Map case                    | E    | 6            | 1     |
| Map measure                 | N    | 6            | 1     |
| Pocket knife - Essential    | E    | 2            | 1     |
| Pocket knife - Essential    | E    | 3            | 2     |
| Pocket knife - Essential    | E    | 4            | 3     |
| Pocket knife - Essential    | E    | 5            | 4     |
| Pocket knife - Essential    | E    | 6            | 1     |
| Pocket knife - Essential    | E    | 7            | 2     |
| Polar Fleece Beanie         | C    | 3            | 2     |
| Sun Hat                     | C    | 3            | 2     |
| Tent - 2 person             | F    | 7            | 2     |
| Tent - 4 person             | F    | 7            | 2     |
| Tent - 8 person             | F    | 7            | 2     |
| Torch                       | E    | 2            | 1     |
| Torch                       | E    | 3            | 2     |
| Torch                       | E    | 4            | 3     |
| Torch                       | E    | 5            | 4     |
| Torch                       | E    | 6            | 1     |

1.6 Name the items that are delivered by Nepalese Corp or sold in the Navigation department

```

SELECT DISTINCT item.Name
FROM item
WHERE ItemID IN
(SELECT ItemID
FROM deliveryitem NATURAL JOIN delivery natural join Supplier
WHERE supplier.Name = 'Nepalese Corp.')
OR ItemID IN
(SELECT ItemID
FROM saleitem NATURAL JOIN sale NATURAL JOIN department
WHERE department.Name = 'Navigation');

```

You could also use UNION

```

SELECT DISTINCT item.Name
FROM item
WHERE ItemID IN
  (SELECT ItemID
   FROM deliveryitem NATURAL JOIN delivery natural join supplier
   WHERE supplier.Name = 'Nepalese Corp.')
UNION
  (SELECT item.Name
   FROM saleitem NATURAL JOIN sale
   NATURAL JOIN department NATURAL JOIN item
   WHERE department.Name = 'Navigation');

```

*Note the second SELECT statement is different selecting the Item Name not Item ID*

| Name                         |
|------------------------------|
| Compass - Silva              |
| Explorina in 10 Easy Lessons |
| Geo positioning system       |
| How to Win Foreign Friends   |
| Map case                     |
| Map measure                  |
| Gortex Rain Coat             |
| Pocket knife - Steadfast     |
| Pocket knife - Essential     |
| Camping chair                |
| BBO - Jumbuk                 |
| Torch                        |
| Tent - 2 person              |
| Tent - 8 person              |
| Tent - 4 person              |

1.7 Find the items that are not sold by departments on the second floor but are sold on other floors within the store

*When solving problems like this, work in steps*

1. Identify the items sold on the second floor,
2. Then find the items that are not in the result from part 1

```

SELECT DISTINCT ItemID
FROM sale inner join saleitem inner Join department
ON sale.SaleID = saleitem.SaleID and sale.DepartmentID =
department.DepartmentID
WHERE ItemID not in
  (SELECT DISTINCT ItemID
   FROM sale inner join saleitem inner Join department
   ON sale.SaleID = saleitem.SaleID and sale.DepartmentID =
department.DepartmentID)

```

```
WHERE department.Floor =2);
```

The inner query identifies the itemid's that ARE sold on the second floor. The outer query then finds all itemids which have been sold but are not in the inner query but only for departments not located on the second floor.

| ItemID | Floor |
|--------|-------|
| 1      | 1     |
| 3      | 1     |
| 3      | 3     |
| 5      | 1     |
| 6      | 1     |
| 9      | 1     |
| 10     | 1     |
| 11     | 1     |
| 15     | 3     |
| 16     | 3     |

Compare that to this query

```
SELECT distinct ItemID, department.Floor  
FROM sale inner join saleitem inner Join department  
ON sale.SaleID = saleitem.SaleID and sale.DepartmentID =  
department.DepartmentID  
WHERE department.Floor!=2  
ORDER BY ITEMID;
```

This query only finds items sold on floors other than the second floor – but this includes items which also happen to have been sold on the second floor.

| ItemID | Floor |
|--------|-------|
| 1      | 1     |
| 3      | 3     |
| 3      | 1     |
| 5      | 1     |
| 6      | 1     |
| 9      | 1     |
| 10     | 1     |
| 11     | 1     |
| 12     | 3     |
| 12     | 4     |
| 12     | 1     |
| 14     | 3     |
| 14     | 4     |
| 14     | 1     |
| 15     | 3     |
| 16     | 3     |
| 17     | 3     |
| 17     | 4     |
| 17     | 1     |

The additional itemid's are 12 14 and 17. A final query will confirm which floors items 12, 14 and 17 are sold on

```
SELECT distinct(item.ItemID), department.Floor
```

```

From item inner join saleitem inner join sale inner join department
on item.ItemID = saleitem.ItemID and
saleitem.SaleID = sale.SaleID and
sale.DepartmentID = department.DepartmentID
WHERE saleitem.ItemID in (12,14,17)
ORDER BY item.itemid, department.floor;

```

|  | ItemID | Floor |
|--|--------|-------|
|  | 12     | 1     |
|  | 12     | 2     |
|  | 12     | 3     |
|  | 12     | 4     |
|  | 14     | 1     |
|  | 14     | 2     |
|  | 14     | 3     |
|  | 14     | 4     |
|  | 17     | 1     |
|  | 17     | 2     |
|  | 17     | 3     |
|  | 17     | 4     |

Be sure you understand the question being asked.

1.8 Find the numbers and names of the employees who earn more than their manager.

```

SELECT emp.EmployeeID, emp.FirstName, emp.LastName, emp.Salary as empSal,
boss.Salary as BossSal
FROM employee emp INNER JOIN employee boss
ON emp.BossID = boss.EmployeeID
WHERE boss.Salary < emp.Salary;

```

*Note: This is a unary join – we have created aliases for the Employee table. The first alias is 'emp' the second 'boss'*

|  | EmployeeID | FirstName | LastName  | empSal   | BossSal  |
|--|------------|-----------|-----------|----------|----------|
|  | 8          | Sarah     | Ferousson | 86000.00 | 73000.00 |

1.9 Type the query to find the average salary of employees in the Clothes department

Your result set should look something like this:

```

SELECT format(avg(salary),2) as AVG_SALARY
FROM employee natural join department
WHERE department.Name = 'Clothes';

```

|  | AVG_SALARY |
|--|------------|
|  | 46.000.00  |

*HINT: Note the formatting of the result*

1.10 Type the query to find, for each department, the average salary of employees

```
SELECT department.name, format(avg(employee.salary),0) as AVG_SALARY  
FROM employee natural join department  
GROUP BY department.name;
```

Your result set should look something like this:

| name       | AVG_SALARY |
|------------|------------|
| Accounting | 60.000     |
| Books      | 45.000     |
| Clothes    | 46.000     |
| Equipment  | 43.000     |
| Furniture  | 45.000     |
| Management | 125.000    |
| Marketing  | 64.000     |
| Navigation | 45.000     |
| Personnel  | 75.000     |
| Purchasing | 79.500     |
| Recreation | 45.000     |

1.11 Find, for each department on the second floor, the average salary of the employees

```
SELECT department.Name, FORMAT(AVG(employee.Salary),2) as AverageSalary  
FROM employee NATURAL JOIN department  
WHERE department.Floor = 2  
GROUP BY department.Name;
```

| Name       | AverageSalary |
|------------|---------------|
| Clothes    | 46.000.00     |
| Recreation | 45.000.00     |

1.12 List suppliers that deliver a total quantity of items of types C and N that is greater than 40

First let's find the items that are of type C and N

```
SELECT item.Name, item.Type  
FROM item  
WHERE item.Type in ('C','N')  
order by item.Name;
```

Then find out how many of those items have been delivered

```
SELECT item.Name, SUM(deliveryitem.Quantity)  
FROM deliveryitem INNER JOIN item  
ON deliveryitem.ItemID = item.ItemID  
WHERE item.Type in ('C','N')  
GROUP BY item.Name;
```

And if the quantity delivered is greater than 40

```
SELECT item.Name, SUM(deliveryitem.Quantity)
FROM deliveryitem INNER JOIN item
ON deliveryitem.ItemID = item.ItemID
WHERE item.Type in ('C','N')
GROUP BY item.Name
HAVING Sum(deliveryitem.Quantity) > 40;
```

Now let's find the Supplier Names and IDs:

```
SELECT delivery.SupplierID, supplier.Name , SUM(deliveryitem.Quantity)
FROM supplier INNER JOIN delivery INNER JOIN deliveryitem Inner Join item
ON supplier.SupplierID = delivery.SupplierID
AND delivery.DeliveryID = deliveryitem.DeliveryID
AND deliveryitem.ItemID = item.ItemID
WHERE item.Type IN ('C','N')
GROUP BY delivery.SupplierID, supplier.Name
HAVING SUM(deliveryitem.Quantity) > 40;
```

Notice the difference in the WHERE statement using an OR:

```
SELECT delivery.SupplierID, supplier.Name , SUM(deliveryitem.Quantity)
FROM supplier INNER JOIN delivery INNER JOIN deliveryitem Inner Join item
ON supplier.SupplierID = delivery.SupplierID
AND delivery.DeliveryID = deliveryitem.DeliveryID
AND deliveryitem.ItemID = item.ItemID
WHERE (item.Type = 'C' OR item.Type = 'N')
GROUP BY delivery.SupplierID, supplier.Name
HAVING SUM(deliveryitem.Quantity) > 40;
```

And the WHERE x OR y condition can be written without parenthesis

```
SELECT delivery.SupplierID, supplier.Name , SUM(deliveryitem.Quantity)
FROM supplier INNER JOIN delivery INNER JOIN deliveryitem Inner Join item
ON supplier.SupplierID = delivery.SupplierID
AND delivery.DeliveryID = deliveryitem.DeliveryID
AND deliveryitem.ItemID = item.ItemID
WHERE item.Type = 'C'
OR item.Type = 'N'
GROUP BY delivery.SupplierID, supplier.Name
HAVING SUM(deliveryitem.Quantity) > 40;
```

The result is the same:

|  | SupplierID | Name                |
|--|------------|---------------------|
|  | 101        | Global Books & Maps |
|  | 105        | All Points Inc.     |

1.13 What is the average delivery quantity of items of type N made by each company who delivers them. Be sure to list the Item name in your answer.

```
SELECT delivery.SupplierID, supplier.Name, item.Type, item.Name,
FORMAT(AVG(deliveryitem.Quantity),2) AS AvgDelQty
FROM supplier inner join delivery inner join deliveryitem inner join item
ON supplier.SupplierID = delivery.SupplierID
AND delivery.DeliveryID = deliveryitem.DeliveryID
AND deliveryitem.ItemID = item.ItemID
WHERE item.Type = 'N'
GROUP BY delivery.SupplierID,supplier.Name,item.Name;
```

| SupplierID | Name                     | Name                   | AvgDelQty |
|------------|--------------------------|------------------------|-----------|
| 101        | Global Books & Maps      | Compass - Silva        | 4.67      |
| 101        | Global Books & Maps      | Geo positioning system | 3.00      |
| 101        | Global Books & Maps      | Map measure            | 10.00     |
| 102        | Neaolese Corp.           | Compass - Silva        | 3.00      |
| 102        | Neaolese Corp.           | Geo positioning system | 4.00      |
| 102        | Neaolese Corp.           | Map measure            | 10.00     |
| 103        | All Soorts Manufacturing | Compass - Silva        | 8.00      |
| 103        | All Soorts Manufacturing | Geo positioning system | 1.50      |
| 103        | All Soorts Manufacturing | Map measure            | 10.00     |
| 105        | All Points Inc.          | Compass - Silva        | 1.00      |

1.14 List the name and salary of the managers with more than 2 employees

```
SELECT employee.FirstName, employee.LastName, employee.Salary
FROM employee
WHERE employeeID IN
    (SELECT BossID
     FROM employee
     GROUP BY BossID
     HAVING COUNT(*) > 2);
```

|  | FirstName | LastName  | Salary    |
|--|-----------|-----------|-----------|
|  | Alice     | Munro     | 125000.00 |
|  | Andrew    | Jackson   | 55000.00  |
|  | Clare     | Underwood | 52000.00  |

1.15 Type the names and salaries of the employees who earn more than any employee in the marketing department

*HINT: Split the problem up into 2 components – calculate max salary of people in marketing (inner query) and then who earns more than that (outer query)...*

```
SELECT employee.FirstName, employee.LastName, employee.Salary  
FROM employee  
WHERE employee.Salary >  
(SELECT MAX(employee.Salary)  
FROM employee NATURAL JOIN department  
WHERE department.Name = "Marketing ");
```

|  | FirstName | LastName  | Salary    |
|--|-----------|-----------|-----------|
|  | Alice     | Munro     | 125000.00 |
|  | Sarah     | Ferausson | 86000.00  |

1.16 Find the supplier id and supplier names that deliver compasses

```
SELECT DISTINCT supplier.SupplierID, supplier.Name  
FROM supplier INNER JOIN delivery INNER JOIN deliveryitem INNER JOIN item  
ON supplier.SupplierID = delivery.SupplierID  
AND delivery.DeliveryID = deliveryitem.DeliveryID  
AND deliveryitem.ItemID = item.ItemID  
WHERE item.Name LIKE 'Compass%';
```

|  | SupplierID | Name                     |
|--|------------|--------------------------|
|  | 101        | Global Books & Maps      |
|  | 102        | Nepalese Corp.           |
|  | 103        | All Sports Manufacturing |
|  | 105        | All Points Inc.          |

*Note, the LIKE condition if you use the following query the result returns no rows:*

```
SELECT DISTINCT supplier.SupplierID, supplier.Name  
FROM supplier INNER JOIN delivery INNER JOIN deliveryitem INNER JOIN item  
ON supplier.SupplierID = delivery.SupplierID  
AND delivery.DeliveryID = deliveryitem.DeliveryID  
AND deliveryitem.ItemID = item.ItemID  
WHERE item.Name = 'Compass';
```

1.17 List item names that are delivered by Nepalese Corp and sold in the Navigation department

```
SELECT DISTINCT item.Name  
FROM item  
WHERE ItemID IN  
(SELECT ItemID  
FROM deliveryitem NATURAL JOIN delivery NATURAL JOIN supplier
```

```

WHERE supplier.Name = 'Nepalese corp.')
AND ItemID IN
(SELECT ItemID
FROM saleitem NATURAL JOIN sale NATURAL JOIN department
WHERE department.Name = 'Navigation');

```

| Name                       |
|----------------------------|
| Geo positioning system     |
| Torch                      |
| Gortex Rain Coat           |
| Pocket knife - Essential   |
| Compass - Silva            |
| Map case                   |
| Map measure                |
| How to Win Foreign Friends |

1.18 Type the query that gives the overall average of the salaries of all employees.

```

SELECT AVG(employee.Salary)
FROM employee;

```

| AVG_SALARY   |
|--------------|
| 60529.411765 |

1.19 Type the query that finds the item id of the items sold on the second floor

```

SELECT DISTINCT saleitem.ItemID
FROM saleitem INNER JOIN sale INNER JOIN department
ON saleitem.SaleID = sale.SaleID and sale.DepartmentID =
department.DepartmentID
WHERE department.Floor = 2
ORDER BY ItemID

```

| ItemID |
|--------|
| 8      |
| 12     |
| 14     |
| 17     |
| 18     |
| 19     |
| 20     |
| 21     |
| 22     |
| 23     |
| 24     |
| 25     |

1.20 Type the query that finds the name and salary of Clare Underwood's manager

```

SELECT employee.FirstName, employee.LastName, employee.Salary
FROM employee
WHERE employeeID IN

```

```
(SELECT BossID
  FROM employee
 WHERE employee.FirstName = 'Clare'
   AND employee.LastName = 'Underwood');
```

|  | FirstName | LastName | Salary   |
|--|-----------|----------|----------|
|  | Ned       | Kelly    | 85000.00 |

1.21 List the ids of the departments where all of the employees earn less than their manager

```
SELECT DISTINCT DepartmentID
FROM employee
WHERE DepartmentID NOT IN
  (SELECT wrk.DepartmentID
    FROM employee wrk INNER JOIN employee boss
    ON wrk.BossID = boss.employeeID
    WHERE wrk.Salary >= boss.Salary);
```

*Hint: Notice that the inner query uses a unary join to create a result set that lists all departmentids where an employee earns more than their boss. That is why the condition is NOT IN*

| DepartmentID |
|--------------|
| 1            |
| 2            |
| 3            |
| 4            |
| 5            |
| 6            |
| 7            |
| 8            |
| 10           |
| 11           |

1.22 Find the names of employees who are in the same department as their manager (as an employee).

Report the name of the employee, the department, and the boss's name

```
SELECT concat (wrk.FirstName, ' ',wrk.LastName) as employee,
       wrk.DepartmentID, CONCAT (boss.FirstName, ' ',boss.LastName) as Boss
  FROM employee wrk INNER JOIN employee boss
  ON wrk.BossID = boss.employeeID
 WHERE wrk.DepartmentID = boss.DepartmentID;
```

|  | Employee         | DepartmentID | Boss        |
|--|------------------|--------------|-------------|
|  | Andrew Jackson   | 11           | Ned Kelly   |
|  | Clare Underwood  | 11           | Ned Kelly   |
|  | Nancy Cartwright | 8            | Todd Beamer |
|  | Sarah Ferausson  | 9            | Brier Patch |

1.23 Type the query to find the name, salary, and managers of the employees of department id 11 who have a salary over \$55,000

*Hint: This will require a unary join to find the managers and employees. You will need to filter your query to limit it to department id 11, and who have a salary over \$25,000. Break this query up into its component parts*

```
SELECT concat (wrk.FirstName, ' ', wrk.LastName) as employeeName, wrk.Salary,  
concat(boss.FirstName, ' ', boss.LastName) as Manager  
FROM employee wrk INNER JOIN employee boss  
ON wrk.BossID = boss.employeeID  
WHERE wrk.DepartmentID = 11  
AND wrk.Salary > 55000;
```

|  | EmployeeName | Salary   | Manager     |
|--|--------------|----------|-------------|
|  | Ned Kelly    | 85000.00 | Alice Munro |

1.24. Among all the departments with total salary greater than \$55,000, find the department names that sell item Number 17

```
SELECT DISTINCT(department.Name)  
FROM saleitem INNER JOIN sale INNER JOIN department  
ON saleitem.SaleID = sale.SaleID  
AND sale.DepartmentID = department.DepartmentID  
WHERE saleitem.ItemID = 17  
AND department.DepartmentID IN  
(SELECT DepartmentID  
FROM employee  
GROUP BY DepartmentID  
HAVING SUM(employee.Salary) > 55000);
```

|  | Name      |
|--|-----------|
|  | Clothes   |
|  | Equipment |

1.25 Find the supplier id and supplier names that deliver both compasses and an item other than compasses

Attempt 1:

```
SELECT DISTINCT delivery.SupplierID, supplier.Name  
FROM supplier INNER JOIN delivery INNER JOIN deliveryitem INNER JOIN item  
ON supplier.SupplierID = delivery.SupplierID  
AND delivery.DeliveryID = deliveryitem.DeliveryID  
AND deliveryitem.ItemID = item.ItemID  
WHERE item.Name NOT LIKE 'Compass%'  
AND delivery.SupplierID IN  
(SELECT SupplierID
```

```

FROM delivery NATURAL JOIN item NATURAL JOIN deliveryitem
WHERE item.Name LIKE 'Compass%')
ORDER BY delivery.SupplierID;

```

Attempt 2:

```

SELECT DISTINCT delivery.SupplierID, supplier.Name
FROM supplier INNER JOIN delivery INNER JOIN deliveryitem INNER JOIN item
ON supplier.SupplierID = delivery.SupplierID
AND delivery.DeliveryID = deliveryitem.DeliveryID
AND deliveryitem.ItemID = item.ItemID
WHERE delivery.SupplierID IN
(SELECT SupplierID
FROM delivery NATURAL JOIN deliveryitem Natural JOIN item
WHERE item.Name LIKE 'Compass%')
GROUP BY delivery.SupplierID, supplier.Name
HAVING COUNT(DISTINCT item.Name) > 1
order by delivery.SupplierID;

```

|  | SupplierID | Name                     |
|--|------------|--------------------------|
|  | 101        | Global Books & Maps      |
|  | 102        | Nedalese Corp.           |
|  | 103        | All Soorts Manufacturing |
|  | 105        | All Points Inc.          |

*Note: Attempt 1 uses the approach to find those suppliers that supply things other than compasses and also supply compasses (sub query).*

*Attempt 2 uses a more generalizable approach. The generalizable approach is better as it allows queries such as “Find suppliers that deliver two items other than compasses” – change the >1 to >2 in the HAVING clause in Attempt 2 to do this. (Attempt 2 uses DISTINCT to handle multiple deliveries of compasses for the same supplier.)*

## SQL Homework - Functions

If you have time you can attempt the following SQL questions or do them at home against the department store schema you have installed on your computer.

Most of this week's homework requires you to read the manual. That is the functions section of the MySQL reference manual <https://dev.mysql.com/doc/refman/5.7/en/functions.html>

H1 How many deliveries have there been in the month of July?

*Hint: the only information you have been given is the month name*

```
SELECT COUNT(DeliveryID)
FROM Delivery
WHERE Monthname(deliverydate) = 'July';
```

H2 List the names of the tents available for sale

```
SELECT name
FROM Item
WHERE name like '%Tent%';
```

H3 What month has had the highest number of sales?

```
SELECT Count(SaleID), Monthname(SaleDate)
FROM Sale
Group By Monthname(SaleDate)
Order by Count(SaleID) DESC
LIMIT 1;
```

H4 List the salary total and employee count for each departmentid. Order by the smallest salary total to largest.

```
SELECT DepartmentID, COUNT(employeeid), SUM(Salary)
FROM Employee
GROUP BY DepartmentID
ORDER BY Sum(Salary);
```

H5 How many sales have been on a Sunday?

```
SELECT count(saleID)
FROM sale
Where DayName(Saledate) = 'Sunday';
```

H6 How many days have elapsed between the first delivery date and most recent delivery date for each supplier?

```
SELECT SupplierID, Datediff(max(deliverydate),min(deliverydate)),
count(distinct(deliverydate))
FROM Delivery
Group by SupplierID;
```

H7 Produce the following output by writing a SQL statement

|  |  |
|--|--|
|  | Where is each department?                      |
|  | The Management department is on floor number 5 |
|  | The Books department is on floor number 1      |
|  | The Clothes department is on floor number 2    |
|  | The Equipment department is on floor number 3  |
|  | The Furniture department is on floor number 4  |
|  | The Navigation department is on floor number 1 |
|  | The Recreation department is on floor number 2 |
|  | The Accounting department is on floor number 5 |
|  | The Purchasing department is on floor number 5 |
|  | The Personnel department is on floor number 5  |
|  | The Marketing department is on floor number 5  |

*Note there is no \_ in the title it is "Where is each department?" not Where\_is\_each\_department?*

```
SELECT concat('The ', name, ' department is on floor number ', floor) as "Where  
is each department?"  
FROM Department;
```

H8 Find the minimum, maximum, average and standard deviation for salaries in each department

```
SELECT DepartmentID, MIN(Salary), MAX(Salary), STDDEV(Salary)  
FROM Employee  
GROUP BY DepartmentID;
```

## Appendix New department Store Physical ER Model

