Actividad 2 — Enmascaramiento

8.1 Crear el rol

```
30
31  CREATE ROLE soporte_joel_cuadras NOLOGIN;
32
```

Data Output | Messages | Notifications

```
CREATE ROLE

Query returned successfully in 354 msec.
```

8.2 Crear una vista de acceso restringido

```
32
33  CREATE VIEW v_clientes_soporte AS
34  SELECT id, nombre,
35  CONCAT(LEFT(correo, 2), '*****', SUBSTRING(correo FROM POSITION('@' IN correo))) AS correo,
36  CONCAT('******', RIGHT(telefono, 4)) AS telefono,
37  CONCAT('*********', RIGHT(rfc, 4)) AS rfc
38  FROM clientes;
```

Data Output | Messages | Notifications

```
CREATE VIEW

Query returned successfully in 41 msec.
```

Consultar la vista:

```
40  SELECT * FROM v_clientes_soporte;
41
```

Data Output | Messages | Notifications

SQL

	id bigint	nombre character varying (120)	correo text	telefono text	rfc text
1	1	Ana López	an*****@example.t...	******45...	*********5ABC
2	2	Carlos Pérez	ca*****@example.t...	******56...	*********0DEF
3	3	María García	ma*****@example....	******67...	*********2GHI
4	4	Luis Torres	lu*****@example.t...	******78...	*********1JKL
5	5	Laura Sánchez	la*****@example.t...	******89...	*********5M...

8.3 Conceder acceso a la vista

Revocar el acceso directo a la tabla:

```
42  GRANT USAGE ON SCHEMA public TO soporte_joel_cuadras;
43  GRANT SELECT ON v_clientes_soporte TO soporte_joel_cuadras;
44  REVOKE ALL ON clientes FROM soporte_joel_cuadras;
45
```

Data Output | Messages | Notifications

```
REVOKE

Query returned successfully in 97 msec.
```

8.4 Verificar el resultado

```
46  GRANT soporte_joel_cuadras TO CURRENT_USER;
47  SET ROLE soporte_joel_cuadras;
```

Data Output | Messages | Notifications

```
SET

Query returned successfully in 66 msec.
```

```
49  SELECT * FROM v_clientes_soporte;
```

Data Output | Messages | Notifications

SQL

	id bigint	nombre character varying (120)	correo text	telefono text	rfc text
1	1	Ana López	an*****@example.t...	******45...	*********5ABC
2	2	Carlos Pérez	ca*****@example.t...	******56...	*********0DEF
3	3	María García	ma*****@example....	******67...	*********2GHI
4	4	Luis Torres	lu*****@example.t...	******78...	*********1JKL
5	5	Laura Sánchez	la*****@example.t...	******89...	*********5M...

```
50
51  SELECT * FROM clientes;
```

Data Output | Messages | Notifications

```
ERROR:  permission denied for table clientes

SQL state: 42501
```

¿Qué información continúa existiendo en la tabla original?
Toda la info, la vista no borra ni cambia nada, solo cambia el cómo se muestran los datos

¿Qué información puede visualizar el usuario soporte?
El id, el nombre completo y el correo, teléfono y RFC con asteriscos

¿Por qué no es suficiente ocultar los datos únicamente en la aplicación?
Porque si alguien se conecta directo a la base de datos vería todo completo

¿Qué ocurriría si soporte tuviera acceso directo a clientes?
La vista no serviría de nada, porque con un select * from clientes vería todos los datos sin ocultar