Dell CloudLink 8.3.x

Support Matrix

June 2026
Rev. 1.0

DELL Technologies

Notes, cautions, and warnings

NOTE: A NOTE indicates important information that helps you make better use of your product.

CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

WARNING: A WARNING indicates a potential for property damage, personal injury, or death.

Copyright © Dell Inc. All Rights Reserved. Dell Technologies, Dell, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.

Contents

Chapter 1: Revision history....4

Chapter 2: Introduction to Dell CloudLink support matrix....5

Hypervisors supported by CloudLink....5
Platforms supported by CloudLink....5
Third party key protectors supported by CloudLink....5
Features supported by CloudLink integrated with PowerFlex....6
PowerFlex software versions supported for CloudLink....6
Self-Encrypting Drive....6
CloudLink as a Key Management Interoperability Protocol server....7

1

Revision history

Table 1. Revisions

Date	Document revision	Description of changes
June 2026	1.0	Initial release

2

Introduction to Dell CloudLink support matrix

The CloudLink support matrix provides information about the supported hypervisors, platforms, key protectors, products, and PowerFlex versions for CloudLink.

The support matrix is intended for use by administrators of virtualized infrastructure who deploy or upgrade CloudLink or PowerFlex.

NOTE: The CloudLink version 8.3.x release is intended for PowerFlex deployments only.

Hypervisors supported by CloudLink

This section lists the hypervisors that CloudLink supports.

CloudLink versions 8.3.x and later support the following hypervisors:

- VMware ESXi or VMware vCenter versions 8.0 U3
- Kernel-based Virtual Machine (KVM)

Platforms supported by CloudLink

This section lists the platforms that CloudLink supports.

For more information about the supported operating systems, see the latest version of the *Dell ClouldLink Release Notes*.

- **Encryption for containers**
  - Dell PowerFlex
  - Dell PowerScale
  - VMware Tanzu
  - PowerStore OpenShift Container Platform

NOTE: CloudLink 8.3.x and later versions do not support the machine encryption functionality.

- **vVols encryption**
  - Dell PowerFlex
  - Dell PowerStore
  - VMware ESXi
  - Dell VxRail

Third party key protectors supported by CloudLink

This section lists the key protectors supported by CloudLink.

- Azure Key Vault
- Cipher Trust 2.4
- SafeNet Luna SA

Features supported by CloudLink integrated with PowerFlex

This topic provides information about the encryption features that are supported by CloudLink with PowerFlex.

- Encryption for PowerFlex—Encrypts software data at rest.
- Key Management of SEDs:
  - Advanced key management for deploying PowerFlex SED.
  - Automated deployment and configuration through PowerFlex Manager.

PowerFlex software versions supported for CloudLink

You can find information about the supported PowerFlex software for CloudLink here.

The following table lists the supported CloudLink and PowerFlex configurations. If you are using CloudLink for PowerFlex SDS-level encryption, then see the preceding sections before deploying or upgrading CloudLink or PowerFlex.

Table 2. Supported CloudLink and PowerFlex configurations

Supported Configurations	PowerFlex 3.6.0.6 and later	PowerFlex 3.6.x	PowerFlex 4.0.1 and later	PowerFlex 4.5.x	PowerFlex 4.6.x	PowerFlex 4.8.x	PowerFlex 5.0.x	PowerFlex 5.1.x
CloudLink 8.1	No	Yes (3.6.4 onwards)	No	Yes	Yes (4.6.0 onwards)	No	No	No
CloudLink 8.1.1	No	No	No	Yes (4.5.3 onwards)	Yes (4.6.1 onwards)	No	No	No
CloudLink 8.1.2	No	No	No	No	Yes	No	No	No
CloudLink 8.2	No	No	No	No	No	Yes	Yes	No
CloudLink 8.3	No	No	No	No	No	No	No	Yes

Self-Encrypting Drive

This topic lists the CloudLink supported Self-Encrypting Drives (SEDs) and associated hardware.

If the PowerFlex uses SEDs in the VMware ESXi environment, use VMware ESXi DirectPath I/O mode to map the host hard drives to each PowerFlex storage virtual machines.

Supported Host Bus Adapter card

CloudLink supports the PowerEdge HBA330 and HBA355i adapter cards.

Supported SEDs

Table 3. Supported SEDs and associated hardware

Component description	Firmware version	SWB	Dell part numbers
Kioxia, PM7 3WPD, SSD, 24Gbps SAS, 2.5 15mm, 512e, 800GB, 1.6TB, 3.2TB, 6.4TB, SED FIPS	C40E	57MM2	RGP9J, 81G77, G4NY4, HDKT0

Table 3. Supported SEDs and associated hardware (continued)

Component description	Firmware version	SWB	Dell part numbers
Kioxia, PM7 1WPD, SSD, 24Gbps SAS, 2.5 15mm, 512e, 1.92TB, 3.84TB, 7.68TB SED FIPS	C40E	57MM2	YTVTF, VGMCD, HCTYM
Kioxia, PM6 1WPD, SSD, 24Gbps SAS, 2.5 15mm, 512e, 1.92TB, 3.84TB, 7.68TB, SED FIPS	BD48	G42W2	H1P07,5T78C, 3VHY3
Kioxia, PM6, 24Gbps SAS, 3WPD, 960Gb, 1.92TB, 3.84TB, 7.68TBSED FIPS	BD48	G42W2	J92FY, 1081V, MD4YN, W06W3
Kioxia, PM7 3WPD, SSD, 24Gbps SAS, 2.5 15mm, 512e, SED FIPS	C40E	57MM2	RGP9J, 81G77, G4NY4, HDKT0
Kioxia, PM7 1WPD, SSD, 24Gbps SAS, 2.5 15mm, 512e, SED FIPS	C40E	57MM2	YTVTF, VGMCD, HCTYM
Kioxia, PM6 1WPD, SSD, 24Gbps SAS, 2.5 15mm, 512e, SED FIPS	BD48	6DH0W	H1P07, 3VHY3, 5T78C
Kioxia, PM6 1WPD, SSD, 12Gbps SAS, 2.5, 512e, SED FIPS	BD48	6DH0W	FH1W9,7F2D1
Kioxia, PM6 3WPD, SSD, 12Gbps SAS, 2.5, 512e, SED FIPS	BD48	6DH0W	WMWKG, DHWH5 , 81H9C
960GB SSD vSAS Mixed Use 12Gbps 512e 2.5in Hot-Plug AG SED Drive, 3DWPD,	"Agnostic Not applicable"		JKCX1
Kioxia, RM6, 3WPD, SSD, 12Gbps vSAS, 2.5 15mm, 512e, 960GB, SED	BJ07	5WMK8	42XXC
1.92TB SSD vSAS Mixed Use 12Gbps 512e 2.5in Hot-Plug AG SED Drive, 3DWPD,	"Agnostic Not applicable"		PDR1R
3.84TB SSD vSAS Mixed Use 12Gbps 512e 2.5in Hot-Plug AG SED Drive, 3DWPD	"Agnostic Not applicable"		4VX39
Kioxia PM6 1WPD, SSD, 12Gbps SAS, 2.5, 512e, SED FIPS	BD48	6DH0W	R9RTY, 7F2D1, FH1W9, M571X
Kioxia RM6 1WPD, SSD, Value SAS, 2.5, 512e, SED	BJ07	5WMK8	GRY0J, 1FGWG, XNXD2, 5MHY8
Kioxia RM6 3WPD, SSD, Value SAS, 2.5, 512e, SED	BJ07	5WMK8	42XXC, N15JP, FXYGR

For information about supported drives in PowerFlex custom node, see *Dell PowerFlex Custom Node R660, R6625, R760, and R7625 with PowerFlex 4.x Driver and Firmware Matrix*.

For more information about supported drives in PowerFlex rack and appliance, see Code & Compatibity Knowledge Hub..

CloudLink as a Key Management Interoperability Protocol server

The CloudLink 8.3.x and later versions do not support the Key Management Interoperability Protocol (KMIP) server functionality.