

PeloReaper Extension User Guide

Version : 2022.11.13

Author : Pelori

■ About PeloReaper Extension

PeloReaper Extension(PeloReaper) is extension plugin for Cockos REAPER(REAPER).
See details on PeloReaper Blog.

<http://peloreaper.blog.jp/archives/52971942.html>

■ Prerequisites

We could run a PeloReaper Extension under:

- Windows 10 (64bit) ※64bit version ONLY
- Microsoft .NET Framework 4.7.2 *1
- Microsoft Visual Studio 2019 VisualC++ Runtime *1
- REAPER v6.42~

We don't mention PC specs. But if REAPER can run well on your PC, it might be enough.

*1: Download from Microsoft and install if you need.

■ Install / Uninstall

See detail information on my blog.

<http://peloreaper.blog.jp/archives/52971942.html>

Various documents can be displayed with the following actions.

- [PeloReaper] Misc: Open PeloReaper document (EULA: AllLanguages)
- [PeloReaper] Misc: Open PeloReaper document (ExtensionGuide: English)
- [PeloReaper] Misc: Open PeloReaper document (ExtensionGuide: Japanese)

※Before starting to use PeloReaper, please make sure to read the EULA.

FX-Randomizer


■ About FX-Randomizer

FX-Randomizer can


- Change FX(VST, VSTi, JSFX) parameters randomly
 - You can choose parameters to be changed (Check box)
- Morph between current and captured FX parameter values.

■ Usage

- ① Run action [[PeloReaper] FXRandomizer: Open FX-Randomizer window]
then, FX-Randomizer window will appear.




- ② Select track which has FX, and show FX-chain window (press FX button if it's not shown).
Then, FX name will be shown in FX-Randomizer window.




- ※Item-take FX is also supported. Try select item instead of track, show take-FX Chain window.
※You have to use FX-Chain window. Floating window's not supported.
※If you selected a track and an item, FX-Randomizer shows take-FX.

- ③ Check parameters you want to change, and click [Randomize!] button.
Then, checked FX parameters will be changed randomly.



■ FX-Randomizer Window



*1. Multiple-Keyword's filtering mode

- AND : Parameters that have all keywords will be shown
- OR : Parameters that have one or more keywords will be shown

Dancer

■ About Dancer

- Dancer is an character animation function.
- You can let characters dance according to playing-beats.
- You can make your own character animations.

■ Usage

①Run action [[PeloReaper] Dancer: Open Dancer window].




Then, a character will appear.
The default animation is "DANCER REAPER-Chan", I hope you like it.

②Play something on REAPER (press Transport Play Button), the character begin to dance.



If you stop to play (press Stop Button), the character also stops to dance.

③You can drag the character around the screen using your mouse (click and hold).



④Right-Click Dancer character, context menu appears.

- Settings
Show Dancer Settings window.
- TopMost window
Switch the Dancer window's top-most state.
- Good Bye
The character disappears.

■ Dancer Settings Window

Dancer Settings

Dancer: DANCER REAPER-Chan

Dance Transition

Transition Type: Sequential

Dance (Trans:None): Waiting

☐ [Seq/Rnd] First(Waiting) dance included

Misc.

Group (used with actions): 0

Animation Speed: [Slider]

Version: 2

Apply

◆ Dancer

You can choose a character to display.

◆ Dance Transition

• Transition Type

None : Dance animation will never change (fixed).
(obeying [Dance (Trans:None)])

Sequential : Play Dance animation sequences sequentially.

Random : Play Dance animation sequences randomly.

• Dance (Trans:None)

Fixed animation sequence used when you choosed "Transition Type" to "None".

• [Seq/Rnd] First(Waiting) dance included

First Dance animation sequence is for "Waiting".

Check this, and you can play it as well (when REAPER Playing).

◆ Misc.

• Group : Group number this Dancer belongs to.

(You need this when control dance with Actions)

• Animation Speed : Speed of animation.

■ Switching dance animation with actions (Advanced)

Dancer has various Actions to switch dances at any given time.


※It is necessary to understand programming concepts such as flag control, thus this is the advanced feature.

•Preparation

Dancer window has its group number (0-3) that the Dancer belongs to.

For each of these groups, you will give the instruction "switch to dance number XX".

Setup your Dancer's group number in the settings window, set [Transition Type] to [None].




•Creating custom action for dance switching

Create a custom action for dance switching by combining several actions.

The custom action should perform the following functions.

1. Clear the dancer group selection state
→ [[PeloReaper] Dancer: Unselect all Dancer groups]
2. Select the dancer group to which you want to give instructions (Multiple selections possible)
→ [[PeloReaper] Dancer: Select Dancer group XX]
3. Switch dances by specifying the dance number (index) for the selected group
→ [[PeloReaper] Dancer: (Selected groups) Switch dance XX]

↓ Example of implementing "Switch to Dance01 for Group0,2" custom action



If you execute such a CustomAction during playback in REAPER, the dance will switch to the specified one.

It is recommended to execute it with Marker-Action so that it can be switched at any time.

•Executing custom action at a marker (Marker-Action)

If you set the marker name to [! + (Action command ID)], the action will be executed when playback cursor reaches it.


※ex.) !12345 → The action(commandID=12345) will be executed at the marker

It is also possible to specify the CommandID of a custom action.



Right-click in ActionList and copy the ID to the clipboard using [Copy selected action command ID].



Create a marker and setup for executing the custom action



Press the play button in REAPER and when the PlayCursor passes this Marker, the dance will switch.



As a tip, you can actually place a MarkerAction to reset the dance at the beginning of the project. This is the dancer status management, so those who are good at programming should try it.

■Dancer sprite sheet specification

- You can add a new dancer with creating a Dancer sprite sheet on your own.

◆Sprite sheet specification

- Image file for the dance animations
 - Fixed 8 frames of animated dance images per dance, side by side.
(When used in IMG mode, the entire image is displayed and no animation is performed.)
 - If multiple dances are included, they are arranged vertically in order.
 - Image size at a frame (displaying size)
 - Frame width = (whole image width) / 8
 - Frame height = (whole image height) / (number of dances)
(The number of dances is determined by the dance definition file described below)
 - Image file format: Transparent PNG
- Dances definition file (*.dat)
 - Text file, file name (excluding extension) should be the same as the above dance image file.
(If the dance image file is Dancer1.png, then Dancer1.dat)
 - Text file contains information on one dance per line.
(Each line should be written in CSV format, and each field should contain information in the following order)
 - (Required) Dance name
 - (Optional) Up to 8 display durations for each frame of the dance image

◆Example of the sprite sheet

- Dances definition file

```
DANCER REAPER-Chan.txt
Waiting,1,2
Stepping,4,2,2,1,4,2,2,1
Held
```

Ex.: Specified only first 2 frames' duration (equals 1,2,1,1,1,1,1,1)

Ex.: Specified durations of all frames (8 frames)

Ex.: No durations specified (equals 1,1,1,1,1,1,1,1)


- Dances image file (PNG)



◆Install your sprite sheets for Dancer

- We will assume that PeloReaper is installed in the UserPlugins folder of the REAPER resource folder.
- Place the sprite sheets' files (png, dat) in UserPlugins/PeloReaper/Dancer.

※If you place new sprite sheets or rewrite definition files, please restart REAPER.



※The REAPER resource folder can be opened from the REAPER menu
[Options > Show REAPER resource path in explorer/finder...].

FavSrc


■ About FavSrc

- Using FavSrc, you can copy item media sources to your favorite folder(directory).
- FavSrc has some features for importing media sources, collaborate with media-explorer as well.
- Item media source types are WAV, MIDI, Movie, Image and so on (anything REAPER accepts).
- You can use FavSrc features for...
 - storing favorite samples (kick, snare, synth timbre, ... you made) to your favorite folders
 - opening your favorite folder with Media Explorer (or Windows Explorer) directly.
 - importing some media sources from your favorite folder randomly.

■ Usage (Getting started)

First, you need to setup your favorite folders settings. To show setting window, run next action.

- [[PeloReaper] FavSrc: Open item media source action setting window...]



Set your favorite folder path to target folder 1.


(Seeing above image, here you can see "R:\Fav\Drums" as your target folder 1 example)

Then, click OK button at the right bottom of this window to apply settings.

Next, select wav item(sample or recorded one) and run the action below.

- [[PeloReaper] FavSrc: Copy item media source to target folder 1]

This action copies your item media source(Sample01.wav) to your target folder 1(R:\Fav\Drums).



Now, you've done the first tutorial.

If you register shortcut (or create button) of this action, you can use this feature anytime you like.

FavSrc has some other features, see "FavSrc Action Reference".

■ Usage notes for Media Source

You need to know what you're copying is media source itself.

Despite FXs you'd insert on items or tracks, media sources of the items keep original data such as waveforms.

Glueing or Rendering item, FXs would be applied to your waveform (this processing creates new wavefile that fx applied as media source). Then you can copy them using FavSrc.


TIPS

- Glue if you use only Take FX for item
 - [Right click item > Glue items] (or use action [Item: Glue items])
- You need to render item if you're using Track FX
 - you can use some actions for rendering like these...
 - [Track: Render selected area of tracks to mono stem tracks (and mute originals)]
 - [Track: Render selected area of tracks to stereo stem tracks (and mute originals)]
 - ...
- How to create MIDI Items' media source file
 - MIDI Items created on REAPER have no media source file-reference by default.
 - You can generate MIDI(SMF) File using the action below.
 - [Convert active take MIDI to .mid file reference]
 - ※ You can revert MIDI Item to non-file-referenced-MIDI using the action below.
 - [Convert active take MIDI to in-project MIDI source data]

■ FavSrc Action Reference

■ [PeloReaper] FavSrc: Open item media source action setting window...

This action shows FavSrc setting window.



- ① Setting Number
- ② Button: Open target folder with Windows Explorer
- ③ Button: Open target folder with REAPER Media Explorer
- ④ Target folder Path
- ⑤ Optional settings for destination filename
 - TakeName Using item take name instead of media source filename
 - Prefix Add prefix text
 - Name Replace filename with this text
 - Num Force add consecutive number (ex. Sample_0001.wav)
 - Bpm Add tempo (BPM)
 - Date Add date

■ [PeloReaper] FavSrc: Open item media source target folder (WindowsExplorer) 1~16

This action opens target folder 1-16 with Windows Explorer.

■ [PeloReaper] FavSrc: Open item media source target folder (ReaperMediaExplorer) 1~16

This action opens target folder 1-16 with REAPER Media Explorer.

※Known issue

Each time you restart REAPER and show Media Explorer window, Media Explorer restores current folder used previous time. Sometimes this behavior looks like the action doesn't works correctly, but it does.


Pay attention to this problem each time you restart REAPER and Media Explorer.

■ [PeloReaper] FavSrc: Copy item media source to target folder 1~16

This action copies media source files to target folder 1-16 (according to setting).

■ [PeloReaper] FavSrc: Copy item media source to target folder...

This action copies media source files to target folder (choose settings on dialog each time).



① Choose folder by setting number

If you created subfolder, you can choose subfolder as destination folder.
(Above image depicts indicating destination folder as "R:\Fav\Drums\Kick".)


② If you override filename settings, check [Override Options] and set some optional settings.

When you want to override the target folder path, check the [TargetPath] checkbox and write arbitrary folder path in the right textbox.

• Check [SubFolder -> Prefix] and toggle [SubFolder] to copy the SubFolder name to the Prefix.

■ [PeloReaper] FavSrc: Import random media source from target folder...

This action imports some media files randomly(or all of them) from a target folder.



① Choose target folder by setting number

You can create and use subfolder like "R:\Fav\Drums\Kick".

② Import Method

- AddNewItemToSelectedTrack Import media on selected track
- AddNewItemToSelectedTrack Import media to a selected item as takes
(If no selected items, new item will be created.)

③ Number of Import Media

- 0 means that all media in target folder will be imported (in order, not randomly).
- If you want to import all files in target folder, set large number of files.

④ Filename filter

- If you set any text here, media files that have the text in filename will be imported.
- Keyword delimiter(comma or space) is available (matches filename contains all keywords)

⑤ Optional setting: try to match tempo

- When you choose other than "None", [Preserve Pitch (sync)] check is available.

⑥ Override target folder path

By checking this checkbox and write an arbitrary folder path in the right textbox, you can override target folder.

Neutrino

■ About NEUTRINO

NEUTRINO is a vocal synthesizer using neural-networks.
<https://n3utrino.work/>

PeloReaperExtension has an action for automating NEUTRINO batch processing.

※The creator of PeloReaper Extension cannot take any responsibility for the use of NEUTRINO itself or any use of audio files generated by it, so please be careful when using it.
Please use this function after correctly understanding all the information such as the terms of use of the NEUTRINO, the rights of the singing voice model, and the scope of use.


■ Running NEUTRINO automatically with MusicXML

■ [PeloReaper] Neutrino: Execute Neutrino automation (Using MusicXML)...


Runs NEUTRINO automatically and converts a MusicXML file into a vocal wave file.
When it succeeded, the generated wave file will be imported as a new track item.

①First, you need to make a MusicXML file with REAPER MIDI Editor (musical notation mode).


- MIDI Editor main menu > [View>Mode: musical notation]
- Click a mouse right button > [Lyrics...], then write lyrics for notes.




- Breath articulation: you can insert an accent articulation instead of a breath.
 - ※Select a note (mouse right button drag) > right click on yellow bar > [Articulation>Accent]
 - ※Accent articulations will be converted to the breath articulations on process ③.



- When you finished to write lyrics and articulations, click the following menu on MIDI Editor.
[File > Notations: Export (PDF, MusicXML)...]
And export a MusicXML file somewhere.
(Remember the file path. You should point the MusicXML file path later.)



②Close MIDI Editor and run this action. Then following dialog will be shown.





Write and select all settings (example setting is above image)

- Neutrino Root NEUTRINO root path (where you unzipped and a Run.bat is there)
- MusicXML MusicXML file path (you saved at ①)
- Singer(Model) Vocal model name
 ※Some models are not included in NEUTRINO-*.zip.
 You need to install some models manually (if you need specific model).
- Refresh Refresh Singer(Model) list (displays installed models only)
- Neutrino Options
 - Use NSF whether to use NSF
 - Style Shift Amount of Style Shift
 - Threads Number of threads for processing (You can leave it default)
- World Options ※World Options won't applied when using the NSF
 - Pitch Shift Amount of pitch shifting by magnification
 - Pitch Smooth Amount of smoothing (%)
 - Formant Shift Amount of formant shifting by magnification
 - Formant Smooth Amount of smoothing (%)
 - Enhance Breathiness Amount of Enhancing Breathiness (%)
- Reset options initialize all option parameters.
- Refer to NEUTRINO blog for details on the various options.
<https://n3utrino.work/1295/>

③Click [OK], then NEUTRINO runs automatically and a result wave file will be imported.

- Log messages will be shown, you must wait until it tells "Done."

- ※This process takes a long time (maybe minutes, it depends on the song length.)



This action will streamline your workflow of using NEUTRINO.

You already don't need to use MuseScore only for inserting breath articulations as well.

MediaFolder

■ About MediaFolder


- MediaFolder window is useful for searching media and inserting media to the arrange view.
- MediaFolder can synchronize MediaExplorer to select and preview media.
- Has a lot of functions (Quick-Path, Random Selection, Easy to use with Keyboard, ...)
- Has some operation for multi window (Grouping, Switch focus)

■ Basic Tutorial


- ① Run action [[PeloReaper] MediaFolder: Show MediaFolder window (Number 01)] to show window.

Shortcut	Description
	[PeloReaper] MediaFolder: Show MediaFolder Window (Group 09)
	[PeloReaper] MediaFolder: Show MediaFolder Window (Group 10)
	[PeloReaper] MediaFolder: Show MediaFolder Window (Number 01)
	[PeloReaper] MediaFolder: Show MediaFolder Window (Number 02)
	[PeloReaper] MediaFolder: Show MediaFolder Window (Number 03)


- ② Specify current path and press [Enter] key to go to specified folder.




- ③ Press [Tab] key to switch focus (Path ComboBox)⇔(Files ListView).



- ④ Select some media file(s) and press [Enter] to insert media to the arrange view.




- ⑤ Check [ME]•[Play] to synchronize MediaExplorer selection state and auto-preview.



MediaFolderWindow

The functions of each part of the MediaFolder window are as follows.




- ① WindowのGroup Number
- ② Go to the parent folder
- ③ Current Path ([Enter] or ArrowButton(Right) to go to new path)
- ④ Bookmarks (Right click: Context menu)
- ⑤ MediaExplorer synchronization, Window top-most settings
 - ME Synchronously select media on the MediaExplorer
 - Play Auto-Preview on the MediaExplorer
 - Top Window top-most state
- ⑥ Search files
- ⑦ Switch files listview display (with [Shift] key, reverse switching order)
- ⑧ Parameters for random selection
- ⑨ Files listview (Right click: context menu)
- ⑩ Window color
- ⑪ Window title name

Select files randomly

[Ctrl+R] to select files randomly.

You can specify the number of selection (or percentage with [%] check box)

Empty [RS] text box means 50% implicitly.



■ Insert media

You can insert media files at EditCursror with selecting some media and press [Enter].
Here are some optional shortcuts.

- [Ctrl+Enter] Insert media as selected items' new takes
 - [Shift+Enter] Insert media (tempo-matched)
 - [Alt+Enter] Insert media (grid-sized)
- Check the following items in the context menu of the file list to insert using MediaExplorer's Action.
[Media Explorer > Option: use ME action to insert media on enter on enter key (single selection only)]
- Works only when a single file is selected in the file list
 - Ctrl, Alt, Shift combination + Enter will result in different insertion methods
 - ※In the context menu [Media Explorer], the modifier key is located to the right of the item [Insert to ~].

■ Insert media randomly

Select files and [Ctrl+I] then some of the selected files will be inserted randomly.

- You can specify the number of insert files with dialog window.
- If you selected items on the ArrangeView, some media will be inserted as a new take.
- Unless you selected any items, selected files will be inserted on the selected track (or new track)
- [Ctrl+Shift+I] is the same above, and tempo-matched (only insersion on a track)

■ Quick-Path

QuickPath is like a bookmark to bind path to number keys(0-9).

- Ctrl+Alt(+Shift)+0-9 Store current path to number key(0-9)
- Ctrl(+Shift)+0~9 Recall path of number key(0-9)
- ※If Shift is pressed, it will be an individual Window local Quick-Path memory/call (otherwise Global)

Right click on the files listview→[Print all quick paths] to display all Quick Paths.

- F2/Shift+F2: Global/Local Quick-Path displaying shortcut

■ Bookmarks

You can save favorite paths as bookmarks.

Right click on the bookmarks button, then context menu will be shown.

- | | |
|-------------------------------------|---|
| •Add current path to favorites | Add current path to bookmark list |
| •Remove current path from favorites | Remove current path from bookmark list |
| •Show favorites file in explorer | Open windows explorer at bookmark list file |

Left click on the bookmarks button, saved favorite paths will be shown. (context menu)

- ※If you edit bookmark list, edit bookmark list file directly.

■ Tags

You can add tag texts to selected files.

With selecting some files and right click, context menu will show up.

- | | |
|--------------------------------------|--|
| •Edit tags of selected item | Edit tags of selected file |
| •Add tags to selected items | Add tags to selected files |
| •Remove tags from selected items | Remove specified tags from selected files |
| •Remove all tags from selected items | Remove all tags from selected files |
| •Load tags from selected media file | Load tags from selected media files (if available) |

■ ☆:Favorite rank

Select files and right click→[Mark selected items as favorite] to set rank number.

You can do it with [Ctrl+G]

■ Search files

By entering keywords in the search text box, you can view only the files that match your keywords. You can enter multiple keywords separated by spaces, and the search will usually be an OR search.

• If the checkbox on the right is turned on, the search will be an AND search.

Following checkboxes allow you to switch the text to be compared when searching.


検索テキストボックス右下にあるチェックボックスで、検索時に比較対象とするテキストを切り替えられます。

- Name Compare to filenames
- Tag Compare to tags

■ Window title


You can set the window title name to each window.

Right click any place of MediaFolder window→[Set window title name] to set the title name.



■ Window color

Click on the left edge of the window to set the desired color.




■ ArrangeView operation

It is also possible to operate the ArrangeView while the focus is on the FileList of the window.

- Move Current Position of EditCursor, track selection
 - [Ctrl+Alt+Left/Right] Move EditCursor to the right/left (1 grid)
 - [Ctrl+Alt+Up/Down] Go to above/below track (track selection)
- Switching grid size
 - [Alt+Shift+Left/Right] Change grid size (Straight)
 - [Alt+Shift+Up/Down] Change grid size (Triplet)
- Transport Play/Stop
 - [Shift+Space] Transport Play/Stop

■ Shortcut keys

[F1] Show all keyboard shortcuts

A screenshot of a ReaScript console window titled "ReaScript console output". It displays a list of keyboard shortcuts for the MediaFolder window, organized under the heading "==== MediaFolder Shortcuts ====". The shortcuts are listed as follows:

```
==== MediaFolder Shortcuts ====
(Files Listview Only)
- Space           Play/Stop file on MediaExplorer
- Shift+Space     Transport Play/Stop
- Enter           Insert media
- Ctrl+Enter      Insert media (as a selected item take)
- Shift+Enter     Insert media (Tempo-Matched)
- Alt+Enter       Insert media (Align item length to grid size)
- Ctrl+Alt+Up/Down Go to above/below track
- Ctrl+Alt+Left/Right Move edit cursor to the left/right
- Ctrl+Alt+Shift+Left/Right Switch grid size (straight)
- Ctrl+Alt+Shift+Up/Down Switch grid size (triplet)
- Alt+Up          Move to the parent folder
- Ctrl+L          Focus current path combobox
- Ctrl+E          Change list view mode
- Ctrl+A          Select all files/dirs
- Ctrl+Shift+A    Invert selection of files
- Ctrl+R          Select files randomly (using RS settings)
```

■ MediaFolder window actions

■ [PeloReaper] MediaFolder: *1 MediaFolder window (Number *2)

*1: Show, Hide, Toggle

*2: 01~10

Show/Hide/Toggle MediaFolder window (By window number).

■ [PeloReaper] MediaFolder: *1 MediaFolder window (Group *2)

*1: Show, Hide, Toggle

*2: 01~10

Show/Hide/Toggle MediaFolder window (By window group number).

This function is useful for switching the display of multiple windows in a group.

■ [PeloReaper] MediaFolder: *1 MediaFolder windows

*1: Show, Hide, Toggle

Show/Hide/Toggle all MediaFolder windows.

Warning: many windows will show up!


GameSynth Integration

■ About GameSynth

- GameSynth is a sound data production tool for games developed by tsugi Studio.
It allows you to create sounds using procedural approaches such as physical modeling.
For more details, please refer to the official website below.
<http://tsugi-studio.com/web/en/products-gamesynth.html>
※ GameSynth tool itself is not included in the PeloReaper Extension package.
- GameSynth Integration includes features such as the ability to render GameSynth patches using GameSynth's command-line converter and automatically import the generated wav files.


■ Basic Tutorial

- ① Purchase GameSynth and set it up, which can be purchased from the original site or from stores such as SONICWIRE. Also, you don't need any special settings in GameSynth tool to use this plugin's GameSynth Integration.
- ② Configure the settings to run GameSynth Integration.
Run [[PeloReaper] GameSynth: GameSynth integration settings window...] action.




If you have installed GameSynth in the default location, you don't need to make any changes. Press [OK] button, then settings will be saved.

- ③ Display the GameSynth Rendering window to render patches of GameSynth.
Run [[PeloReaper] GameSynth: Show GameSynth render window...] action.




Rendered wav files will be automatically imported for each patch in the specified number.




■ Window Details

■ GameSynth Integration Settings Window



- GameSynth.exe Location(path) of the GameSynth.exe
- GameSynthC.exe Location(path) of the GameSynthC.exe (Command-line tool)
- Patch Root Dir GameSynth patch root folder. Default location is below.
(Your User Folder)\AppData\Local\Tsugi\GameSynth\Patches

■ GameSynth Rendering Window



① Search textbox for patches

The combo box on the right side allows you to decide the search method(AND, OR, RegExp). If the search method is [RegExp], regular expressions can be used, and only in this case, the search will be executed by entering the Enter key.

② Patch list. You need to check box of patches to render.

Right-click to display the menu for item selection, etc.

You can also use the following shortcut keys.

- Ctrl+A Select all patches
- Ctrl+Shift+A Toggle all check boxes of patches
- Ctrl+R Select patches randomly (the number of selection is set by Ctrl+Shift+R)
- Ctrl+Shift+R Select patches randomly (input number of selection)
- Tab Focus the search textbox
- F3 Focus the search textbox
- F5 Refresh patch list

③ Rendering options

Specifies the rendering options for patch rendering or random generation.

- Num of files The number of wav files to be rendered per patch
- Variation(%) Variation value of the GameSynth patch
- Bit depth Bit depth of the wav file
- Stereo Using stereo audio channels
- Generate patch Whether to save the generated patch (for random generation only)

④ Wav file importing options

- Destination Specify the destination (Track, ItemTake) to import the rendered wav file.
- Tempo matched Tempo-matched import (only for importing files to a track)

⑤ Buttons for executing to render

- Render (Checked patches) Render patches checked in the list of ②
- Totally random generate Automatically generate wavs with the number of [Num of files], regardless of the check in ②.

⑥ Status display

Displays the running status. When rendering finished, "Completed." appears here.

■ GameSynth Integration Action Reference

■ [PeloReaper] GameSynth: Open GameSynth integration settings window...

Displays the GameSynth Integration Settings window.

■ [PeloReaper] GameSynth: *1 GameSynth render window...

*1: Syow, Hide, Toggle

Switches the display of the GameSynth Render window.

■ [PeloReaper] GameSynth: Launch GameSynth tool (GameSynth)...

Launches the GameSynth Tool.

■ [PeloReaper] GameSynth: Launch GameSynth tool (PatchRepositorySite)...

Displays the GameSynth Patch distribution site in your Web browser.
Please refer to the GameSynth manual for how to use the site.



VOICEVOX Integration

■ VOICEVOXについて

- ・VOICEVOX is a free text-to-speech software.
For more details, please refer to the official website below.
<https://voicevox.hiroshiba.jp/>
- ※VOICEVOX-related files are not included with PeloReaper. They must be downloaded separately as described below.
- ・About PeloReaperExtensionのVOICEVOX Integration
PeloReaper implements the ability to perform speech synthesis using VOICEVOX ENGINE.
This function converts text into an audio file and imports it into REAPER.
・Support version: VOICEVOX ver.0.13.3

■ Basic tutorial (VOICEVOX ENGINE Integration)

- ① Prepare the runtime environment
Download and Install VOICEVOX
<https://voicevox.hiroshiba.jp/>
Start VOICEVOX Editor (VOICEVOX ENGINE will be started at the same time).
Check that the VOICEVOX itself is working properly. If it is OK, the preparation is completed.
※Leave VOICEVOX Editor running to use it as a text-to-speech server.
- ② Execute audio synthesis
■ [PeloReaper] VOICEVOX: Generate dialogue with VOICEVOX ENGINE TTS...
Select the Speaker's voice style, enter text in the Text field, and press the "Generate" button.
If the process is successful, the synthesized wav file is imported into REAPER.



- ・Parameters
 - ・Speaker You can select a combination of speaker types and vocal styles.
 - ・Text text for text-to-speech
 - ・Generate This button performs the text-to-speech and imports the wav file into REAPER.

■ Batch processing with CSV file


- [PeloReaper] VOICEVOX: Generate dialogue with VOICEVOX ENGINE TTS (CVS: *1)...
 - [PeloReaper] VOICEVOX: Generate dialogue with VOICEVOX CORE TTS (CVS: *1)...
- *1: ShiftJIS, UTF8

If you prepare a CSV file, you can import wav files by batch text-to-speech processing.
Each field of the CSV record describes the following in turn.

- SpeakerID Specify ID number to represent speaker/style(0~)
The numbers can be found in the VOICEVOX CORE TTS Settings window.
Rows (records) whose SpeakerID is not a number are skipped.
- Text text for text-to-speech.
Depending on the [Kana] described below, the text will be written differently.
- Kana Whether Kana mode is enabled or not.
 - 0 Normal Japanese strings can be specified for text.
 - 1 Text can be specified in AquesTalk-like Kana format
 - If blank, the value is the same as if the value were 0.
- Insert time You can specify the time to import the wav file in seconds or time code.
 - To specify in seconds, specify numerically
ex.) 1, 2.2, ...
 - Specify in HH:MM:SS:FF format when specifying by time code
ex.) 00:01:02:15, ...
 - If blank, it is inserted at the end of the previous line of Item.
- Example of a simple description in Excel (just save this to a CSV file)
※ Four fields are required per line, so provide a label line like the first line without kana or time.

	A	B	C	D
1	SpeakerID	テキスト	かな指定	配置時刻
2	0	こんにちは。		
3	10	こんちわ。		
4	0	どこの出身なんですか？		
5	10	北海道ですよ。		
6	14	私は秋田ですね。		

Execute the above Action and specify the CSV file, and the process will be executed.




■ Basic tutorial (VOICEVOX CORE Integration)


① Prepare the necessary files for VOICEVOX CORE

- VOICEVOX CORE (core.dll)
Download and extract voicevox_core-windows-x64-cpu-0.13.2.zip from the following location.
https://github.com/VOICEVOX/voicevox_core/releases/tag/0.13.2
- ONNX Runtime (onnxruntime.dll)
Download and extract onnxruntime-win-x64-1.13.1.zip from the following location.
<https://github.com/microsoft/onnxruntime/releases/tag/v1.13.1>
Copy onnxruntime.dll to the VOICEVOX CORE files' folder (the same location of core.dll).
- OpenJTalk dictionary files
Download and extract open_jtalk_dic_utf_8-1.11.tar.gz from the following location.
https://sourceforge.net/projects/open-jtalk/files/Dictionary/open_jtalk_dic-1.11/

- VOICEVOX CORE folder(location can be anywhere) after performing the above operations
※core.dll, onnxruntime.dll are required files




- OpenJTalk dictionary folder



② Location settings



- Execute the action [[PeloReaper] VOICEVOX: Show VOICEVOX settings window...]
 - VOICEVOX CORE Path Specify the folder path of the VOICEVOX CORE folder.
 - OpenJTalk Dic Path Specify the folder path of the OpenJTalk dictionary folder.
- Save settings with [Save] button.



※The above example is just an example, and the location of each folder is arbitrary.

③ Execute audio synthesis

- Execute the action [[PeloReaper] VOICEVOX: Generate dialogue with VOICEVOX CORE TTS...]
- Select the Speaker's voice style, enter text in the Text field, and press the "Generate" button.



•Parameters

- Speaker You can select a combination of speaker types and vocal styles.
- Kana Enables Kana text(like Aquestalk kana-format) mode
 - ex of Kana) コンニチワ、ミナ'サン
- Text text for text-to-speech
- Generate This button performs the text-to-speech and imports the wav file into REAPER.

•Warnings

- In normal mode(Kana=OFF), intonation and other adjustments are not possible.
- If you wish to make adjustments, you must set Kana=ON and enter text in Kana format.

MIDI

■ About MIDI


You can use some actions for the MIDI Editor.

※Actions below are available in the action list [MIDI Editor] section only.

■ Toggle Key-snap option on the MIDI Editor Action

■ [PeloReaper] MIDI: MIDIEditor Toggle key snap(Scale)

This action toggles the KeySnap option checkbox on the MIDI Editor.



■ Select previous/next key signature root

■ [PeloReaper] MIDI: MIDIEditor Select key signature root *1

*1: Prev, Next

Select previous/next key signature root in MIDI Editor.

※REAPER already has the same functional actions but they never update piano roll settings...

■ Show scale settings

■ [PeloReaper] MIDI: MIDIEditor Show current scale settings

This action shows current scale settings.


■ Overlapping notes detection

■ [PeloReaper] MIDI: Check overlapping notes

This action checks if there are any overlapping notes, and ask you whether to correct them.
(If there are some, confirmation dialog will be shown)

■ Overlapping notes problem

As you can see an image below, these two notes are overlapping.



REAPER cannot treat these notes correctly (especially the second note).

For example, when we try to select second note with some action, REAPER selects the overlapped part as a second note. Another case, when we change the note state with ReaScript, sometimes notes would lengthen to the end of current MIDI item unexpectedly.

This action is for checking this problem and correcting notes if necessary.

REAPER has some options below. You can use them as well.

- Correcting overlapping notes action
 - [Correct overlapping notes]
- MIDI Editor option (menu)
 - [Options > Automatically correct overlapping notes]

■ Setting time selection to current measure

■ [PeloReaper] MIDI: Set TimeSelection to current measure

This action set the time selection to current measure.

■ Moving pitch cursor to notes pitch

■ [PeloReaper] MIDI: Move pitch cursor to next higher note pitch (*1, *2)

■ [PeloReaper] MIDI: Move pitch cursor to next lower note pitch (*1, *2)

*1: Any, SelectedOnly, SmartSelect

*2: EditCursorOverlapped, (nothing)

The pitch cursor will move to the pitch of some notes.

*1

Any	Any notes will be candidates
SelectedOnly	Only selected notes will be candidates
SmartSelect	Some notes selected: "SelectedOnly" mode, otherwise "Any" mode

*2

(nothing)	Any notes will be candidates
EditCursorOverlapped	Notes overlapping with edit cursor will be candidates

■ [PeloReaper] MIDI: Move pitch cursor to notes pitch at edit cursor (*1, *2)

*1: Any, Selected, Smart

*2: Highest, Lowest, Cycle

The pitch cursor will move to the lowest/highest pitch of notes.

*1

Any	Any notes will be candidates
Selected	Only selected notes will be candidates
Smart	Some notes selected: "Selected" mode, otherwise "Any" mode

*2

Highest	Move to the highest pitch
Lowest	Move to the lowest pitch
Cycle	Execute cyclically these modes above

■ Changing length of selected notes

- [PeloReaper] MIDI: Multiple selected notes length by 2/3
Notes length will be multiplied by two thirds.


■ Setting velocity of selected notes

- [PeloReaper] MIDI: Set selected notes' velocity to 1~127
The velocity of selected notes will be set to the value(1, 10, 20, ..., 120, 127).
- [PeloReaper] MIDI: Set selected notes' velocity to 10~100 percent
The velocity of selected notes will be set to the value of percentage(10~100).

■ Setting interpolated velocities of selected notes

- [PeloReaper] MIDI: Set selected notes' velocity interpolated (*1) ...
- [PeloReaper] MIDI: Set selected notes' velocity interpolated (*1) with before settings
*1: Linear, EaseIn, EaseOut, EaseInOut, Cycle


The velocity of selected notes will be set to interpolated values within the specified range.
The action which has "with Before Settings" will use start/end velocity settings you specified before (on Set Velocities Range dialog).
The action of *1=Cycle will be executed with changing interpolation curve cyclically.




• Linear



• EaseIn



• EaseOut



• EaseInOut



■ Setting velocities of selected notes randomly

■ [PeloReaper] MIDI: Set selected notes' velocity to random value of range (*1, *2)

*1: SetRange, UseBeforeSettings

*2: OneRandomVelocity, RandomVelocities

The velocity of selected notes will be set randomly.

*1


SetRange You can specify a range of random values (Dialog)

UseBeforeSettings The range of random values you set before will be used

*2

OneRandomVelocity Velocities will set to one random value


RandomVelocities Velocities will set to random values of each



• OneRandomVelocity



• RandomVelocities



■ Random setting of Note's Pitch in a specific range

■ [PeloReaper] MIDI: (*1) note pitch randomize window...

*1: Show, Hide, Toggle

Sets display state of note pitch randomize window.

■ [PeloReaper] MIDI: Randomize selected notes pitch with range (setting (*1)(, *2))


*1: 00~08

*2: One random, Avoid duplication

Sets notes' pitch randomly based on the randomize range settings.

- Normal (*2: nothing) Pitch duplications exists
- Avoid duplication Avoids pitch duplications
- One random uses one random pitch for all selected notes

□ Randomize MIDI note pitch window



① Range generator

This is the utility for creating random range settings for ease.

- Base pitch Minimum pitch of the pitch range
- Semitones Number of semitones from base pitch
- Clear Clear the result text box
- Add Create and add the pitch range setting based on [Base pitch][Semitones]
- Capture Captures notes' pitch range from selected notes on MIDI Editor
- Copy to 1-8 Copy result settings to the settings 1-8

② Slots of pitch range settings (1-8)

- Pitch range (1-8) Settings of pitch range (multiple ranges can be combined with comma)
- Randomize Execute randomization (+Shift key: avoid pitch duplication)
- OneRandom Sets one random note pitch to the selected notes

③ Save/Load all settings

- Save Save all settings to file
- Load Load all settings from file
- Clear all Clear all settings on the window


□ Shortcuts on the window

- Ctrl+(1-8) Execute randomization (pitch duplication allowed)
- Ctrl+Shift+(1-8) Execute randomization (pitch duplication avoided)
- Ctrl+Alt+(1-8) Execute one-random

■ Deleting a note at Edit/Pitch cursor (or selected notes)

■ [PeloReaper] MIDI: Delete selected notes or delete note at edit/pitch cursor (Smart delete)

When there are no selection of notes, a note at both Edit and Pitch cursor will be deleted.
Otherwise (there are some selection of notes), they will be deleted.



■ Deleting Notes except for lowest pitch note at edit cursor

■ [PeloReaper] MIDI: Delete notes except for lowest pitch note (*1)

*1: IgnoreSelection, SelectedNotesOnly, Smart

Some notes at edit cursor except for lowest pitch note will be deleted.

*1

IgnoreSelection


SelectedNotesOnly

Smart

Any notes at edit cursor will be candidates

Only selected notes at edit cursor will be candidates

Some notes selected: "SelectedNotesOnly" mode,
otherwise "IgnoreSelection" mode



■ Add or move note selection

■ [PeloReaper] MIDI: Smart select note horizontally(*1 *2)

*1: Add, Select

*2: Next, Previous

This action adds notes to selection, or move selections of notes to other notes.

- If there are notes with the same pitch in the direction of movement, they'll be candidates for selection.
- Otherwise, if there are any notes in the direction of movement, they'll be candidates.
- If no note is selected, a nearest note to Edit/Pitch cursor will be selected.

■ [PeloReaper] MIDI: Smart select note vertically(*1 *2)

*1: Add, Select

*2: Higher, Lower

This action adds notes to selection, or move selections of notes to other notes.

- Basically, notes which starts the same time will be candidates for selection.
- If there are no notes with the same start time in the direction of movement, any other notes in the direction of movement will be candidates.
- If no note is selected, a nearest note to Edit/Pitch cursor will be selected.

■ Selecting all notes at Edit cursor(vertically) or Pitch cursor(horizontally)

■ [PeloReaper] MIDI: Unselect notes at edit cursor

■ [PeloReaper] MIDI: Select notes at edit cursor (*1)

*1: Add, Select, Toggle

The selection state of all notes at edit cursor will be set.

■ [PeloReaper] MIDI: Unselect notes at pitch cursor

■ [PeloReaper] MIDI: Select notes at pitch cursor (*1)

*1: Add, Select, Toggle

The selection state of all notes at pitch cursor will be set.

■ Selecting nearest note to pitch cursor at edit cursor

■ [PeloReaper] MIDI: Unselect note nearest to the pitch cursor at edit cursor

■ [PeloReaper] MIDI: Select note nearest to the pitch cursor at edit cursor (*1)

*1: AddSelection, Select, Toggle

The selection state of note nearest to pitch cursor at edit cursor will be set.

This action is useful for selecting a note nearest both Edit and Pitch cursor.

■ Selecting bass notes

■ [PeloReaper] MIDI: Select bass notes in time selection

Bass notes in time selection will be selected.

- If there is no time selection, all notes will be checked.

■ Detecting melody notes intervals of P4, P5

■ [PeloReaper] MIDI: Detect selected notes P4,P5 intervals (Monophonic)

This action detects monophonic melody notes intervals are 5 semitones or 7 semitones. Detected notes will keep selection.

■ Important notes of scale snapping actions below

■ Scale settings

REAPER accepts scale setting as a 12 numeric characters string.

This indicates available scale tones in the scale, for example Major Scale is 10203405067.

Technically, for scale snapping, all that matters is which values are not zero.

There is an example of scale setting file. : (REAPER resource folder)/Data/sample.reascale
(You can import a scale setting file like this on MIDI Editor window)

■ Restriction of scale settings

Following actions which use scale settings require a specific scale setting rule.

But don't worry about it, default scale settings which REAPER has go with the rule.

★ **Restriction: Scale tone numbers are unique in the scale**

OK: 102034050607

NG: 102234050677 (2,7 is doubled)

When you download .reascale file from internet (ex. REAPER forum), be careful about this rule.

■ Moving pitch cursor according to scale

■ [PeloReaper] MIDI: Move pitch cursor up according to scale

■ [PeloReaper] MIDI: Move pitch cursor down according to scale

If key snapping is enabled, pitch cursor will move up/down according to scale settings.

■ Moving pitch cursor to specific scale tone according to scale

■ [PeloReaper] MIDI: Move pitch cursor to nearest *1 scale tone

*1: 1st, 2nd, 3rd, 4th, ...

Pitch cursor will move to the nearest scale tone pitch according to scale settings.

• This action is available when key snapping is enabled.

■ [PeloReaper] MIDI: Move pitch cursor to *1 scale tone (within current octave range)

*1: 1st, 2nd, 3rd, 4th, ...

Pitch cursor will move to the scale tone pitch within the current octave according to scale settings.

• This action is available when key snapping is enabled.

■ Inserting scale interval note based on current pitch

■ [PeloReaper] MIDI: Insert scale(Diatonic) interval note at pitch cursor up *1

■ [PeloReaper] MIDI: Insert scale(Diatonic) interval note at pitch cursor down *1

*1: 1st, 2nd, 3rd, 4th, ...

This action inserts interval note from current pitch according to scale settings.

• This action is available when key snapping is enabled and current pitch is one of the scale tone.

• This is useful for inserting diatonic chords of sorts.

■ Inserting chromatic scale tones based on current pitch

■ [PeloReaper] MIDI: Insert chromatic scale interval note at pitch cursor up *1

■ [PeloReaper] MIDI: Insert chromatic scale interval note at pitch cursor down *1

*1: 1st, 2nd, 3rd, 4th, ...

This action inserts chromatic scale interval note based on current pitch.

• Even if key snapping is enabled, this doesn't obey key snapping.

■ Sending MIDI note ON/OFF at pitch cursor

■ [PeloReaper] MIDI: MIDIEditor Send note on message (at pitch cursor, velocity: 10~100%)

■ [PeloReaper] MIDI: MIDIEditor Send note off message (at pitch cursor)

Send MIDI Note ON/OFF (as a Virtual Keyboard).

• Assigning a shortcut, you can audition some notes with a PC keyboard without mouse click on piano roll keyboard (especially useful for drums and samplers).

• Better to assign shortcut to [Send all notes off to all MIDI outputs/plugin-ins] for stopping sounds.

■ Sending MIDI note ON/OFF at pitch cursor (Scale Tone)

■ [PeloReaper] MIDI: MIDIEditor Send scale(Diatonic) interval note on at pitch cursor *1 *2

■ [PeloReaper] MIDI: MIDIEditor Send chromatic scale interval note on at pitch cursor *1 *2

*1: Up, Down *2: 1st~12th

Send MIDI Note ON message at pitch cursor according to scale setting on MIDI Editor.

Diatonic: Scale tone only, Chromatic: Force chromatic if key-snap is enabled.

■ [PeloReaper] MIDI: MIDIEditor Set scale note on velocity...

Set a note on velocity for above actions.

■ PitchCursor位置を基準にScale上の相対音程でNote挿入やNote ONを発行 (モード切替可能)

■ [PeloReaper] MIDI: MIDIEditor Execute switchable scale(Diatonic) note action *1 *2

■ [PeloReaper] MIDI: MIDIEditor Execute switchable scale(Chromatic) note action *1 *2

Executes some scale-tone oriented actions depends on internal mode.
internal modes are following.

■ [PeloReaper] MIDI: MIDIEditor Switch switchable scale note action (*3)

*1: Up, Down *2: 1st~12th *3: Next, Previous

Modes (switchable) InsertNote+NoteOn

InsertNote

NoteOn


Switch internal modes for switchable-actions.

InsertNote, NoteOn functions are the same as actions written before.

■ Inserting multiple pitch CC

■ [PeloReaper] MIDI: Insert multiple MIDI CCs under selected notes range...

Inserts multiple pitch CC events under selected notes whole range.



■ Set selected CC values interpolated

■ [PeloReaper] MIDI: Set selected CC values interpolated (*1) ...

■ [PeloReaper] MIDI: Set selected CC values interpolated (*1) with before settings

■ [PeloReaper] MIDI: Set selected CC values interpolated (*1) using selected CC min max

*1: Linear, EaseIn, EaseOut, EaseInOut, Cycle

Sets selected CC values interpolated according to interpolation type. (see below images)

•First, use [[PeloReaper] MIDI: Set selected CC values interpolated (*1) ...] to specify CC values' range.

•Next, you can use "... with before setting" actions to recalculate values with no dialog.

•"... using selected CC min max" actions use the selected CC's min, max values to calculate.

•Linear



•EaseInOut



•EaseIn




•EaseOut



■ Duplicate Notes

■ [PeloReaper] MIDI: Duplicate selected notes (Octaves in a row)...

Duplicate the selected notes in a row to the specified octave upper/lower.



- Octaves Higher How many octaves up to duplicate consecutively (0: no duplication)
- Octaves Lower How many octaves down to duplicate continuously (0: no duplication)

Misc

■ About Misc

Here are miscellaneous actions (not categorized before).


■ Actions for copying media source to local proj

- [PeloReaper] Misc: Copy item source media to local proj and replace
 - [PeloReaper] Misc: Copy item source media to local proj and replace (with console log)
- This action copies selected item's media source to it's owner project media folder and replaces reference to it.

It is useful when you copy items between projects.

For example, When you copied item from ProjA to ProjB, copied item's media source reference would not be changed (ProjA item and ProjB item refer to the same media source file).

Using these actions, you can copy media source to ProjB and replace item's reference to it.



■ Open item media source file path in Windows Explorer

- [PeloReaper] Misc: Open selected item(take) media source file path in Windows Explorer
- This action opens item(take) media source file path in Window Explorer.

■ Open REAPER project file using BWF(bext) chunk in the wave file

■ [PeloReaper] Misc: Show wav file bext chunk info...

You can select wave file and show bext chunk info.

■ [PeloReaper] Misc: Open project from wav file bext chunk info (Embedded by REAPER)...

you can open REAPER project file with selecting wave file which has bext chunk info.
If you've already opened it, its project tab will be shown as current project.


If you render wave files with BWF(bext) info just in case, you would be able to find REAPER project file easily. Because a path of the project file is written in the bext chunk.
(Of course if your project file had moved anywhere, you could not open it. But the path of the project might help you find the project files.)

■ How to write BWF(bext) info in a wave file

Actions above are available only when a bext chunk info is written in the wave file.

To write this info, you have to render wave files with these checkbox ON.

- [Write BWF('bext') chunk]
- [Include project filename in BWF data]



■ Zoom to selected items

■ [PeloReaper] Misc: Zoom selected items (Wheel)

Zoom In/Out at the center of selected items with mouse wheel.

※This action should be assigned to the mouse wheel shortcut.

■ Select items near edit cursor

■ [PeloReaper] Misc: Select item near edit cursor on selected tracks (*1)

■ [PeloReaper] Misc: Unselect item near edit cursor on selected tracks (*1)

■ [PeloReaper] Misc: Toggle item near edit cursor on selected tracks (*1)

*1: Near, Next, Prev

Select items on the selected tracks and near the edit cursor.

■ Move edit cursor

■ [PeloReaper] Misc: Move edit cursor to loop start

■ [PeloReaper] Misc: Move edit cursor to loop end

Move edit cursor to loop start/end.

■ Change item length

- [PeloReaper] Misc: Set selected item length to grid size

Changes the length of the selected item to grid size.

- [PeloReaper] Misc: Add selected item length (Grid size)

- [PeloReaper] Misc: Subtract selected item length (Grid size)

Lengthen/Shorten the length of the selected item by grid size.

- [PeloReaper] Misc: Halve selected item length

- [PeloReaper] Misc: Double selected item length

- [PeloReaper] Misc: Triple selected item length

Halve/Double/Triple the length of the selected items.

■ Item volume

- [PeloReaper] Misc: Apply track volume to selected items (Reset track volume to 0dBFS)

Set the volume of the selected Item's parent Track to the Item's volume. The volume of the parent Track will be cleared.

■ FX Deletion

- [PeloReaper] Misc: Remove track fx whose name matches the pattern(*1)...
 - [PeloReaper] Misc: Remove take fx whose name matches the pattern(*1)...
- *1: Text, RegularExpression
Deletes FX with names matching the specified text/regular expression.

■ Setting FXParameter Value

- [PeloReaper] Misc: Set (*1) fx parameter value(*2)...
- *1: track, take
*2: (Normalized)
Sets specified track/take fx parameter values.

■ Volume Adjustment FX

- [PeloReaper] Misc: Add volume adjustment to (*1) fx (set Adjustment to 0dB)
- *1: track, take
Adds [JS: Volume Adjustment] jsfx and sets its [Adjustment] parameter to 0dB.

■ FX Chain Windows

- [PeloReaper] Misc: Switch fx chain window to (*1) (cycle)
- *1: previous, next
Switches fx chain windows to the previous/next one.
- [PeloReaper] Misc: Move fx chain window to (*1) of screen
- *1: cycle positions, left top, left center, left bottom, center top, center, center bottom, right top, right center, right bottom
Moves fx chain window to the specified position.
•In the case of [cycle positions], [left top] to [right bottom] are cycled.
- [PeloReaper] Misc: Focus last focused fx chain window
- Focuses the last focused fx chain window.

■ Collaboration with iZotope Relay

※iZotope Relay is included with plug-ins such as iZotope Neutron.
For more information, please refer to the following URL.
<https://www.izotope.jp/jp/products/category/plugin/>

- [PeloReaper] Misc: (Plugin Specific:iZotope Relay) Apply Relay global output gain to track volume (*1)
(*1: with clearing Relay output gain, with removing Relay fx)
Apply iZotope Relay's "Global Output Gain" to track volume.
 - (with Clearing Relay Output Gain) Reset Relay's gain after processing
 - (with Removing Relay FX) Delete Relay instance after processing
- [PeloReaper] Misc: (Plugin Specific:iZotope Relay) Remove all Relay fx instances from selected tracks
Removes Relay instances from the selected tracks.


■ Subtitles - SRT File

■ [PeloReaper] Misc: Export selected regions to subtitle file(SRT)...

The name of the Region that overlaps the time selection is written as a subtitle in the SRT file.

■ [PeloReaper] Misc: Export selected regions in Region Render Matrix to subtitle file(SRT)...

Export the name of the Region with a check in RegionRenderMatrix to be rendered in some way to the SRT file as a subtitle.



※In the figure above, all of Regions 1-3 are written to the SRT file.

■ [PeloReaper] Misc: Import subtitle file(SRT) and create regions...

Read the SRT file and create a Region at the time code specified for each subtitle.
(Region name = Subtitle)

■ [PeloReaper] Misc: Import subtitle file(SRT) and VOICEPEAK wave files(ex. 1-Filename.wav)...

This function is designed to work with AHS VOICEPEAK and allows you to easily import audio files into REAPER by following the steps below.

※For more information about VOICEPEAK, please refer to the following URL.

<https://www.ah-soft.com/voice/6nare/>

① Prepare lines(dialogues) in SRT file

② Import SRT files in VOICEPEAK and make vocal adjustments

※Refer to the VOICEPEAK manual for information on how to operate VOICEPEAK.

③ Use VOICEPEAK's export function to export the wav file to the location where the SRT file prepared in ① is located.

・At this time, check the [Save in separate blocks] and set the first naming rule to [1,2,3...].
(Wave files like 1-Filename.wav, 2-Filename.wav, ... will be generated)



※Place the SRT file and the sequentially numbered wav file in the same location, as shown on the left

④ By executing this Action and specifying the SRT file in the location where the wav file was exported in step ③, the wav file will automatically be placed in the SRT timecode location.




↑ Example of wav file automatically placed at subtitle timing

■ Creating video image sequence(thumbnails) track


- [PeloReaper] Misc: Create image sequence(thumbnails) track from selected video item...
Create an image sequence (thumbnail) track for the selected video item using ffmpeg.

□ Video to image sequence settings window



- ffmpeg.exe path Specify the path of ffmpeg.exe file
- Image settings
 - Image duration (sec) Duration of generated image item (seconds)
 - Image width (px) Width of generated image file (pixels)
- Generate Run processing (generate an image sequence track)

• Example



■ Contact Us

•PeloReaper Blog

<http://peloreaper.blog.jp/>

•Twitter (@pelori)

<https://twitter.com/pelori>

Copyright © 2018 Pelori All rights reserved.