DBMS Task 5

```
use bill;
create table orders (
    order_id int primary key,
    customer_id int
);
insert into orders values
(1, 101),
(2, 102),
(3, 103),
(4, 104),
(5, 105);
create table payment (
    payment_id int auto_increment primary key,
    order_id int not null unique,
    payment_date date not null,
    payment_mode varchar(30) not null,
    payment_status varchar(20) not null default 'pending',
    transaction_amount decimal(10,2) not null,

    check (payment_mode in (
        'upi',
        'credit card',
        'debit card',
        'net banking',
        'cash on delivery'
    )),

    check (payment_status in (
        'pending',
```

```
        'success',
        'failed'
    )),

    check (transaction_amount > 0),

    foreign key (order_id)
        references orders(order_id)
);
insert into payment
(order_id, payment_date, payment_mode, payment_status, transaction_amount)
values
(1, '2026-10-20', 'upi', 'success', 1500.00),
(2, '2026-10-21', 'credit card', 'success', 2500.00),
(3, '2026-10-22', 'debit card', 'failed', 1200.00),
(4, '2026-10-23', 'net banking', 'pending', 3000.00),
(5, '2026-10-24', 'cash on delivery', 'pending', 800.00);
select * from payment;

select * from payment
where payment_status = 'success';

select * from payment
where payment_status = 'failed';

select * from payment
where payment_status = 'pending';

select * from payment
where order_id = 1;
```

```
update payment
set payment_status = 'success',
   payment_date = '2026-10-27'
where order_id = 3
and payment_status = 'failed';

select count(*) as successful_payments
from payment
where payment_status = 'success';

select count(*) as failed_payments
from payment
where payment_status = 'failed';

select payment_mode, count(*) as total_transactions
from payment
group by payment_mode;

select payment_mode, count(*) as total_transactions
from payment
group by payment_mode
order by total_transactions desc
limit 1;

select sum(transaction_amount) as total_revenue
from payment
where payment_status = 'success';

select payment_mode,
     sum(transaction_amount) as total_revenue
from payment
```

```
where payment_status = 'success'
group by payment_mode;

select avg(transaction_amount) as average_amount
from payment;

select payment_status, count(*) as total_transactions
from payment
group by payment_status;

select c.customer_id,
    c.customer_name,
    o.order_id,
    p.payment_id,
    p.payment_date,
    p.payment_mode,
    p.payment_status,
    p.transaction_amount
from payment p
join orders o on p.order_id = o.order_id
join customer c on o.customer_id = c.customer_id;

select c.customer_id,
    c.customer_name,
    p.order_id,
    p.payment_date,
    p.payment_mode,
    p.payment_status,
    p.transaction_amount
from payment p
join orders o on p.order_id = o.order_id
```

```
join customer c on o.customer_id = c.customer_id
order by c.customer_id, p.payment_date desc;

select o.order_id,
       p.payment_mode,
       p.payment_status,
       p.transaction_amount
from orders o
join payment p on o.order_id = p.order_id
where p.payment_status in ('failed', 'pending');

select
   sum(case when payment_status = 'success' then 1 else 0 end)
       as successful_transactions,
   sum(case when payment_status = 'failed' then 1 else 0 end)
       as failed_transactions,
   sum(case when payment_status = 'pending' then 1 else 0 end)
       as pending_transactions
from payment;
```