


Buttons




Buttons are used throughout the user interface to perform actions, change modes, save data and launch new screens.

Element Specification





Anatomy



Button

Behavior

Gains Focus

- Show browser default focus ring (typically a dotted line "around" the button).
- Appearance change Lighter background (see Mouse Over below and Appearance and Styling highlighted state

below)

Loses Focus

 Appearance change
Darker background (see Mouse Over below and Appearance and Styling – highlighted state

below)

Mouse Over

Enabled Buttons



Appearance change
Lighter background (see Appearance and Styling
highlighted state below)

• cursor Pointer

Disabled Buttons

cursor



Appearance change
None.

Mouse Buttons

Click
Perform action

Keyboard Controls and Shortcuts

• Enter Perform action if the button has the focus.

Tab (Shift-Tab)
Move focus to the next (previous) UI element in

Arrow.

the tab order.



Layout

All dimensions are in pixels unless otherwise noted.



Conventions

- There are no real borders in buttons. The illusion of borders is drawn in the background images. The dimensions shown above are drawn in relation to the invisible box surrounding the button and include the borders built into the background images.
- The maximum width of a button as shown above is determined by the combined width of the left and right background images. The actual width of a button is determined by the Label which is influenced by language localization. In the event that the actual width exceeds the maximum, the button will fail safely in that it will still function although it will show a gap in the background.

Appearance and Styling

•	background-color	transparent	
•	background-image	Normal State	
		img_button_normal_left_	bkg.png
		img_button_normal_right_bkg.png	
		Highlighted State	
		img_button_highlight_left	t_bkg.png
		img_button_highlight_rig	ht_bkg.png
•	border	n/a	built into images
•	opacity	100%	button enabled
		0.7	disabled (Firefox and Safari)
		filter: alpha (opacity=40)	disabled (IE7)
		Note: The opacity settings above apply to the text in the button label (if present). The color change for disabled text (see the <i>Fonts</i> UI Specification) will not be applied to buttons.	



Icon

Behavior

No independent behavior.

Appearance and Styling

background-color
transparent
built into button

built into button background images.

icon-image varies with button

Label

The Label is compliant with the $\underline{\textit{Fonts}}$ UI Specification for normal text except as noted below.

Behavior

No independent behavior.

Appearance and Styling

width varies with content

• line-height 22 px



Issues

No known issues.

Change History

November 26, 2007	Vern McGeorge	Fixed a few image file names.
November 20, 2007	Vern McGeorge	Revised to comply with image file naming convention.
August 13, 2007	Vern McGeorge	Final comments in. Complete.
August 3, 2007	Vern McGeorge	Sprint 7 comments in.
July 27, 2007	Vern McGeorge	Re-organized for sprint 7 sign-off.
June 27, 2007	Vern McGeorge	Published for reference only to support review of Top Pane spec.
June 11, 2007	Vern McGeorge	Completed Appearance, Styling and Layout. Spec is complete.
May 24, 2007	Vern McGeorge	Published into Sprint 2 in support of menu.doc that supersedes menu_behaviors.txt
May 08, 2007	Vern McGeorge	Second draft for review following incorporation of new button style. Complete with regard to Behavior only. Appearance, Styling and Layout need to be completed.
April 10, 2007	Vern McGeorge	Reconstructed from file system corruption.
March 08, 2007	Vern McGeorge	One more re-vamp leading to a template and process that will allow me to describe any feature within the context of any other feature
March 07, 2007	AH, VM, JN	Consensus reached on format
March 06, 2007	Vern McGeorge	First cut of button spec
March 02, 2007	Vern McGeorge	Initial version of UI Specification

Legend:

•	AH	Andrei Hersimchuk
•	VM	Vern McGeorge
•	JN	Joel Nave