High Quality Depth Refinement with Color Photometric Stereo

Songyou Peng

Supervised by:

Dr. Yvain Quéau

Prof. Daniel Cremers



Computer Vision Group

Department of Computer Science

Technical University of Munich



A Thesis Submitted for the Degree of MSc Erasmus Mundus in Vision and Robotics (VIBOT)

Werner von Braun

Contents

A	ckno	wledgments	v
1	Intr	roduction	1
	1.1	Research Goal	1
	1.2	Outline	1
		1.2.1 References	1
2	Bac	kground	2
	2.1	RGB-D Cameras	2
		2.1.1 General	2
		2.1.2 ASUS Xtion PRO LIVE	2
	2.2	Shape from Shading & Photometric Stereo	2
	2.3	Intrinsic Image Decomposition	2
	2.4	Depth Map Refinement	2
	2.5	Super-resolution Imaging	2
3	Met	thodology	3
	3.1	Pre-Processing	3
		3.1.1 Depth inpainting	3
		3.1.2 Depth denoising	4
	3.2	RGBD-Fusion method	4

		3.2.1 ddd	4		
	3.3	Proposed method 1: RGB Ratio Model	4		
		3.3.1 Limitations	4		
	3.4	Proposed method 2: Robust Lighting Variation Model without Regularization	4		
		3.4.1 Depth super-resolution	4		
4	Res	ults and Evaluation	5		
	4.1	RGB-D Cameras	5		
		4.1.1 General	5		
		4.1.2 ASUS Xtion PRO LIVE	5		
	4.2	Shape from Shading & Photometric Stereo	5		
	4.3	Intrinsic Image Decomposition	5		
	4.4	Super-resolution Imaging	5		
5	Con	nclusion	6		
	5.1	RGB-D Cameras	6		
		5.1.1 General	6		
		5.1.2 ASUS Xtion PRO LIVE	6		
	5.2	Shape from Shading & Photometric Stereo	6		
	5.3	Intrinsic Image Decomposition	6		
	5.4	Super-resolution Imaging	6		
\mathbf{A}	The	first appendix	7		
Bi	Bibliography 8				

List of Figures

List of Tables

Acknowledgments

Leave this part until I finish the whole thesis

Introduction

- 1.1 Research Goal
- 1.2 Outline

1.2.1 References

You can reference other authors by using the *citecommand* [1] [2]. You are encouraged to use bib files and let bibtex do the job for you.

Background

Joint estimation of depth, reflectance and illumination for depth refinement

- 2.1 RGB-D Cameras
- 2.1.1 General
- 2.1.2 ASUS Xtion PRO LIVE
- 2.2 Shape from Shading & Photometric Stereo
- 2.3 Intrinsic Image Decomposition
- 2.4 Depth Map Refinement
- 2.5 Super-resolution Imaging

Methodology

3.1 Pre-Processing

The first step for most of the image processing tasks is to pre-process the initial input image. Due to the hardware limitation of modern inexpensive RGBD sensors, there usually exist holes with missing values on the depth images. Also, the depth data is often noisy so we need to do denoising and acquire a relative smooth surface.

In this section, we will describe respectively the basic depth inpainting and denoising algorithm that we use for our pre-processing.

3.1.1 Depth inpainting

Image inpainting itself is a very mutual area and has been widely applied as a useful tool for many modern computer vision applications, e.g, restore the damaged parts of ancient paintings, or remove unwanted texts or objects in a photography. Since the idea of image inpainting is to automatically replace the lost or undesired parts of an image with the neighbouring information by interpolating, we were inspired to apply it to fill in the missing depth information.

3.1.2 Depth denoising

3.2 RGBD-Fusion method

3.2.1 ddd

3.3 Proposed method 1: RGB Ratio Model

3.3.1 Limitations

- LEDs have to be set up far away from each other.
- Natural illumination is a problem.
- Only feasible for the simple albedo cases

3.4 Proposed method 2: Robust Lighting Variation Model without Regularization

3.4.1 Depth super-resolution

Results and Evaluation

- 4.1 RGB-D Cameras
- 4.1.1 General
- 4.1.2 ASUS Xtion PRO LIVE
- 4.2 Shape from Shading & Photometric Stereo
- 4.3 Intrinsic Image Decomposition
- 4.4 Super-resolution Imaging

Conclusion

- 5.1 RGB-D Cameras
- 5.1.1 General
- 5.1.2 ASUS Xtion PRO LIVE
- 5.2 Shape from Shading & Photometric Stereo
- 5.3 Intrinsic Image Decomposition
- 5.4 Super-resolution Imaging

Appendix A

The first appendix

If you need to add any appendix, do it here... Etc.

Bibliography

- [1] Witold Pokorski and Graham G. Ross. Flat directions, string compactification and three generation models. 1998.
- [2] Dumitru Ghilencea and Graham G. Ross. Unification and extra space-time dimensions. 1998.