

[illegible]

Level-Conversion

Connector_Relay

Diagram illustrating the pinout for the Connector_Relay (J1). The connector has 18 pins, with pins 1 through 12 labeled on the left and pins 13 through 18 labeled on the right. The ground (GND) is connected to pin 17.

Pinout details:

- Pin 1:** Motor_{EN}
- Pin 2:** TX_{Receiver}-RX_{Antenna}-5V
- Pin 3:** Motor1_{PWM}
- Pin 4:** RX_{Receiver}-TX_{Antenna}-5V
- Pin 5:** Motor2_{PWM}
- Pin 6:** PH_{Interface}-From
- Pin 7:** Motor3_{PWM}
- Pin 8:** EN_{Interface}-From
- Pin 9:** Motor4_{PWM}
- Pin 10:** EN_{Interface}-From
- Pin 11:** BallCatch_{Front}
- Pin 12:** EN_{Interface}-From
- Pin 13:** BallCatch_{Back}
- Pin 14:** Kick_{Cmp}
- Pin 15:** Dribbler_{Back}
- Pin 16:** Kick_{Cmp}
- Pin 17:** Kick_{Stroke}
- Pin 18:** EN_{BOOST}

Power supply connections are shown at the top: +3.3V and +5V. The ground (GND) is connected to pin 17.

Buzzer

The diagram shows a circuit for a buzzer. A 5V supply is connected to a buzzer component. The buzzer is connected to a resistor labeled R6 with a value of 1k. The other end of the resistor is connected to the input 1 of an AND gate labeled BZ1 Buzzer. The input 2 of the AND gate is connected to GND. The output of the AND gate is connected to the buzzer.

Diagram of the RESET_BTN circuit:

- A +3.3V supply is connected to a 10k resistor (R8).
- The other end of R8 is connected to a node labeled **Main_RST**.
- This node is also connected to one terminal (1) of a switch (SW1).
- The other terminal (2) of the switch is connected to a 100nF capacitor (C2).
- The other end of C2 is connected to GND.

The diagram shows a circuit with a 5V DC voltage source on the left. A green wire connects the positive terminal of the source to the anode of an LED, which is represented by a red triangle pointing right. A red label 'LED' is placed above the LED symbol. A green wire also connects the cathode of the LED (the shorter, wider base) to a resistor, represented by a red rectangle. The resistor is labeled 'R9' and '330' in green. Below the resistor is a red diode symbol pointing left, labeled 'D1' and 'LED_Small' in green. Finally, a green wire connects the bottom of the diode to a ground symbol, labeled 'GND' in green.

Pinout diagram for the J2 Connector_Sub:

- Pin 1: J2 Conn_Sub (connected to +3.3V)
- Pin 2: TX_{0perry}-RX_{unitIV2}
- Pin 3: RX_{0perry}-TX_{unitIV2}
- Pin 4: TX_{0perry}-RX_{unitIV1}
- Pin 5: RX_{0perry}-TX_{unitIV1}
- Pin 6: RX_{0perry}-TX_{esp826C02}
- Pin 7: TX_{0perry}-RX_{esp826C02}
- Pin 8: TX_{0perry}-RX_{unitIV5}
- Pin 9: SW_{START}
- Pin 10: RX_{0perry}-TX_{unitIV5}
- Pin 11: GND
- Pin 12: (unlabeled)
- Pin 13: (unlabeled)
- Pin 14: RX_{0perry}-TX_{esp826C301}
- Pin 15: TX_{0perry}-RX_{esp826C301}
- Pin 16: RX_{0perry}-TX_{unitIV3}
- Pin 17: TX_{0perry}-RX_{unitIV3}
- Pin 18: TX_{0perry}-RX_{unitIV6}
- Pin 19: RX_{0perry}-TX_{unitIV6}

Power connections: +3.3V (Pin 1), +5V (Pin 19), GND (Pin 11).