

Software Studio

軟體設計與實驗

DOM

Hung-Kuo Chu

Department of Computer Science
National Tsing Hua University

CS2410



What is DOM?

Document Object Model

The whole HTML document is an object.
We can use JavaScript to control the HTML document.



Finding Objects in DOM

- document.getElementById(**id_name**):
 - Find a node with its id.
- document.getElementsByClassName(**class_name**)
 - Find a node with its class.
- document.getElementsByTagName (**tag_name**)
 - Find a node with its tag.

<**p** **class**="class_name" **id**="id_name">Content</p>



Manipulating Objects in DOM

- `node.style.css_attribute`:
 - Get or set CSS attribute.
- `node.innerHTML`:
 - Get or set HTML content of a node.
- `node.attribute_name`:
 - Get or set HTML attribute of a node.

`<button id="id" autofocus style="font-size:50pt">Click!!</button>`

[More information about DOM](#)



A DOM Example

```
<html>
<head>
  <meta content="text/html; charset=UTF-8">
  <title>DOM example #1</title>
  <script type="text/javascript">
    function init() {
      var text = document.getElementById("dom1");
      text.innerHTML = "Hello DOM!!";
    }
  </script>
</head>
<body onload="init();">
  <p id="dom1"></p>
</body>
</html>
```

Hello DOM!!



DOM Example (explained)

```
<html>
<head>
  <meta content="text/html; charset=UTF-8">
  <title>DOM example #1</title>
  <script type="text/javascript">
    function init() {
      var text = document.getElementById("dom1");
      text.innerHTML = "Hello DOM!!";
    }
  </script>
</head>
<body onload="init();">
  <p id="dom1"></p>
</body>
</html>
```

First we use **getElementById** to get the object with specific id. ("dom1" in this example)

And then we use **innerHTML** to modify **content** of this object to display our string.

The <p> is an object in JavaScript with "**dom1**" as its id.

We can use getElementById to modify its content.



DOM Example (explained)

```
<html>
<head>
  <meta content="text/html; charset=UTF-8">
  <title>DOM example #1</title>
  <script type="text/javascript">
    function init() {
      var text = document.getElementById("dom1");
      text.innerHTML = "Hello DOM!!";
    }
  </script>
</head>
<body onload="init();" >
  <p id="dom1"></p>
</body>
</html>
```

First we use **getElementById** to get the object with specific id. ("dom1" in this example)

And then we use **innerHTML** to modify **content** of this object to display our string.

The <p> is an object in JavaScript with "**dom1**" as its id.

We can use **getElementById** to modify its content.



Try yourself!

Q:How can we change the value of the HTML <input> tag?

```
<html>  
  <body>  
    <input type="text" id="SStudio" value="0" readonly>  
  </body>  
</html>
```

```
var answer = document.getElementById("SStudio");  
answer.value = "1";
```



Further Reading

- <https://ithelp.ithome.com.tw/articles/10202689>

